


# OfficeLUX RAYET 2.0


60 | doppelt asymmetrisch



## LIGHT DISTRIBUTION CURVE



## TECHNICAL DRAWING



## LIGHT INFORMATION

beam angle	double-asymmetric
color temperature	4.000 K
color tolerance	< 5 SDCM
color rendering index	> 80

## PROPERTIES

through-wiring	5 x 2,5 mm <sup>2</sup>
connection	Terminal: 5-pole max. 2,5 mm <sup>2</sup>
module per circuit breaker B10A	18
module per circuit breaker B16A	29
module per circuit breaker C10A	30
module per circuit breaker C16A	49
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60Hz

## ORDER OVERVIEW

OfficeLUX RAYET 2.0 60   double asymmetric	
product code	126026400147
EAN code	4260374018940
warranty	5 years

## ACCESSORIES

## PERFORMANCE

luminous efficiency	158 lm/W
system performance	57 W
luminous flux	9.000 lm
dimmmable	No

## RESILIENCE

protection class	I
impact resistance	IK04
protection type	IP40
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	–20 to +45 °C
foodready	No

## MATERIAL

cover	diffuse cover
material (cover)	PMMA
material (housing)	Aluminium
housing color	Silvergrey

## SCOPE OF DELIVERY

Module includes 1x clip for ceiling installation
--

## DIMENSION

L x W x H / Ø (H2)	1450 x 64 x 95 (105) mm
weight	3,3 kg