



NoviLUX PRO 125



LIGHT DISTRIBUTION CURVE



TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	110°
color temperature	4.000 K
color tolerance	< 5 SDCM
color rendering index	> 80

PROPERTIES

through-wiring	No
connection	Terminal: 3-pole max. 2,5 mm ²
module per circuit breaker B10A	21
module per circuit breaker B16A	34
module per circuit breaker C10A	35
module per circuit breaker C16A	57
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

NoviLUX PRO 125	
product code	501240100022
EAN code	4260374014614
warranty	3 years

ACCESSORIES

No accessories available

PERFORMANCE

luminous efficiency	98 lm/W
system performance	10 W
luminous flux	.980 lm
dimmmable	No

RESILIENCE

protection class	II
impact resistance	IK08
protection type	IP44
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	–25 to +50 °C
foodready	Yes

MATERIAL

cover	diffuse cover
material (cover)	PC
material (housing)	PC
housing color	White

SCOPE OF DELIVERY

includes mounting material

DIMENSION

L x W x H / Ø (H2)	Ø 144 (125) x 46 mm
weight	0,3 kg