


# ClickLUX 2.0

5000-90 EM-EB



## LIGHT DISTRIBUTION CURVE



## TECHNICAL DRAWING



## LIGHT INFORMATION

beam angle	90°
color temperature	5.000 K
color tolerance	< 4 SDCM
color rendering index	> 80

## PROPERTIES

through-wiring	4 x 1,5 mm² + 1 x 2,5 mm²
connection	Plug: 7-pole max. 2,5 mm²
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz

## ORDER OVERVIEW

ClickLUX 2.0 5000-90 EM-EB (self-contained)

product code	701550220095
EAN code	4260374019275
warranty	5 years

## ACCESSORIES

ClickLUX connection plug

ClickLUX connector cable 1500mm

ClickLUX 2.0 blank module

ClickLUX 2.0 blank cover

ClickLUX 2.0 clip system 1

ClickLUX 2.0 clip system 3

ClickLUX 2.0 mounting clip for blank cover

## PERFORMANCE

luminous efficiency	155 lm/W
system performance	56 W
luminous flux	8.700 lm
dimmmable	Dip switch

## RESILIENCE

protection class	I
impact resistance	IK05
protection type	IP40
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	0 to +50°C
foodready	Available on request

## MATERIAL

cover	diffuse cover
material (cover)	PC
material (housing)	Aluminium
housing color	Grey

## SCOPE OF DELIVERY

mounting clip system type 2 pre-installed

## DIMENSION

L x W x H / Ø (H2)	1.528 x 67 x 65 mm
weight	2,2 kg