




IndustryLUX FLAT NEO


234 | 50 x 140°



LIGHT DISTRIBUTION CURVE



TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	50 x 140°
color temperature	5.000 K
color tolerance	< 5 SDCM
color rendering index	< 80

PROPERTIES

through-wiring	No
connection	Plug: 3-pole max. 2,5 mm ²
module per circuit breaker B10A	1
module per circuit breaker B16A	3
module per circuit breaker C10A	2
module per circuit breaker C16A	4
switching cycles	> 500.000
voltage range AC	100 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

IndustryLUX FLAT NEO 234 50 x 140°	
product code	445023510039
EAN code	4260374015369
warranty	5 years

ACCESSORIES

No accessories available

PERFORMANCE

luminous efficiency	144 lm/W
system performance	234 W
luminous flux	33.600 lm
dimnable	No

RESILIENCE

protection class	I
impact resistance	IK10
protection type	IP65
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	–40 to +50 °C
foodready	No

MATERIAL

cover	Transparent cover
material (cover)	PC
material (housing)	Aluminium
housing color	Black

SCOPE OF DELIVERY

includes connector plug

DIMENSION

L x W x H / Ø (H2)	381 x 438 (509) x 58 (318) mm
weight	9,1 kg