

SDVR-110151-ZA

4CH 5 IN 1 DIGITAL VIDEO RECORDER (2MP)



Product Highlights

- 5 in1 4CH Metal DVR
- Supported Upto 2 MP Input
- Recording 15 FPS @ 1080N Resolution
- Supports Analogue/AHD/HDCVI/HDTVI/IP
- Supports 4CH BNC + 2CH IP
- Supports 1CH Audio
- Supports WIFI
- Supports P2P
- Supports 1 SATA upto 6 TB
- Supports Intelligent Function
- Supports HDMI/VGA
- Supports Free Dropbox upload upto 2 GB
- 12V DC/2A with 24W Power Consumption


Specifications

Model Number	SDVR-110151-ZA
System	
Video System	PAL/NTSC
Operating System	Linux (Embedded)
Video IN	
No. of Channels	4ch BNC
No. of Analogue/ AHD /HDCVI / HDTVI/ IP Input	4ch BNC + 2ch IP input
Video Resolution Live	1080N
Recording Speed	960 * 1080 @ 15 fps each ch, 720 @ 15 fps each ch, 960H @ 30 fps each ch
Audio In / Out	
No. of Channels IN	1
No. of Channels OUT	1
Display	
Interface	1 HDMI, 1 VGA
Multi Screen Display	1/4/6
OSD Menu	Camera Title, Time, Video Loss, Camera Lock, Motion Detection, Recording
Recording	
Compression	H.265 , H.264
Resolution	Analog/AHD/HDCVI/HDTVI : 1080N/720P/960H IP : 2MP/720P/960H
Record Rate	1080 @ 15 fps each ch, 720 @ 15 fps each ch, 960H @ 30 fps each ch
Bitrate	32~6144 Kbps
Frame Rate Live	25 fps @ 1080N
Frame Rate Playback	15fps @ 8ch
Record Interval	1 min - 9 min
Total Bandwidth	10 Mbps
Recording	
Playback	Synchronous Playback
Search Mode	Time/Date, Alarm, Motion Detection and Exact Search
Playback Function	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen , Repeat, Shuffle, Backup Selection, Digital Zoom
Video Detection & Alarm	
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer & Screen Tips
Video Detection	Motion Detection, MD Zones : 396 (22 * 18) , Video Loss, Tampering & Diagnosis
Storage	
Internal HDD	1 SATA upto 6 TB
Backup	
USB	1 × 2.0, 1 × 3.0
Network	
Interface	1 RJ-45 (100M)
Network Function	HTTP, TCP/IP, IPv4/IPv6, WIFI, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, P2P, IP Search
Smart Phone	Android & iOS
Interoperability	ONVIF 2.42

Specifications

Auxilliary Interface	
RS485	Yes
Electrical	
Power Supply	12V DC / 2A
Power Consumption	24 Watts
Enviromental	
Operating Temperature	-10°C - 50°C and 90% humidity or less than that
Storage Temperature	Below 40°C
Construction	
Dimensions	300 × 227 × 53mm
Included Accessories	Power Supply, Mouse, Remote Control, HDD Connectors, Software CD, User Manual
Certifications	CE, FCC, UL & RoHS

Dimensions



Rear Panel

