Business Continuity and Recovery Plan

Document owner: Business Resilience

Review frequency: Annual

Classification: Internal

Purpose

Coordinate service recovery while preserving tenant and authorization boundaries.

Scope

Covers RAGVault API, PostgreSQL, Qdrant, document storage, identity dependencies, and operator communications.

Definitions

Control owner: the role accountable for implementation and evidence.

Exception: a documented, approved, and time-bounded deviation.

Roles and responsibilities

The incident commander sets recovery priorities.

Service owners restore components and verify health.

Security validates access controls before user traffic resumes.

Mandatory rules

Recovery objectives are approved by service owners.

Backups are protected separately from production credentials.

A restored vector index must match the source tenant and ACL metadata.

Failover does not bypass authentication or authorization.

Unverified content is not exposed during degraded operation.

Operating procedure

Declare the incident and assign a recovery lead.

Restore database state from the approved recovery point.

Restore or rebuild vectors from authorized source records.

Run health, tenant-filter, and permission checks in a restricted environment.

Resume traffic after security and business owners accept evidence.

Examples

If Qdrant is rebuilt, re-ingest through the tenant-aware document workflow.

If the API is unavailable, users receive a service notice rather than an alternate unsecured export.

Exceptions

Emergency access is time-limited and logged.

A recovery exception names the approver and compensating monitoring.

Audit evidence and review

Record recovery point, component versions, verification results, and downtime.

Run a tabletop exercise annually and track corrective actions.