

Scan Report

October 1, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “Immediate scan of IP 10.199.231.85”. The scan started at Thu Oct 1 14:56:48 2026 UTC and ended at Thu Oct 1 16:04:18 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
1.1	Host Authentications	2
2	Results per Host	2
2.1	10.199.231.85	2
2.1.1	Critical 21/tcp	2
2.1.2	Critical 80/tcp	3
2.1.3	Critical 22/tcp	4
2.1.4	High 631/tcp	5
2.1.5	High 21/tcp	7
2.1.6	High 80/tcp	8
2.1.7	Medium 631/tcp	10
2.1.8	Medium 21/tcp	12
2.1.9	Medium 80/tcp	13
2.1.10	Medium 22/tcp	18
2.1.11	Low 22/tcp	21
2.1.12	Low general/icmp	22
2.1.13	Low general/tcp	23

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
10.199.231.85	3	4	13	3	0	0
Total: 1	3	4	13	3	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 23 results selected by the filtering described above. Before filtering there were 444 results.

1.1 Host Authentications

Host	Protocol	Result	Port/User
10.199.231.85	SMB	Success	Protocol SMB, Port 445, User

2 Results per Host

2.1 10.199.231.85

Host scan start Thu Oct 1 14:57:55 2026 UTC

Host scan end Thu Oct 1 16:04:14 2026 UTC

Service (Port)	Threat Level
21/tcp	Critical
80/tcp	Critical
22/tcp	Critical
631/tcp	High
21/tcp	High
80/tcp	High
631/tcp	Medium
21/tcp	Medium
80/tcp	Medium
22/tcp	Medium
22/tcp	Low
general/icmp	Low
general/tcp	Low

2.1.1 Critical 21/tcp

Critical (CVSS: 10.0)

NVT: ProFTPD 'mod_copy' Unauthenticated Copying Of Files Via SITE CPFR/CPTO Vulnerability (Apr 2015) - Active Check

Summary

... continues on next page ...

...continued from previous page ...
ProFTPD is prone to an unauthenticated copying of files vulnerability.
Quality of Detection (QoD): 99%
Vulnerability Detection Result The target was found to be vulnerable
Impact Under some circumstances this could result in remote code execution.
Solution: Solution type: VendorFix Ask the vendor for an update.
Vulnerability Detection Method Tries to copy /etc/passwd to /tmp/passwd.copy with SITE CPFR/CPTO command. Details: ProFTPD 'mod_copy' Unauthenticated Copying Of Files Via SITE CPFR/CPTO Vulnerab. ↪... OID:1.3.6.1.4.1.25623.1.0.105254 Version used: 2026-03-17T05:57:28Z
References cve: CVE-2015-3306 url: http://bugs.proftpd.org/show_bug.cgi?id=4169 cert-bund: CB-K15/0791 cert-bund: CB-K15/0553 dfn-cert: DFN-CERT-2015-0839 dfn-cert: DFN-CERT-2015-0576

[[return to 10.199.231.85](#)]

2.1.2 Critical 80/tcp

Critical (CVSS: 10.0)
NVT: Drupal Coder RCE Vulnerability (SA-CONTRIB-2016-039) - Active Check
Summary Drupal is prone to a remote code execution (RCE) vulnerability.
Quality of Detection (QoD): 95%
Vulnerability Detection Result Vulnerable URL: http://10.199.231.85/drupal/sites/all/modules/coder/coder_upgrad ↪e/scripts/coder_upgrade.run.php
Solution: Solution type: VendorFix Install the latest version.
Vulnerability Insight The Coder module checks your Drupal code against coding standards and other best practices. It can also fix coding standard violations and perform basic upgrades on modules. The module doesn't sufficiently validate user inputs in a script file that has the php extension. A malicious unauthenticated user can make requests directly to this file to execute arbitrary php code.
Vulnerability Detection Method Checks for known error message from affected modules. Details: Drupal Coder RCE Vulnerability (SA-CONTRIB-2016-039) - Active Check OID:1.3.6.1.4.1.25623.1.0.105818 Version used: 2023-07-21T05:05:22Z
References url: https://www.drupal.org/node/2765575

[[return to 10.199.231.85](#)]

2.1.3 Critical 22/tcp

Critical (CVSS: 9.8)
NVT: SSH Brute Force Logins With Default Credentials Reporting
Summary It was possible to login into the remote SSH server using default credentials.
Quality of Detection (QoD): 95%
Vulnerability Detection Result It was possible to login with the following credentials <User>:<Password> vagrant:vagrant
Impact This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.
Solution: Solution type: Mitigation Change the password as soon as possible.
Affected Software/OS The following products are known to use the default credentials checked by the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013) used for this reporting: - CVE-2017-16523: MitraStar GPT-2541GNAC (HGU) 1.00(VNJ0)b1 and DSL-100HN-T1 ES_113WJY0b16 devices - CVE-2017-20214: FLIR Thermal Camera F/FC/PT/D - CVE-2018-25138: FLIR AX8 Thermal Camera - CVE-2018-25147: Microhard Systems IPn4G - CVE-2019-25241: FaceSentry Access Control System - CVE-2019-25291: INIM Electronics Smartliving SmartLAN/G/SI - CVE-2020-29583: Zyxel Firewall / AP Controller - CVE-2020-36915: Adtec Digital SignEdge Digital Signage Player - CVE-2020-37092: Netis E1+ devices - CVE-2020-9473: S. Siedle & Soehne SG 150-0 Smart Gateway before 1.2.4 - CVE-2021-27797: Brocade Fabric OS - CVE-2021-47744: Cypress Solutions CTM-200/CTM-ONE - CVE-2023-1944: minikube 1.29.0 and probably prior - CVE-2023-53983: Anevia Flamingo XL/XS - CVE-2024-22902: Vinchin Backup & Recovery - CVE-2024-31970: AdTran SRG 834-5 HDC17600021F1 devices (with SmartOS 11.1.1.1) during a window of time when the device is being set up - CVE-2024-46328: VONETS VAP11G-300 v3.3.23.6.9 - CVE-2025-12592: Legacy Vivotek devices - CVE-2025-68718: KAYSUS KS-WR1200 - CVE-2026-36538: Netis AC1200 Router NC21 V4.0.1.4296 - CVE-2026-35905: T3 Technology CPE models T625Pro v1.0.07, T6825G v1.0.03 and T7281 v1.0.03 - Various additional products like e.g. Ubiquiti EdgeMax / EdgeRouter, Crestron AM-100 and similar for which no CVE was assigned (See 'default_credentials.inc' file on the file system for a full list) Other products might be affected as well.
Vulnerability Insight As the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.
Vulnerability Detection Method Reports default credentials detected by the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013). Details: SSH Brute Force Logins With Default Credentials Reporting OID:1.3.6.1.4.1.25623.1.0.103239 Version used: 2026-06-10T06:59:19Z
References cve: CVE-1999-0501 cve: CVE-1999-0502 cve: CVE-1999-0507 cve: CVE-1999-0508 cve: CVE-2005-1379
... continues on next page ...

...continued from previous page ...	
cve:	CVE-2006-5288
cve:	CVE-2009-3710
cve:	CVE-2012-4577
cve:	CVE-2016-1000245
cve:	CVE-2017-16523
cve:	CVE-2017-20214
cve:	CVE-2018-25138
cve:	CVE-2018-25147
cve:	CVE-2019-25241
cve:	CVE-2019-25291
cve:	CVE-2020-29583
cve:	CVE-2020-36915
cve:	CVE-2020-37092
cve:	CVE-2020-9473
cve:	CVE-2021-27797
cve:	CVE-2021-47744
cve:	CVE-2023-1944
cve:	CVE-2023-53983
cve:	CVE-2024-22902
cve:	CVE-2024-31970
cve:	CVE-2024-46328
cve:	CVE-2025-12592
cve:	CVE-2025-41696
cve:	CVE-2025-68718
cve:	CVE-2026-36538
cve:	CVE-2026-35905
url:	https://www.cisa.gov/known-exploited-vulnerabilities-catalog
cisa:	Known Exploited Vulnerability (KEV) catalog
cert-bund:	WID-SEC-2025-2760

[[return to 10.199.231.85](#)]

2.1.4 High 631/tcp

High (CVSS: 7.5)	
NVT: SSL/TLS: Report Vulnerable Cipher Suites for HTTPS	
Product detection result cpe:/a:ietf:transport_layer_security Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0. ↪802067)	
Summary This routine reports all SSL/TLS cipher suites accepted by a service where attack vectors exists only on HTTPS services.	
Quality of Detection (QoD): 98%	
Vulnerability Detection Result 'Vulnerable' cipher suites accepted by this service via the TLSv1.0 protocol: TLS_RSA_WITH_3DES_EDE_CBC_SHA (SWEET32) 'Vulnerable' cipher suites accepted by this service via the TLSv1.1 protocol: TLS_RSA_WITH_3DES_EDE_CBC_SHA (SWEET32) 'Vulnerable' cipher suites accepted by this service via the TLSv1.2 protocol: TLS_RSA_WITH_3DES_EDE_CBC_SHA (SWEET32)	
Impact This could allow remote attackers to obtain sensitive information or have other, unspecified impacts.	
Solution: Solution type: Mitigation The configuration of this services should be changed so that it does not accept the listed cipher suites anymore. Please see the references for more resources supporting you with this task.	
Affected Software/OS	
...continues on next page ...	

...continued from previous page ...
All services accepting vulnerable SSL/TLS cipher suites via HTTPS.
Vulnerability Insight These rules are applied for the evaluation of the vulnerable cipher suites: - 64-bit block cipher 3DES vulnerable to the SWEET32 attack (CVE-2016-2183).
Vulnerability Detection Method Checks previous collected cipher suites. Details: SSL/TLS: Report Vulnerable Cipher Suites for HTTPS OID:1.3.6.1.4.1.25623.1.0.108031 Version used: 2026-06-03T07:18:10Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security Method: SSL/TLS: Report Supported Cipher Suites OID: 1.3.6.1.4.1.25623.1.0.802067
References cve: CVE-2016-2183 cve: CVE-2016-6329 cve: CVE-2020-12872 url: https://configurator.tlsref.org/ url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014 url: https://sweet32.info cert-bund: WID-SEC-2026-0180 cert-bund: WID-SEC-2024-1277 cert-bund: WID-SEC-2024-0209 cert-bund: WID-SEC-2024-0064 cert-bund: WID-SEC-2022-2226 cert-bund: WID-SEC-2022-1955 cert-bund: CB-K21/1094 cert-bund: CB-K20/1023 cert-bund: CB-K20/0321 cert-bund: CB-K20/0314 cert-bund: CB-K20/0157 cert-bund: CB-K19/0618 cert-bund: CB-K19/0615 cert-bund: CB-K18/0296 cert-bund: CB-K17/1980 cert-bund: CB-K17/1871 cert-bund: CB-K17/1803 cert-bund: CB-K17/1753 cert-bund: CB-K17/1750 cert-bund: CB-K17/1709 cert-bund: CB-K17/1558 cert-bund: CB-K17/1273 cert-bund: CB-K17/1202 cert-bund: CB-K17/1196 cert-bund: CB-K17/1055 cert-bund: CB-K17/1026 cert-bund: CB-K17/0939 cert-bund: CB-K17/0917 cert-bund: CB-K17/0915 cert-bund: CB-K17/0877 cert-bund: CB-K17/0796 cert-bund: CB-K17/0724 cert-bund: CB-K17/0661 cert-bund: CB-K17/0657 cert-bund: CB-K17/0582 cert-bund: CB-K17/0581 cert-bund: CB-K17/0506 cert-bund: CB-K17/0504 cert-bund: CB-K17/0467 cert-bund: CB-K17/0345
...continues on next page ...

...continued from previous page ...

```

cert-bund: CB-K17/0098
cert-bund: CB-K17/0089
cert-bund: CB-K17/0086
cert-bund: CB-K17/0082
cert-bund: CB-K16/1837
cert-bund: CB-K16/1830
cert-bund: CB-K16/1635
cert-bund: CB-K16/1630
cert-bund: CB-K16/1624
cert-bund: CB-K16/1622
cert-bund: CB-K16/1500
cert-bund: CB-K16/1465
cert-bund: CB-K16/1307
cert-bund: CB-K16/1296
dfn-cert: DFN-CERT-2025-0041
dfn-cert: DFN-CERT-2021-1618
dfn-cert: DFN-CERT-2021-0775
dfn-cert: DFN-CERT-2021-0770
dfn-cert: DFN-CERT-2021-0274
dfn-cert: DFN-CERT-2020-2141
dfn-cert: DFN-CERT-2020-0368
dfn-cert: DFN-CERT-2019-1455
dfn-cert: DFN-CERT-2019-0068
dfn-cert: DFN-CERT-2018-1296
dfn-cert: DFN-CERT-2018-0323
dfn-cert: DFN-CERT-2017-2070
dfn-cert: DFN-CERT-2017-1954
dfn-cert: DFN-CERT-2017-1885
dfn-cert: DFN-CERT-2017-1831
dfn-cert: DFN-CERT-2017-1821
dfn-cert: DFN-CERT-2017-1785
dfn-cert: DFN-CERT-2017-1626
dfn-cert: DFN-CERT-2017-1326
dfn-cert: DFN-CERT-2017-1239
dfn-cert: DFN-CERT-2017-1238
dfn-cert: DFN-CERT-2017-1090
dfn-cert: DFN-CERT-2017-1060
dfn-cert: DFN-CERT-2017-0968
dfn-cert: DFN-CERT-2017-0947
dfn-cert: DFN-CERT-2017-0946
dfn-cert: DFN-CERT-2017-0904
dfn-cert: DFN-CERT-2017-0816
dfn-cert: DFN-CERT-2017-0746
dfn-cert: DFN-CERT-2017-0677
dfn-cert: DFN-CERT-2017-0675
dfn-cert: DFN-CERT-2017-0611
dfn-cert: DFN-CERT-2017-0609
dfn-cert: DFN-CERT-2017-0522
dfn-cert: DFN-CERT-2017-0519
dfn-cert: DFN-CERT-2017-0482
dfn-cert: DFN-CERT-2017-0351
dfn-cert: DFN-CERT-2017-0090
dfn-cert: DFN-CERT-2017-0089
dfn-cert: DFN-CERT-2017-0088
dfn-cert: DFN-CERT-2017-0086
dfn-cert: DFN-CERT-2016-1943
dfn-cert: DFN-CERT-2016-1937
dfn-cert: DFN-CERT-2016-1732
dfn-cert: DFN-CERT-2016-1726
dfn-cert: DFN-CERT-2016-1715
dfn-cert: DFN-CERT-2016-1714
dfn-cert: DFN-CERT-2016-1588
dfn-cert: DFN-CERT-2016-1555
dfn-cert: DFN-CERT-2016-1391
dfn-cert: DFN-CERT-2016-1378

```

[\[return to 10.199.231.85 \]](#)

2.1.5 High 21/tcp

High (CVSS: 7.5)
NVT: FTP Brute Force Logins With Default Credentials Reporting
Summary It was possible to login into the remote FTP server using weak/known credentials.
Quality of Detection (QoD): 95%
Vulnerability Detection Result It was possible to login with the following credentials <User>:<Password> vagrant:vagrant
Impact This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.
Solution: Solution type: Mitigation Change the password as soon as possible.
Vulnerability Insight The following devices are / software is known to be affected: - CVE-2001-1594: Codonics printer FTP service as used in GE Healthcare eNTEGRA P&R - CVE-2013-7404: GE Healthcare Discovery NM 750b - CVE-2014-9198: Schneider Electric ETG3000 FactoryCast HMI gateways - CVE-2015-7261: QNAP iArtist Lite distributed with QNAP Signage Station - CVE-2016-8731: Foscam C1 devices - CVE-2017-8218: vsftpd on TP-Link C2 and C20i devices - CVE-2018-9068: IMM2 for IBM and Lenovo System x - CVE-2018-17771: Ingenico Telium 2 PoS terminals - CVE-2018-19063, CVE-2018-19064: Foscam C2 and Opticam i5 devices - CVE-2018-25147: Microhard Systems IPn4G - CVE-2020-36915: Adtec Digital SignEdge Digital Signage Player Note: As the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.
Vulnerability Detection Method Reports weak/known credentials detected by the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717). Details: FTP Brute Force Logins With Default Credentials Reporting OID:1.3.6.1.4.1.25623.1.0.108718 Version used: 2026-01-16T15:42:49Z
References cve: CVE-1999-0501 cve: CVE-1999-0502 cve: CVE-1999-0507 cve: CVE-1999-0508 cve: CVE-2001-1594 cve: CVE-2013-7404 cve: CVE-2014-9198 cve: CVE-2015-7261 cve: CVE-2016-8731 cve: CVE-2017-8218 cve: CVE-2018-9068 cve: CVE-2018-17771 cve: CVE-2018-19063 cve: CVE-2018-19064 cve: CVE-2018-25147 cve: CVE-2020-36915

[\[return to 10.199.231.85 \]](#)

2.1.6 High 80/tcp

High (CVSS: 7.5)
NVT: Drupal Core SQLi Vulnerability (SA-CORE-2014-005) - Active Check
Summary Drupal is prone to an SQL injection (SQLi) vulnerability.
Quality of Detection (QoD): 98%
Vulnerability Detection Result Vulnerable URL: http://10.199.231.85/drupal/?q=node&destination=node
Impact Exploiting this issue could allow an attacker to execute arbitrary code, to gain elevated privileges and to compromise the application, access or modify data, or exploit latent vulnerabilities in the underlying database.
Solution: Solution type: VendorFix Updates are available. Please see the references for more information.
Affected Software/OS Drupal 7.x versions prior to 7.32 are vulnerable.
Vulnerability Insight Drupal fails to sufficiently sanitize user-supplied data before using it in an SQL query.
Vulnerability Detection Method Sends a special crafted HTTP POST request and checks the response. Details: Drupal Core SQLi Vulnerability (SA-CORE-2014-005) - Active Check OID:1.3.6.1.4.1.25623.1.0.105101 Version used: 2023-07-26T05:05:09Z
References cve: CVE-2014-3704 url: https://www.drupal.org/forum/newsletters/security-advisories-for-drupal-core/2014-10-15/sa-core-2014-005-drupal-core-sql url: http://www.securityfocus.com/bid/70595 cert-bund: CB-K14/1301 cert-bund: CB-K14/0920 dfn-cert: DFN-CERT-2014-1369 dfn-cert: DFN-CERT-2014-0958

High (CVSS: 7.5)
NVT: Test HTTP dangerous methods
Summary Misconfigured web servers allows remote clients to perform dangerous HTTP methods such as PUT and DELETE.
Quality of Detection (QoD): 99%
Vulnerability Detection Result We could upload the following files via the PUT method at this web server: http://10.199.231.85/uploads/puttest594193309.html We could delete the following files via the DELETE method at this web server: http://10.199.231.85/uploads/puttest594193309.html
Impact - Enabled PUT method: This might allow an attacker to upload and run arbitrary code on this web server. - Enabled DELETE method: This might allow an attacker to delete additional files on this web server.
Solution: Solution type: Mitigation Use access restrictions to these dangerous HTTP methods or disable them completely.
Affected Software/OS Web servers with enabled PUT and/or DELETE methods.
... continues on next page ...

...continued from previous page ...
Vulnerability Detection Method Checks if dangerous HTTP methods such as PUT and DELETE are enabled and can be misused to upload or delete files. Details: Test HTTP dangerous methods OID:1.3.6.1.4.1.25623.1.0.10498 Version used: 2023-08-01T13:29:10Z
References url: http://www.securityfocus.com/bid/12141 owasp: OWASP-CM-001

[[return to 10.199.231.85](#)]

2.1.7 Medium 631/tcp

Medium (CVSS: 4.3)
NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection
Product detection result cpe:/a:ietf:transport_layer_security:1.0 Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)
Summary It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.
Quality of Detection (QoD): 98%
Vulnerability Detection Result In addition to TLSv1.2+ the service is also providing the deprecated TLSv1.0 and ↪ TLSv1.1 protocols and supports one or more ciphers. Those supported ciphers c ↪an be found in the 'SSL/TLS: Report Supported Cipher Suites' (OID: 1.3.6.1.4.1 ↪.25623.1.0.802067) VT.
Impact An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection. Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.
Solution: Solution type: Mitigation It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols. Please see the references for more resources supporting you with this task.
Affected Software/OS - All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols - CVE-2023-41928: Kiloview P1 4G and P2 4G Video Encoder - CVE-2024-41270: Gorush v1.18.4 - CVE-2025-3200: Multiple products from Wiesemann & Theis
Vulnerability Insight The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like: - CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST) - CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)
Vulnerability Detection Method Checks the used TLS protocols of the services provided by this system. Details: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection OID:1.3.6.1.4.1.25623.1.0.117274 Version used: 2026-06-03T07:18:10Z
Product Detection Result ...continues on next page ...

...continued from previous page ...
Product: cpe:/a:ietf:transport_layer_security:1.0 Method: SSL/TLS: Version Detection OID: 1.3.6.1.4.1.25623.1.0.105782
References cve: CVE-2011-3389 cve: CVE-2015-0204 cve: CVE-2023-41928 cve: CVE-2024-41270 cve: CVE-2025-3200 url: https://configurator.tlsref.org/ url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014 url: https://datatracker.ietf.org/doc/rfc8996/ url: https://vnhacker.blogspot.com/2011/09/beast.html url: https://web.archive.org/web/20201108095603/https://censys.io/blog/freak url: https://certvde.com/en/advisories/VDE-2025-031/ url: https://gist.github.com/nyxfqq/cfae38fada582a0f576d154belaeb1fc url: https://advisories.ncsc.nl/advisory?id=NCSC-2024-0273 cert-bund: WID-SEC-2026-0180 cert-bund: WID-SEC-2023-1435 cert-bund: CB-K18/0799 cert-bund: CB-K16/1289 cert-bund: CB-K16/1096 cert-bund: CB-K15/1751 cert-bund: CB-K15/1266 cert-bund: CB-K15/0850 cert-bund: CB-K15/0764 cert-bund: CB-K15/0720 cert-bund: CB-K15/0548 cert-bund: CB-K15/0526 cert-bund: CB-K15/0509 cert-bund: CB-K15/0493 cert-bund: CB-K15/0384 cert-bund: CB-K15/0365 cert-bund: CB-K15/0364 cert-bund: CB-K15/0302 cert-bund: CB-K15/0192 cert-bund: CB-K15/0079 cert-bund: CB-K15/0016 cert-bund: CB-K14/1342 cert-bund: CB-K14/0231 cert-bund: CB-K13/0845 cert-bund: CB-K13/0796 cert-bund: CB-K13/0790 dfn-cert: DFN-CERT-2020-0177 dfn-cert: DFN-CERT-2020-0111 dfn-cert: DFN-CERT-2019-0068 dfn-cert: DFN-CERT-2018-1441 dfn-cert: DFN-CERT-2018-1408 dfn-cert: DFN-CERT-2016-1372 dfn-cert: DFN-CERT-2016-1164 dfn-cert: DFN-CERT-2016-0388 dfn-cert: DFN-CERT-2015-1853 dfn-cert: DFN-CERT-2015-1332 dfn-cert: DFN-CERT-2015-0884 dfn-cert: DFN-CERT-2015-0800 dfn-cert: DFN-CERT-2015-0758 dfn-cert: DFN-CERT-2015-0567 dfn-cert: DFN-CERT-2015-0544 dfn-cert: DFN-CERT-2015-0530 dfn-cert: DFN-CERT-2015-0396 dfn-cert: DFN-CERT-2015-0375 dfn-cert: DFN-CERT-2015-0374 dfn-cert: DFN-CERT-2015-0305
...continues on next page ...

...continued from previous page ...	
dfn-cert:	DFN-CERT-2015-0199
dfn-cert:	DFN-CERT-2015-0079
dfn-cert:	DFN-CERT-2015-0021
dfn-cert:	DFN-CERT-2014-1414
dfn-cert:	DFN-CERT-2013-1847
dfn-cert:	DFN-CERT-2013-1792
dfn-cert:	DFN-CERT-2012-1979
dfn-cert:	DFN-CERT-2012-1829
dfn-cert:	DFN-CERT-2012-1530
dfn-cert:	DFN-CERT-2012-1380
dfn-cert:	DFN-CERT-2012-1377
dfn-cert:	DFN-CERT-2012-1292
dfn-cert:	DFN-CERT-2012-1214
dfn-cert:	DFN-CERT-2012-1213
dfn-cert:	DFN-CERT-2012-1180
dfn-cert:	DFN-CERT-2012-1156
dfn-cert:	DFN-CERT-2012-1155
dfn-cert:	DFN-CERT-2012-1039
dfn-cert:	DFN-CERT-2012-0956
dfn-cert:	DFN-CERT-2012-0908
dfn-cert:	DFN-CERT-2012-0868
dfn-cert:	DFN-CERT-2012-0867
dfn-cert:	DFN-CERT-2012-0848
dfn-cert:	DFN-CERT-2012-0838
dfn-cert:	DFN-CERT-2012-0776
dfn-cert:	DFN-CERT-2012-0722
dfn-cert:	DFN-CERT-2012-0638
dfn-cert:	DFN-CERT-2012-0627
dfn-cert:	DFN-CERT-2012-0451
dfn-cert:	DFN-CERT-2012-0418
dfn-cert:	DFN-CERT-2012-0354
dfn-cert:	DFN-CERT-2012-0234
dfn-cert:	DFN-CERT-2012-0221
dfn-cert:	DFN-CERT-2012-0177
dfn-cert:	DFN-CERT-2012-0170
dfn-cert:	DFN-CERT-2012-0146
dfn-cert:	DFN-CERT-2012-0142
dfn-cert:	DFN-CERT-2012-0126
dfn-cert:	DFN-CERT-2012-0123
dfn-cert:	DFN-CERT-2012-0095
dfn-cert:	DFN-CERT-2012-0051
dfn-cert:	DFN-CERT-2012-0047
dfn-cert:	DFN-CERT-2012-0021
dfn-cert:	DFN-CERT-2011-1953
dfn-cert:	DFN-CERT-2011-1946
dfn-cert:	DFN-CERT-2011-1844
dfn-cert:	DFN-CERT-2011-1826
dfn-cert:	DFN-CERT-2011-1774
dfn-cert:	DFN-CERT-2011-1743
dfn-cert:	DFN-CERT-2011-1738
dfn-cert:	DFN-CERT-2011-1706
dfn-cert:	DFN-CERT-2011-1628
dfn-cert:	DFN-CERT-2011-1627
dfn-cert:	DFN-CERT-2011-1619
dfn-cert:	DFN-CERT-2011-1482

[\[return to 10.199.231.85 \]](#)

2.1.8 Medium 21/tcp

Medium (CVSS: 4.8)
NVT: FTP Unencrypted Cleartext Login
Summary The remote host is running a FTP service that allows cleartext logins over unencrypted connections.
...continues on next page ...

...continued from previous page ...
Quality of Detection (QoD): 70%
Vulnerability Detection Result The remote FTP service accepts logins without a previous sent 'AUTH TLS' command ↔. Response(s): Non-anonymous sessions: 331 Password required for gbvt Anonymous sessions: 331 Anonymous login ok, send your complete email address ↔ as your password
Impact An attacker can uncover login names and passwords by sniffing traffic to the FTP service.
Solution: Solution type: Mitigation Enable FTPS or enforce the connection via the 'AUTH TLS' command. Please see the manual of the FTP service for more information.
Vulnerability Detection Method Tries to login to a non FTPS enabled FTP service without sending a 'AUTH TLS' command first and checks if the service is accepting the login without enforcing the use of the 'AUTH TLS' command. Details: FTP Unencrypted Cleartext Login OID:1.3.6.1.4.1.25623.1.0.108528 Version used: 2023-12-20T05:05:58Z

[[return to 10.199.231.85](#)]

2.1.9 Medium 80/tcp

Medium (CVSS: 6.1)
NVT: jQuery < 1.9.0 XSS Vulnerability
Summary jQuery is prone to a cross-site scripting (XSS) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 1.6.2 Fixed version: 1.9.0 Installation path / port: /phpmyadmin/setup/./js/jquery/jquery-1.6.2.js Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info): - Identified file: http://10.199.231.85/phpmyadmin/setup/./js/jquery/jquery-1.6 ↔.2.js - Referenced at: http://10.199.231.85/phpmyadmin/setup/
Solution: Solution type: VendorFix Update to version 1.9.0 or later.
Affected Software/OS jQuery prior to version 1.9.0.
Vulnerability Insight The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '<' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '<' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.
Vulnerability Detection Method Checks if a vulnerable version is present on the target host.
...continues on next page ...

Details: jQuery < 1.9.0 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141636 Version used: 2023-07-14T05:06:08Z	...continued from previous page ...
References cve: CVE-2012-6708 url: https://bugs.jquery.com/ticket/11290 cert-bund: WID-SEC-2026-1752 cert-bund: WID-SEC-2022-0673 cert-bund: CB-K22/0045 cert-bund: CB-K18/1131 dfn-cert: DFN-CERT-2025-1803 dfn-cert: DFN-CERT-2023-1197 dfn-cert: DFN-CERT-2020-0590	

Medium (CVSS: 6.1)
NVT: jQuery < 1.9.0 XSS Vulnerability
Summary jQuery is prone to a cross-site scripting (XSS) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 1.6.2 Fixed version: 1.9.0 Installation path / port: /phpmyadmin/js/jquery/jquery-1.6.2.js Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info): - Identified file: http://10.199.231.85/phpmyadmin/js/jquery/jquery-1.6.2.js - Referenced at: http://10.199.231.85/phpmyadmin/
Solution: Solution type: VendorFix Update to version 1.9.0 or later.
Affected Software/OS jQuery prior to version 1.9.0.
Vulnerability Insight The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '<' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '<' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: jQuery < 1.9.0 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141636 Version used: 2023-07-14T05:06:08Z
References cve: CVE-2012-6708 url: https://bugs.jquery.com/ticket/11290 cert-bund: WID-SEC-2026-1752 cert-bund: WID-SEC-2022-0673 cert-bund: CB-K22/0045 cert-bund: CB-K18/1131 dfn-cert: DFN-CERT-2025-1803 dfn-cert: DFN-CERT-2023-1197 dfn-cert: DFN-CERT-2020-0590

Medium (CVSS: 5.0)
NVT: Sensitive File Disclosure (HTTP)
Summary The script attempts to identify files containing sensitive data at the remote web server.
Quality of Detection (QoD): 70%
Vulnerability Detection Result The following files containing sensitive information were identified: Description: Microsoft IIS / ASP.NET Core Module web.config file accessible. T ↪his could contain sensitive information about the structure of the application ↪ / web server and shouldn't be accessible. Match: <configuration> <system.webServer> Used regex: ^\s*<(configuration system\.web(Server)?>> Extra match 1: </system.webServer> </configuration> Used regex: ^\s*</(configuration system\.web(Server)?>> URL: http://10.199.231.85/drupal/web.config
Impact Based on the information provided in these files an attacker might be able to gather additional info and/or sensitive data like usernames and passwords.
Solution: Solution type: Mitigation The sensitive files shouldn't be accessible via a web server. Restrict access to it or remove it completely.
Vulnerability Insight Currently the script is checking for files like e.g.: - Software (Blog, CMS) configuration or log files - Web / application server configuration / password files (e.g. .htaccess, .htpasswd, web.config, web.xml, ...) - Cloud (e.g. AWS) configuration files - Files containing API keys for services / providers - Database backup files (e.g. .sql, ...) - Editor / history files (e.g. .lessht, .dbshell, ...) - SSH or SSL/TLS Private Keys - Generic environment files (e.g. .env including the ones from Codeigniter, ...) - CVE-2017-16894: Laravel framework specific environment/.env files
Vulnerability Detection Method Enumerate the remote web server and check if sensitive files are accessible. Details: Sensitive File Disclosure (HTTP) OID:1.3.6.1.4.1.25623.1.0.107305 Version used: 2025-10-29T05:40:29Z
References cve: CVE-2017-16894

Medium (CVSS: 5.0)
NVT: Unprotected Web App / Device Installers (HTTP)
Summary The script attempts to identify installation/setup pages of various web apps/devices that are publicly accessible and not protected by e.g. account restrictions or having their setup finished.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following web app/device installers are unprotected/have not finished their ↪setup and are publicly accessible (URL:Description): http://10.199.231.85/phpmyadmin/setup/index.php - CubeCart / phpMyAdmin install ↪r
Impact ... continues on next page ...

...continued from previous page ...
It is possible to install or reconfigure the software. In doing so, the attacker could overwrite existing configurations. It could be possible for the attacker to gain access to the base system
Solution: Solution type: Mitigation Setup and/or installation pages for Web Apps should not be publicly accessible via a web server. Restrict access to it, remove it completely or finish the setup of the application / device.
Vulnerability Detection Method Enumerate the remote web server and check if unprotected web apps/devices are accessible for installation. Details: Unprotected Web App / Device Installers (HTTP) OID:1.3.6.1.4.1.25623.1.0.107307 Version used: 2025-12-18T05:46:55Z

Medium (CVSS: 5.0)
NVT: Drupal 7.0 Information Disclosure Vulnerability - Active Check
Summary Drupal is prone to an information disclosure vulnerability.
Quality of Detection (QoD): 95%
Vulnerability Detection Result Vulnerable URL: http://10.199.231.85/drupal/modules/simpletest/tests/upgrade/drupal-6.upload.database.php
Impact Successful exploitation will allow attacker to obtain sensitive information that could aid in further attacks.
Solution: Solution type: WillNotFix No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.
Affected Software/OS Drupal version 7.0 is known to be affected.
Vulnerability Insight The flaw is due to insufficient error checking, allows remote attackers to obtain sensitive information via a direct request to a .php file, which reveals the installation path in an error message.
Vulnerability Detection Method Details: Drupal 7.0 Information Disclosure Vulnerability - Active Check OID:1.3.6.1.4.1.25623.1.0.902574 Version used: 2021-12-01T11:10:56Z
References cve: CVE-2011-3730 url: http://code.google.com/p/inspathx/source/browse/trunk/paths_vuln/_README url: http://code.google.com/p/inspathx/source/browse/trunk/paths_vuln/drupal-7.0

Medium (CVSS: 4.8)
NVT: Cleartext Transmission of Sensitive Information via HTTP
Summary The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following input fields were identified (URL:input name): ...continues on next page ...

...continued from previous page ...	
<pre> http://10.199.231.85/drupal/:pass http://10.199.231.85/drupal/?D=A:pass http://10.199.231.85/payroll_app.php:password http://10.199.231.85/phpmyadmin/:pma_password http://10.199.231.85/phpmyadmin/?D=A:pma_password http://10.199.231.85/phpmyadmin/changelog.php:pma_password http://10.199.231.85/phpmyadmin/index.php:pma_password http://10.199.231.85/phpmyadmin/license.php:pma_password http://10.199.231.85/phpmyadmin/url.php:pma_password </pre>	
Impact	An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.
Solution:	
Solution type: Workaround	Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.
Affected Software/OS	Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.
Vulnerability Detection Method	Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection. The script is currently checking the following: - HTTP Basic Authentication (Basic Auth) - HTTP Forms (e.g. Login) with input field of type 'password' Details: Cleartext Transmission of Sensitive Information via HTTP OID:1.3.6.1.4.1.25623.1.0.108440 Version used: 2023-09-07T05:05:21Z
References	url: https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management url: https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure url: https://cwe.mitre.org/data/definitions/319.html

Medium (CVSS: 4.3)	
NVT: jQuery < 1.6.3 XSS Vulnerability	
Summary	jQuery is prone to a cross-site scripting (XSS) vulnerability.
Quality of Detection (QoD): 80%	
Vulnerability Detection Result	Installed version: 1.6.2 Fixed version: 1.6.3 Installation path / port: /phpmyadmin/setup/./js/jquery/jquery-1.6.2.js Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info): - Identified file: http://10.199.231.85/phpmyadmin/setup/./js/jquery/jquery-1.6.2.js - Referenced at: http://10.199.231.85/phpmyadmin/setup/
Solution:	
Solution type: VendorFix	Update to version 1.6.3 or later.
Affected Software/OS	jQuery prior to version 1.6.3.
Vulnerability Insight	...continues on next page ...

...continued from previous page ...
Cross-site scripting (XSS) vulnerability in jQuery before 1.6.3, when using location.hash to select elements, allows remote attackers to inject arbitrary web script or HTML via a crafted tag.
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: jQuery < 1.6.3 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141637 Version used: 2023-07-14T05:06:08Z
References cve: CVE-2011-4969 url: https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/ cert-bund: WID-SEC-2026-1752 cert-bund: CB-K17/0195 dfn-cert: DFN-CERT-2017-0199 dfn-cert: DFN-CERT-2016-0890

Medium (CVSS: 4.3)
NVT: jQuery < 1.6.3 XSS Vulnerability
Summary jQuery is prone to a cross-site scripting (XSS) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 1.6.2 Fixed version: 1.6.3 Installation path / port: /phpmyadmin/js/jquery/jquery-1.6.2.js Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info): - Identified file: http://10.199.231.85/phpmyadmin/js/jquery/jquery-1.6.2.js - Referenced at: http://10.199.231.85/phpmyadmin/
Solution: Solution type: VendorFix Update to version 1.6.3 or later.
Affected Software/OS jQuery prior to version 1.6.3.
Vulnerability Insight Cross-site scripting (XSS) vulnerability in jQuery before 1.6.3, when using location.hash to select elements, allows remote attackers to inject arbitrary web script or HTML via a crafted tag.
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: jQuery < 1.6.3 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141637 Version used: 2023-07-14T05:06:08Z
References cve: CVE-2011-4969 url: https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/ cert-bund: WID-SEC-2026-1752 cert-bund: CB-K17/0195 dfn-cert: DFN-CERT-2017-0199 dfn-cert: DFN-CERT-2016-0890

[[return to 10.199.231.85](#)]

2.1.10 Medium 22/tcp

Medium (CVSS: 5.3)
NVT: Weak Host Key Algorithm(s) (SSH)
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↔)
Summary The remote SSH server is configured to allow / support weak host key algorithm(s).
Quality of Detection (QoD): 80%
Vulnerability Detection Result The remote SSH server supports the following weak host key algorithm(s): host key algorithm Description ----- ↔----- ssh-dss Digital Signature Algorithm (DSA) / Digital Signature Stand ↔ard (DSS)
Solution: Solution type: Mitigation Disable the reported weak host key algorithm(s).
Vulnerability Detection Method Checks the supported host key algorithms of the remote SSH server. Currently weak host key algorithms are defined as the following: - ssh-dss: Digital Signature Algorithm (DSA) / Digital Signature Standard (DSS) Details: Weak Host Key Algorithm(s) (SSH) OID:1.3.6.1.4.1.25623.1.0.117687 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565
References url: https://www.rfc-editor.org/rfc/rfc8332 url: https://www.rfc-editor.org/rfc/rfc8709 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.6

Medium (CVSS: 5.3)
NVT: Weak Key Exchange (KEX) Algorithm(s) Supported (SSH)
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↔)
Summary The remote SSH server is configured to allow / support weak key exchange (KEX) algorithm(s).
Quality of Detection (QoD): 80%
Vulnerability Detection Result The remote SSH server supports the following weak KEX algorithm(s): KEX algorithm Reason ----- ↔----- diffie-hellman-group-exchange-sha1 Using SHA-1 diffie-hellman-group1-sha1 Using Oakley Group 2 (a 1024-bit MODP group ↔) and SHA-1
...continues on next page ...

...continued from previous page ...
Impact An attacker can quickly break individual connections.
Solution: Solution type: Mitigation Disable the reported weak KEX algorithm(s) - 1024-bit MODP group / prime KEX algorithms: Alternatively use elliptic-curve Diffie-Hellmann in general, e.g. Curve 25519.
Vulnerability Insight - 1024-bit MODP group / prime KEX algorithms: Millions of HTTPS, SSH, and VPN servers all use the same prime numbers for Diffie-Hellman key exchange. Practitioners believed this was safe as long as new key exchange messages were generated for every connection. However, the first step in the number field sieve-the most efficient algorithm for breaking a Diffie-Hellman connection-is dependent only on this prime. A nation-state can break a 1024-bit prime.
Vulnerability Detection Method Checks the supported KEX algorithms of the remote SSH server. Currently weak KEX algorithms are defined as the following: - non-elliptic-curve Diffie-Hellmann (DH) KEX algorithms with 1024-bit MODP group / prime - ephemeral generated key exchange groups uses SHA-1 - using RSA 1024-bit modulus key Details: Weak Key Exchange (KEX) Algorithm(s) Supported (SSH) OID:1.3.6.1.4.1.25623.1.0.150713 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565
References url: https://weakdh.org/sysadmin.html url: https://www.rfc-editor.org/rfc/rfc9142 url: https://www.rfc-editor.org/rfc/rfc9142#name-summary-guidance-for-implementations url: https://www.rfc-editor.org/rfc/rfc6194 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.5

Medium (CVSS: 4.3)
NVT: Weak Encryption Algorithm(s) Supported (SSH)
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↔)
Summary The remote SSH server is configured to allow / support weak encryption algorithm(s).
Quality of Detection (QoD): 80%
Vulnerability Detection Result The remote SSH server supports the following weak client-to-server encryption algorithms: ↔algorithm(s): 3des-cbc aes128-cbc aes192-cbc aes256-cbc arcfour arcfour128 arcfour256 blowfish-cbc cast128-cbc rijndael-cbc@lysator.liu.se ...continues on next page ...

...continued from previous page ...
The remote SSH server supports the following weak server-to-client encryption al <pre> ↳ gorithm(s): 3des-cbc aes128-cbc aes192-cbc aes256-cbc arcfour arcfour128 arcfour256 blowfish-cbc cast128-cbc rijndael-cbc@lysator.liu.se </pre>
Solution: Solution type: Mitigation Disable the reported weak encryption algorithm(s).
Vulnerability Insight - The 'arcfour' cipher is the Arcfour stream cipher with 128-bit keys. The Arcfour cipher is believed to be compatible with the RC4 cipher [SCHNEIER]. Arcfour (and RC4) has problems with weak keys, and should not be used anymore. - The 'none' algorithm specifies that no encryption is to be done. Note that this method provides no confidentiality protection, and it is NOT RECOMMENDED to use it. - A vulnerability exists in SSH messages that employ CBC mode that may allow an attacker to recover plaintext from a block of ciphertext.
Vulnerability Detection Method Checks the supported encryption algorithms (client-to-server and server-to-client) of the remote SSH server. Currently weak encryption algorithms are defined as the following: - Arcfour (RC4) cipher based algorithms - 'none' algorithm - CBC mode cipher based algorithms Details: Weak Encryption Algorithm(s) Supported (SSH) OID: 1.3.6.1.4.1.25623.1.0.105611 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565
References url: https://www.rfc-editor.org/rfc/rfc8758 url: https://www.kb.cert.org/vuls/id/958563 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.3

[[return to 10.199.231.85](#)]

2.1.11 Low 22/tcp

Low (CVSS: 2.6)
NVT: Weak MAC Algorithm(s) Supported (SSH)
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↳)
Summary The remote SSH server is configured to allow / support weak MAC algorithm(s).
Quality of Detection (QoD): 80%
Vulnerability Detection Result The remote SSH server supports the following weak client-to-server MAC algorithm ...continues on next page ...

...continued from previous page ...	
↔(s):	<pre> hmac-md5 hmac-md5-96 hmac-md5-96-etm@openssh.com hmac-md5-etm@openssh.com hmac-sha1-96 hmac-sha1-96-etm@openssh.com umac-64-etm@openssh.com umac-64@openssh.com The remote SSH server supports the following weak server-to-client MAC algorithm ↔(s): hmac-md5 hmac-md5-96 hmac-md5-96-etm@openssh.com hmac-md5-etm@openssh.com hmac-sha1-96 hmac-sha1-96-etm@openssh.com umac-64-etm@openssh.com umac-64@openssh.com </pre>
Solution:	Solution type: Mitigation Disable the reported weak MAC algorithm(s).
Vulnerability Detection Method	Checks the supported MAC algorithms (client-to-server and server-to-client) of the remote SSH server. Currently weak MAC algorithms are defined as the following: - MD5 based algorithms - 96-bit based algorithms - 64-bit based algorithms - 'none' algorithm Details: Weak MAC Algorithm(s) Supported (SSH) OID: 1.3.6.1.4.1.25623.1.0.105610 Version used: 2024-06-14T05:05:48Z
Product Detection Result	Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565
References	url: https://www.rfc-editor.org/rfc/rfc6668 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.4

[[return to 10.199.231.85](#)]

2.1.12 Low general/icmp

Low (CVSS: 2.1)	
NVT: ICMP Timestamp Reply Information Disclosure	
Summary	The remote host responded to an ICMP timestamp request.
Quality of Detection (QoD):	80%
Vulnerability Detection Result	The following response / ICMP packet has been received: - ICMP Type: 14 - ICMP Code: 0
Impact	This information could theoretically be used to exploit weak time-based random number generators in other services.
Solution:	...continues on next page ...

...continued from previous page ...	
Solution type: Mitigation	Various mitigations are possible: - Disable the support for ICMP timestamp on the remote host completely - Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)
Vulnerability Insight	The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.
Vulnerability Detection Method	Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received. Details: ICMP Timestamp Reply Information Disclosure OID:1.3.6.1.4.1.25623.1.0.103190 Version used: 2025-01-21T05:37:33Z
References	cve: CVE-1999-0524 url: https://datatracker.ietf.org/doc/html/rfc792 url: https://datatracker.ietf.org/doc/html/rfc2780 cert-bund: CB-K15/1514 cert-bund: CB-K14/0632 dfn-cert: DFN-CERT-2014-0658

[[return to 10.199.231.85](#)]

2.1.13 Low general/tcp

Low (CVSS: 2.6)	
NVT: TCP Timestamps Information Disclosure	
Summary	The remote host implements TCP timestamps and therefore allows to compute the uptime.
Quality of Detection (QoD): 80%	
Vulnerability Detection Result	It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 892016 Packet 2: 892288
Impact	A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution:	
Solution type: Mitigation	To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS	TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight	The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
Vulnerability Detection Method	...continues on next page ...

...continued from previous page ...
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z
References url: https://datatracker.ietf.org/doc/html/rfc1323 url: https://datatracker.ietf.org/doc/html/rfc7323 url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152 url: https://www.fortiguard.com/psirt/FG-IR-16-090

[[return to 10.199.231.85](#)]