Nutzung von GeoDaten in den Sozialwissenschaften - Paket spdep

Jan-Philipp Kolb

08 April 2016

Das erste Gesetz der Geographie (TFLG)

"All things are related, but nearby things are more related than distant things" [Tobler, 1970]

Eine Karte von Afrika

```
library(maptools)
data(wrld_simpl)
Africa <- wrld_simpl[wrld_simpl@data$REGION==2,]
plot(Africa)</pre>
```



Das Zentrum eines Polygonzuges

```
library(sp)
Af <- coordinates(Africa)
plot(Africa)
points(x=Af[1,1],y=Af[1,2],col="red",pch=20)</pre>
```



Die nächsten Nachbarn finden

```
library(spdep)
Af_nb <- tri2nb(Af)</pre>
```


Die Nachbarn für das erste Land:

```
## [[1]]
## [1] 26 27 24 32 48
```

Af_nb[1]

Die Nachbarn finden

```
plot(Africa)
plot(Africa[1,],col="red",add=T)
plot(Africa[Af_nb[1][[1]],],col="orange",add=T)
```



Die 10 nächsten Nachbarn finden

```
IDs <- row.names(as(Africa, "data.frame"))
Af10_nb <- knn2nb(knearneigh(Af, k = 10), row.names = IDs)
plot(Africa)
plot(Africa[1,],col="red",add=T)
plot(Africa[Af10_nb[1][[1]],],col="orange",add=T)</pre>
```




Die Distanz berechnen

```
Af <- coordinates(Africa) # get centroid
library(raster)
pointDistance(Af[1:4,], lonlat=TRUE) # compute distance

## [,1] [,2] [,3] [,4]
## [1,] 0 NA NA NA
## [2,] 4763231 0 NA NA
## [2,] 4763231 0 NA NA
## [3,] 2055609 2954497 0 NA
## [4,] 3484053 1295173 1839191 0
```

Berechnen/zeichnen einer Distanzmatrix

```
Dist_Af <- pointDistance(Af, lonlat=TRUE)
Af_color <- Dist_Af[,1]
Af_color <- Af_color/max(Af_color)
Af_color <- rgb(Af_color,0,0)
plot(Africa,col=Af_color)</pre>
```



Links

Raster, CMSAF and solaR

```
https://procomun.wordpress.com/2011/06/17/raster-cmsaf-and-solar/
```

Getting rasters into shape from R

```
https://johnbaumgartner.wordpress.com/2012/07/26/getting-rasters-into-shape-from-r/
```