

# REGRESSION IN R

Jan-Philipp Kolb

16 Mai, 2019

# WHY A PART ON SIMPLE REGRESSION

- ▶ some machine learning concepts are based on regression
- ▶ I would like to remind you how simple regression in R works.
- ▶ I also want to show the constraints
- ▶ In a next step we will learn, how to coop with that

# VARIABLES OF THE MTCARS DATASET

Help for the `mtcars` dataset:


- ▶ `mpg` - Miles/(US) gallon
- ▶ `cyl` - Number of cylinders
- ▶ `disp` - Displacement (cu.in.)
- ▶ `hp` - Gross horsepower
- ▶ `drat` - Rear axle ratio
- ▶ `wt` - Weight (1000 lbs)
- ▶ `qsec` - 1/4 mile time
- ▶ `vs` - Engine (0 = V-shaped, 1 = straight)
- ▶ `am` - Transmission (0 = automatic, 1 = manual)
- ▶ `gear` - Number of forward gears
- ▶ `carb` - Number of carburetors

## DATASET MTCARS


	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4			21.0	6	160.0	110	3.90	2.620	16.46	0	
Mazda RX4 Wag			21.0	6	160.0	110	3.90	2.875	17.02	0	
Datsun 710			22.8	4	108.0	93	3.85	2.320	18.61	1	
Hornet 4 Drive			21.4	6	258.0	110	3.08	3.215	19.44	1	
Hornet Sportabout			18.7	8	360.0	175	3.15	3.440	17.02	0	
Valiant			18.1	6	225.0	105	2.76	3.460	20.22	1	
Duster 360			14.3	8	360.0	245	3.21	3.570	15.84	0	
Merc 240D			24.4	4	146.7	62	3.69	3.190	20.00	1	
Merc 230			22.8	4	140.8	95	3.92	3.150	22.90	1	
Merc 280			19.2	6	167.6	123	3.92	3.440	18.30	1	
Merc 280C			17.8	6	167.6	123	3.92	3.440	18.90	1	
Merc 450SE			16.4	8	275.8	180	3.07	4.070	17.40	0	
Merc 450SL			17.3	8	275.8	180	3.07	3.730	17.60	0	
Merc 450SLC			15.2	8	275.8	180	3.07	3.780	18.00	0	
Cadillac Fleetwood			10.4	8	472.0	205	2.93	5.250	17.98	0	
Lincoln Continental			10.4	8	460.0	215	3.00	5.424	17.82	0	

## DISTRIBUTIONS OF TWO VARIABLES OF MTCARS

**density.default(x = mtcars\$**  
**density.default(x = mtcars\$**



N = 32 Bandwidth = 0.3455



N = 32 Bandwidth = 2.477

# A SIMPLE REGRESSION MODEL

DEPENDENT VARIABLE - MILES PER GALLON (MPG)

INDEPENDENT VARIABLE - WEIGHT (WT)

```
##  
## Call:  
## lm(formula = mpg ~ wt, data = mtcars)  
##  
## Coefficients:  
## (Intercept)          wt  
##      37.285      -5.344
```

## GET THE MODEL SUMMARY

```
##
## Call:
## lm(formula = mpg ~ wt, data = mtcars)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.5432 -2.3647 -0.1252  1.4096  6.8727
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  37.2851     1.8776   19.858 < 2e-16 ***
## wt          -5.3445     0.5591   -9.559 1.29e-10 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 3.046 on 30 degrees of freedom
## Multiple R-squared:  0.7528, Adjusted R-squared:  0.7446
## F-statistic: 91.38 on 1 and 30 DF,  p-value: 1.294e-10
```

# THE MODEL FORMULA

## MODEL WITHOUT INTERCEPT

```
##      Estimate Std. Error  t value    Pr(>|t|)
## wt  5.291624   0.5931801  8.920771 4.55314e-10
```

## ADDING FURTHER VARIABLES

```
##              Estimate Std. Error  t value    Pr(>|t|)
## (Intercept) 39.686261   1.7149840 23.140893 3.043182e-20
## wt          -3.190972   0.7569065 -4.215808 2.220200e-04
## cyl         -1.507795   0.4146883 -3.635972 1.064282e-03
```



# THE COMMAND `as.formula`

```
## [1] "formula"
```

# THE COMMAND MODEL . MATRIX

# FURTHER POSSIBILITIES TO SPECIFY THE FORMULA

INTERACTION EFFECT

TAKE THE LOGARITHM

## A MODEL WITH INTERACTION EFFECT


-disp - Displacement (cu.in.)

##	Estimate	Std. Error	t value	Pr(> t )
## (Intercept)	44.08199770	3.123062627	14.114990	2.955567e-14
## wt	-6.49567966	1.313382622	-4.945763	3.216705e-05
## disp	-0.05635816	0.013238696	-4.257078	2.101721e-04
## wt:disp	0.01170542	0.003255102	3.596022	1.226988e-03

# EXPLORING INTERACTIONS

```
library(jtools)
interact_plot(m3d, pred = "wt", modx = "disp")
```

- ▶ With a continuous moderator (in our case `disp`) you get three lines — 1 standard deviation above and below the mean and the mean itself.



## EXAMPLE: OBJECT ORIENTATION

- ▶ m3 is now a special regression object
- ▶ Various functions can be applied to this object

##	Mazda RX4	Mazda RX4 Wag	Datsun 710	Horn
##	22.27914	21.46545	26.25203	
##	Hornet Sportabout	Valiant		
##	16.64696	19.59873		
##	Mazda RX4	Mazda RX4 Wag	Datsun 710	Horn
##	-1.2791447	-0.4654468	-3.4520262	
##	Hornet Sportabout	Valiant		
##	2.0530424	-1.4987281		

# MAKE MODEL PREDICTION

```
## [1] 21.0 21.0 22.8 21.4 18.7 18.1
```

```
##           Mazda RX4           Mazda RX4 Wag
```

```
##           23.28261           21.91977
```

```
## Hornet Sportabout           Valiant
```

```
##           18.90014           18.79325
```


```
Datsun 710
```

```
24.88595
```

```
Horn
```


# RESIDUAL PLOT - MODEL ASSUMPTIONS VIOLATED?

- ▶ the case if a deviation pattern from line






# RESIDUAL PLOT





- If the residuals are normally distributed, they should be on the same line.

# REGRESSION DIAGNOSTIC WITH BASE-R




# THE VISREG-PACKAGE




# THE VISREG-PACKAGE

- ▶ The default-argument for `type` is `conditional`.
- ▶ Scatterplot of `mpg` and `wt` plus regression line and confidence bands



# VISUALISATION WITH VISREG

- ▶ Second argument - Specification covariate for visualisation
- ▶ plot shows the effect on the expected value of the response by moving the x variable away from a reference point on the x-axis (for numeric variables, the mean).





# REGRESSION WITH FACTORS

- The effects of factors can also be visualized with visreg:

##	Estimate	Std. Error	t value	Pr(> t )
## (Intercept)	33.990794	1.8877934	18.005569	6.257246e-17
## cyl6	-4.255582	1.3860728	-3.070244	4.717834e-03
## cyl8	-6.070860	1.6522878	-3.674214	9.991893e-04
## wt	-3.205613	0.7538957	-4.252065	2.130435e-04

# EFFECTS OF FACTORS




# THE COMMAND MODEL . MATRIX




## THE PACKAGE VISREG - INTERACTIONS

##	Estimate	Std. Error	t value	Pr(> t )
## (Intercept)	39.571196	3.193940	12.3894599	2.058359e-12
## cyl6	-11.162351	9.355346	-1.1931522	2.435843e-01
## cyl8	-15.703167	4.839464	-3.2448150	3.223216e-03
## wt	-5.647025	1.359498	-4.1537586	3.127578e-04
## cyl6:wt	2.866919	3.117330	0.9196716	3.661987e-01
## cyl8:wt	3.454587	1.627261	2.1229458	4.344037e-02


## CONTROL OF THE GRAPHIC OUTPUT WITH LAYOUT.




# THE PACKAGE VISREG - INTERACTIONS OVERLAY



# THE PACKAGE VISREG - VISREG2D



# THE PACKAGE VISREG - SURFACE



# PRODUCING NICE TABLE OUTPUT WITH PACKAGE STARGAZER

## EXAMPLE HTML OUTPUT:



	<i>Dependent variable:</i>
	mpg
wt	-3.125*** (0.911)
cyl	-1.510*** (0.422)
am	0.176 (1.304)
Constant	39.418*** (2.641)
Observations	32
R <sup>2</sup>	0.830

# EXERCISE

- ▶ Install the package `AmesHousing` and create a processed Version of the Ames housing data with the variables `Sale_Price`, `Gr_Liv_Area` and `TotRms_AbvGrd`
- ▶ Create a suitable regression model with `Sale_Price` as dependent and `Gr_Liv_Area` and `TotRms_AbvGrd` as independent variables. What do you think?

# THE PROBLEM - OVERFITTING

- Our model doesn't generalize well from our training data to unseen data.






# THE SIGNAL AND THE NOISE

- ▶ In predictive modeling, you can think of the “signal” as the true underlying pattern that you wish to learn from the data.
- ▶ “Noise,” on the other hand, refers to the irrelevant information or randomness in a dataset.

*the signal and the  
and the noise and  
the noise and the  
noise and the no  
why so many and  
predictions fail—  
but some don't th  
and the noise and  
the noise and the*

# OVERFITTING.



# WHAT CAN BE DONE AGAINST OVERFITTING

- ▶ Cross Validation
- ▶ Train with more data
- ▶ Remove features
- ▶ Regularization - e.g. ridge and lasso regression
- ▶ Ensembling - e.g. bagging and boosting

# CROSS-VALIDATION


- ▶ Cross-validation is a powerful preventative measure against overfitting.
- ▶ Use your initial training data to generate multiple mini train-test splits. Use these splits to tune your model.

## CROSS VALIDATION IN R

```
## Linear Regression
##
## 47 samples
## 5 predictor
##
## No pre-processing
## Resampling: Leave-One-Out Cross-Validation
## Summary of sample sizes: 46, 46, 46, 46, 46, 46, ...
## Resampling results:
##
##      RMSE      Rsquared    MAE
##      7.738618  0.6128307  6.116021
##
```

# K-FOLD CROSS VALIDATION

# THE BIAS VARIANCE TRADEOFF



# GOOD LITERATURE FOR LINEAR REGRESSION IN R

## USEFUL PDF DOCUMENT:

J H Maindonald - **Using R for Data Analysis and Graphics  
Introduction, Code and Commentary**

- ▶ Introduction to R
- ▶ Data analysis
- ▶ Statistical models
- ▶ Inference concepts
- ▶ Regression with one predictor
- ▶ Multiple linear regression
- ▶ Extending the linear model
- ▶ ...

# LINKS - LINEAR REGRESSION

- ▶ Regression - **r-bloggers**
- ▶ The complete book of **Faraway**- very intuitive
- ▶ Good introduction on **Quick-R**
- ▶ **Multiple regression**
- ▶ **15 Types of Regression you should know**
- ▶ **ggeffects** - **Create Tidy Data Frames of Marginal Effects for 'ggplot' from Model Outputs**



# SHINY APP - DIAGNOSTICS FOR SIMPLE LINEAR REGRESSION

[https://gallery.shinyapps.io/slr\\_diag/](https://gallery.shinyapps.io/slr_diag/)

Diagnostics for simple linear regression

Select a trend:

- ☐ Linear up
- ☐ Linear down
- ☐ Curved up
- ☐ Curved down
- ☒ Fan-shaped

☒ Show residuals


This applet uses ordinary least squares (OLS) to fit a regression line to the data with the selected trend. The applet is designed to help you practice evaluating whether or not the linear model is an appropriate fit to the data. The three diagnostic plots on the lower half of the page are provided to help you identify undesirable patterns in the residuals that may arise from non-linear trends in the data.

[Rate this app!](#)

[View code](#)

[Check out other apps](#)

[Want to learn more for free?](#)



► Shiny App - Simple Linear Regression

# RESOURCES

- ▶ machine learning iteration