M. Marks: 100

Time: 60 minutes

1. A solid round bar with diameter of 50 mm is made of hot-rolled AISI 1095 steel (Sut = 830 MPa and Sy = 460 MPa). The bar is not rotating. The bar is loaded with a repeated bending load that caused the bending moment to fluctuate between 0 and 3500 Nm. **(10)**
   a. Find corrected endurance limit
   b. Find the number of cycles to failure. Use the most conservative fatigue failure theory. Consider f = 0.9. **(15)**

2. For a rod having natural frequency equal to 20 Hz, calculate the ratio of transmissibility if the speed is increased from 300 rpm to 600 rpm and the damping ratio is reduced from 0.5 to 0.3. **(10)**

3. 2000 pieces of cylinders are to be manufactured. The cylinders are designed to contain gas at (10, 2) Bar. The outer diameter is 250±5 mm and the thickness is given by (2, 0.01) mm.

   Calculate hoop stress in cylinder using $\sigma = \dfrac{Pr}{2t}$

   Where P = inner pressure; r = outer radius; t = thickness of wall

   Find the expected number of failed cylinders if Aluminium (80, 6) MPa is used as material of the cylinder. **(34)**

z	0.00	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.09
-3.4	0.0003	0.0003	0.0003	0.0003	0.0003	0.0003	0.0003	0.0003	0.0003	0.0002
-3.3	0.0005	0.0005	0.0005	0.0004	0.0004	0.0004	0.0004	0.0004	0.0004	0.0003
-3.2	0.0007	0.0007	0.0006	0.0006	0.0006	0.0006	0.0006	0.0005	0.0005	0.0005
-3.1	0.0010	0.0009	0.0009	0.0009	0.0008	0.0008	0.0008	0.0008	0.0007	0.0007
-3.0	0.0013	0.0013	0.0013	0.0012	0.0012	0.0011	0.0011	0.0011	0.0010	0.0010
-2.9	0.0019	0.0018	0.0018	0.0017	0.0016	0.0016	0.0015	0.0015	0.0014	0.0014
-2.8	0.0026	0.0025	0.0024	0.0023	0.0023	0.0022	0.0021	0.0021	0.0020	0.0019
-2.7	0.0035	0.0034	0.0033	0.0032	0.0031	0.0030	0.0029	0.0028	0.0027	0.0026
-2.6	0.0047	0.0045	0.0044	0.0043	0.0041	0.0040	0.0039	0.0038	0.0037	0.0036
-2.5	0.0062	0.0060	0.0059	0.0057	0.0055	0.0054	0.0052	0.0051	0.0049	0.0048
-2.4	0.0082	0.0080	0.0078	0.0075	0.0073	0.0071	0.0069	0.0068	0.0066	0.0064
-2.3	0.0107	0.0104	0.0102	0.0099	0.0096	0.0094	0.0091	0.0089	0.0087	0.0084
-2.2	0.0139	0.0136	0.0132	0.0129	0.0125	0.0122	0.0119	0.0116	0.0113	0.0110
-2.1	0.0179	0.0174	0.0170	0.0166	0.0162	0.0158	0.0154	0.0150	0.0146	0.0143
-2.0	0.0228	0.0222	0.0217	0.0212	0.0207	0.0202	0.0197	0.0192	0.0188	0.0183
-1.9	0.0287	0.0281	0.0274	0.0268	0.0262	0.0256	0.0250	0.0244	0.0239	0.0233
-1.8	0.0359	0.0351	0.0344	0.0336	0.0329	0.0322	0.0314	0.0307	0.0301	0.0294
-1.7	0.0446	0.0436	0.0427	0.0418	0.0409	0.0401	0.0392	0.0384	0.0375	0.0367
-1.6	0.0548	0.0537	0.0526	0.0516	0.0505	0.0495	0.0485	0.0475	0.0465	0.0455
-1.5	0.0668	0.0655	0.0643	0.0630	0.0618	0.0606	0.0594	0.0582	0.0571	0.0559
-1.4	0.0808	0.0793	0.0778	0.0764	0.0749	0.0735	0.0721	0.0708	0.0694	0.0681
-1.3	0.0968	0.0951	0.0934	0.0918	0.0901	0.0885	0.0869	0.0853	0.0838	0.0823
-1.2	0.1151	0.1131	0.1112	0.1093	0.1075	0.1056	0.1038	0.1020	0.1003	0.0985
-1.1	0.1357	0.1335	0.1314	0.1292	0.1271	0.1251	0.1230	0.1210	0.1190	0.1170
-1.0	0.1587	0.1562	0.1539	0.1515	0.1492	0.1469	0.1446	0.1423	0.1401	0.1379

4. Between cylindrical roller bearing and deep groove ball bearing of similar dimensions, which would have higher radial load carrying capacity and Why? **(6)**

5. A bearing is needed for an off-shore oil rig operations requiring water and dust exclusion. Which type of rolling element bearing would you select and why? **(6)**

6. A uniform steel shaft (E=210 GPa, Specific weight =75 kN/m³) of 25mm diameter is supported as a cantilever. Find the lowest critical speed of shaft. **(7)**

7. A V-pulley of diameter 500 mm and width 125 mm is to be mounted on a shaft. Square key of side "d/4" each and length "l" is used to transmit 500 N.m torque from shaft of diameter "d" to the hub of a pulley. Assuming the length of the key to be equal to the width of the pulley and yield strength of the shaft material as 400 MPa, find the average shear stress developed in the key. **(12)**

------------X-------------X-------------End of Paper-------------X-------------X------------