

Final project

Jared Adam

12/6/2024

Packages

Data import and wrangling

```
set.seed(654321)
s21 <- read_csv('data/2021 Sentinel Prey Assessment.csv')
s22 <- read_csv("data/PSA_CE2_SentinelPrey.csv")
s23 <- read_csv('data/PSA_Sent.prey.2023.csv')
```

I need to get total predation into a column as a binary. 1 = predation, 0 = not

2021 cleaning

```
s21
```

A tibble: 5,281 × 17

	location	date	n.weather	d.weather	growth_stage	plot_id	rep.block
treatment							
##	<chr>	<chr>	<dbl>	<chr>	<chr>	<dbl>	<dbl>
<dbl>							
##	1 PA	6/16/2...	15.3	18.44	V3	101	1
1							
##	2 PA	6/16/2...	15.3	18.44	V3	101	1
1							
##	3 PA	6/16/2...	15.3	18.44	V3	101	1
1							
##	4 PA	6/16/2...	15.3	18.44	V3	101	1
1							
##	5 PA	6/16/2...	15.3	18.44	V3	101	1
1							
##	6 PA	6/16/2...	15.3	18.44	V3	101	1
1							
##	7 PA	6/16/2...	15.3	18.44	V3	102	1
3							
##	8 PA	6/16/2...	15.3	18.44	V3	102	1
3							
##	9 PA	6/16/2...	15.3	18.44	V3	102	1
3							
##	10 PA	6/16/2...	15.3	18.44	V3	102	1
3							

```
## # i 5,271 more rows
## # i 9 more variables: row <dbl>, sample <dbl>, n.absent <chr>, n.partial
<chr>,
## #   n.predated <chr>, d.absent <chr>, d.partial <chr>, d.predated <chr>,
## #   to.predated <chr>
```

```
clean21 <- s21 %>%
  mutate(year = '2021') %>%
  dplyr::select(location, year, growth_stage, plot_id, rep.block, treatment,
to.predated) %>%
  mutate(to.predated = as.double(to.predated)) %>%
  dplyr::rename(block = rep.block) %>%
  group_by(location, year, growth_stage, plot_id, block, treatment) %>%
  # dplyr::summarise(total = sum(to.predated)) %>%
  na.omit() %>%
  mutate(treatment = case_when(
    treatment == '33' ~ '3',
    .default = as.factor(treatment))) %>%
  dplyr::filter(treatment != '6',
                treatment != '7',
                treatment != '8') %>%
  mutate_at(vars(1:6), as.factor)
```

```
# 2022 cleaning
s22
```

```
## # A tibble: 3,246 × 19
##   location date      am.weather pm.weather growth_stage plotid block
treatment
##   <chr>      <chr>          <dbl> <chr>      <chr>          <dbl> <dbl>
<dbl>
##  1 PA      6/22/2022      22.7 26.1      V3            101      1
1
##  2 PA      6/22/2022      22.7 26.1      V3            101      1
1
##  3 PA      6/22/2022      22.7 26.1      V3            101      1
1
##  4 PA      6/22/2022      22.7 26.1      V3            101      1
1
##  5 PA      6/22/2022      22.7 26.1      V3            101      1
1
##  6 PA      6/22/2022      22.7 26.1      V3            101      1
1
##  7 PA      6/22/2022      22.7 26.1      V3            102      1
3
##  8 PA      6/22/2022      22.7 26.1      V3            102      1
3
##  9 PA      6/22/2022      22.7 26.1      V3            102      1
3
```

```

## 10 PA      6/22/2022      22.7 26.1      V3      102      1
3
## # i 3,236 more rows
## # i 11 more variables: row <dbl>, sample <dbl>, am.absent <chr>,
## #   am.partial <chr>, am.predators <chr>, pm.absent <chr>, pm.partial
<chr>,
## #   pm.predators <chr>, to.predated <dbl>, n.predated <dbl>, d.predated
<dbl>

unique(s22$treatment)

## [1] 1 3 2 4

unique(s22$growth_stage)

## [1] "V3" "V5" "R3" "R2"

clean22 <- s22 %>%
  mutate(year = '2022') %>%
  dplyr::select(location, year, growth_stage, plotid, block, treatment,
to.predated) %>%
  dplyr::rename(plot_id = plotid) %>%
  mutate(growth_stage = case_when(growth_stage == 'R2' ~ 'R3',
                                .default = as.character(growth_stage))) %>%
  dplyr::group_by(location, year, growth_stage, plot_id, block, treatment)
%>%
  # dplyr::summarise(total = sum(to.predated)) %>%
  mutate_at(vars(1:6), as.factor)

# 2023 cleaning

clean23 <- s23 %>%
  mutate(year = '2023') %>%
  relocate(am.partial, am.absent, pm.partial, pm.absent) %>%
  mutate_at(vars(1:4), as.double) %>%
  mutate(to.predated = if_else(am.partial | am.absent | pm.partial |
pm.absent == 1, 1, 0)) %>%
  relocate(to.predated) %>%
  mutate(growth_stage = case_when((location == 'NC' & date == '7/20/2023') ~
'R3',
                                .default = as.character(growth_stage))) %>%
  dplyr::select(location, year, growth_stage, plotid, block, treatmetn,
to.predated) %>%
  dplyr::rename(plot_id = plotid,
                treatment = treatmetn) %>%
  group_by(location, year, growth_stage, plot_id, block, treatment) %>%
  na.omit() %>%
  filter(treatment != 5) %>%
  mutate_at(vars(1:6), as.factor)

```

```

# and in the darkness, bind them
sent <- rbind(clean21, clean22, clean23)
as_tibble(sent)

## # A tibble: 12,432 × 7
##   location year growth_stage plot_id block treatment to.predated
##   <fct>    <fct> <fct>      <fct>  <fct> <fct>      <dbl>
## 1 PA      2021 V3         101    1    1          0
## 2 PA      2021 V3         101    1    1          0
## 3 PA      2021 V3         101    1    1          0
## 4 PA      2021 V3         101    1    1          0
## 5 PA      2021 V3         101    1    1          0
## 6 PA      2021 V3         101    1    1          0
## 7 PA      2021 V3         102    1    3          1
## 8 PA      2021 V3         102    1    3          1
## 9 PA      2021 V3         102    1    3          0
## 10 PA     2021 V3         102    1    3          1
## # i 12,422 more rows

dim(sent)

## [1] 12432      7

unique(sent$location)

## [1] PA FL IL IA KS KY MD NE NY NC OH TX VT VA WI DE
## Levels: DE FL IA IL KS KY MD NC NE NY OH PA TX VA VT WI

```

Experimental design

Data: Sentinel Prey assessment of arthropod-predator activity in corn fields.

These data come from the Precision Sustainable Agriculture effort through the USDA. I am the lead on the entomology component of this project and responsible for analyzing this three year data set which spans multiple states. This effort began during my Master's degree, but I only analyzed Pennsylvania data for my thesis.

Study design: **Treatments** = 4; No cover crop, early-terminated cover crop, late-terminated cover crop, planting green **Plots** = 20; 5-6 blocks (location dependent) composed of 4 plots each = 20 plots / study site / year **Years** = 3 (2021,2022,2023) **Locations** = This project comprises 16 states. Not all states collected sentinel prey data every year. Each site year was in a different field. **Effort** = Data were collected at three corn growth stages / year (V3,V5,R3). **Sample** = 6 sentinel prey traps were placed in each plot = 120 samples collected / growth stage. Total sample effort per state per season = 360 samples.


Variables: **Response** = Total level of predation. This is a binomial of 6 traps/ counts per plot. Pseudoreplication is account for in the random term. **Explanatory** = Crop growth stage (timing, three levels) and treatment (four levels). I am not interested in the fixed

effects of location. **Random effects** = Plot in block in location, in year. I want to account for pseudoreplication and all of the site/year combinations.

Plots were randomly assigned to each block. Field sites were as random as they could be at each respective research station. Sentinel prey traps were placed between pre-determined rows and at specific length intervals within each plot to maintain consistency.


Locating missing values

```
library(mi)
# make an object of the missing df and then present the image
tdf <- missing_data.frame(data.frame(sent))
image(tdf)
```



Preliminary data display

```
sent %>%
  ggplot() +
  geom_mosaic(aes(x = product(treatment), fill = to.predated), offset =
0.04)+
  facet_wrap(~growth_stage)+
  scale_fill_colorblind()+
  labs(title = 'Mosaic plot of Predation by Treatment and Growth Stage',
       y = 'Density',
       x = 'Treatment')
```



Modeling

Theoretical model:

$$\{Predation|Treatment, GrowthStage\} \sim \beta_0 + \beta_{1I_{\{Treatment = 2\}}_i} + \beta_{2I_{\{Treatment = 4\}}_i} + \beta_{3I_{\{Treatment = 3\}}_i} + \beta_{4I_{\{GrowthStage = V5\}}_i} + \beta_{5I_{\{GrowthStage = V3\}}_i} + \text{Year}_i + \text{Location}_i + \text{Block}_i + \text{Plot}_i + \text{Error}_i$$

Add the appropriate stuff below

$$\pi_{\{Predation|Treatment, GrowthStage\}} \sim \beta_0 + \beta_{1I_{\{Treatment = 2\}}} + \beta_{2I_{\{Treatment = 4\}}} + \beta_{3I_{\{Treatment = 3\}}} + \beta_{4I_{\{GrowthStage = V5\}}} + \beta_{5I_{\{GrowthStage = V3\}}}$$

Initial model

sent

```
## # A tibble: 12,432 × 7
## # Groups:   location, year, growth_stage, plot_id, block, treatment
## [2,091]
##   location year growth_stage plot_id block treatment to.predated
##   <fct>    <fct> <fct>      <fct>  <fct> <fct>      <dbl>
## 1 PA      2021 V3        101    1    1          0
## 2 PA      2021 V3        101    1    1          0
## 3 PA      2021 V3        101    1    1          0
## 4 PA      2021 V3        101    1    1          0
## 5 PA      2021 V3        101    1    1          0
## 6 PA      2021 V3        101    1    1          0
```

```

## 7 PA      2021 V3      102      1      3      1
## 8 PA      2021 V3      102      1      3      1
## 9 PA      2021 V3      102      1      3      0
## 10 PA     2021 V3      102      1      3      1
## # i 12,422 more rows

m2 <- glmer(to.predated ~ treatment*growth_stage +
(1|year/location/block/plot_id) , family = binomial, data = sent)
summary(m2)

## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula:
## to.predated ~ treatment * growth_stage + (1 | year/location/block/plot_id)
## Data: sent
##
##      AIC      BIC    logLik deviance df.resid
##  9135.0   9253.8  -4551.5   9103.0   12416
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -11.4203   0.0801   0.2125   0.4224   2.9757
##
## Random effects:
## Groups                                Name      Variance Std.Dev.
## plot_id:(block:(location:year)) (Intercept) 2.611e-01 0.511004
## block:(location:year)          (Intercept) 1.701e-01 0.412483
## location:year                  (Intercept) 2.689e+00 1.639802
## year                          (Intercept) 1.545e-05 0.003931
## Number of obs: 12432, groups:
## plot_id:(block:(location:year)), 744; block:(location:year), 191;
## location:year, 39; year, 3
##
## Fixed effects:
##
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    3.03307    0.29061  10.437 < 2e-16
## treatment2     0.03549    0.16020   0.222 0.824674
## treatment4     0.22142    0.17252   1.283 0.199352
## treatment3     0.62055    0.17515   3.543 0.000396
## growth_stageV5 -1.15589    0.13170  -8.776 < 2e-16
## growth_stageV3 -1.92785    0.13398 -14.389 < 2e-16
## treatment2:growth_stageV5 0.03110    0.18796   0.165 0.868581
## treatment4:growth_stageV5 0.08776    0.20154   0.435 0.663242
## treatment3:growth_stageV5 -0.02574    0.20392  -0.126 0.899541
## treatment2:growth_stageV3 0.29511    0.18920   1.560 0.118818
## treatment4:growth_stageV3 0.44923    0.20103   2.235 0.025439
## treatment3:growth_stageV3 0.31249    0.20397   1.532 0.125508
##
## Correlation of Fixed Effects:


```

```
##          (Intr) trtmn2 trtmn4 trtmn3 grw_V5 grw_V3 t2:_V5 t4:_V5 t3:_V5
## treatment2 -0.272
## treatment4 -0.248  0.458
## treatment3 -0.246  0.453  0.421
## grwth_stgV5 -0.293  0.511  0.472  0.466
## grwth_stgV3 -0.300  0.511  0.474  0.464  0.647
## trtmnt2:_V5  0.199 -0.724 -0.332 -0.327 -0.693 -0.446
## trtmnt4:_V5  0.185 -0.334 -0.719 -0.305 -0.646 -0.415  0.453
## trtmnt3:_V5  0.184 -0.330 -0.306 -0.744 -0.639 -0.412  0.448  0.417
## trtmnt2:_V3  0.203 -0.727 -0.334 -0.330 -0.451 -0.692  0.622  0.294  0.290
## trtmnt4:_V3  0.192 -0.339 -0.728 -0.310 -0.424 -0.655  0.297  0.623  0.273
## trtmnt3:_V3  0.191 -0.335 -0.309 -0.747 -0.420 -0.645  0.292  0.272  0.645
##          t2:_V3 t4:_V3
## treatment2
## treatment4
## treatment3
## grwth_stgV5
## grwth_stgV3
## trtmnt2:_V5
## trtmnt4:_V5
## trtmnt3:_V5
## trtmnt2:_V3
## trtmnt4:_V3  0.459
## trtmnt3:_V3  0.454  0.427
## optimizer (Nelder_Mead) convergence code: 0 (OK)
## Model failed to converge with max|grad| = 0.0296809 (tol = 0.002,
component 1)
```


Anova(m2)

```
## Analysis of Deviance Table (Type II Wald chisquare tests)
##
## Response: to.predated
##          Chisq Df Pr(>Chisq)
## treatment      60.9286  3  3.722e-13
## growth_stage    526.0579  2 < 2.2e-16
## treatment:growth_stage  8.2544  6      0.22
```

```
plot(allEffects(m2), type = 'link', ylab = 'estimated log differnces in total
predation', grid = T)
```

```
plot(allEffects(m2), type = 'response', xlim = c(0,1), ylab = 'estimated
probability differences in total predation', grid = T)
```



* There is weak evidence against the null of no interaction between treatment and growth stage Chi squared(6) = 8.25, $p = 0.22$, after controlling for the random effect of plot nested in block nested in location nested in year, and will remove the interaction term from the model.

Model refinement

```
m3 <- glmer(to.predated ~ treatment+growth_stage +
(1|year/location/block/plot_id) , family = binomial, data = sent)
summary(m3)

## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula:
## to.predated ~ treatment + growth_stage + (1 | year/location/block/plot_id)
## Data: sent
##
##      AIC      BIC   logLik deviance df.resid
##  9131.1   9205.4  -4555.5   9111.1    12422
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -11.4488   0.0811   0.2124   0.4229   2.9455
##
## Random effects:
## Groups                                Name      Variance Std.Dev.
## plot_id:(block:(location:year)) (Intercept) 2.600e-01 0.50988
## block:(location:year)           (Intercept) 1.700e-01 0.41236
## location:year                   (Intercept) 2.672e+00 1.63473
## year                           (Intercept) 5.569e-06 0.00236
## Number of obs: 12432, groups:
## plot_id:(block:(location:year)), 744; block:(location:year), 191;
## location:year, 39; year, 3
##
## Fixed effects:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    2.92687    0.27926  10.481 < 2e-16
## treatment2     0.15828    0.09462   1.673  0.0944
## treatment4     0.42821    0.10271   4.169 3.06e-05
## treatment3     0.72957    0.09942   7.338 2.16e-13
## growth_stageV5 -1.13027    0.07256 -15.578 < 2e-16
## growth_stageV3 -1.68191    0.07334 -22.932 < 2e-16
##
## Correlation of Fixed Effects:
##              (Intr) trtmn2 trtmn4 trtmn3 grw_V5
## treatment2  -0.161
## treatment4  -0.138  0.451
## treatment3  -0.141  0.468  0.436
## grwth_stgV5 -0.172 -0.003 -0.015 -0.026
## grwth_stgV3 -0.176 -0.007 -0.024 -0.041  0.625
## optimizer (Nelder_Mead) convergence code: 0 (OK)
## Model failed to converge with max|grad| = 0.0104819 (tol = 0.002,
## component 1)

Anova(m3)
```

```
## Analysis of Deviance Table (Type II Wald chisquare tests)
```

```
##
```


```
## Response: to.predated
```

```
##           Chisq Df Pr(>Chisq)
```


```
## treatment    60.988  3  3.615e-13
```

```
## growth_stage 528.427  2  < 2.2e-16
```

```
plot(allEffects(m3), type = 'link', ylab = 'Estimated log differences in total  
predation', grid = T)
```



```
plot(allEffects(m3), type = 'response', xlim = c(0,1), ylab = 'Estimated  
probability differences in total predation', grid = T)
```



```
cld(emmeans(m3, ~treatment, adjust = 'tukey', type = 'response'), Letters =
letters)
```

```
## treatment prob SE df asymp.LCL asymp.UCL .group
## 1 0.880 0.0290 Inf 0.787 0.935 a
## 2 0.895 0.0257 Inf 0.812 0.944 a
## 4 0.918 0.0209 Inf 0.849 0.957 b
## 3 0.938 0.0161 Inf 0.884 0.968 c
##
## Results are averaged over the levels of: growth_stage
## Confidence level used: 0.95
## Conf-level adjustment: sidak method for 4 estimates
## Intervals are back-transformed from the logit scale
## P value adjustment: tukey method for comparing a family of 4 estimates
## Tests are performed on the log odds ratio scale
## significance level used: alpha = 0.05
## NOTE: If two or more means share the same grouping symbol,
## then we cannot show them to be different.
## But we also did not show them to be the same.
```

```
cld(emmeans(m3, ~growth_stage, adjust = 'tukey', type = 'response'), Letters
= letters)
```

```
## growth_stage prob SE df asymp.LCL asymp.UCL .group
## V3 0.828 0.03850 Inf 0.717 0.902 a
## V5 0.893 0.02584 Inf 0.814 0.941 b
## R3 0.963 0.00981 Inf 0.931 0.980 c
##
## Results are averaged over the levels of: treatment
```

```
## Confidence level used: 0.95
## Conf-level adjustment: sidak method for 3 estimates
## Intervals are back-transformed from the logit scale
## P value adjustment: tukey method for comparing a family of 3 estimates
## Tests are performed on the log odds ratio scale
## significance level used: alpha = 0.05
## NOTE: If two or more means share the same grouping symbol,
##       then we cannot show them to be different.
##       But we also did not show them to be the same.
```

R squared and ICC

```
r.squaredGLMM(m3)
```

```
##               R2m      R2c
## theoretical 0.08286345 0.527981
## delta      0.05596765 0.356609
```

```
library(performance)
```

```
r2(m3)
```

```
## # R2 for Mixed Models
##
##   Conditional R2: 0.528
##   Marginal R2: 0.083
```

```
summary(m3)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
##   Approximation) [glmerMod]
##   Family: binomial ( logit )
## Formula:
## to.predated ~ treatment + growth_stage + (1 | year/location/block/plot_id)
##   Data: sent
##
##      AIC      BIC   logLik deviance df.resid
##  9131.1   9205.4  -4555.5   9111.1    12422
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -11.4488   0.0811   0.2124   0.4229   2.9455
##
## Random effects:
##   Groups                                Name      Variance Std.Dev.
## plot_id:(block:(location:year)) (Intercept) 2.600e-01 0.50988
## block:(location:year)          (Intercept) 1.700e-01 0.41236
## location:year                  (Intercept) 2.672e+00 1.63473
## year                          (Intercept) 5.569e-06 0.00236
## Number of obs: 12432, groups:
## plot_id:(block:(location:year)), 744; block:(location:year), 191;
## location:year, 39; year, 3
##
```

```
## Fixed effects:
##               Estimate Std. Error z value Pr(>|z|)
## (Intercept)    2.92687    0.27926  10.481 < 2e-16
## treatment2     0.15828    0.09462   1.673  0.0944
## treatment4     0.42821    0.10271   4.169 3.06e-05
## treatment3     0.72957    0.09942   7.338 2.16e-13
## growth_stageV5 -1.13027    0.07256 -15.578 < 2e-16
## growth_stageV3 -1.68191    0.07334 -22.932 < 2e-16
##
## Correlation of Fixed Effects:
##               (Intr) trtmn2 trtmn4 trtmn3 grw_V5
## treatment2  -0.161
## treatment4  -0.138  0.451
## treatment3  -0.141  0.468  0.436
## grwth_stgV5 -0.172 -0.003 -0.015 -0.026
## grwth_stgV3 -0.176 -0.007 -0.024 -0.041  0.625
## optimizer (Nelder_Mead) convergence code: 0 (OK)
## Model failed to converge with max|grad| = 0.0104819 (tol = 0.002,
component 1)

# for plot
(2.600e-01) / (2.600e-01 + 1.700e-01 + .672e+00 + 5.569e-06)

## [1] 0.2359335
```

The ICC for plot id is 0.236.

Final plots

```
sent %>%
  ggplot()+
  geom_mosaic(aes(x = product(treatment), fill = to.predated))+
  scale_fill_manual(values = c("#E7298A", "#1B9E77"))+
  scale_x_productlist(labels=c("No CC", "Early", "Late", "Green"))+
  labs(title = 'Whole Team Sentinel Prey ~ Treatment',
       x = 'Treatment',
       y = 'Estimated proportion',
       caption = 'Figure 5:\nTotal predation binary where 1 = predation and 0
= no predation.\nPredation levels differed between the no-cover and late-
terminated treatment\nand the no-cover and planting-green treatment (p <
0.05).\nCompact letter display denotes differences among treatments.')+
  guides(fill = guide_legend(title = 'Predation:\n0 = no predation\n1 =
predation'))+
  theme(legend.title = element_text(size = 14),
        legend.text = element_text(size = 14),
        axis.text.x = element_text(size=16),
        axis.text.y = element_text(size = 16),
        axis.title = element_text(size = 18),
        plot.title = element_text(size = 18),
        plot.subtitle = element_text(size = 12),
```

```

panel.grid.major.y = element_line(color = "darkgrey"),
panel.grid.major.x = element_blank(),
panel.grid.minor = element_blank(),
strip.text = element_text(size = 12),
plot.caption = element_text(hjust = 0, size = 12, color = "grey25"),
axis.ticks.length=unit(.25, "cm"))+
annotate('text', x = 0.15, y = 0.95, label = 'a', size = 8)+
annotate('text', x = .4, y = 0.95, label = 'a', size = 8)+
annotate('text', x = .65, y = 0.95, label = 'b', size = 8)+
annotate('text', x = .875, y = 0.95, label = 'c', size = 8)

```




Figure 5:
Total predation binary where 1 = predation and 0 = no predation.
Predation levels differed between the no-cover and late-terminated treatment and the no-cover and planting-green treatment ($p < 0.05$).
Compact letter display denotes differences among treatments.

```

sent %>%
  ggplot()+
  geom_mosaic(aes(x = product(growth_stage), fill = to.predated))+
  scale_fill_manual(values = c("#E7298A", "#1B9E77"))+
  labs(title = 'Whole Team Sentinel Prey ~ Growth Stage',
       x = 'Growth Stage',
       y = 'Estimated proportion',
       caption = 'Figure 6:\nTotal predation binary where 1 = predation and 0
= no predation.\nPredation levels differed among all growth stages (p <
0.05), where R3 was the highest,\nfollowed by V5, and then V3. Growth stages
are ordered in reverse-chronological order.\nCompact letter display denotes
differences among growth stages')+
  guides(fill = guide_legend(title = 'Predation:\n0 = no predation\n1 =
predation'))+
  theme(legend.title = element_text(size = 14),
        legend.text = element_text(size = 14),
        axis.text.x = element_text(size=16),
        axis.text.y = element_text(size = 16),

```

```

axis.title = element_text(size = 18),
plot.title = element_text(size = 18),
plot.subtitle = element_text(size = 12),
panel.grid.major.y = element_line(color = "darkgrey"),
panel.grid.major.x = element_blank(),
panel.grid.minor = element_blank(),
strip.text = element_text(size = 12),
plot.caption = element_text(hjust = 0, size = 12, color = "grey25"),
axis.ticks.length=unit(.25, "cm"))+
annotate('text', x = 0.175, y = 0.95, label = 'a', size = 8)+
annotate('text', x = .5, y = 0.95, label = 'b', size = 8)+
annotate('text', x = .85, y = 0.95, label = 'c', size = 8)

```




Figure 6:
Total predation binary where 1 = predation and 0 = no predation.
Predation levels differed among all growth stages ($p < 0.05$), where R3 was the highest, followed by V5, and then V3. Growth stages are ordered in reverse-chronological order.
Compact letter display denotes differences among growth stages

Table 1

table as a proportion

sent %>%

```

group_by(location, treatment, growth_stage) %>%
summary()

```

##	location	year	growth_stage	plot_id	block	treatment
##	IL	:1296	2021:5004	R3:4334	203 : 608	1:2681 1:3439
##	OH	:1173	2022:3246	V5:4196	103 : 607	2:2491 2:3203
##	VT	:1080	2023:4182	V3:3902	303 : 607	3:2493 4:2605
##	PA	:1074		401 : 603	4:2514	3:3185
##	KY	:1054		102 : 591	5:1969	
##	KS	: 848		202 : 589	6: 284	
##	(Other)	:5907		(Other):8827		


```
## to.predated
## Min. :0.0000
## 1st Qu.:1.0000
## Median :1.0000
## Mean :0.8103
## 3rd Qu.:1.0000
## Max. :1.0000
##

sent %>%
  group_by(growth_stage) %>%
  summary()

## location year growth_stage plot_id block treatment
## IL :1296 2021:5004 R3:4334 203 : 608 1:2681 1:3439
## OH :1173 2022:3246 V5:4196 103 : 607 2:2491 2:3203
## VT :1080 2023:4182 V3:3902 303 : 607 3:2493 4:2605
## PA :1074 401 : 603 4:2514 3:3185
## KY :1054 102 : 591 5:1969
## KS : 848 202 : 589 6: 284
## (Other):5907 (Other):8827
## to.predated
## Min. :0.0000
## 1st Qu.:1.0000
## Median :1.0000
## Mean :0.8103
## 3rd Qu.:1.0000
## Max. :1.0000
##

tally(to.predated ~ treatment + growth_stage, data = sent)

## , , growth_stage = R3
##
## treatment
## to.predated 1 2 4 3
## 0 128 125 96 77
## 1 1018 1024 802 1064
##
## , , growth_stage = V5
##
## treatment
## to.predated 1 2 4 3
## 0 277 232 179 167
## 1 918 836 692 895
##
## , , growth_stage = V3
##
## treatment
## to.predated 1 2 4 3
```

```
##      0  371  281  221  204
##      1  727  705  615  778
```

```
datasummary_balance( ~ to.predated,data = sent)
```

		0		1	
		N	Pct.	N	Pct.
location	DE	193	8.2	405	4.0
	FL	19	0.8	692	6.9
	IA	16	0.7	705	7.0
	IL	95	4.0	1201	11.9
	KS	345	14.6	503	5.0
	KY	373	15.8	681	6.8
	MD	192	8.1	408	4.1
	NC	19	0.8	341	3.4
	NE	65	2.8	706	7.0
	NY	94	4.0	474	4.7
	OH	531	22.5	642	6.4
	PA	240	10.2	834	8.3
	TX	22	0.9	698	6.9
	VA	49	2.1	239	2.4
	VT	38	1.6	1042	10.3
	WI	67	2.8	503	5.0
year	2021	883	37.4	4121	40.9
	2022	676	28.7	2570	25.5
	2023	799	33.9	3383	33.6
growth_stage	R3	426	18.1	3908	38.8
	V5	855	36.3	3341	33.2
	V3	1077	45.7	2825	28.0
plot_id	101	161	6.8	425	4.2
	102	112	4.7	479	4.8
	103	126	5.3	481	4.8
	104	119	5.0	426	4.2
	201	112	4.7	452	4.5
	202	117	5.0	472	4.7
	203	113	4.8	495	4.9
	204	129	5.5	445	4.4
	301	111	4.7	478	4.7

	0		1	
	N	Pct.	N	Pct.
302	112	4.7	455	4.5
303	123	5.2	484	4.8
304	120	5.1	450	4.5
401	130	5.5	473	4.7
402	112	4.7	477	4.7
403	106	4.5	461	4.6
404	101	4.3	473	4.7
501	108	4.6	400	4.0
502	79	3.4	422	4.2
503	82	3.5	442	4.4
504	71	3.0	386	3.8
601	2	0.1	111	1.1
602	1	0.0	75	0.7
603	9	0.4	86	0.9
604	11	0.5	96	1.0
505	5	0.2	22	0.2
506	3	0.1	33	0.3
701	5	0.2	49	0.5
702	2	0.1	34	0.3
706	2	0.1	34	0.3
803	3	0.1	33	0.3
804	7	0.3	25	0.2
805	1	0.0	35	0.3
901	4	0.2	32	0.3
905	6	0.3	27	0.3
906	4	0.2	50	0.5
105	2	0.1	16	0.2
106	11	0.5	7	0.1
205	3	0.1	15	0.1
206	3	0.1	15	0.1
305	4	0.2	14	0.1
306	5	0.2	13	0.1
405	6	0.3	12	0.1
406	4	0.2	13	0.1

		0		1	
		N	Pct.	N	Pct.
	605	0	0.0	30	0.3
	705	2	0.1	33	0.3
	801	3	0.1	32	0.3
	902	1	0.0	17	0.2
	606	0	0.0	9	0.1
	802	4	0.2	13	0.1
	904	1	0.0	17	0.2
	1	631	26.8	2050	20.3
	2	479	20.3	2012	20.0
	3	468	19.8	2025	20.1
block	4	435	18.4	2079	20.6
	5	331	14.0	1638	16.3
	6	14	0.6	270	2.7
	1	776	32.9	2663	26.4
	2	638	27.1	2565	25.5
	4	496	21.0	2109	20.9
	3	448	19.0	2737	27.2
treatment					

```
# install.packages('openxlsx')
# library(openxlsx)
#
# table <- favstats(to.predated ~ treatment + growth_stage, data = sent)
# write.xlsx(table, 'test.xlsx')
# favstats(to.predated ~ growth_stage, data = sent)
# favstats(to.predated ~ treatment, data = sent)
# citation('mosaic')
```

Study design figure

```
tally(~ year, sent)
```

```
## year
## 2021 2022 2023
## 5004 3246 4182
```

```
tally(~location, sent)
```

```
## location
## DE FL IA IL KS KY MD NC NE NY OH PA TX VA VT
WI
## 598 711 721 1296 848 1054 600 360 771 568 1173 1074 720 288 1080
570
```

```

tally(~block, sent)

## block
##      1      2      3      4      5      6
## 2681 2491 2493 2514 1969  284

tally(~plot_id, sent)

## plot_id
## 101 102 103 104 201 202 203 204 301 302 303 304 401 402 403 404 501 502
## 503 504
## 586 591 607 545 564 589 608 574 589 567 607 570 603 589 567 574 508 501
## 524 457
## 601 602 603 604 505 506 701 702 706 803 804 805 901 905 906 105 106 205
## 206 305
## 113  76  95 107  27  36  54  36  36  36  32  36  36  33  54  18  18  18
## 18  18
## 306 405 406 605 705 801 902 606 802 904
##  18  18  17  30  35  35  18   9  17  18

names1 <- list("Year 2021", "Year 2022", "Year 2023")
names2 <- list("Loc. 1", "...", "Loc. 16", "...", "Loc. 1", "...", "Loc. 16")
names3 <- list("Block 1", "...", "Block 6")
names4 <- list("Plot 1", "...", "Plot 4")
namesF <- list("Treatment", "Growth Stage")
namesR <- list("Year", "Location in Year", "Block in Location", "Observation
Error")

```

Citations

```

citation('DiagrammeRsvg')

## To cite package 'DiagrammeRsvg' in publications use:
##
##   Iannone R (2016). _DiagrammeRsvg: Export DiagrammeR Graphviz Graphs
##   as SVG_. R package version 0.1,
##   <https://CRAN.R-project.org/package=DiagrammeRsvg>.
##
## A BibTeX entry for LaTeX users is
##
##   @Manual{,
##     title = {DiagrammeRsvg: Export DiagrammeR Graphviz Graphs as SVG},
##     author = {Richard Iannone},
##     year = {2016},
##     note = {R package version 0.1},
##     url = {https://CRAN.R-project.org/package=DiagrammeRsvg},
##   }

citation('car')

```

```

## To cite the car package in publications use:
##
## Fox J, Weisberg S (2019). _An R Companion to Applied Regression_,
## Third edition. Sage, Thousand Oaks CA.
## <https://socialsciences.mcmaster.ca/jfox/Books/Companion/>.
##
## A BibTeX entry for LaTeX users is
##
## @Book{,
##   title = {An {R} Companion to Applied Regression},
##   edition = {Third},
##   author = {John Fox and Sanford Weisberg},
##   year = {2019},
##   publisher = {Sage},
##   address = {Thousand Oaks {CA}},
##   url = {https://socialsciences.mcmaster.ca/jfox/Books/Companion/},
## }

citation('effects')

## To cite effects in publications use:
##
## John Fox and Sanford Weisberg (2019). An R Companion to Applied
## Regression, 3rd Edition. Thousand Oaks, CA
## <https://socialsciences.mcmaster.ca/jfox/Books/Companion/index.html>
##
## For predictor effects or partial residuals also cite:
##
## John Fox, Sanford Weisberg (2018). Visualizing Fit and Lack of Fit in
## Complex Regression Models with Predictor Effect Plots and Partial
## Residuals. Journal of Statistical Software, 87(9), 1-27. doi
## 10.18637/jss.v087.i09
##
## For generalized linear models also cite:
##
## John Fox (2003). Effect Displays in R for Generalised Linear Models.
## Journal of Statistical Software, 8(15), 1-27. doi
## 10.18637/jss.v008.i15
##
## For usage in multinomial and proportional-odds logit models also cite:
##
## John Fox, Jangman Hong (2009). Effect Displays in R for Multinomial
## and Proportional-Odds Logit Models: Extensions to the effects
## Package. Journal of Statistical Software, 32(1), 1-24. doi
## 10.18637/jss.v032.i01
##
## To see these entries in BibTeX format, use 'print(<citation>,
## bibtex=TRUE)', 'toBibtex(.)', or set
## 'options(citation.bibtex.max=999)'.

```

```
citation('emmeans')
```

```
## To cite package 'emmeans' in publications use:
```

```
##
```

```
## Lenth R (2024). _emmeans: Estimated Marginal Means, aka Least-Squares
```

```
## Means_. R package version 1.10.4, commit
```

```
## 52c445c77326050a97e70999b376424266495419,
```

```
## <https://github.com/rvlenth/emmeans>.
```

```
##
```

```
## A BibTeX entry for LaTeX users is
```

```
##
```

```
## @Manual{,
```

```
## title = {emmeans: Estimated Marginal Means, aka Least-Squares Means},
```

```
## author = {Russell V. Lenth},
```

```
## year = {2024},
```

```
## note = {R package version 1.10.4, commit
```

```
52c445c77326050a97e70999b376424266495419},
```

```
## url = {https://github.com/rvlenth/emmeans},
```

```
## }
```