

# Scalar LinearSDE Model Reduction

September 9, 2020

## 1 Model Reduction on a Linear SDE

```
[1]: include("modgen_LSDE.jl")  
include("../Tools/Model_Reduction_Dev.jl")
```

```
[1]: vector_wiener_filter_fft
```

```
[2]: using JLD  
using PyPlot  
using DSP: nextfastfft
```

the model is

$$dX_t = AX_t dt + \sigma dW_t$$

my implementation of Euler-Maruyama produces

$$X_{n+1} = (1 + hA)X_n + \sqrt{h}\sigma u_n \quad \text{where } u_n \sim N(0, 1)$$

### 1.1 Generate the data

```
[3]: A = reshape([-0.5],1,1)  
      = reshape([1],1,1)  
Xo = [1]  
t_disc = 1000  
gap = 1  
scheme = "EM"  
  
t_start = 0  
t_stop = 1e5  
h = 1e-2  
  
Δt = h*gap  
M_out = 20  
  
X = modgen_LSDE(t_start,t_stop,h,  
    A = A,  
    = ,  
    Xo = Xo,  
    t_disc = t_disc,
```

```

        gap = gap,
        scheme = scheme)

d, N = size(X)

nfft = nextfastfft(N)
X = [X zeros(d,nfft-N)]

_exp, _int = auto_times(X[:])*Δt
N_eff      = N*Δt/_int

Psi(x) = x

```

[3]: Psi (generic function with 1 method)

```

[4]: @time h_wf = get_wf(X, Psi, par = 2000);
X = X[:,1:N]

```

```

Number of CKMS iterations: 980
errK errR : 2.6111004081224627e-11 5.386992398075367e-16
50.368920 seconds (524.99 M allocations: 26.345 GiB, 10.80% gc time)

```

```

[4]: 1×9900001 Array{Float64,2}:
 0.290761  0.299407  0.391377  0.474412  ... -0.555082 -0.507017 -0.542111

```

```

[5]: (_exp, N_eff)

```

```

[5]: (1.9941733720085884, 50067.3040042568)

```

```

[6]: 1 .+ h*A

```

```

[6]: 1×1 Array{Float64,2}:
 0.995

```

```

[7]: h_wf

```

```

[7]: 1×1×20 Array{Float64,3}:
[:, :, 1] =
 0.9953233294463933

[:, :, 2] =
-0.00020919004589103283

[:, :, 3] =
-0.00024203960050139507

```

...

```
[:, :, 18] =  
-0.0003234461200461408
```

```
[:, :, 19] =  
5.553214528984618e-5
```

```
[:, :, 20] =  
-0.00010097015574818532
```

## 1.2 Get reduced (reproduced) model (no noise)

```
[8]: # d, N = size(X)  
# nu = size(Psi(X[:,1]),1)  
# M_out = size(h_wf,3)  
  
# X_rm = zeros(d,N); X_rm[:,1:M_out] = X[:,1:M_out]  
  
# PSI = zeros(nu,N);  
# for i = 1:M_out  
#     PSI[:,i] = Psi(X_rm[:,i])  
# end  
  
# for i = M_out + 1 : N  
#     X_rm[:,i] = sum(h_wf[:, :, k]*PSI[:, i-k] for k = 1:M_out, dims = 2)  
#     PSI[:,i] = Psi(X_rm[:,i])  
# end
```

## 1.3 Get reduced (reproduced) model with noise

```
[8]: d, N = size(X)  
nu = size(Psi(X[:,1]),1)  
M_out = 2 #size(h_wf,3)  
  
X_rm = zeros(d,N); X_rm[:,1:M_out] = X[:,1:M_out]  
  
PSI = zeros(nu,N);  
for i = 1:M_out  
    PSI[:,i] = Psi(X_rm[:,i])  
end  
  
for i = M_out + 1 : N  
    X_rm[:,i] = sum(h_wf[:, :, k]*PSI[:, i-k] for k = 1:M_out, dims = 2) +  
    sqrt(h)*randn(d)  
    PSI[:,i] = Psi(X_rm[:,i])
```

```
end
```

```
[26]: data = Dict(  
      "h_wf" => h_wf,  
      "A" => A,  
      " " => ,  
      "Xo" => Xo,  
      "t_disc" => t_disc,  
      "gap" => gap,  
      "scheme" => scheme,  
      "t_start" => t_start,  
      "t_stop" => t_start,  
      "h" => h,  
      "X_55" => X,  
      "X__rm_55_h_4" => X_rm)  
  
save("Data\\LSDE_wfs.jld",data)
```

UndefVarError: X\_rm not defined

Stacktrace:

[1] top-level scope at In[26]:1

```
[27]: data = load("Data\\LSDE_wfs.jld")
```

```
[27]: Dict{String,Any} with 12 entries:  
  "t_disc"      => 1000  
  "h"           => 0.01  
  "X__rm_55_h_4" => [0.15406 -0.0238143 ... -2.61855e-322 -2.61855e-322]  
  "t_start"     => 0  
  " "           => [1]  
  "t_stop"      => 0  
  "Xo"          => [1]  
  "scheme"      => "EM"  
  "A"           => [-0.9]  
  "h_wf"        => [0.990711]...  
  "gap"         => 1  
  "X_55"        => [0.15406 -0.0238143 ... 0.0 0.0]
```

```
[11]: blup = findall(isnan,X_rm[1,:])[1]
```

BoundsError: attempt to access 0-element Array{Int64,1} at index [1]

Stacktrace:

```
[1] getindex(::Array{Int64,1}, ::Int64) at .\array.jl:744  
[2] top-level scope at In[11]:1
```


```
[12]: findall(x -> x > 10^1, X_rm[1,:])[1]
```

BoundsError: attempt to access 0-element Array{Int64,1} at index [1]

Stacktrace:


```
[1] getindex(::Array{Int64,1}, ::Int64) at .\array.jl:744  
[2] top-level scope at In[12]:1
```

```
[13]: plot([X[1:1000:end] X_rm[1:1000:end]])
```



```
[13]: 2-element Array{PyObject,1}:
      PyObject <matplotlib.lines.Line2D object at 0x000000003AC2C388>
      PyObject <matplotlib.lines.Line2D object at 0x000000003AC39748>
```

```
[14]: emp_pdf(X[1:9900001])
      emp_pdf(X_rmn[1:9900001])
```




```
[14]: 3-element Array{Array{T,1} where T,1}:
      [7.960089133092796e-6, 0.0, 0.0, 0.0, 7.960089133092796e-6,
      1.5920178266185593e-5, 7.960089133092798e-6, 7.960089133092793e-6,
      7.960089133092793e-6, 0.0 ... 0.0, 0.0, 0.0, 1.5920178263758864e-5,
      1.5920178263758864e-5, 7.960089136253981e-6, 0.0, 7.960089136253981e-6,
      7.960089127504881e-6, 7.960089136253981e-6]
      [-4.8770898630617925, -4.864400295254425, -4.851710727447058,
      -4.8390211596396915, -4.826331591832325, -4.813642024024958, -4.800952456217591,
      -4.788262888410225, -4.775573320602858, -4.76288375279549 ... 4.982704323262182,
      4.99539389106955, 5.008083458876916, 5.0207730266842825, 5.03346259449165,
      5.046152162299016, 5.058841730106383, 5.07153129791375, 5.084220865721117,
      5.096910433528484]
      PyCall.PyObject[PyObject <matplotlib.lines.Line2D object at
```

0x00000000476C2BC8>]

```
[15]: lags = 0:1000

A_rm = my_autocor(X_rmn[:,lags])
A      = my_autocor(X[:,lags])

plot(lags*h,[A A_rm])
```



C:\Users\jared\.julia\conda\3\lib\site-packages\numpy\core\\_asarray.py:85:  
ComplexWarning: Casting complex values to real discards the imaginary part  
return array(a, dtype, copy=False, order=order)

```
[15]: 2-element Array{PyCall.PyObject,1}:
      PyObject <matplotlib.lines.Line2D object at 0x0000000047737FC8>
      PyObject <matplotlib.lines.Line2D object at 0x00000000021B3BC8>
```

```
[16]: z_spect = z_spect_scalar(X[:, n = 3, p=100, ty = "ave")
      z_spect_rm = z_spect_scalar(X_rmn[:, n = 3, p=100, ty = "ave")


      Θ = 2* (1:1000:nfft)/nfft
      Z = exp.(im*Θ)
```

```

a = 1 + h*A[1,1]
z_spect_ana_fun(z) = h* / ( (1-a*z^(-1))*(1-a*z) )
z_spect_ana = real(z_spect_ana_fun.(Z))

semilogy(θ,[z_spect[1:1000:nfft] z_spect_rm[1:1000:nfft] z_spect_ana])

```



```

[16]: 3-element Array{PyCall.PyObject,1}:
      PyObject <matplotlib.lines.Line2D object at 0x00000000473E09C8>
      PyObject <matplotlib.lines.Line2D object at 0x00000000473F3148>
      PyObject <matplotlib.lines.Line2D object at 0x00000000473F3308>

```

```
[ ]:
```