

## Programming Projects P-2

### Project One --- JIFFIES

This assignment will involve designing two kernel modules:

1. **Design a kernel module that creates a /proc file named /proc/jiffies that reports the current value of jiffies when the /proc/jiffies file is read, such as with the command**  
`cat /proc/jiffies`  
**Be sure to remove /proc/jiffies when the module is removed.**
2. **Design a kernel module that creates a proc file named /proc/seconds that reports the number of elapsed seconds since the kernel module was loaded. This will involve using the value of jiffies as well as the HZ rate. When a user enters the command**  
`cat /proc/seconds`  
**your kernel module will report the number of seconds that have elapsed since the kernel module was first loaded. Be sure to remove /proc/seconds when the module is removed.**

See detailed instructions below...

### I. Kernel Modules Overview

The first part of this project involves following a series of steps for creating and inserting a module into the Linux kernel.

You can list all kernel modules that are currently loaded by entering the command

```
lsmod
```

This command will list the current kernel modules in three columns: name, size, and where the module is being used.

```
#include <linux/init.h>
#include <linux/kernel.h>
#include <linux/module.h>

/* This function is called when the module is loaded. */
int simple_init(void) {
    printk(KERN INFO "Loading Kernel Module\n");
    return 0;
}

/* This function is called when the module is removed. */
void simple_exit(void) {
    printk(KERN INFO "Removing Kernel Module\n");
}

/* Macros for registering module entry and exit points. */
module_init(simple_init);
module_exit(simple_exit);

MODULE_LICENSE("GPL");
MODULE_DESCRIPTION("Simple Module");
MODULE_AUTHOR("SGG");
```

**Figure 2.21** Kernel module simple.c.

The program in Figure 2.21 (named simple.c and available with the source code for this text) illustrates a very basic kernel module that prints appropriate messages when it is loaded and unloaded.

The function simple\_init() is the **module entry point**, which represents the function that is invoked when the module is

loaded into the kernel. Similarly, the simple `exit()` function is the **module exit point** — the function that is called when the module is removed from the kernel.

The module entry point function must return an integer value, with 0 representing success and any other value representing failure. The module `exit_point` function returns `void`. Neither the module entry point nor the module `exit_point` is passed any parameters. The two following macros are used for registering the module entry and exit points with the kernel:

```
module_init(simple_init)

module_exit(simple_exit)
```

Notice in the figure how the module entry and exit point functions make calls to the `printk()` function. `printk()` is the kernel equivalent of `printf()`, but its output is sent to a kernel log buffer whose contents can be read by the `dmesg` command. One difference between `printf()` and `printk()` is that `printk()` allows us to specify a priority flag, whose values are given in the `<linux/printk.h>` include file. In this instance, the priority is `KERN_INFO`, which is defined as an **informational** message.

The final lines—`MODULE_LICENSE()`, `MODULE_DESCRIPTION()`, and `MODULE_AUTHOR()`—represent details regarding the software license, description of the module, and author. For our purposes, we do not require this information, but we include it because it is standard practice in developing kernel modules.

This kernel module `simple.c` is compiled using the `Makefile` accompanying the source code with this project. To compile the module, enter the following on the command line:

```
make
```

The compilation produces several files. The file `simple.ko` represents the compiled kernel module. The following step illustrates inserting this module into the Linux kernel.

## II. Loading and Removing Kernel Modules

Kernel modules are loaded using the `insmod` command, which is run as follows:

```
sudo insmod simple.ko
```

To check whether the module has loaded, enter the `lsmod` command and search for the module `simple`. Recall that the module entry point is invoked when the module is inserted into the kernel. To check the contents of this message in the kernel log buffer, enter the command

```
dmesg
```

You should see the message "Loading Module."

Removing the kernel module involves invoking the `rmmod` command (notice that the `.ko` suffix is unnecessary):

```
sudo rmmod simple
```

Be sure to check with the `dmesg` command to ensure the module has been removed.

Because the kernel log buffer can fill up quickly, it often makes sense to clear the buffer periodically. This can be accomplished as follows:

```
sudo dmesg -c
```

Proceed through the steps described above to create the kernel module and to load and unload the module. Be sure to check the contents of the kernel log buffer using `dmesg` to ensure that you have followed the steps properly.

As kernel modules are running within the kernel, it is possible to obtain values and call functions that are available only in the kernel and not to regular user applications. For example, the Linux include file `<linux/hash.h>` defines several hashing functions for use within the kernel. This file also defines the constant value `GOLDEN_RATIO_PRIME` (which is defined as an unsigned long). This value can be printed out as follows:

```
printk(KERN_INFO "%lu\n", GOLDEN_RATIO_PRIME);
```

As another example, the include file `<linux/gcd.h>` defines the following function

```
unsigned long gcd(unsigned long a, unsigned b);
```

which returns the greatest common divisor of the parameters `a` and `b`.

Once you are able to correctly load and unload your module, complete the following additional steps:

1. **Print out the value of `GOLDEN_RATIO_PRIME` in the `simple_init()` function.**
2. **Print out the greatest common divisor of 3,300 and 24 in the `simple_exit()` function.**

As compiler errors are not often helpful when performing kernel development, it is important to compile your program often by running `make` regularly. Be sure to load and remove the kernel module and check the kernel log buffer using `dmesg` to ensure that your changes to `simple.c` are working properly.

In Section 1.4.3, we described the role of the timer as well as the timer interrupt handler. In Linux, the rate at which the timer ticks (the **tick rate**) is the value `HZ` defined in `<asm/param.h>`. The value of `HZ` determines the frequency of the timer interrupt, and its value varies by machine type and architecture. For example, if the value of `HZ` is 100, a timer interrupt occurs 100 times per second, or every 10 milliseconds. Additionally, the kernel keeps track of the global variable `jiffies`, which maintains the number of timer interrupts that have occurred since the system was booted. The `jiffies` variable is declared in the file `<linux/jiffies.h>`.

1. **Print out the values of `jiffies` and `HZ` in the `simple_init()` function.**
2. **Print out the value of `jiffies` in the `simple_exit()` function.**

Before proceeding to the next set of exercises, consider how you can use the different values of `jiffies` in `simple_init()` and `simple_exit()` to determine the number of seconds that have elapsed since the time the kernel module was loaded and then removed.

### III. The /proc File System

The `/proc` file system is a “pseudo” file system that exists only in kernel memory and is used primarily for querying various kernel and per-process statistics.

```
#include <linux/init.h>
#include <linux/kernel.h>
#include <linux/module.h>
#include <linux/proc_fs.h>
#include <asm/uaccess.h>
```

```
#define BUFFER_SIZE 128
#define PROC_NAME "hello"
```

```

ssize_t proc_read(struct file *file, char __user *usr_buf,
                  size_t count, loff_t *pos);

static struct file_operations proc_ops = {
    .owner = THIS_MODULE,
    .read = proc_read,
};

/* This function is called when the module is loaded. */
int proc_init(void) {
    /* creates the /proc/hello entry */
    proc_create(PROC_NAME, 0666, NULL, &proc_ops);
    return 0;
}

/* This function is called when the module is removed. */
void proc_exit(void) {
    /* removes the /proc/hello entry */
    remove_proc_entry(PROC_NAME, NULL);
}

```

**Figure 2.22** The /proc file-system kernel module, Part 1

This exercise involves designing kernel modules that create additional entries in the /proc file system involving both kernel statistics and information related to specific processes. The entire program is included in Figure 2.22 and Figure 2.23. We begin by describing how to create a new entry in the /proc file system. The following program example (named hello.c and available with the source code for this text) creates a /proc entry named /proc/hello. If a user enters the command

```
cat /proc/hello
```

the infamous Hello World message is returned.

```

/* This function is called each time /proc/hello is read */
ssize_t proc_read(struct file *file, char user *usr_buf, size_t count, loff_t *pos) {
    int rv = 0;
    char buffer[BUFFER_SIZE];
    static int completed = 0;

    if (completed) {
        completed = 0;
        return 0;
    }
    completed = 1;

    rv = sprintf(buffer, "Hello World\n");

    /* copies kernel space buffer to user space usr_buf */
    copy_to_user(usr_buf, buffer, rv);
    return rv;
}

module_init(proc_init);
module_exit(proc_exit);

MODULE_LICENSE("GPL");
MODULE_DESCRIPTION("Hello Module");
MODULE_AUTHOR("SGG");

```

**Figure 2.23** The /proc file system kernel module, Part 2

In the module entry point `proc_init()`, we create the new `/proc/hello` entry using the `proc_create()` function. This function is passed `proc_ops`, which contains a reference to a struct file operations. This struct initializes the `.owner` and `.read` members. The value of `.read` is the name of the function `proc_read()` that is to be called whenever `/proc/hello` is read.

Examining this `proc_read()` function, we see that the string "Hello World\n" is written to the variable `buffer` where `buffer` exists in kernel memory. Since `/proc/hello` can be accessed from user space, we must copy the contents of `buffer` to user space using the kernel function `copy_to_user()`. This function copies the contents of kernel memory `buffer` to the variable `usr_buf`, which exists in user space.

Each time the `/proc/hello` file is read, the `proc_read()` function is called repeatedly until it returns 0, so there must be logic to ensure that this function returns 0 once it has collected the data (in this case, the string "Hello World\n") that is to go into the corresponding `/proc/hello` file.

Finally, notice that the `/proc/hello` file is removed in the module exit point `proc_exit()` using the function `remove_proc_entry()`.

<b>cpsc 351-Project One --- Jiffies Project --- due 24 Mar 2021 at 2359</b>
Name: Jared Dyreson
Repository: <a href="https://www.github.com/JaredDyreson/Jiffies-Kernel-Mod">https://www.github.com/JaredDyreson/Jiffies-Kernel-Mod</a>
Verify each of the following items and check the correct column. Incorrectly marked items will incur a 5% penalty.

Completed	Not Completed	Jiffies Project
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<b>Modify the hello.c project, and confirm that it correctly makes (using make), and displays the GOLDEN_PRIME_RATIO on module load, and the gcd of 3300 and 24 on module removal.</b>
<input checked="" type="checkbox"/>	<input type="checkbox"/>	Create a kernel module that creates a proc file named proc/jiffies, and that reports the current value of jiffies when the proc/jiffies file is read, such as with the command: <b>cat proc/jiffies</b>
<input checked="" type="checkbox"/>	<input type="checkbox"/>	Be sure /proc/jiffies is removed when the module is removed
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<b>Save the output of /proc/jiffies, and submit it with your project</b>
<input checked="" type="checkbox"/>	<input type="checkbox"/>	Create a kernel module that creates a proc fie named /proc/seconds, that reports the number of elapsed seconds since the kernel module was loaded, such as with the command <b>cat proc/seconds</b>
<input checked="" type="checkbox"/>	<input type="checkbox"/>	Your calculation involves jiffies and HZ, and includes the header files needed to compile and run your code
<input checked="" type="checkbox"/>	<input type="checkbox"/>	Be sure /proc/seconds is removed when the module is removed
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<b>Save the output of reading from /proc/seconds, and submit it with your project</b>
Comments		