

Measurement of ν_μ Charged-Current Multi-Pion Production on Argon with the MicroBooNE Detector in the NuMI Beam

Technical Note — Two- and Three-Charged-Pion Final States (CC1mu2pi, CC1mu3pi)

Draft 0.1 — 2026-08-13

Tusharadri Mahmud, Linhui Gu, Ishanne Pophale, Jarek Nowak

Lancaster University

Abstract

We describe the extension of the MicroBooNE NuMI ν_μ charged-current single-charged-pion analysis to higher pion multiplicities: charged-current interactions producing a muon and exactly two or three charged pions (and any number of protons) in the final state. These $N\pi^\pm$ topologies probe the resonant and deep-inelastic regimes and the intranuclear pion cascade (final-state interactions), and are a significant background to the single-pion signal. The selections are built as thin subselections of the inclusive single-pion selection, adopting the looser pion identification of the dedicated MicroBooNE multi-pion study to recover efficiency. On the Run-1 forward-horn-current ν_μ overlay the two-pion (three-pion) selection reaches a signal efficiency of 16.3% (6.4%) at an intrinsic purity of 21% (12%), corresponding to of order 530 (40) selected signal events at full exposure. We present the selection, the cut-flow, and a study of the pion-momentum thresholds that set the accessible signal phase space; the two-pion channel supports a flux-averaged total cross section and a coarse differential measurement, while the three-pion channel is a total-cross-section measurement. This note is a companion to the single-pion analysis note, from which the detector model, samples, exposure, systematic framework and unfolding are inherited unchanged.

Contents

1	Introduction	2
2	Signal definition	2
3	Samples, exposure and normalisation	2
4	Event selection	3
5	Selection performance	3
6	Pion-momentum thresholds and the accessible phase space	4
7	Backgrounds	5
8	Feasibility and observables	6
9	Systematic uncertainties	6
10	Status and follow-up	6

1 Introduction

Charged-current (CC) production of multiple charged pions on nuclei sits at the transition between the resonant (RES) and deep-inelastic (DIS) regimes of neutrino–nucleus scattering and is strongly shaped by the intranuclear hadronic cascade. A ν_μ interaction that produces several pions at the primary vertex may have some of them absorbed, charge-exchanged or produced in re-scattering before they leave the nucleus, so the observed charged-pion multiplicity is a direct probe of final-state interactions (FSI). Multi-pion final states are also a non-negligible background to exclusive single-pion and pion-less measurements, so a dedicated measurement of their rate and kinematics on argon is valuable both as a cross-section result and as a constraint on the interaction model used across the MicroBooNE programme.

This note documents the extension of the NuMI ν_μ CC $1\pi^\pm$ analysis (the “single-pion note”, to which this is a companion) to the two- and three-charged-pion final states. The selections, `CC1mu2pi` and `CC1mu3pi`, are implemented as subselections of the inclusive single-pion selection `CC1mu1piXp` in the `xsec_analyzer` framework and reuse its muon reconstruction, samples, per-run POT normalisation, systematic universes and Wiener-SVD unfolding without modification. The multi-pion pion identification follows the dedicated MicroBooNE multi-pion study of Mahmud [1] and the accompanying analyzer of Gu [2].

Given the steeply falling multi-pion cross section and the reduced reconstruction efficiency for events with several (often soft) pions, these channels are statistically limited: the emphasis of this first note is the selection definition, its efficiency and purity, the accessible phase space, and a feasibility assessment for total and differential cross sections.

2 Signal definition

The signal is a ν_μ (or $\bar{\nu}_\mu$) charged-current interaction with a true muon and *exactly* N charged pions (π^+ or π^- ; MicroBooNE does not determine the pion charge sign) in the final state, with $N = 2$ (`CC1mu2pi`) or $N = 3$ (`CC1mu3pi`). The signal is inclusive with respect to protons, neutrons and neutral pions/electromagnetic activity, subject to the requirement that there is exactly one muon and no other charged leptons. The interaction vertex must lie in the fiducial volume defined in the single-pion note.

Pion-momentum threshold. The accessible signal phase space is bounded from below by the momenta of the pions themselves: a pion must be energetic enough to produce a reconstructable track. In a genuine two- or three-pion event the sub-leading pions are systematically softer than the leading one, and the softest pion sets the floor on how often the full topology can be reconstructed. The single-pion signal definition applies a threshold to *the* pion; for the multi-pion channels this must be generalised so that the momentum requirement applies consistently to *all* N pions rather than to one. Section 6 quantifies the true leading and sub-leading pion spectra and studies the selection efficiency as a function of a per-pion momentum threshold, and recommends the threshold that defines the measurable phase space. That study (Section 6) adopts a per-pion threshold of $p_\pi > 0.10 \text{ GeV}/c$ applied to *all* N pions (the pion tracking turn-on), together with the muon threshold $p_\mu > 0.15 \text{ GeV}/c$ inherited from the single-pion definition.

3 Samples, exposure and normalisation

The samples, beam exposure, per-run protons-on-target normalisation, beam-off (EXT) cosmic treatment and dirt overlay are identical to the single-pion note and are not repeated here. All results in this draft use the Run-1 forward-horn-current (FHC) ν_μ overlay for the efficiency and cut-flow studies; the extension to the full FHC, RHC and combined exposures follows the same

per-run machinery. As in the parent analysis, the beam-on data remain blinded and all data-like distributions use Poisson-thrown fake data.

4 Event selection

`CC1mu2pi` and `CC1mu3pi` inherit the complete `CC1mu1piXp` selection — the same slice, fiducial-volume, topology and muon-candidate requirements — and the same reconstructed observables. Only the pion identification and the required charged-pion multiplicity differ. In the code the multiplicity is a virtual (`required_charged_pions()`) so that the derived value ($N = 2, 3$) takes effect inside the inherited signal definition and reco selection.

Re-using the single-pion pion identification directly gives a prohibitively low efficiency (4.2% for 2π , 0.8% for 3π), because that identification was tuned to isolate a single energetic pion and reject protons: a tight 4 cm vertex window, a track-multivariate/Bragg/length requirement, and cuts on the single muon-pion opening angle and on electromagnetic showers. Following Mahmud [1] and Gu [2], the multi-pion selections loosen the pion identification through five parameters, implemented as overridable virtuals on the base class so that the single-pion selection is left byte-for-byte unchanged (Table 1):

Table 1: Pion-identification parameters overridden by the multi-pion selections. The inclusive defaults reproduce the single-pion selection exactly.

Parameter	Single-pion default	Multi-pion
Vertex-to-track window	4 cm	9.5 cm
Pion identification	LLR-PID + TMVA + Bragg + length	LLR-PID only
Uncontained pions allowed	0	1
μ - π opening-angle cut	applied	not applied
Shower (π^0) veto	applied	not applied

The wider vertex window recovers pions from secondary scatters and slightly displaced starts; the log-likelihood-ratio-only identification drops the proton-rejection cuts that were specific to the one-pion topology; the “maximum uncontainment” tolerance allows a single pion per event to leave the detector; and the opening-angle and shower cuts, which are one-pion-topology cuts (a single μ - π pair, and an electromagnetic veto), are dropped because they are ill-defined or unwanted for a multi-pion, EM-inclusive signal. In the pion loop the contained and uncontained pion candidates are tallied separately and the charged-pion count is formed as the number of contained pions plus up to one uncontained pion.

5 Selection performance

Table 2 gives the cut-flow for both selections on the Run-1 FHC ν_μ overlay. The dominant efficiency loss is at the N -pion identification stage (`MuonCandidate`→`ContainedPions`): reconstructing N pion-like tracks is the efficiency ceiling, while the upstream vertex/topology/muon requirements and the downstream wire-gap and track-multiplicity cuts are comparatively gentle. The loosened identification raises the efficiency by a factor of ~ 4 (2π) and ~ 8 (3π) relative to the single-pion identification, turning 3π from a non-measurement ($\mathcal{O}(1)$ event) into a viable one (~ 40 events).

Table 2: Multi-pion cut-flow yields (Run-1 FHC ν_μ overlay, POT-weighted; beam-off cosmics and dirt not included). “Total” is signal + MC background; Eff. is the cumulative signal efficiency relative to the generated signal (None stage); Pur. = Signal/Total and is MC-intrinsic (an upper bound — the real-sample purity is lower once EXT cosmics, which dominate at these multiplicities, are included). The shower veto and opening-angle cut are not applied.

Cut	Total	Signal	Bkg MC	Eff. [%]	Pur. [%]
<i>CC1mu2pi — exactly 2 charged pions</i>					
None	759 496	3 251	756 245	100.0	0.4
InFiducialVol	177 783	2 751	175 033	84.6	1.5
Topological	83 662	2 259	81 403	69.5	2.7
MuonCandidate	58 791	2 014	56 776	62.0	3.4
ContainedPions	3 372	719	2 653	22.1	21.3
MuonIn3Planes	3 181	681	2 500	21.0	21.4
PionIn3Planes	2 786	600	2 186	18.5	21.5
Final	2 500	530	1 970	16.3	21.2
<i>CC1mu3pi — exactly 3 charged pions</i>					
None	759 496	625	758 871	100.0	0.08
InFiducialVol	177 783	518	177 265	82.9	0.3
Topological	83 662	425	83 237	68.0	0.5
MuonCandidate	58 791	365	58 426	58.4	0.6
ContainedPions	447	50	397	8.0	11.2
MuonIn3Planes	415	48	367	7.7	11.6
PionIn3Planes	384	45	339	7.2	11.7
Final	344	40	304	6.4	11.6

These efficiencies sit below the values reported in the dedicated study [1] (37% for 2π , 31% for 3π) because the selections here retain the inherited muon-momentum-quality, wire-gap, track-multiplicity and software-trigger requirements that the leaner study omits; the trade is a lower efficiency for a markedly higher intrinsic purity, which is the more favourable operating point for a cross-section extraction.

6 Pion-momentum thresholds and the accessible phase space

The efficiency ceiling at the N -pion identification stage is driven by the softest pions in the event. The signal multiplicity is currently defined by counting charged pions above a negligible momentum ($p_\pi > 0$), so a true N -pion event is counted as signal however soft its sub-leading pions are — including pions too soft to produce a reconstructable track. Such events enter the efficiency denominator but can never enter the numerator, mechanically depressing the quoted efficiency. A physically meaningful signal definition applies a momentum threshold to *all* N pions, restricting the measurement to a phase space that can actually be reconstructed.

Method. For each true N -pion signal event we record the leading (hardest) and minimum (softest) true charged-pion momenta, `mc_pionpm_lead_mom` and `mc_pionpm_min_mom`. The efficiency as a function of a per-pion threshold $p_\pi^{\min}$ is then evaluated on the sub-sample whose *softest* pion exceeds the threshold,

$$\varepsilon(p_\pi^{\min}) = \frac{N(\text{selected} \wedge \text{signal} \wedge p_\pi^{\text{soft}} > p_\pi^{\min})}{N(\text{signal} \wedge p_\pi^{\text{soft}} > p_\pi^{\min})},$$

which isolates the effect of removing unreconstructable soft-pion events from the signal definition.

Results. The sub-leading pions are indeed substantially softer than the leading one: on the Run-1 FHC overlay the mean leading (softest) true charged-pion momentum is 0.52 (0.27) GeV/ c for 2π and 0.57 (0.21) GeV/ c for 3π (Table 3). A significant fraction of events have a pion below the tracking turn-on: 10% (18%) of 2π (3π) signal events have their softest pion below 0.10 GeV/ c , rising to 30% (51%) below 0.175 GeV/ c . These events, with an unreconstructable pion, are counted as signal at the current $p_\pi > 0$ threshold but can never pass the reco selection.

Table 3: Signal efficiency as a function of a per-pion momentum threshold $p_\pi^{\min}$ (applied to all N pions via the softest one), Run-1 FHC ν_μ overlay. “Kept” is the fraction of the $p_\pi > 0$ signal retained; Eff. is the efficiency evaluated within the restricted phase space.

$p_\pi^{\min}$ [GeV/ c]	CC1mu2pi		CC1mu3pi	
	Kept	Eff. [%]	Kept	Eff. [%]
0 (current)	1.00	16.3	1.00	6.4
0.10	0.90	17.1	0.82	6.2
0.175	0.70	18.9	0.49	8.1
0.25	0.43	20.2	0.26	5.6

The central result is that raising the threshold *barely changes the efficiency*: restricting to events whose softest pion exceeds 0.175 GeV/ c — i.e. where all pions are comfortably above tracking turn-on — still yields an efficiency of only $\sim 19\%$ (2π). Roughly four in five events with fully reconstructable pions are still lost. The efficiency ceiling is therefore *intrinsic multi-track reconstruction* — resolving N distinct pion tracks from a common vertex in the presence of hadronic re-interactions and track merging — and not the soft-pion threshold. The soft sub-leading pions are a real but secondary effect (10–18% of events genuinely below tracking threshold).

Recommendation. A per-pion momentum threshold of $p_\pi^{\min} \simeq 0.10$ GeV/ c (the pion tracking turn-on) applied to all N pions is adopted for the signal definition: it removes the genuinely unreconstructable soft tail (10–18% of events) at negligible efficiency cost, defines an honest measurable phase space, and preserves $\sim 90\%$ (2π) / $\sim 82\%$ (3π) of the signal — important given the limited statistics, especially for 3π . A tighter 0.175 GeV/ c threshold, matching the single-pion measured phase space, would be cleaner but sacrifices half of the 3π signal and is not justified by the marginal efficiency gain. The threshold does not, and is not expected to, recover the bulk of the efficiency, which is limited by reconstruction and is corrected for by the unfolding.

We also note a bookkeeping issue in the inherited signal definition that must be fixed for the multi-pion channels: the momentum and opening-angle requirements are applied to `TrueCandidatePionP`, which is assigned the *last* charged pion encountered in the daughter loop rather than a well-defined pion. For the single-pion signal this is unambiguous, but for $N > 1$ it applies the cut to an arbitrary pion. The fix, to be applied together with the 0.10 GeV/ c threshold, is to require the softest of the N pions to exceed the threshold (equivalently, to apply the cut to all N).

7 Backgrounds

At these multiplicities the beam-off cosmic (EXT) contribution is expected to dominate the background, followed by ν_μ CC events of the wrong charged-pion multiplicity (single-pion events with an extra mis-identified track, or higher-multiplicity events losing a pion) and neutral-current interactions with charged-pion-like tracks. The cut-flow of Table 2 is the ν_μ overlay only and therefore does not yet include EXT or dirt; a full background composition, including the data-driven EXT subtraction inherited from the parent analysis, is deferred to the next revision. The

MC background composition and any dedicated multi-pion background-control sidebands will be reported alongside.

8 Feasibility and observables

With of order 530 selected signal events at full exposure, the two-pion channel can support a flux-averaged total cross section and, plausibly, a coarse (two- to three-bin) differential measurement in a robust observable such as the leading-pion momentum or the total visible hadronic energy. The three-pion channel, with of order 40 selected signal events, is a flux-averaged total-cross-section measurement. Both will use the same Wiener-SVD unfolding and systematic treatment as the parent analysis; the reduced statistics argue for coarse binning and, for 3π , a single integrated bin. A concrete observable set and binning will be fixed once the threshold study defines the signal phase space and the background model is in place.

9 Systematic uncertainties

The systematic framework — flux (PPFX), cross-section (GENIE reweight), reinteraction and detector-variation universes, propagated through the response matrix and unfolding — is inherited unchanged from the single-pion note. The multi-pion channels are expected to be statistics-limited, so a full systematic evaluation is deferred until the selection and phase space are finalised; the detector-variation samples and the flux/cross-section universes are already available in the same processed files.

10 Status and follow-up

- Selections CC1mu2pi / CC1mu3pi implemented, compiled and validated on Run-1 FHC; cut-flow, efficiency and purity established (Section 5).
- Pion-momentum threshold study in progress (Section 6); will fix the accessible phase space and the per-pion threshold, and correct the signal-def bookkeeping for $N > 1$.
- To do: full background composition including EXT and dirt; extension to full FHC, RHC and combined exposures; observable/binning choice; total (and, for 2π , coarse differential) cross-section extraction with the inherited unfolding and systematics.

References

- [1] T. Mahmud, *Study of ν_μ charged-current three-charged-pion production in MicroBooNE* (CC3 π^+ selection), MSc by Research thesis, Lancaster University.
- [2] L. Gu, multi-pion event-selection analyzer for the MicroBooNE NuMI cross-section framework (private communication / internal code).
- [3] I. Pophale and J. Nowak, *Measurement of $\nu_\mu + \bar{\nu}_\mu$ charged-current single-pion production differential cross sections on argon with MicroBooNE in the NuMI beam*, MicroBooNE analysis note (companion document).