

▼ potentia

> __pycache__

🔗 __init__.py

🔗 asgi.py

🔗 settings.py

1

🔗 test_views.py

🔗 urls.py

🔗 views.py

🔗 wsgi.py



CI Python Linter

```
1  """
2  ASGI config for potentia project.
3
4  It exposes the ASGI callable as a module-level variable named ``application``.
5
6  For more information on this file, see
7  https://docs.djangoproject.com/en/4.2/howto/deployment/asgi/
8  """
9
10 import os
11
12 from django.core.asgi import get_asgi_application
13
14 os.environ.setdefault('DJANGO_SETTINGS_MODULE', 'potentia.settings')
15
16 application = get_asgi_application()
17
```

Settings:



Results:

All clear, no errors found



CI Python Linter

```
1  """
2  Django settings for potentia project.
3
4  Generated by 'django-admin startproject' using Django 4.2.27.
5
6  For more information on this file, see
7  https://docs.djangoproject.com/en/4.2/topics/settings/
8
9  For the full list of settings and their values, see
10 https://docs.djangoproject.com/en/4.2/ref/settings/
11 """
12
13 import os
14 import sys
15 from pathlib import Path
16 import dj_database_url
17 from django.contrib.messages import constants as messages
18 if os.path.isfile('env.py'):
19     import env
20
21 BASE_DIR = Path(__file__).resolve().parent.parent
22 TEMPLATES_DIR = os.path.join(BASE_DIR, 'templates')
23
24 SECRET_KEY = os.environ.get("SECRET_KEY")
25
26 DEBUG = os.environ.get("DEBUG_VALUE", "False") == "True"
27
28 ALLOWED_HOSTS = ['.herokuapp.com', '127.0.0.1', ]
29
30 INSTALLED_APPS = [
31     'django.contrib.admin',
32     'django.contrib.auth',
33     'django.contrib.contenttypes',
34     'django.contrib.sessions',
35     'django.contrib.messages',
36     'django.contrib.staticfiles',
37 ]
38
39 MIDDLEWARE = [
40     'django.middleware.security.SecurityMiddleware',
41     'django.contrib.sessions.middleware.SessionMiddleware',
42     'django.middleware.common.CommonMiddleware',
43     'django.middleware.csrf.CsrfViewMiddleware',
44     'django.contrib.auth.middleware.AuthenticationMiddleware',
45     'django.contrib.messages.middleware.MessageMiddleware',
46 ]
47
48 ROOT_URLCONF = 'potentia.urls'
49
50 WSGI_APPLICATION = 'potentia.wsgi.application'
51
52 DATABASES = {
53     'default': dj_database_url.config(
54         default='sqlite://db.sqlite3',
55         conn_max_age=600,
56         conn_health_checks=True,
57     )
58 }
59
60 EMAIL_BACKEND = 'django.core.mail.backends.smtp.EmailBackend'
61 EMAIL_HOST = 'smtp.gmail.com'
62 EMAIL_HOST_USER = 'potentia@codeinstitute.com'
63 EMAIL_HOST_PASSWORD = 'password'
64 EMAIL_USE_TLS = True
65
66 LOGGING = {
67     'version': 1,
68     'disable_existing_loggers': False,
69     'handlers': {
70         'console': {
71             'class': 'logging.StreamHandler',
72         },
73     },
74     'loggers': {
75         'django': {
76             'handlers': ['console'],
77             'level': 'INFO',
78             'propagate': True,
79         },
80         'potentia': {
81             'handlers': ['console'],
82             'level': 'INFO',
83             'propagate': False,
84         },
85     },
86 }
```

Settings:



Results:

All clear, no errors found



CI Python Linter

```
1 """
2 Django settings for error handling
3 """
4 from django.urls import reverse
5 from django.test import TestCase
6
7
8 class Custom404Tests(TestCase):
9
10     def test_custom_404_view(self):
11         """
12         Test the handler404 view is used for an invalid url.
13         """
14         response = self.client.get('/non-existent-url/')
15         self.assertEqual(response.status_code, 404)
16         self.assertContains(
17             response,
18             "Something went wrong, as this page is not found!",
19             status_code=404,
20         )
21
22     def test_404_for_non_existent_post(self):
23         """
24         Test the handler404 view is used when a coaching post is not found.
25         """
26         response = self.client.get(
27             reverse('coaching_post_detail', args=['non-existent-slug'])
28         )
29         self.assertEqual(response.status_code, 404)
30         self.assertContains(
31             response,
```

Settings:



Results:

All clear, no errors found



CI Python Linter

```
1  """
2  URL configuration for potentia project.
3
4  The `urlpatterns` list routes URLs to views. For more information please see:
5      https://docs.djangoproject.com/en/4.2/topics/http/urls/
6  Examples:
7  Function views
8      1. Add an import:  from my_app import views
9      2. Add a URL to urlpatterns:  path('', views.home, name='home')
10 Class-based views
11     1. Add an import:  from other_app.views import Home
12     2. Add a URL to urlpatterns:  path('', Home.as_view(), name='home')
13 Including another URLconf
14     1. Import the include() function: from django.urls import include, path
15     2. Add a URL to urlpatterns:  path('blog/', include('blog.urls'))
16 """
17 from django.contrib import admin
18 from django.urls import path, include
19
20 urlpatterns = [
21     path('about/', include('about.urls'), name='about_urls'),
22     path("accounts/", include("allauth.urls")),
23     path('admin/', admin.site.urls),
24     path('enquire/', include('enquire.urls'), name='enquire_urls'),
25     path('summernote/', include('django_summernote.urls')),
26     path('', include('home.urls'), name='home_urls'),
27 ]
28
29 handler404 = 'potentia.views.handler404'
30 handler500 = 'potentia.views.handler500'
31
```

Settings:



Results:

All clear, no errors found



CI Python Linter

```
1  """
2  Django settings for error handling.
3  Views to handle errors.
4  """
5  from django.shortcuts import render
6
7
8  def handler404(request, exception=None):
9      """ Error Handler 404 - Page Not Found """
10     return render(request, "errors/404.html", status=404)
11
12
13  def handler500(request):
14      """ Error Handler 500 - Internal Server Error """
15     return render(request, "errors/500.html", status=500)
16  |
```

Settings:



Results:

All clear, no errors found



CI Python Linter

```
1  """
2  WSGI config for potentia project.
3
4  It exposes the WSGI callable as a module-level variable named ``application``.
5
6  For more information on this file, see
7  https://docs.djangoproject.com/en/4.2/howto/deployment/wsgi/
8  """
9
10 import os
11
12 from django.core.wsgi import get_wsgi_application
13
14 os.environ.setdefault('DJANGO_SETTINGS_MODULE', 'potentia.settings')
15
16 application = get_wsgi_application()
17
```

Settings:



Results:

All clear, no errors found