

Input =
Result =
Static Value =
Logic High =
Logic Low =
Non-Default =

Configure register settings

Address (Hex)	Read / Write	Default (Hex)	7	6	5	4	Bit #		3	2	1	0	Value	Read Command
0x00	R/W	00h	MUX[3:0]				GAIN[2:0]					PGA_BYPASS	3Eh	20h
			0	0	1	1	1	1	1	0				
			AINP = AIN1, AINN = AIN2				128 V/V					PGA enabled (default)		
0x01	R/W	00h	DR[2:0]			MODE[1:0]			CM	TS	BCS	#N/D	24h	
			#N/D	#N/D	#N/D	0	1	0	0	0				
			20 SPS (default)			Duty-cycle mode			Single-shot mode (default)	Disables temp sensor (default)	Current sources off (default)			
0x02	R/W	00h	VREF[1:0]		50/60[1:0]		PSW		IDAC[2:0]				47h	28h
			0	1	0	0	0	1	1	1				
			External reference using REFP0 and REFN0 inputs		No 50-Hz or 60-Hz rejection (default)		Switch is always open (default)		1500 μ A					
0x03	R/W	00h	I1MUX[2:0]			I2MUX[2:0]				DRDYM		---	A4h	2Ch
			1	0	1	0	0	1	0	0				
			IDAC1 connected to REFP0			IDAC2 connected to AIN0/REFP1				Dedicated DRDY pin only (default)		Reserved		



[Table of Contents](#)

Legend

#
#
#
#
#
#

Write
Command

40h, 3Eh

#N/D

48h, 47h

4Ch, A4h