Designer's Data Sheet

Power Field Effect Transistor

N-Channel Enhancement-Mode Silicon Gate TMOS

MTH30N20

TMOS

TMOS POWER FET
30 AMPERES
$r_{DS(on)}$ = 0.08 OHM
200 VOLTS

This TMOS Power FET is designed for medium voltage, high speed power switching applications such as switching regulators, converters, solenoid and relay drivers.

- Silicon Gate for Fast Switching Speeds — Switching Times Specified at 100°C
- Designer's Data — I_{DSS}, $V_{DS(on)}$, $V_{GS(th)}$ and SOA Specified at Elevated Temperature
- Rugged — SOA is Power Dissipation Limited
- Source-to-Drain Diode Characterized for Use With Inductive Loads



CASE 340-02
TO-218AC

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Drain-Source Voltage	V_{DSS}	200	Vdc
Drain-Gate Voltage (R_{GS} = 1 MΩ)	V_{DGR}	200	Vdc
Gate-Source Voltage Continuous Non-repetitive ($t_p \leq 50\ \mu s$)	 V_{GS} V_{GSM}	 ±20 ±40	 Vdc Vpk
Drain Current — Continuous — Pulsed	I_D I_{DM}	30 90	Adc
Total Power Dissipation @ T_C = 25°C Derate above 25°C	P_D	150 1.2	Watts W/°C
Operating and Storage Temperature Range	T_J, T_{stg}	−65 to 150	°C

THERMAL CHARACTERISTICS

Thermal Resistance — Junction to Case — Junction to Ambient	$R_{\theta JC}$ $R_{\theta JA}$	0.83 30	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 5 seconds	T_L	275	°C

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Drain-Source Breakdown Voltage (V_{GS} = 0, I_D = 0.25 mA) MTH30N20	$V_{(BR)DSS}$	200	—	Vdc
Zero Gate Voltage Drain Current (V_{DS} = Rated V_{DSS}, V_{GS} = 0) (V_{DS} = Rated V_{DSS}, V_{GS} = 0, T_J = 125°C)	I_{DSS}	 — —	 10 100	μAdc
Gate-Body Leakage Current, Forward (V_{GSF} = 20 Vdc, V_{DS} = 0)	I_{GSSF}	—	100	nAdc
Gate-Body Leakage Current, Reverse (V_{GSR} = 20 Vdc, V_{DS} = 0)	I_{GSSR}	—	100	nAdc

(continued)

Designer's Data for "Worst Case" Conditions — The Designer's Data Sheet permits the design of most circuits entirely from the information presented. Limit curves — representing boundaries on device characteristics — are given to facilitate "worst case" design

ELECTRICAL CHARACTERISTICS — continued (T_C = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
ON CHARACTERISTICS*					
Gate Threshold Voltage (V_{DS} = V_{GS}, I_D = 1 mA) T_J = 100°C		$V_{GS(th)}$	2 1.5	4.5 4	Vdc
Static Drain-Source On-Resistance (V_{GS} = 10 Vdc, I_D = 15 Adc)		$r_{DS(on)}$	—	0.08	Ohm
Drain-Source On-Voltage (V_{GS} = 10 V) (I_D = 30 Adc) (I_D = 15 Adc, T_J = 100°C)		$V_{DS(on)}$	— —	2.85 1.92	Vdc
Forward Transconductance (V_{DS} = 10 V, I_D = 15 A)		g_{FS}	10	—	mhos
DYNAMIC CHARACTERISTICS					
Input Capacitance	(V_{DS} = 25 V, V_{GS} = 0, f = 1 MHz) See Figure 11	C_{iss}	—	5500	pF
Output Capacitance		C_{oss}	—	1500	
Reverse Transfer Capacitance		C_{rss}	—	500	
SWITCHING CHARACTERISTICS* (T_J = 100°C)					
Turn-On Delay Time	(V_{DD} = 25 V, I_D = 0.5 Rated I_D R_{gen} = 50 ohms) See Figures 9, 13 and 14	$t_{d(on)}$	—	50	ns
Rise Time		t_r	—	300	
Turn-Off Delay Time		$t_{d(off)}$	—	150	
Fall Time		t_f	—	150	
Total Gate Charge	(V_{DS} = 0.8 Rated V_{DSS}, I_D = Rated I_D, V_{GS} = 10 V) See Figure 12	Q_g	85 (Typ)	95	nC
Gate-Source Charge		Q_{gs}	45 (Typ)	—	
Gate-Drain Charge		Q_{gd}	40 (Typ)	—	
SOURCE DRAIN DIODE CHARACTERISTICS*					
Forward On-Voltage	(I_S = Rated I_D, V_{GS} = 0)	V_{SD}	1.2 (Typ)	2	Vdc
Forward Turn-On Time		t_{on}	Limited by stray inductance		
Reverse Recovery Time		t_{rr}	200 (Typ)	—	ns
INTERNAL PACKAGE INDUCTANCE					
Internal Drain Inductance (Measured from the contact screw on tab to center of die) (Measured from the drain lead 0.25" from package to center of die)		L_d	4 (Typ) 5 (Typ)	— —	nH
Internal Source Inductance (Measured from the source lead 0.25" from package to source bond pad)		L_s	10 (Typ)	—	

*Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.

3

TYPICAL ELECTRICAL CHARACTERISTICS



Figure 1. On-Region Characteristics



Figure 2. Gate-Threshold Voltage Variation With Temperature



Figure 3. Transfer Characteristics



Figure 4. Breakdown Voltage Variation With Temperature



Figure 5. On-Resistance versus Drain Current



Figure 6. On-Resistance Variation With Temperature

SAFE OPERATING AREA INFORMATION



Figure 7. Maximum Rated Forward Biased Safe Operating Area



Figure 8. Maximum Rated Switching Safe Operating Area

FORWARD BIASED SAFE OPERATING AREA

The FBSOA curves define the maximum drain-to-source voltage and drain current that a device can safely handle when it is forward biased, or when it is on, or being turned on. Because these curves include the limitations of simultaneous high voltage and high current, up to the rating of the device, they are especially useful to designers of linear systems. The curves are based on a case temperature of 25°C and a maximum junction temperature of 150°C. Limitations for repetitive pulses at various case temperatures can be determined by using the thermal response curves. Motorola Application Note, AN569, "Transient Thermal Resistance-General Data and Its Use" provides detailed instructions.

SWITCHING SAFE OPERATING AREA

The switching safe operating area (SOA) of Figure 8 is the boundary that the load line may traverse without incurring damage to the MOSFET. The fundamental limits are the peak current, I_{DM} and the breakdown voltage, $V_{(BR)DSS}$. The switching SOA shown in Figure 8 is applicable for both turn-on and turn-off of the devices for switching times less than one microsecond.

The power averaged over a complete switching cycle must be less than:

$$\frac{T_{J(max)} - T_C}{R_{\theta JC}}$$



Figure 9. Resistive Switching Time Variation versus Gate Resistance



Figure 10. Thermal Response



Figure 11. Capacitance Variation



Figure 12. Gate Charge versus Gate-to-Source Voltage

3

RESISTIVE SWITCHING



Figure 13. Switching Test Circuit



Figure 14. Switching Waveforms

OUTLINE DIMENSIONS

CASE 340-02
TO-218AC



STYLE 2
PIN 1. GATE
2 DRAIN
3 SOURCE
4 DRAIN

DIM	MILLIMETERS MIN	MILLIMETERS MAX	INCHES MIN	INCHES MAX
A	20.32	21.08	0.800	0.830
B	15.49	15.90	0.610	0.626
C	4.19	5.08	0.165	0.200
D	1.02	1.65	0.040	0.065
E	1.35	1.65	0.053	0.065
G	5.21	5.72	0.205	0.225
H	2.65	2.94	0.104	0.116
J	0.51	0.71	0.020	0.028
K	12.70	15.49	0.500	0.610
L	15.88	16.51	0.625	0.650
N	12.19	12.70	0.480	0.500
Q	4.04	4.22	0.159	0.166

NOTES
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH