
Let's Drink

mockito



- A short introduction to mock framework



Agenda

- Mock? Why?
- Mockito ?
- Mockito - how to drink it? - framework basics
- Mockito and Spring
- Mockito – drinking examples
- Mockito with threads
- Mockito - pros and cons
- What else to use?
- Rules to remember



Mock? Why?

- Mock - a simulated object that mimics the behavior of a real object in controlled ways.



Mock? Why?

- Better and faster testing and tests (also TTM)
- Integrate different systems
- Simpler small box -> Better design
- Faster to find bugs -> higher quality
- Why bother asking?



Mockito?

- is a mocking framework that tastes really good. It lets you write beautiful tests with clean & simple API. Mockito doesn't give you hangover because the tests are very readable and they produce clean verification errors (from code.google.com/p/mockito)



Mockito, how to drink it? framework basics

Stub - Mockito can mock concrete classes, not only interfaces

- *import static org.mockito.Mockito.*;*
-
- *//mock creation*
- *LinkedList mockedList = mock(LinkedList.class);*
-
- *//using mock object*
- *mockedList.add("one");*
- *mockedList.clear();*
-
- *//verification*
- *verify(mockedList).add("one");*
- *verify(mockedList).clear();*
-
- Once created, mock will remember all interactions. Then you can selectively verify whatever interaction you are interested in.
- By default, for all methods that return value, mock returns null, an empty collection or appropriate primitive/primitive wrapper value (e.g: 0, false, ... for int/Integer, boolean/Boolean, ...).
- Stubbing can be overridden: for example common stubbing can go to fixture setup but the test methods can override it. Please note that overriding stubbing is a potential code smell that points out too much stubbing
- Once stubbed, the method will always return stubbed value regardless of how many times it is called.
- Last stubbing is more important - when you stubbed the same method with the same arguments many times.



Mockito, how to drink it? framework basics

Spy - Mockito support test spies not just mocks

- `List spy = spy(new LinkedList());`
-
- *//optionally, you can stub out methods:*
- `when(spy.size()).thenReturn(100);`
-
- *//using the spy calls real methods*
- `spy.add("one");`
- `spy.add("two");`
-
- *//prints "one" - the first element of a list*
- `System.out.println(spy.get(0));`
-
- *//size() method was stubbed - 100 is printed*
- `System.out.println(spy.size());`
-
- *//optionally, you can verify*
- `verify(spy).add("one");`
- `verify(spy).add("two");`

Important note on spying real objects!

1. Sometimes it's impossible to use `when(Object)` for stubbing spies. Example:

```
List list = new LinkedList();  
List spy = spy(list);
```

//Impossible: real method is called so spy.get(0) throws IndexOutOfBoundsException (the list is yet empty)

```
when(spy.get(0)).thenReturn("foo");
```

//You have to use doReturn() for stubbing
`doReturn("foo").when(spy).get(0);`

2. Mockito doesn't mock final methods so the bottom line is: when you spy on real objects + you try to stub a final method = trouble.



Mockito, how to drink it? framework basics

•Argument matchers

- Stubbing Build in (anyInt(), eq(), anyString()...)
- *when(mockedList.get(anyInt())).thenReturn("element");*
- Stubbing Hamcrest (argThat(org.hamcrest.Matcher))
- *when(mockedList.contains(argThat(isValid()))).thenReturn("element");*
- ArgumentCaptor to capture argument values for further assertion
- *public class ArgumentCaptor<T> extends java.lang.Object*
- *ArgumentCaptor<Person> argument = ArgumentCaptor.forClass(Person.class);*
- *verify(mock).doSomething(argument.capture());*
- *assertEquals("John", argument.getValue().getName());*
- Also possible in verification
- *verify(mockedList).get(anyInt());*



Mockito, how to drink it? framework basics

Verifying - verify()

- `mockedList.add("once");`
- `mockedList.add("twice");`
- `mockedList.add("twice");`
-
- *//following two verifications work exactly the same - times(1) is used by default*
- `verify(mockedList).add("once");`
-
- *//exact number of invocations verification*
- `verify(mockedList, times(2)).add("twice");`
-
- *//verification using never(). never() is an alias to times(0)*
- `verify(mockedList, never()).add("never happened");`
-
- *//verification using atLeast()/atMost()*
- `verify(mockedList, atLeastOnce()).add("three times");`
- `verify(mockedList, atLeast(2)).add("five times");`
- `verify(mockedList, atMost(5)).add("three times");`
-
- `verifyZeroInteractions(mockedList2)...`



Mockito, how to drink it? framework basics

•Maintain order – inOrder()

```
List firstMock = mock(List.class);  
List secondMock = mock(List.class);
```

```
//using mocks  
firstMock.add("was called first");  
secondMock.add("was called second");
```

```
//create inOrder object passing any mocks that need to be verified in order  
InOrder inOrder = inOrder(firstMock, secondMock);
```

```
//following will make sure that firstMock was called before secondMock  
inOrder.verify(firstMock).add("was called first");  
inOrder.verify(secondMock).add("was called second");
```



Mockito, how to drink it? framework basics

- **Return value thenReturn()**

- *when(mock.someMethod("some arg")).thenReturn("foo");*

- **Stubbing voids requires doReturn()**

- *doReturn("bar").when(mock).foo();*



Mockito, how to drink it? framework basics

•Exception thenThrow()

- when(mock.someMethod("some arg"))*
- .thenThrow(new RuntimeException())*

•Stubbing voids requires doThrow()

- *doThrow(new RuntimeException()).when(mockedList).clear();*
- *//following throws RuntimeException:*
- *mockedList.clear();*



Mockito, how to drink it? framework basics

•Return statefull mock answer thenAnswer()

```
•.when(mock.someMethod(anyString())).thenAnswer(new Answer() {  
•    Object answer(InvocationOnMock invocation) {  
•        Object[] args = invocation.getArguments();  
•        Object mock = invocation.getMock();  
•        return "called with arguments: " + args;  
•    }  
•});
```

•Stubbing voids do Answer()

```
• doAnswer(new Answer() {  
•     public Object answer(InvocationOnMock invocation) {  
•         Object[] args = invocation.getArguments();  
•         Mock mock = invocation.getMock();  
•         return null;  
•     })  
• .when(mock).someMethod();
```



Mockito, how to drink it? framework basics

•Other

- Calling real method
- `when(mock.someMethod()).thenCallRealMethod();`
- BDD aliases (given)
- Serializable mocks
- `mock(List.class, withSettings().serializable());`
- Annotations
- `@Mock, @Captor, @Spy, @InjectMocks`
- Verification with timeout
- `verify(mock, timeout(100)).someMethod();`
- Reset (try not to use to often)
- `reset(mock)`



Mockito and Spring

Hardcoded approach

```
•@RunWith(SpringJUnit4ClassRunner.class)
•@ContextConfiguration(locations = {
•    "classpath:applicationConfig.xml"
•})
•public class DoSthTest {

•@Test
•public void shouldDoSth() {}
•// given
•    HttpClient mockHttpClient = Mockito.mock(HttpClient.class);
•    serviceToTest.setHttpClient(mockHttpClient);
•    ...
•}
```



Mockito pros and cons

•Pros

- Mockito is almost everywhere (python, java, c++, .Net)
- A Good Humane Interface for Stubbing
- Class (not just Interface) Mocks
- Supports Test Spies, not just Mocks
- Better Void Method Handling
- Easy to write
- Easy to learn
- Validation

•Cons

- Difficult to read (solution -> use given, when, then approach)
- AbstractTestCases maintenance (solution -> avoid it)
- Verify vs asserts can be badly used (try to use asserts)
- Hard to learn ArgumentMatcher (solution -> just learn it ;))
- Limitations of framework (rare cases but cant do anything about it)
 - Cannot mock final classes
 - Cannot mock static methods
 - Cannot mock final methods - their real behavior is executed without any exception. Mockito cannot warn you about mocking final methods so be vigilant.
 - Cannot mock equals(), hashCode(). But that you should not mock
 - Spying on real methods where real implementation references outer Class via OuterClass.this is impossible. Don't worry, this is extremely rare case.



What else to use

- PowerMock (private, final,static methods)
- Jmockit (constructors and static methods mocking)
- Hamcrest (library of matcher objects (also known as constraints or predicates) allowing 'match' rules to be defined declaratively)
- ?



General rules to remember

- Mock it outside your code
- If you cannot test your code -> then probably you should change it ;) cause its badly written
- Test first
- Only one concrete class , mock the rest
- Only mock your nearest neighbour (Law of Demeter -> dont talk with strangers)
- Think ;) and then write



Thank you for your attention

