

Test case 0

Test case 1

Test case 2

1	5
2	1 4
3	2 5
4	3 898
5	1 3
6	2 12

Expected Output:

1	EVEN
2	PRIME
3	PALINDROME
4	ODD
5	COMPOSITE

Download

Next Challenge

hackerank.com/challenges/java-lambda-expressions/problem

School

Facebook

Twitter

LinkedIn

Congratulations

You solved this challenge. Would you like to challenge your friends?

Congratulations

You solved this challenge. Would you like to challenge your friends?

[Next Challenge](#)

Test case 0

Compiler Message

Success

Test case 1

Test case 2

Input (stdin)

[Download](#)

```
1 5
2 amy 100
3 david 100
4 heraldo 50
5 aakashsha 75
6 aleksa 150
```

Test case 3

Test case 4

Test case 5

Expected Output

[Download](#)

```
1 aleksa 150
```



You have earned 10.00 points!
You are now 30 points away from the 3rd star for your java badge.



Congratulations

You solved this challenge. Would you like to challenge your friends?



Next Challenge

Test case 0

Compiler Message

Test case 1

Success

Test case 2

Input (stdin)

Download

Test case 3

```
1 5
2 33 Rumpa 3.68
3 85 Ashis 3.85
4 56 Samiha 3.75
5 19 Samara 3.75
6 22 Fahim 3.76
```

Line: 24 Col: 2

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations

You solved this challenge. Would you like to challenge your friends?



Next Challenge

Test case 0

Test case 1

Test case 2

Test case 3

Test case 4

Test case 5

Test case 6

Compiler Message

Success

Input (stdin)

```
1 5
2 amy 100
3 david 100
4 heraldo 50
5 aakansha 75
6 aleksa 150
```

Download

Expected Output

Download

leetcode.com/problems/running-sum-of-1d-array/

Problem List

Submit

School

Premium

Description

Editorial

Solutions

Submissions

1480. Running Sum of 1d Array

EasyTopicsCompaniesHint

Given an array `nums`. We define a running sum of an array as `runningSum[i] = sum(nums[0]...nums[i])`.

Return the running sum of `nums`.

Example 1:

Input: `nums = [1,2,3,4]`
Output: `[1,3,6,10]`
Explanation: Running sum is obtained as follows: `[1, 1+2, 1+2+3, 1+2+3+4]`.

Example 2:

Input: `nums = [1,1,1,1,1]`
Output: `[1,2,3,4,5]`
Explanation: Running sum is obtained as follows: `[1, 1+1, 1+1+1, 1+1+1+1, 1+1+1+1+1]`.

Example 3:

Input: `nums = [3,1,2,10,1]`
Output: `[3,4,6,16,17]`

8.9K218153 Online

Code

JavaAuto

```
1
2
3
4
5
6
7
8
9
10
11
class Solution {
    public int[] runningSum(int[] nums) {
        for (int i = 1; i < nums.length; i++) {
            nums[i] = nums[i] + nums[i - 1];
        }
        return nums;
    }
}
```

SavedLn 11, Col 2

Testcase

Test Result

AcceptedRuntime: 0 ms

Case 1Case 2Case 3

Input

nums =
[1, 2, 3, 4]

leetcode.com/problems/richest-customer-wealth/

Problem List

Submit

Run

Ctrl

0

School

Premium

Description

Editorial

Solutions

Submissions

1672. Richest Customer Wealth

EasyTopicsCompaniesHint

You are given an $m \times n$ integer grid `accounts` where `accounts[i][j]` is the amount of money the i^{th} customer has in the j^{th} bank. Return the **wealth** that the richest customer has.

A customer's **wealth** is the amount of money they have in all their bank accounts. The richest customer is the customer that has the maximum **wealth**.

Example 1:

Input: `accounts = [[1,2,3],[3,2,1]]`
Output: 6
Explanation:
1st customer has wealth = 1 + 2 + 3 = 6
2nd customer has wealth = 3 + 2 + 1 = 6
Both customers are considered the richest with a wealth of 6 each, so return 6.

Example 2:

Input: `accounts = [[1,5],[7,3],[3,5]]`
Output: 10
Explanation:
1st customer has wealth = 6
2nd customer has wealth = 10
3rd customer has wealth = 8
The 2nd customer is the richest with a wealth of 10.

4.9K10833 Online

Code

JavaAuto

```
1 class Solution {
2     public int maximumWealth(int[][] accounts) {
3
4         int maxWealth = 0;
5
6         for (int i = 0; i < accounts.length; i++) {
7
8             int wealth = 0;
9
10            for (int j = 0; j < accounts[i].length; j++) {
11                wealth = wealth + accounts[i][j];
12            }
13
14            if (wealth > maxWealth) {
15                maxWealth = wealth;
16            }
17        }
18    }
```

SavedLn 21, Col 2

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2Case 3

Input

accounts =
[[1,2,3],[3,2,1]]

leetcode.com/problems/squares-of-a-sorted-array/

Problem List

Run

Submit

School

Premium

Description

Editorial

Solutions

Submissions

977. Squares of a Sorted Array

Attempted

Easy

Topics

Companies

Given an integer array `nums` sorted in **non-decreasing** order, return an array of *the squares of each number* sorted in non-decreasing order.

Example 1:

Input: `nums = [-4,-1,0,3,10]`
Output: `[0,1,9,16,100]`
Explanation: After squaring, the array becomes `[16,1,0,9,100]`. After sorting, it becomes `[0,1,9,16,100]`.

Example 2:

Input: `nums = [-7,-3,2,3,11]`
Output: `[4,9,9,49,121]`

Constraints:

- `1 <= nums.length <= 104`
- `-104 <= nums[i] <= 104`
- `nums` is sorted in **non-decreasing** order.

10.4K194131 Online

Code

Java

Auto

```
1 import java.util.Arrays;
2
3 class Solution {
4     public int[] sortedSquares(int[] nums) {
5
6         for (int i = 0; i < nums.length; i++) {
7             nums[i] = nums[i] * nums[i];
8         }
9
10        Arrays.sort(nums);
11
12        return nums;
13    }
14 }
```

SavedLn 14, Col 2

Testcase

Test Result

AcceptedRuntime: 1 ms

Case 1Case 2

Input

nums =
[-4,-1,0,3,10]

leetcode.com/problems/find-pivot-index/

Problem List

Submit

Run

Ctrl

Submit

0

School

Premium

Description

Editorial

Solutions

Submissions

724. Find Pivot Index

EasyTopicsCompaniesHint

Given an array of integers `nums`, calculate the **pivot index** of this array.

The **pivot index** is the index where the sum of all the numbers **strictly** to the left of the index is equal to the sum of all the numbers **strictly** to the index's right.

If the index is on the left edge of the array, then the left sum is `0` because there are no elements to the left. This also applies to the right edge of the array.

Return the **leftmost pivot index**. If no such index exists, return `-1`.

Example 1:

Input: `nums = [1,7,3,6,5,6]`

Output: `3`

Explanation:

The pivot index is 3.

Left sum = `nums[0] + nums[1] + nums[2] = 1 + 7 + 3 = 11`

Right sum = `nums[4] + nums[5] = 5 + 6 = 11`

Example 2:

Input: `nums = [1,2,3]`

Output: `-1`

Explanation:

Code

Java

Auto

```
11 int leftSum = 0;
12
13 // Find pivot index
14 for (int i = 0; i < nums.length; i++) {
15
16     int rightSum = totalSum - leftSum - nums[i];
17
18     if (leftSum == rightSum) {
19         return i;
20     }
21
22     leftSum += nums[i];
23 }
24
25 return -1;
26 }
27 }
```

SavedLn 27, Col 2

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1Case 2Case 3

Input

nums =
[1,7,3,6,5,6]

9.5K273163 Online

Line: 24 Col: 2

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations

You solved this challenge. Would you like to challenge your friends?



Next Challenge

Test case 0

Test case 1

Test case 2

Test case 3

Test case 4

Test case 5

Test case 6

Compiler Message

Success

Input (stdin)

```
1 5
2 amy 100
3 david 100
4 heraldo 50
5 aakansha 75
6 aleksa 150
```

Download

Expected Output

Download

leetcode.com/problems/richest-customer-wealth/

Problem List

Submit

Run

Ctrl

0

School

Premium

Description

Editorial

Solutions

Submissions

1672. Richest Customer Wealth

EasyTopicsCompaniesHint

You are given an $m \times n$ integer grid `accounts` where `accounts[i][j]` is the amount of money the i^{th} customer has in the j^{th} bank. Return the **wealth** that the richest customer has.

A customer's **wealth** is the amount of money they have in all their bank accounts. The richest customer is the customer that has the maximum **wealth**.

Example 1:

Input: `accounts = [[1,2,3],[3,2,1]]`
Output: 6
Explanation:
1st customer has wealth = 1 + 2 + 3 = 6
2nd customer has wealth = 3 + 2 + 1 = 6
Both customers are considered the richest with a wealth of 6 each, so return 6.

Example 2:

Input: `accounts = [[1,5],[7,3],[3,5]]`
Output: 10
Explanation:
1st customer has wealth = 6
2nd customer has wealth = 10
3rd customer has wealth = 8
The 2nd customer is the richest with a wealth of 10.

4.9K10833 Online

Code

JavaAuto

```
1 class Solution {
2     public int maximumWealth(int[][] accounts) {
3
4         int maxWealth = 0;
5
6         for (int i = 0; i < accounts.length; i++) {
7
8             int wealth = 0;
9
10            for (int j = 0; j < accounts[i].length; j++) {
11                wealth = wealth + accounts[i][j];
12            }
13
14            if (wealth > maxWealth) {
15                maxWealth = wealth;
16            }
17        }
18    }
```

SavedLn 21, Col 2

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2Case 3

Input

accounts =
[[1,2,3],[3,2,1]]