Code Blame 35 lines (30 loc) · 682 Bytes

```c
#include <sys/types.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>

#define SharedMemSize 50

void main()
{
    char c;
    int shmid;
    key_t key;
    char *shared_memory;
    key = 5677;

    // Create segment with the key specified
    if ((shmid = shmget(key, SharedMemSize, IPC_CREAT | 0666)) < 0)
    {
        // perror explains error code
        perror("shmget");
        exit(1);
    }

    // Attach the segment
    if((shared_memory= shmat(shmid, NULL, 0)) == (char *) -1) {
        perror("shmat");
        exit(1);
    }

    sprintf(shared_memory," Welcome to Shared Memory");
    sleep(2);
    exit(0);
}
```

Code Blame 30 lines (25 loc) · 607 Bytes

```c
#include <sys/types.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <stdio.h>
#include <stdlib.h>

#define SharedMemSize 50

void main()
{
    int shmid;
    key_t key;
    char *shared_memory;
    key = 5677;

    if ((shmid = shmget(key, SharedMemSize, 0666)) < 0) {
        perror("shmget");
        exit(1);
    }

    // Attach the segment to our data space
    if((shared_memory = shmat(shmid, NULL, 0))==(char *) -1) {
        perror("shmat");
        exit(1);
    }

    // Read the message sender sent to the shared memory
    printf("Message Received: %s \n",shared_memory);
    exit(0);
}
```

jashwanth@localhost:~/Lab/OS/IPC

~/Lab/OS/IPC

```
jashwanth@lecalhost:~/Lab/OS/IPC$ gcc sender.c -o s && gcc receiver.c -o r
jashwanth@localhost:~/Lab/OS/IPC$ ./s
jashwanth@localhost:~/Lab/OS/IPC$ ./r
Message Received:  Welcome to Shared Memory
jashwanth@localhost:~/Lab/OS/IPC$
```