

Newly Added by EXL

Phase 1 : Release 1

chat Table: These 2 columns in chat table **newly added by EXL Team.**

```
ALTER TABLE chats
ADD COLUMN temporary BOOLEAN NOT NULL DEFAULT FALSE,
ADD COLUMN view BOOLEAN NOT NULL DEFAULT TRUE ;
```

sharedlinks Table : Newly created by EXL Team.

```
CREATE TABLE IF NOT EXISTS sharedlinks (
id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
-- REQUIRED RELATIONSHIPS
user_id UUID NOT NULL REFERENCES auth.users(id) ON DELETE CASCADE,
chat_id UUID NOT NULL REFERENCES chats(id) ON DELETE CASCADE,
workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE CASCADE,
-- METADATA
created_at TIMESTAMPTZ NOT NULL DEFAULT CURRENT_TIMESTAMP,
updated_at TIMESTAMPTZ,
url TEXT NOT NULL,
type character varying null,
name TEXT NOT NULL CHECK (char_length(name) <= 200) );
```

--- RLS ---

```
ALTER TABLE sharedlinks ENABLE ROW LEVEL SECURITY;
```

```
CREATE POLICY "Allow full access to own sharedlinks"
ON sharedlinks
USING (user_id = auth.uid())
WITH CHECK (user_id = auth.uid());
```

UserInstructions Table: Newly created by EXL Team.

```
CREATE TABLE IF NOT EXISTS userinstructions (  
  -- ID  
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),  
  -- REQUIRED RELATIONSHIPS  
  user_id UUID NOT NULL REFERENCES auth.users(id) ON DELETE CASCADE,  
  -- METADATA  
  created_at TIMESTAMPTZ NOT NULL DEFAULT CURRENT_TIMESTAMP,  
  updated_at TIMESTAMPTZ,  
  -- REQUIRED  
  description TEXT NOT NULL CHECK (char_length(description) <= 500));
```

*** This below Storage Bucket newly created by EXL Team.*

Storage Bucket name : rag-pipeline

Directories:

1. chunking
2. digitization
3. pdf-uploads

Phase 1 : Release 2

Projects Table: Newly created by EXL Team.

```
CREATE TABLE IF NOT EXISTS projects (  
  -- ID  
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),  
  -- REQUIRED RELATIONSHIPS  
  user_id UUID NOT NULL REFERENCES auth.users(id) ON DELETE CASCADE,  
  workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE CASCADE,  
  -- METADATA  
  created_at TIMESTAMPTZ NOT NULL DEFAULT CURRENT_TIMESTAMP,  
  updated_at TIMESTAMPTZ,  
  -- REQUIRED  
  project_title TEXT NOT NULL CHECK (char_length(description) <= 500),  
  description TEXT NOT NULL CHECK (char_length(description) <= 500));
```

--- RLS ---

```
ALTER TABLE projects ENABLE ROW LEVEL SECURITY;
```

```
CREATE POLICY "Allow full access to own projects"  
  ON projects  
  USING (user_id = auth.uid())  
  WITH CHECK (user_id = auth.uid());
```

Upload_files: Newly created by EXL Team.

```
CREATE TABLE IF NOT EXISTS upload_files (  
  -- ID  
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),  
  -- REQUIRED RELATIONSHIPS  
  user_id UUID NOT NULL REFERENCES auth.users(id) ON DELETE CASCADE,  
  project_id UUID REFERENCES projects(id) ON DELETE SET NULL,  
  chat_id UUID REFERENCES chats(id) ON DELETE SET NULL,  
  -- METADATA  
  created_at TIMESTAMPTZ NOT NULL DEFAULT CURRENT_TIMESTAMP,  
  updated_at TIMESTAMPTZ,  
  --OPTIONAL  
  description TEXT NULL CHECK (char_length(description) <= 100),  
  file_name TEXT NULL CHECK (char_length(file_name) <= 100),  
  file_type TEXT NULL CHECK (char_length(file_type) <= 100),  
  -- REQUIRED  
  file_url TEXT NOT NULL CHECK (char_length(file_url) <= 1000),  
  file_path TEXT NOT NULL CHECK (char_length(file_path) <= 1000));
```

uploaded_chunks: Newly created by EXL Team.

```
CREATE TABLE IF NOT EXISTS uploaded_chunks (  
  -- ID  
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),  
  -- REQUIRED RELATIONSHIPS  
  user_id UUID NOT NULL REFERENCES auth.users(id) ON DELETE CASCADE,  
  project_id UUID REFERENCES projects(id) ON DELETE SET NULL,  
  chat_id UUID REFERENCES chats(id) ON DELETE SET NULL,
```

```

-- METADATA
created_at TIMESTAMPTZ NOT NULL DEFAULT CURRENT_TIMESTAMP,
updated_at TIMESTAMPTZ,
--OPTIONAL
description TEXT NULL CHECK (char_length(description) <= 100),
file_name TEXT NULL CHECK (char_length(file_name) <= 100),
file_type TEXT NULL CHECK (char_length(file_type) <= 100),
-- REQUIRED
file_url TEXT NOT NULL CHECK (char_length(file_url) <= 1000),
file_path TEXT NOT NULL CHECK (char_length(file_path) <= 1000));

```

extracted_text: Newly created by EXL Team.

```

CREATE TABLE IF NOT EXISTS extracted_text (
-- ID
id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
-- REQUIRED RELATIONSHIPS
user_id UUID NOT NULL REFERENCES auth.users(id) ON DELETE CASCADE,
project_id UUID REFERENCES projects(id) ON DELETE SET NULL,
chat_id UUID REFERENCES chats(id) ON DELETE SET NULL,
-- METADATA
created_at TIMESTAMPTZ NOT NULL DEFAULT CURRENT_TIMESTAMP,
updated_at TIMESTAMPTZ,
--OPTIONAL
description TEXT NULL CHECK (char_length(description) <= 100),
file_name TEXT NULL CHECK (char_length(file_name) <= 100),
file_type TEXT NULL CHECK (char_length(file_type) <= 100),
-- REQUIRED
source_type TEXT NOT NULL CHECK (char_length(source_type) <= 100),
file_url TEXT NOT NULL CHECK (char_length(file_url) <= 1000),
file_path TEXT NOT NULL CHECK (char_length(file_path) <= 1000));

```

Feedbacks Table: Newly created by EXL Team.

```

CREATE TABLE IF NOT EXISTS feedbacks (
-- ID
id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),

```

```
user_id UUID NOT NULL REFERENCES auth.users(id) ON DELETE CASCADE,  
-- METADATA  
created_at TIMESTAMPTZ NOT NULL DEFAULT CURRENT_TIMESTAMP,  
-- REQUIRED  
email TEXT NOT NULL CHECK (char_length(email) <= 500),  
feedback TEXT NOT NULL CHECK (char_length(feedback) <= 500),  
user_liked TEXT NOT NULL CHECK (char_length(feedback) <= 500),  
rating INTEGER NOT NULL );
```

----- RLS -----

```
ALTER TABLE feedbacks ENABLE ROW LEVEL SECURITY;  
  
CREATE POLICY "Allow full access to feedbacks"  
  ON feedbacks  
  USING (user_id = auth.uid())  
  WITH CHECK (user_id = auth.uid());
```

chat Table : 1 column in chat table **newly added by EXL Team.**

```
ALTER TABLE chats  
ADD COLUMN project_id UUID REFERENCES projects(id) ON DELETE SET NULL
```

--- RLS ---

```
ALTER TABLE chats ENABLE ROW LEVEL SECURITY;  
  
CREATE POLICY "Users can view their own chats."  
  ON chats  
  USING ((( SELECT auth.uid() AS uid) = user_id));
```

userinstructions: 1 column in userinstructions table newly added.

```
ALTER TABLE userinstructions  
ADD COLUMN project_id UUID REFERENCES projects(id) ON DELETE SET NULL;
```

profiles: 1 column in profiles table newly added.

```
ALTER TABLE profiles  
ADD COLUMN job_role TEXT;
```