Rajalakshmi Engineering College

Department of Artificial Intelligence and Data Science

AD23633-GENERATIVE AI LAB

Ex No 3: Simple GAN with TensorFlow and MNIST Dataset

Aim

To implement and understand a simple Generative Adversarial Network (GAN) using TensorFlow on the MNIST handwritten digit dataset and generate synthetic digit images.

Objectives

- Understand the working of Generator and Discriminator in GAN.
- Learn how GANs generate synthetic images from random noise.
- Implement a simple GAN using TensorFlow/Keras.
- Visualize the generated handwritten digit images.

Algorithm

1. Import required TensorFlow, Keras, NumPy and Matplotlib libraries.
2. Load the MNIST dataset using keras.datasets.
3. Preprocess the images by converting them to float values and normalizing them.
4. Reshape the dataset to include the channel dimension.
5. Define training parameters such as batch size, noise dimension and number of epochs.
6. Create dataset batches using TensorFlow Dataset API.
7. Build the Generator model to convert random noise into image data.
8. Build the Discriminator model to classify images as real or fake.
9. Define loss function and optimizers for training.
10. Train the Discriminator using real images and generated fake images.
11. Train the Generator to fool the Discriminator.
12. Repeat the process for multiple epochs.
13. Generate synthetic digit images after training and display them.

Code Walkthrough with Explanation

1. Import Required Libraries

Code:

```
import tensorflow as tf

from tensorflow import keras

import numpy as np

import matplotlib.pyplot as plt
```

Explanation:

This section imports the libraries required for the experiment.
TensorFlow and Keras are used to build and train neural networks.
NumPy helps perform numerical operations, and Matplotlib is used to visualize the generated images.

2. Load the MNIST Dataset

Code:

```
(x_train, _), (_, _) = keras.datasets.mnist.load_data()
```

Explanation:

This line loads the MNIST handwritten digit dataset.
Only the images are required for GAN training, so the labels are ignored.

3. Preprocess the Images

Code:

```
x_train = x_train.astype("float32")

x_train = (x_train - 127.5) / 127.5   # Normalize to [-1, 1]

x_train = x_train.reshape(x_train.shape[0], 28, 28, 1)
```

Explanation:

The images are converted to float format for computation.
Pixel values are normalized to the range [-1,1] because the generator uses tanh activation.
Images are reshaped to include the channel dimension (28×28×1).

4. Define Training Parameters

Code:

```
batch_size = 64
noise_dim = 100
epochs = 10
```

Explanation:

Batch size determines how many images are processed in one step.
Noise dimension represents the size of the random vector given to the generator.
Epochs represent how many times the dataset is used for training.

5. Create Dataset Batches

Code:

```
dataset = tf.data.Dataset.from_tensor_slices(x_train).shuffle(60000).batch(batch_size)
```

Explanation:

TensorFlow dataset API is used to create shuffled batches of the dataset.
This improves training efficiency and prevents the model from learning patterns in data order.

6. Build the Generator

Code:

```
generator = keras.Sequential([
    keras.layers.Input(shape=(noise_dim,)),
    keras.layers.Dense(128, activation='relu'),
    keras.layers.Dense(28 * 28 * 1, activation='tanh'),
    keras.layers.Reshape((28, 28, 1))
```

Explanation:

The generator creates fake images from random noise.
The Dense layers learn patterns from the noise and produce 784 pixel values.
The reshape layer converts this vector into a 28×28 image.

7. Build the Discriminator

Code:

```
discriminator = keras.Sequential([
    keras.layers.Input(shape=(28, 28, 1)),
    keras.layers.Flatten(),
    keras.layers.Dense(128, activation='relu'),
    keras.layers.Dense(1, activation='sigmoid')
])
```

Explanation:

The discriminator evaluates whether an image is real or fake.
Flatten converts the image into a vector and dense layers classify it.
The sigmoid output gives a probability value between 0 and 1.

8. Define Loss and Optimizers

Code:

```
loss_fn = keras.losses.BinaryCrossentropy()
g_optimizer = keras.optimizers.Adam(learning_rate=0.0002)
d_optimizer = keras.optimizers.Adam(learning_rate=0.0002)
```

Explanation:

Binary cross entropy is used because this is a binary classification problem.
Adam optimizer updates the parameters of Generator and Discriminator.

9. Training Process

Start training for multiple epochs

for epoch in range(epochs):

Explanation

- This loop runs the training process for the specified number of epochs.
- One epoch means the model sees the entire training dataset once.
- If epochs = 20, the GAN will train on the full dataset 20 times.

Read one batch of real images

for real_images in dataset:

Explanation

- The dataset is divided into batches.
- In each iteration, one batch of real MNIST images is taken.
- This helps training happen in smaller chunks instead of loading all images at once.

Find the current batch size

batch_size_now = real_images.shape[0]

Explanation

- This gives the number of images in the current batch.
- Usually it is equal to the chosen batch size, such as 64.
- The last batch may sometimes contain fewer images.

Create labels for real and fake images

real_labels = tf.ones((batch_size_now, 1))
fake_labels = tf.zeros((batch_size_now, 1))

Explanation

- real_labels contains all 1s, which means “real image”.
- fake_labels contains all 0s, which means “fake image”.
- These labels are used while training the Discriminator.

Train Discriminator

Generate random noise

noise = tf.random.normal((batch_size_now, noise_dim))

Explanation

- Random numbers are created from a normal distribution.
- These random values are the input to the Generator.
- The size of the noise vector is noise_dim.

Generator creates fake images

fake_images = generator(noise, training=True)

Explanation

- The Generator takes the random noise as input.
- It converts that noise into fake handwritten digit images.
- These images are not real; they are synthetic images created by the Generator.

Start recording Discriminator operations

with tf.GradientTape() as tape:

Explanation

- GradientTape records all computations inside this block.
- TensorFlow uses this recorded information to compute gradients later.
- These gradients are needed to update the Discriminator weights.

Discriminator checks real images

real_output = discriminator(real_images, training=True)

Explanation

- The Discriminator receives real images from the dataset.
- It predicts whether each image is real.
- The output values are probabilities close to 1 for real images.

Discriminator checks fake images

fake_output = discriminator(fake_images, training=True)

Explanation

- Now the Discriminator receives fake images made by the Generator.
- It predicts whether each image is fake.
- The output values should ideally be close to 0 for fake images.

Compute loss for real images

real_loss = loss_fn(real_labels, real_output)

Explanation

- This compares the Discriminator's prediction for real images with the correct label 1.
- If the Discriminator correctly identifies real images, the loss becomes smaller.

Compute loss for fake images

fake_loss = loss_fn(fake_labels, fake_output)

Explanation

- This compares the Discriminator's prediction for fake images with the correct label 0.
- If the Discriminator correctly identifies fake images, this loss becomes smaller.

Total Discriminator loss

d_loss = real_loss + fake_loss

Explanation

- The total Discriminator loss is the sum of:
    - real image loss
    - fake image loss
- This tells how well the Discriminator is performing overall.

Compute Discriminator gradients

d_gradients = tape.gradient(d_loss, discriminator.trainable_variables)

Explanation

- TensorFlow calculates how the Discriminator weights should change to reduce the loss.
- These changes are called gradients.

Update Discriminator weights

d_optimizer.apply_gradients(zip(d_gradients, discriminator.trainable_variables))

Explanation

- The optimizer applies the gradients to update the Discriminator's weights.
- After this step, the Discriminator becomes better at distinguishing real and fake images.

Train Generator

Create new random noise

noise = tf.random.normal((batch_size_now, noise_dim))

Explanation

- A new set of random noise vectors is created.
- This is used again as input to the Generator for its own training step.

Start recording Generator operations

with tf.GradientTape() as tape:

Explanation

- TensorFlow again records all operations inside this block.
- This time it will compute gradients for the Generator.

Generator creates new fake images

generated_images = generator(noise, training=True)

Explanation

- The Generator creates another batch of fake images from the noise.
- These images will now be used to train the Generator.

Discriminator evaluates generated images

output = discriminator(generated_images, training=True)

Explanation

- The generated images are passed to the Discriminator.
- The Discriminator tries to judge whether they are real or fake.

Compute Generator loss

g_loss = loss_fn(real_labels, output)

Explanation

- This is the important GAN idea.
- The Generator wants the Discriminator to think fake images are real.
- So the generated images are compared with real_labels instead of fake_labels.

Meaning

- If the Discriminator says the fake image is real, the Generator succeeds.
- If not, the Generator must improve.

Compute Generator gradients

g_gradients = tape.gradient(g_loss, generator.trainable_variables)

Explanation

- TensorFlow computes how the Generator weights should change to reduce Generator loss.
- These gradients help the Generator learn to create better fake images.

Update Generator weights

g_optimizer.apply_gradients(zip(g_gradients, generator.trainable_variables))

Explanation

- The optimizer updates the Generator's weights.
- After this step, the Generator improves and produces more realistic images.

End of One Epoch

print(f"Epoch [{epoch+1}/{epochs}] D Loss: {d_loss.numpy():.4f} G Loss: {g_loss.numpy():.4f}")

Explanation

- After all batches in one epoch are completed, the loss values are printed.
- D Loss shows how well the Discriminator is working.
- G Loss shows how well the Generator is learning to fool the Discriminator.

10.Generate images after training

noise = tf.random.normal((16, noise_dim))

generated_images = generator(noise, training=False)

11. Display generated images

fig, axes = plt.subplots(4, 4, figsize=(6, 6))

for i, ax in enumerate(axes.flat):

    ax.imshow((generated_images[i, :, :, 0] + 1) / 2, cmap='gray')

    ax.axis("off")

plt.tight_layout()

plt.show()

The output will display synthetic handwritten digit images generated by the trained Generator.

```
Epoch [1/10] D Loss: 0.3521 G Loss: 1.8244
Epoch [2/10] D Loss: 0.8050 G Loss: 1.2133
Epoch [3/10] D Loss: 0.4504 G Loss: 1.6689
Epoch [4/10] D Loss: 0.5874 G Loss: 1.6971
Epoch [5/10] D Loss: 0.4640 G Loss: 1.9110
Epoch [6/10] D Loss: 0.9899 G Loss: 1.2293
Epoch [7/10] D Loss: 0.6068 G Loss: 1.7615
Epoch [8/10] D Loss: 0.7526 G Loss: 2.1441
Epoch [9/10] D Loss: 0.6546 G Loss: 1.6244
Epoch [10/10] D Loss: 0.5972 G Loss: 2.6689
```



231501506

Question No	Question	Student Answer
1	Identify the section of the code where the MNIST dataset is loaded. Why are the labels ignored in this GAN implementation?	(x_train, _), (_, _) = keras.datasets.mnist.load_data() Labels are ignored because GAN is an unsupervised model and only needs images to learn data distribution.
2	Observe the preprocessing step (x_train - 127.5) / 127.5. Why are the pixel values converted to the range [-1, 1]?	Pixel values are normalized to [-1,1] to match the tanh activation in the generator, improving training stability.
3	**Locate the variable noise_dim = 100. What is the purpose of the random noise vector in the Generator?**	The noise vector acts as input to the generator and helps create diverse synthetic images from random data.
4	**Identify the Generator architecture in the code. How many Dense layers are used in the Generator model?**	The generator uses 2 Dense layers.
5	**Locate the Discriminator model in the program. What is the purpose of the Flatten layer?**	The Flatten layer converts a 2D image into a 1D vector for processing in Dense layers.

231501506

Question No	Question	Student Answer
6	**Observe the final layer of the Discriminator that uses sigmoid activation. Why is sigmoid used here?**	Sigmoid is used to output a probability between 0 and 1, indicating real or fake.
7	**Identify the loss function used in the GAN. Why is Binary Cross Entropy used in this experiment?**	Binary Cross Entropy is used because the problem is binary classification (real vs fake).
8	**Why is the Discriminator trained using both real images and generated fake images?**	To learn to distinguish between real and fake images effectively.
9	**In Generator training, fake images are compared with real_labels. Why is this done?**	To trick the discriminator into thinking fake images are real, improving generator performance.
10	**How many synthetic images are displayed at the end of training?**	16 images (4 × 4 grid).
11	**Change epochs = 20 to epochs = 50 and run the program again. What difference do you observe in the generated images?**	Images become clearer and more realistic due to longer training.
12	**Change noise_dim from 100 to 50. What happens to the generated images?**	Image quality may reduce because less noise dimension limits feature learning.
13	**Increase the number of neurons in the Generator from 128 to 256. Does the output improve?**	Yes, slightly improved output due to higher learning capacity.

231501506

Question No	Question	Student Answer
14	**Change the batch size from 64 to 128. What impact does this have on training?**	Training becomes more stable but slower per update.
15	**Add one more Dense layer to the Generator. Does the quality of images improve?**	Yes, image quality may improve due to deeper learning.
16	**Add one more Dense layer to the Discriminator. What change do you observe in training results?**	Discriminator becomes stronger, but may overpower generator if too deep.
17	**Replace ReLU with LeakyReLU in the networks. Does training become more stable?**	Yes, training becomes more stable due to reduced dead neuron problem.
18	**Observe Generator loss and Discriminator loss during training. What trend do you notice?**	Loss values fluctuate due to adversarial training (no smooth convergence).
19	**Compare the results of the original GAN and improved GAN. Which one produces clearer digits?**	Improved GAN produces clearer and more realistic digits.
20	**Why does the Generator initially produce random noisy images?**	Because weights are randomly initialized and not trained yet.

231501506

Question No	Question	Student Answer
21	**What happens if the Discriminator becomes too strong compared to the Generator?**	Generator fails to learn because discriminator easily detects fake images.
22	**Why is GAN training considered unstable compared to normal neural networks?**	Because two networks compete, causing instability and non-converging loss.
23	**Mention two real-world applications of GANs other than image generation.**	• Data augmentation • Deepfake / video generation
24	**How can this GAN architecture be modified to generate color images instead of grayscale images?**	Change output shape to (height, width, 3) and train on RGB datasets.

Result

Thus, a simple Generative Adversarial Network (GAN) was implemented using TensorFlow and trained on the MNIST dataset. The Generator successfully produced synthetic handwritten digit images similar to the original MNIST digits.