

Full Stack PBL

Users

- 1.) _id
- 2.) userName
- 3.) email (unique, indexed)
- 4.) password (hashed)
- 5.) pfp – image
- 6.) role [rider | organizer | sponsor]
- 7.) createdAt
- 8.) updatedAt

Rider

- 1.) _id
- 2.) userId (ObjectId, ref Users, unique)
- 3.) name
- 4.) age
- 5.) city
- 6.) Bike [Array of String] – A user can have many bikes
- 7.) ridingStyle [Array of String] – A user can prefer many styles
- 8.) bio[String] – Max 250 Words

Organizer

- 1.) _id
- 2.) userId (ObjectId, ref Users, unique)
- 3.) banner
- 4.) name
- 5.) description
- 6.) socailLinks (if any)
- 7.) website (if any)
- 8.) GSTIN

Rides

- 1) _id
- 2) userId (ObjectId, ref Organizer)
- 3) sponsorId(ObjectId, ref Sponsors) – Can be None if no sponsors, Array
- 4) banner – image
- 5) startLocation
- 6) endLocation
- 7) entryFee (default : 0)
- 8) date
- 9) time
- 10) length
- 11) difficulty [Easy | Moderate | Hard | Extreme]

- 12) type [Adventure | Highway | City | OffRoad]
- 13) maxSeats
- 14) bookedSeats (default : 0)
- 15) title
- 16) status [Upcoming | Ongoing | Cancelled | Completed]
- 17) createdAt
- 18) communicationLink
- 19) communicationType [telegram, whatsapp, email]

Sponsors:

- 1.) _id
- 2.) userId (Ref Users, Unique)
- 3.) brandName
- 4.) banner
- 5.) website
- 6.) description

Riders <-> Rides

- 1.) _id
- 2.) riderId (ObjectId)
- 3.) rideId (ObjectId)
- 4.) status
- 5.) purchasedAt

Developer Note:

- Location will be stored as:

```
startLocation: {  
  city: "Delhi",  
  coordinates: { type: "Point", coordinates: [lng, lat] }  
}
```

- All the field of the documents in a collection will Use camelCase variable declaration. Eg. userName, startLocation, etc. .
- We will have to create indexes and also geospatial indexes for better performance, refer to these documentations - <https://www.mongodb.com/docs/manual/geospatial-queries/>