

VPN Connect

Configuration Manual

Prepared by Paul van Santen
13 August 2018

Table of Contents

VPN SETUP	3
VPN CONNECT	5
REGISTRY SETTING	7

VPN Setup

This Manual is intended to provide a means for connecting to one of Alarm NZ VPN servers via the Internet.

It is intended for users with a Windows 10 PC


For security reasons, User names, Passwords, Pre-shared keys (PSK) and Access IP addresses will be given to the user when required in a separate document. This document shows examples of these only and where they need to be entered into the various screens

Occasionally an addition/configuration of a registry key will be required for successful connection. This procedure is described in a following section


1- Select Settings from the start menu Icon



2- Select "Network and Internet"




3- Select "VPN"



4- Select "Add a VPN Connection"




5- Insert information and Details provided into the following fields and press "Save"




VPN Connect

To initiate the connection of the VPN follow the following instruction

1- Left Click mouse on the Network Icon and select the VPN that you would like to connect to. (there could be several choices if more than 1 VPN was set up)




2- Press "Connect"




3- Connection should now be connected – Press Disconnect to Disconnect from VPN If connection is not successful try configuring the Registry key – Reboot and retry the connection

Registry Key Addition/Configuration


- 1- Login to the PC as Administrator or a user who is a member of the Administrator Group.
- 2- Search "Regedit"




- 3- "Run Command"
- 4- Navigate to the entry HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\PolicyAgent.




5- Right mouse click on the "Policy Agent" folder and select new DWORD (32 bit) Value



6- Enter "AssumeUDPEncapsulationContextOnSendRule" and Enter.



7- Right Mouse click on the new key and Modify the new entry and change Value Data from 0 to 2 - then OK



Value 0 -> Cannot establish security associations with servers that are located behind NAT devices.

Value 2 -> Can establish security associations with servers that are located behind NAT devices.- use this one

8- : Reboot the computer and try to setup the connection again