HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Precision Farming Using Autonomous Vehicle

Group A1:

Jaouaher Belgacem Jasmeet Singh Matta

Arsany Girgis

(1)

HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

The Software Modelling

Context Diagram



State Machine Diagram



Use Case Diagram



Requirement Diagram



Parametric Diagram



HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Activity Diagram



HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Sequence Diagram



TinkerCad simulation



HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

The Hardware Modelling

HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Design Inspiration



(1)

Design1





Design2







HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Design2





HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Final Design





HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Final Design



HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Code Implementation

HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Motor Pins Configuration

```
// This is to rotate motor
void switchState()
{
    switch (state)
    {
    case Stop:
        digitalWrite(motorA1, LOW);
        digitalWrite(motorB1, LOW);
        digitalWrite(motorA2, LOW);
        digitalWrite(motorB2, LOW);
        break;

    case Forward:
        digitalWrite(motorA1, HIGH);
        digitalWrite(motorB1, HIGH);
        digitalWrite(motorA2, LOW);
        digitalWrite(motorB2, LOW);
        break;

    case Right:
        digitalWrite(motorA1, HIGH);
        digitalWrite(motorB1, LOW);
        digitalWrite(motorA2, LOW);
        digitalWrite(motorB2, HIGH);
        break;

    case Left:
        digitalWrite(motorA1, LOW);
        digitalWrite(motorB1, HIGH);
        digitalWrite(motorA2, HIGH);
        digitalWrite(motorB2, LOW);
        break;

    case Backward:
        digitalWrite(motorA1, LOW);
        digitalWrite(motorB1, LOW);
        digitalWrite(motorA2, HIGH);
        digitalWrite(motorB2, HIGH);
        break;
    }
}
```

HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Line Follower Logic

```
void onLine()
{
    if (digitalRead(ln1) == HIGH && digitalRead(ln2) == HIGH)
    {
        change = true;
        state = Forward;
    }
    if (digitalRead(ln1) == HIGH && digitalRead(ln2) == LOW)
    {
        state = Left;
    }
    if (digitalRead(ln1) == LOW && digitalRead(ln2) == HIGH)
    {
        state = Right;
    }
```

HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Line Follower Logic

```
    if (digitalRead(ln1) == LOW && digitalRead(ln2) == LOW)
    {
        if (change == true)
        {
            change = false;
            mapp(); // Here we are updating the position on map
        }
        state = Stop;
        switchState();
        Movement();
    }
    switchState();
}
```

Object Detection



HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Object Detection

```
#define sonicTrig 12
#define sonicEcho 11
volatile int duration, distance;
volatile bool objectDetected= false;
void setup() {
   pinMode(sonicTrig,OUTPUT);
   pinMode(sonicEcho,INPUT);
   Serial.begin(9600);
}

void loop() {
void ultraSonic()
{
  digitalWrite(sonicTrig,HIGH);
    digitalWrite(sonicTrig,LOW);
    duration = pulseIn(sonicEcho,HIGH);
    distance = duration*0.0343/2;
    Serial.print("The Distance: ");
    Serial.println(distance);
/* the distance should be positive because at some points
 *  the ultrasonic detects with negative numbers*/
 */
    if (distance <=50 && distance >= 0)
      {
        Serial.println ("Object detected" );
        Serial.print ("Distance of the object from the car is " );
        Serial.print ( distance);
        Serial.println ( " cm");// print out the distance in cm.
        objectDetected = true;}
      else{ objectDetected = false;}
}
```

90° Turn


Move On Line
Yes
Move backward
Detected turn position?
Stop
No
Turn
Move forward

HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

90° Turn

```
case Backward:
//analogWrite(motorPowerA,180);
//analogWrite(motorPowerB,100);

digitalWrite(motorA1,LOW);
digitalWrite(motorB1,LOW);
digitalWrite(motorA2,HIGH);
digitalWrite(motorB2,HIGH);
break;
```

```
void rotateLeft()
{

      state = Backward;
      switchState();
      state = Stop;
      digitalWrite(motorA1,LOW);
      digitalWrite(motorB1,HIGH);
      digitalWrite(motorA2,HIGH);
      digitalWrite(motorB2,LOW);
      delay(500);
}
```

90° Turn

```
void rotateRight()
{

      state = Backward;
      switchState();
      state = Stop;
      digitalWrite(motorA1,HIGH);
      digitalWrite(motorB1,LOW);
      digitalWrite(motorA2,LOW);
      digitalWrite(motorB2,HIGH);
      delay(500);
}
```

```
if (digitalRead (ln1)== LOW && digitalRead(ln2)== LOW)
{
  rotateRight();
  state= Forward;
  switchState();

}
```

Mapping





Algorithm





HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Algorithm







Obstacle Avoidance



Color Detection

```
// This is to update the color variable and also to calibrate the readings
void getColor(){
    if ((redPW >= 114 && redPW <= 150) && (greenPW >= 324 && greenPW <= 350) && (bluePW >= 364 && bluePW <= 395))
    {
        currentColor = 0;} // orange
    else if ((redPW >= 320 && redPW <= 340) && (greenPW >= 505 && greenPW <= 520) && (bluePW >= 235 && bluePW <= 355))
    {
        currentColor = 3;} // purple
    else if ((redPW >= 174 && redPW <= 230) && (greenPW >= 190 && greenPW <= 210) && (bluePW >= 320 && bluePW <= 335))
    {
        currentColor = 2;} // green
    else if ((redPW >= 232 && redPW <= 290) && (greenPW >= 170 && greenPW <= 190) && (bluePW >= 130 && bluePW <= 160))
    {
        currentColor = 1;} // cyan
    else if ((redPW >= 90 && redPW <= 108) && (greenPW >= 95 && greenPW <= 115) && (bluePW >= 80 && bluePW <= 95))
    {
        currentColor = 4;} // white
    else if (((redPW >= 900 && redPW <= 960) && (greenPW >= 1000 && greenPW <= 1065) && (bluePW >= 800 && bluePW <= 860))
    || ((redPW >= 622 && redPW <= 750) && (greenPW >= 710 && greenPW <= 810) && (bluePW >= 500 && bluePW <= 677)))
    { // if it detects gray or black will consider it black
        currentColor = 5;} // black
}
```

Color Detection

```
// This is to get Green using filter  s2 s3
int getGreenPW()
{
    digitalWrite(S2, HIGH);
    digitalWrite(S3, HIGH);
    int PW;
    PW = pulseIn(sensorOut, LOW);
    return PW;
}
// This is to get Blue using filter  s2 s3
int getBluePW()
{
    digitalWrite(S2, LOW);
    digitalWrite(S3, HIGH);
    int PW;
    PW = pulseIn(sensorOut, LOW);
    return PW;
}
```

```
void loop()
{
    Serial.println(currentColor);
```

```
// This is to get red using filter  s2 s3
int getRedPW()
{
    digitalWrite(S2, LOW);
    digitalWrite(S3, LOW);
    int PW;
    PW = pulseIn(sensorOut, LOW);
    return PW;
}
// This code is to get current color
void colorCall()
{
    redPW = getRedPW();
    bluePW = getBluePW();
    greenPW = getGreenPW();
    getColor();
}
```

HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

Sources

1: pixabay.com

HAMM-LIPPSTADT
UNIVERSITY OF APPLIED SCIENCES

THANK YOU FOR YOUR ATTENTION