

freesurfer: Connecting the Freesurfer Software with R

by John Muschelli, Elizabeth M. Sweeney, Ciprian M. Crainiceanu

Abstract We present the package **freesurfer**, a set of R functions that interface with Freesurfer, a commonly-used open-source software package for processing and analyzing structural neuroimaging data. The **freesurfer** package performs operations on `nifti` image objects in R using command-line functions from Freesurfer, and returns R objects back to the user. **freesurfer** allows users to process neuroanatomical images and provides functionality to convert and read the output of the Freesurfer pipelines. We present an example of the analysis of structural magnetic resonance images, which demonstrates how R users can interface with Freesurfer and analyze the results of the complete Freesurfer analysis pipeline.

Introduction

Freesurfer is a commonly-used software for processing and analyzing anatomical neuroimaging data (Fischl, 2012), developed by the Laboratory for Computational Neuroimaging at the Athinoula A. Martinos Center for Biomedical Imaging. This software provides open-source, command-line tools for image processing tasks such as brain extraction/skull-stripping (Ségonne et al., 2004), bias-field correction (Sled et al., 1998), segmentation of structures within the brain (Fischl et al., 2002, 2004), and image registration (Fischl et al., 1999; Reuter et al., 2010). Many of these functions are used extensively in medical imaging pipelines and Freesurfer has a complete pipeline packaged with its software as well.

We have previously published a similar adaptation of the FSL imaging software (Jenkinson et al., 2012) to R, called **fsR** (Muschelli et al., 2015). Again, we note that there exist a number of R packages for reading and manipulating image data, including **AnalyzeFMRI** (Bordier et al., 2011), **RNiftyReg** (Clayden, 2015), and **fmri** (Tabelow and Polzehl, 2011) (see the Medical Imaging CRAN task view <http://cran.r-project.org/web/views/MedicalImaging.html> for more information). Although these packages are useful for performing image analysis, much of the functionality of image preprocessing and processing that Freesurfer provides are not currently implemented in R, including surface-based registration. The **ANTsR** package (<https://github.com/stnava/ANTsR>) is a currently unpublished R package that interfaces with the ANTs (advanced normalization tools) software suite (Avants et al., 2011), where a lot of additional functionality has been implemented, but this package has not been released onto CRAN. Moreover, having multiple options for image processing through R allows for users to compare methods and the flexibility of using multiple packages to achieve a working data processing pipeline.

In particular, we provide an interface to users to the state-of-the-art anatomical processing implemented in Freesurfer, as well as a suite of tools that simplify analyzing the output of Freesurfer. The **freesurfer** allow R users to implement complete anatomical imaging analysis without necessarily learning Freesurfer-specific syntax.

Imaging formats in freesurfer and R

The **freesurfer** package relies on the **oro.nifti** (Whitcher et al., 2011) package implementation of images (referred to as `nifti` objects) that are in the Neuroimaging Informatics Technology Initiative (NIfTI) format, as well as other common image formats such as ANALYZE. Some Freesurfer functions require other formats, such as MINC (<http://www.bic.mni.mcgill.ca/ServicesSoftware/MINC>). The Freesurfer installation provides functions to convert from MINC to NIfTI formats and there are implemented in functions such as `nii2mnc` and `mnc2nii` in R. Moreover, the `mri_convert` Freesurfer function has been interfaced in the **freesurfer** package (same function name), which allows for a more general conversion tool of imaging types for R users than currently implemented in native R.

Reconstruction pipeline in Freesurfer

The Freesurfer pipeline and analysis workflow for neuroanatomical images is based on a structural magnetic resonance image (MRI) of the brain. The specific type of image commonly used in this software is a T1-weighted image, a specific MRI sequence commonly taken. The full pipeline is implemented in the Freesurfer `recon-all` function, where the “recon” stands for reconstruction (<https://surfer.nmr.mgh.harvard.edu/fswiki/recon-all>). Using the `-all` flag in the the

recon-all function performs over 30 different steps and takes 20-40 hours to fully process a subject when performing all the steps. This process is the common way of fully processing an T1-weighted image in Freesurfer, and is implemented in the recon_all **freesurfer** function.

If there are problems with the result of this processing, there are multiple steps users can edit certain parts of the processing, such as skull-stripping, where non-brain tissues are removed from the image. The remainder of the pipeline can be run after these steps. The full pipeline is broken down into 3 separate steps, referred to as autorecon1, autorecon2, and autorecon3, which correspond to the flags in recon-all used to initiate these steps. We have written wrapper functions autorecon1, autorecon2, and autorecon3, respectively, for simplicity to the R user. This allows users to run pieces of the pipeline if desired or restart a failed process after correction to the data.

R function setup

To use **freesurfer**, a working installation of Freesurfer is required. The following code was run using Freesurfer version "freesurfer-Darwin-lion-stable-pub-v5.3.0". The Freesurfer version can be accessed using the fs_version function. **freesurfer** must also have the path of Freesurfer specified. If using R from a shell environment, and the FREESURFER_HOME environment variable is set (which can be done when installing Freesurfer), **freesurfer** will use this as the path to Freesurfer. If using R through a graphical user interface (GUI) such as RStudio (RStudio, Boston, MA), environmental variables and paths are not explicitly exported. Therefore, FREESURFER_HOME is not set, **freesurfer** will try the default directories of Mac OSX and Linux. If the user did not perform a standard installation of Freesurfer, the path to Freesurfer can be specified using options(freesurfer.path="/path/to/freesurfer").

We will discuss the setup functions for the **freesurfer** package and how they can be used in analysis and example code. For testing, whether a user has a Freesurfer installation, the have_fs function provides a logical indicator as a result. The fs_dir function will return the directory of the Freesurfer installation.

Structure of Freesurfer analyses

During the installation of Freesurfer, a series of variables are set up in the user's shell environment. One of these variables is SUBJECTS_DIR, which refers to a directory of the output of analysis from all subjects. This setup allows users to simply specify a subject identifier to analyze, rather than a specific path or multiple intermediate files.

This setup may not be desirable if the user prefers to structure the data from multiple studies into different folders. For example, the asegstats2table function takes the anatomical segmentation statistics and convert it to a table. The default argument for asegstats2table is to pass in a subject name rather than a file. The **freesurfer** asegstats2table function allows the R user to specify a different subject directory to read in the file, while not overriding the default set by SUBJECTS_DIR. This functionality allows users to have separate folders with subjects and read in the data by simply switching the subj_dir argument in the R function.

Similarly to the fs_dir function, the fs_subj_dir function will return the path to the Freesurfer subjects directory if it is set.

Some Freesurfer functions require an image as an input. For those functions, the R **freesurfer** functions that call those Freesurfer functions will take in a filename or a nifti object. The R code will convert the nifti to the corresponding input required for Freesurfer. From the user's perspective, the input/output process is all within R. The advantage of this approach is that the user can read in an image, do manipulations of the nifti object using standard syntax for arrays, and pass this object into the **freesurfer** R function. Thus, users can use R functionality to manipulate objects while seamlessly passing these object to Freesurfer through **freesurfer**.

Example analyses and use of functions

In the default subjects directory in the Freesurfer installation, there is a subject named "bert", where recon-all was run. In the sub-directory for subject bert, there are 3 folders which we will explore the results: "mri", which contain imaging data, "stats", which containing statistics based on structures of the brain, and "surf", which contain the surface and curvature output from the Freesurfer processing.

Reconstruction

For the recon_all function, users must specify the input file (a T1-weighted image), the output directory, and the subject identifier. This function will take 20-40 hours to fully process the input file.

```
recon_all(infile, outdir, subjid)
```

A user can see the result of this output in the “bert” directory as an example:

```
list.files(path = file.path(fs_subj_dir(), "bert"))

[1] "bem"      "label"    "mri"      "scripts"  "src"      "stats"    "surf"
[8] "tmp"      "touch"    "trash"
```

We will read in some of the output in the following sections.

Reading in anatomical statistics

The “aseg.stats” in the “stats” folder of subject bert corresponds to measures and statistics from the anatomical segmentation. The read_aseg_stats function reads this corresponding file and creates a list of 2 different data.frames:

```
file = file.path(fs_subj_dir(), "bert", "stats", "aseg.stats")
out = read_aseg_stats(file)
names(out)
```

```
[1] "measures" "structures"
```

The measures element corresponds to global measurements of the brain (e.g. volume of the brain) as well as measures of gross anatomical structures (e.g. gray matter).

```
head(out$measures[, c("meaning", "value", "units")])
```

	meaning	value
1	brain segmentation volume	1193318.000000
2	brain segmentation volume without ventricles	1174082.000000
3	brain segmentation volume without ventricles from surf	1173867.217735
4	left hemisphere cortical gray matter volume	237947.199463
5	right hemisphere cortical gray matter volume	238312.856735
6	total cortical gray matter volume	476260.056198

	units
1	mm^3
2	mm^3
3	mm^3
4	mm^3
5	mm^3
6	mm^3

In some imaging analyses, comparing at these large measures of brain volume over time or across groups are of interest.

The structures element corresponds to a set of measures and statistics for a set of fixed anatomical structures.

```
head(out$structures)
```

	Index	SegId	NVoxels	Volume_mm3	StructName	normMean
1	1	4	6563	6562.6	Left-Lateral-Ventricle	36.0959
2	2	5	228	228.3	Left-Inf-Lat-Vent	54.8842
3	3	7	15708	15708.2	Left-Cerebellum-White-Matter	92.7562
4	4	8	58536	58535.7	Left-Cerebellum-Cortex	77.2709
5	5	10	8150	8150.4	Left-Thalamus-Proper	92.8386
6	6	11	3214	3213.7	Left-Caudate	80.9591

	normStdDev	normMin	normMax	normRange
1	12.2771	16	91	75
2	10.7839	22	87	65
3	5.5123	40	107	67
4	9.9521	17	142	125
5	7.0182	49	109	60
6	8.2079	49	105	56

Similarly with global measures, these structure-specific measures can be used in analysis. Moreover, a large deviation in volume for a specific subject may indicate atrophy of a structure or an indication of a segmentation error.


MRI conversion

The typical output format from Freesurfer is MGH/MGZ format, which is explained here: <https://surfer.nmr.mgh.harvard.edu/fswiki/FsTutorial/MghFormat>. As NIfTI formats are one of the most common formats and has been the common format for analysis in the **oro.nifti** and **neurobase** packages, it is useful to convert these files to a NIfTI format to use in R. The `mri_convert` Freesurfer function will be used for that. Here we will use the T1-weighted image from the “bert” subject and convert it to NIfTI:

```
library(freesurfer)
bert_dir = file.path(fs_subj_dir(), "bert")
t1_mgz = file.path(bert_dir, "mri", "T1.mgz")
t1_nii_fname = tempfile(fileext = ".nii.gz")
freesurfer::mri_convert(t1_mgz, t1_nii_fname)
```

After this file is a NIfTI file, we can read it into R, and then plot the image:

```
library(neurobase)
img = neurobase::readnii(t1_nii_fname)
neurobase::ortho2(img, add.orient = FALSE)
```



Note, the image is not stored in the “RPI” format which is assumed when displaying using the **neurobase** `ortho2` function.

As this is a commonly-used function, we have wrapped these two steps into the `readmgz` and `readmgh` functions, which warp `mri_convert` and `readnii`. Here we show that these steps are equivalent to the `readmgz` function:


```
img_mgz = readmgz(t1_mgz)
all(img == img_mgz)

[1] TRUE
```

Brain extraction

The `mri_watershed` function will segment the brain from the remainder of the image, such as extra-cranial tissues. We can pass in the `nifti` object and the output is a brain-extracted `nifti` object.

```
ss = mri_watershed(img)
ortho2(ss)
```



We see that the area of the skull, eyes, face, and other areas of the image are removed. We do see some areas that are likely non brain, such as the top left area of the top left panel of figure.

As the result in a `nifti` object, we can create a mask by standard logical operations. As MRI scans are commonly non-zero, the non-zero areas of the image are the “brain”:

```
mask = ss > 0
```

We can then use this mask to perform operations on the image, such as subsetting.

Bias-field correction

MRI images typically exhibit good contrast between soft tissue classes, but intensity inhomogeneities in the radio frequency field can cause differences in the ranges of tissue types at different spatial locations (e.g. top versus bottom of the brain). These inhomogeneities/non-uniformities can cause problems with algorithms based on histograms, quantiles, or raw intensities (Zhang et al., 2001). Therefore, correction for image inhomogeneities is a crucial step in many analyses. The `Freesurfer` function `nu_correct` performs the non-uniformity correction by Sled et al. (1998) and the `freesurfer` function of the same name will run the correction and return an image.

The `Freesurfer` `nu_correct` function requires a MNC format (<http://www.bic.mni.mcgill.ca/ServicesSoftware/MINC>). For this to work, you can convert the `nifti` object to a MNC file using `nii2mnc` and pass that file into `nu_correct`. The `freesurfer` `nu_correct` function will run the correction and then convert the output MNC to a `Nifti` object.


```
mnc = nii2mnc(img)
print(mnc)
```

```
[1] "/var/folders/1s/wrtqcpnx685_zk570bnx9_rr0000gr/T/RtmprAbuIo/file1519022caadd1.mnc"

nu_from_mnc = nu_correct(file = mnc)
class(nu_from_mnc)

[1] "nifti"
attr(,"package")
[1] "oro.nifti"

ortho2(nu_from_mnc)
```



If you pass in a nifti object in directly into `nu_correct`, the function will automatically convert any NIfTI input files, and then run the correction. We can also pass in a mask (generated from above) to run the correction only the areas of the brain.

```
nu_nifti = nu_correct(file = img, mask = mask)
class(nu_from_mnc)

[1] "nifti"
attr(,"package")
[1] "oro.nifti"
```

Overall, this correction is a way to make the intensities of the brain more homogeneous spatially. This method is different from that implemented in FSL (and therefore **fslr**), so it provides an alternative method to the R user than currently available.

Label files

Here we will read a label file for the left hemisphere cortex:

```
file = file.path(fs_subj_dir(), "bert", "label", "lh.cortex.label")
out = read_fs_label(file)
head(out)
```

	vertex_num	r_coord	a_coord	s_coord	value
1	0	-12.882	-102.449	-9.782	0.0000000000
2	1	-13.331	-102.518	-9.829	0.0000000000
3	2	-13.637	-102.514	-10.077	0.0000000000
4	3	-13.031	-102.596	-10.024	0.0000000000
5	4	-13.331	-102.510	-10.254	0.0000000000
6	5	-13.610	-102.483	-10.295	0.0000000000

The coordinates are mostly used in these files, not the value assigned. They can be used for registration as well.

Surface Files

For the initial release, we did not implement a method to read the annotation files and other surface-based files that Freesurfer uses. Reading in these files are planned for a future release.

Conclusion

The neuroimaging community has developed a large collection of tools for image processing and analysis. Some of the fundamental functionality of neuroimage processing is being added to R packages, such as our previous work porting FSL to R using **fsR** and the actively-developed GitHub **ANTsR** package. Additional third-party software still has additional functionality that is not present in R, such as the surface-based registration and processing of Freesurfer. We present **freesurfer** to bridge this gap and provide R users functions from Freesurfer. Interfacing R with existing, powerful software provides users with thoroughly-tested software and an additional community of users, which would not be available if the functions were rewritten in R. Although this external software dependency may not be an advantage for the software, it benefits from the years of previous testing.

There has been an increasing popularity of similar interfacing of tools within the Python community such as Nipype (Gorgolewski et al., 2011) (<https://qa.debian.org/popcon.php?package=nipype>). As many users of R may not have experience with Python or bash scripting, we believe **freesurfer** provides a lower threshold for use in the R community.

Most importantly, as **freesurfer** is based on the R framework, all the benefits of using R are available, such as dynamic documents, Shiny applications, customized figures, and state-of-the-art statistical methods. These benefits provide unique functionality compared to other software packages for neuroimaging.

Bibliography

- B. B. Avants, N. J. Tustison, G. Song, P. A. Cook, A. Klein, and J. C. Gee. A reproducible evaluation of ANTs similarity metric performance in brain image registration. *NeuroImage*, 54(3):2033–2044, feb 2011. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2010.09.025. URL <http://www.sciencedirect.com/science/article/pii/S1053811910012061>. [p1]
- C. Bordier, M. Dojat, P. L. de Micheaux, and others. Temporal and spatial independent component analysis for fMRI data sets embedded in the AnalyzeFMRI R package. *Journal of Statistical Software*, 44(9):1–24, 2011. URL <http://www.hal.inserm.fr/inserm-00659425/>. [p1]
- J. Clayden. *RNiftyReg: Medical Image Registration Using the NiftyReg Library*, Jon Clayden and based on original code by Marc Modat and Pankaj Daga, 2015. URL <http://CRAN.R-project.org/package=RNiftyReg>. R package version 1.1.3. [p1]
- B. Fischl. Freesurfer. *Neuroimage*, 62(2):774–781, 2012. [p1]
- B. Fischl, M. I. Sereno, R. B. Tootell, A. M. Dale, et al. High-resolution intersubject averaging and a coordinate system for the cortical surface. *Human brain mapping*, 8(4):272–284, 1999. [p1]
- B. Fischl, D. H. Salat, E. Busa, M. Albert, M. Dieterich, C. Haselgrove, A. Van Der Kouwe, R. Killiany, D. Kennedy, S. Klaveness, et al. Whole brain segmentation: automated labeling of neuroanatomical structures in the human brain. *Neuron*, 33(3):341–355, 2002. [p1]
- B. Fischl, D. H. Salat, A. J. van der Kouwe, N. Makris, F. Ségonne, B. T. Quinn, and A. M. Dale. Sequence-independent segmentation of magnetic resonance images. *Neuroimage*, 23:S69–S84, 2004. [p1]

- K. Gorgolewski, C. D. Burns, C. Madison, D. Clark, Y. O. Halchenko, M. L. Waskom, and S. S. Ghosh. Nipype: a flexible, lightweight and extensible neuroimaging data processing framework in python. *Frontiers in neuroinformatics*, 5, 2011. URL <http://www.ncbi.nlm.nih.gov/pmc/articles/PMC3159964/>. [p7]
- M. Jenkinson, C. F. Beckmann, T. E. J. Behrens, M. W. Woolrich, and S. M. Smith. FSL. *NeuroImage*, 62(2):782–790, aug 2012. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2011.09.015. URL <http://www.sciencedirect.com/science/article/pii/S1053811911010603>. [p1]
- J. Muschelli, E. Sweeney, M. Lindquist, and C. Crainiceanu. fslr: Connecting the fsl software with R. *The R Journal*, 7(1):163–175, 2015. [p1]
- M. Reuter, H. D. Rosas, and B. Fischl. Highly accurate inverse consistent registration: a robust approach. *Neuroimage*, 53(4):1181–1196, 2010. [p1]
- F. Ségonne, A. Dale, E. Busa, M. Glessner, D. Salat, H. Hahn, and B. Fischl. A hybrid approach to the skull stripping problem in MRI. *Neuroimage*, 22(3):1060–1075, 2004. [p1]
- J. G. Sled, A. P. Zijdenbos, and A. C. Evans. A nonparametric method for automatic correction of intensity nonuniformity in MRI data. *Medical Imaging, IEEE Transactions on*, 17(1):87–97, 1998. URL http://ieeexplore.ieee.org/xpls/abs_all.jsp?arnumber=668698. [p1, 5]
- K. Tabelow and J. Polzehl. Statistical parametric maps for functional MRI experiments in R: The package fmri. *Journal of Statistical Software*, 44(11):1–21, 2011. URL <http://www.jstatsoft.org/v44/i11/paper>. [p1]
- B. Whitner, V. J. Schmid, and A. Thornton. Working with the DICOM and NIFTI Data Standards in R. *Journal of Statistical Software*, 44(6):1–28, 2011. URL <http://www.jstatsoft.org/v44/i06/paper>. [p1]
- Y. Zhang, M. Brady, and S. Smith. Segmentation of brain MR images through a hidden Markov random field model and the expectation-maximization algorithm. *Medical Imaging, IEEE Transactions on*, 20(1):45–57, 2001. URL http://ieeexplore.ieee.org/xpls/abs_all.jsp?arnumber=906424. [p5]

John Muschelli
Johns Hopkins Bloomberg School of Public Health
Department of Biostatistics
615 N Wolfe St, Baltimore, MD, 21205
jmuschel@jhsphe.edu

Elizabeth M. Sweeney
Rice University
Department of Statistics
6100 Main St, Duncan Hall, Houston, TX, 77005
ems15@rice.edu

Ciprian M. Crainiceanu
Johns Hopkins Bloomberg School of Public Health
Department of Biostatistics
615 N Wolfe St, Baltimore, MD, 21205
ccraini1@jhu.edu