

Relaxation allowance guide (Specifically needed as poster to be printed)

FACTORS	TYPICAL EXAMPLES To convert lb (multiply by 0.454 kilogram) to KG			ALLOW- ANCES
A. Energy Output (affecting muscular recovery) Negligible..... Very Light..... Light..... ... Medium..... Heavy..... Very Heavy..... Exceptional..... ...		Equivalent to handling	Men	Women
			Per cent	Per cent
		No load	0 - 6	0 - 6
		Light bench work-seated		
		Light bench work-standing	6 - 7 1/2	6 - 7 1/2
		Light shoveling	7 1/2 - 12	7 1/2 - 16
		Hack sawing or filling	12 - 19	16 - 30
		Swinging heavy hammer 7 - 28lb	19 - 30	-
		40 - 60lb	30 - 50	-
		60 - 112lb		
B. Posture 1. Sit 2. Stand (both feet) 3. Stand (one foot) 4. Lying down 5. Crouch	Normal sedentary work Whenever body is erect and support on feet only Standing on one leg (using a foot control) On side, face or back When body is bent, but support on feet or knees	Above 112lb	Per cent	
			0 - 1	
			1 - 2 1/2	
			2 1/2 - 4	
			2 1/2 - 4	
C. Motions 1. Normal 2. Limited 3. Awkward 4. Confined (limbs only) 5. Confined (whole body)	Free swing of hammer Limited swing of hammer Carrying heavy load in one hand Working with arms above head Working at thin coal seam		Per cent	
			0	
			0 - 5	
			0 - 5	
			5 - 10	
D. Visual Fatigue 1. Intermittent	Reading meters or gauges		Lighting Good	Lighting Poor/Variable
			0%	

eye attention	Precision machine work	2%	1%	
2. Nearly continuous eye attention				
3. Continuous eye attention – varying focus				
4. Continuous eye attention – fixed focus				
Inspecting moving or stationary cloth for faults	2%	5%		
Inspecting minute and/or moving objects			4%	8%
E. Personal needs		2 1/2 %		
F. Thermal conditions	<u>Temperature</u>	<u>Humidity</u>		
		<u>Normal</u>	<u>Excessive</u>	
1. Freezing	Below 30 ⁰ F	Over 10%	Over 12%	
2. Low	32 ⁰ – 55 ⁰ F	0 – 10%	12 – 5%	
3. Normal	55 ⁰ - 75 ⁰ F	0%	5%	
4. High	75 ⁰ - 100 ⁰ F	0 – 40%	5 – 100%	
5. Excessive	Above 100 ⁰ F	Over 40%	Over 100%	
G. Atmospheric Conditions			Per cent	
1. Good.....	Well ventilated rooms or fresh air	0		
.....	Badly ventilated air, presence of non-toxic but foetid odours or non-injurious fumes	0 – 5		
2. Fair.....	Presence of toxic dusts or heavy concentration of non-toxic dusts involving use of breathing filters	5 – 10		
....	Presence of toxic fumes or dusts involving use of respiratory	10 – 20		
3. Poor.....				
...				
4. Bad.....				
...				
H. Other influences of Environment			Per cent	
1. Clean, healthy, dry and bright surroundings, low noise level			0	
2. Where work cycle is continuously repetitive and between 5 and 10 seconds			0 – 1	
3. Where work cycle is continuously repetitive and less than 5 seconds			1 - 3	
4. Where there is a complete absence of company Day – men			1	
Day – women, Night – men			2	
5. Excessive noise e.g. riveting (allowance related to continuity of noise)			0 – 5	
6. Where effect of such disturbing influences might be detrimental to quality of output			0 – 5	
7. Vibration of floors or machines, e.g. pneumatic drilling (allowance related to			5 – 10	

continuity of vibration)	
8. Extreme conditions, e.g. dirt, noise, etc	5 – 15

Note:

1. This table is intended as a guide in assessing the relaxation allowances for individual elements
2. Although allowances are usually additive for the individual elements, assessment for elements incurring high allowances may require some reduction when followed by elements incurring less.