

MECHANISM-LEVEL SIM2REAL CONTRACTS: BRANCH-STRUCTURED EVIDENCE FOR EMBODIED WORLD-ACTION MODELS

Anonymous authors

Paper under double-blind review

ABSTRACT

We study sim-to-real transfer for robot manipulation. The motivating bet is: Transfer by preserving causal mechanisms rather than matching observation statistics. We introduce a mechanism-level representation that keeps physically admissible but unrealized action outcomes as explicit branches. A synthetic contact-style evaluation shows that the proposed branch mechanism improves hidden-mode success and tail-risk relative to observed-only, augmentation-as-data, and scalar-uncertainty baselines.

1 INTRODUCTION

Robotics papers often collapse unobserved physical alternatives into extra data, variance, or a single predicted next state. For sim-to-real transfer for robot manipulation, this can erase the difference between modes that are visually similar but action-critical. This paper asks whether a world-action model should expose those alternatives to the planner before execution.

2 HOSTILE PRIOR WORK

The closest hostile records include (pri, 2023a; 2025; 2023b;c; 2026a;b). They make generic world models, contact prediction, and uncertainty insufficient as novelty claims. Our boundary is narrower: preserve branch-valued contact futures as the planning object.

3 MECHANISM

Given state s and action a , the model returns an observed next-state prediction plus a finite atlas $B(s, a)$ of admissible latent branches. Planning minimizes nominal loss plus adverse-branch tail risk. This is not bigger data or a new benchmark; it changes the object represented by the WAM.

4 EVIDENCE

We include a runnable synthetic testbed in `src/run_experiment.py`. It compares four variants under nominal and hidden-mode-shift conditions.

Variant	Split	Success	Tail risk
observed_only_wam	nominal	0.512	0.488
observed_only_wam	hidden_mode_shift	0.170	0.830
augmentation_as_data_wam	nominal	0.575	0.425
augmentation_as_data_wam	hidden_mode_shift	0.255	0.745
scalar_uncertainty_wam	nominal	0.625	0.375
scalar_uncertainty_wam	hidden_mode_shift	0.362	0.637
proposed_branch_mechanism	nominal	0.777	0.223
proposed_branch_mechanism	hidden_mode_shift	0.568	0.432

5 LIMITATIONS

The evidence is synthetic. It supports the mechanism boundary and failure mode, not real-robot state of the art. Hardware validation, richer contact geometry, and learned branch discovery remain open.

6 CONCLUSION

Mechanism-Level Sim2Real Contracts argues that embodied world-action models should preserve unrealized physical alternatives when those alternatives change downstream action value.

REFERENCES

- Robust visual sim-to-real transfer for robotic manipulation, 2023a.
<http://arxiv.org/abs/2307.15320v1>.
- Bi-touch: Bimanual tactile manipulation with sim-to-real deep reinforcement learning, 2023b.
<http://arxiv.org/abs/2307.06423v1>.
- Zero-shot sim-to-real transfer of reinforcement learning framework for robotics manipulation with demonstration and force feedback, 2023c. <https://doi.org/10.1017/s0263574722001230>.
- In-hand manipulation of articulated tools with dexterous robot hands with sim-to-real transfer, 2025.
<http://arxiv.org/abs/2509.23075v3>.
- Symbridge: Bilateral-symmetry-aware vision-language-action learning with head-mounted display teleoperation for sim2real transfer in bimanual manipulation, 2026a.
<https://doi.org/10.20944/preprints202605.1763.v1>.
- Exogs: A 4d real-to-sim-to-real framework for scalable manipulation data collection, 2026b.
<http://arxiv.org/abs/2601.18629v1>.