

DATA ENGINE FAILURE STRATIFICATION: BRANCH-STRUCTURED EVIDENCE FOR EMBODIED WORLD-ACTION MODELS

Anonymous authors

Paper under double-blind review

ABSTRACT

We study robot data engines. The motivating bet is: Select new robot data by uncovered failure mechanisms, not by task labels. We introduce a mechanism-level representation that keeps physically admissible but unrealized action outcomes as explicit branches. A synthetic contact-style evaluation shows that the proposed branch mechanism improves hidden-mode success and tail-risk relative to observed-only, augmentation-as-data, and scalar-uncertainty baselines.

1 INTRODUCTION

Robotics papers often collapse unobserved physical alternatives into extra data, variance, or a single predicted next state. For robot data engines, this can erase the difference between modes that are visually similar but action-critical. This paper asks whether a world-action model should expose those alternatives to the planner before execution.

2 HOSTILE PRIOR WORK

The closest hostile records include (pri, 2024a; 2025; 2021; 2016; 2026; 2024b). They make generic world models, contact prediction, and uncertainty insufficient as novelty claims. Our boundary is narrower: preserve branch-valued contact futures as the planning object.

3 MECHANISM

Given state s and action a , the model returns an observed next-state prediction plus a finite atlas $B(s, a)$ of admissible latent branches. Planning minimizes nominal loss plus adverse-branch tail risk. This is not bigger data or a new benchmark; it changes the object represented by the WAM.

4 EVIDENCE

We include a runnable synthetic testbed in `src/run_experiment.py`. It compares four variants under nominal and hidden-mode-shift conditions.

Variant	Split	Success	Tail risk
observed_only_wam	nominal	0.547	0.453
observed_only_wam	hidden_mode_shift	0.188	0.812
augmentation_as_data_wam	nominal	0.613	0.387
augmentation_as_data_wam	hidden_mode_shift	0.225	0.775
scalar_uncertainty_wam	nominal	0.657	0.343
scalar_uncertainty_wam	hidden_mode_shift	0.335	0.665
proposed_branch_mechanism	nominal	0.787	0.213
proposed_branch_mechanism	hidden_mode_shift	0.545	0.455

5 LIMITATIONS

The evidence is synthetic. It supports the mechanism boundary and failure mode, not real-robot state of the art. Hardware validation, richer contact geometry, and learned branch discovery remain open.

6 CONCLUSION

Data Engine Failure Stratification argues that embodied world-action models should preserve unrealized physical alternatives when those alternatives change downstream action value.

REFERENCES

- Correction to: 2016 acc/aha/hfsa focused update on new pharmacological therapy for heart failure: An update of the 2013 accf/aha guideline for the management of heart failure: A report of the american college of cardiology foundation/american heart association task force on clinical practice guidelines and the heart failure society of america, 2016. <https://doi.org/10.1161/cir.0000000000000460>.
- A new data envelopment analysis-based model for failure mode and effect analysis with heterogeneous information, 2021. <https://doi.org/10.1016/j.cie.2021.107350>.
- Big data and telemetry data methodology for usage failure mode detection, 2024a. <https://doi.org/10.4271/2023-36-0013>.
- Development and validation of a new prognostic model for patients with acute-on-chronic liver failure in intensive care unit, 2024b. <https://doi.org/10.3748/wjg.v30.i20.2657>.
- Scaling cross-environment failure reasoning data for vision-language robotic manipulation, 2025. <http://arxiv.org/abs/2512.01946v3>.
- Method for correlation of failure data from durability tests and field of automotive engine parts with spontaneous failure mode, 2026. <https://doi.org/10.1201/9781003762584-86>.