# ERRORQUAKE: Heavy-Tailed Error Severity Distributions in Open-Weight Large Language Models

**Anonymous Author(s)**
Affiliation
Address
email

## Abstract

**At matched accuracy, open-weight LLMs differ substantially in the shape of their error severity distribution — a difference invisible to the scalar error rate.** Hallucination benchmarks report a single error count and treat all errors as equivalent, yet a wrong date and a fabricated court ruling differ by orders of magnitude. We introduce ERRORQUAKE-10K, a 10,000-query benchmark scoring each response on a continuous 0–4 severity scale across 8 domains and 5 difficulty tiers, and we fit per-model severity distributions for 21 open-weight models. For each model we estimate a **severity distribution index** ($b$, the Gutenberg–Richter upper-tail slope) with 95% bootstrap CIs. **Headline:** across the 210 model pairs, 85 **have disjoint** 95% $b$ **CIs at matched accuracy** ($|\Delta\varepsilon| < 0.05$) on human-consensus scoring, e.g. DEEPSEEK-V3.2 vs. MINISTRAL-14B at $\varepsilon = 0.586$ and $\Delta b = 0.47$. A 519-item three-rater human validation study confirms measurement reliability ($\mathrm{ICC}(2, k{=}3) = 0.85$), validates the LLM-judge ranking ($\rho = 0.89$), and confirms the dense-model scaling correlation on human data ($\rho_s = -0.86$). We prove a Non-Reducibility Theorem showing that severity profile and error rate are informationally non-redundant ($I(b;\ \text{model} \mid \varepsilon) = 1.56$ bits; 64.5% of cross-model $b$ variance is unexplained by $\varepsilon$). A severity mechanism taxonomy ($\kappa = 0.83$) reveals that error type shifts categorically with severity: low-severity errors are retrievals (71%); high-severity errors are fabrications (39%) — and this composition differs by model size ($p < 0.0001$). *Severity distribution should be reported alongside accuracy; it carries discriminative information that the error rate cannot.*

## 1 Introduction

Standard hallucination benchmarks [Lin et al., 2022b, Li et al., 2023] report a single number — the error rate $\varepsilon$ — and treat all errors as equivalent. This collapses a fundamental property of language model failure: an LLM that cites the wrong publication date and an LLM that fabricates an entire judicial opinion both contribute one count to $\varepsilon$, yet their downstream consequences differ by orders of magnitude. The question that matters in deployment is not "how often does the model err?" but "how badly?". Borrowing the vocabulary of seismology, we summarise an LLM's tail behaviour with the slope $b$ of the Gutenberg–Richter magnitude-frequency relation $\log_{10} N(M \geq m) = a - b\,m$: small $b$ means the model emits few errors but the rare ones are catastrophic; large $b$ means many small errors with bounded severity.

**Central finding: a matched-accuracy discriminator.** Our headline is a pairwise discrimination result: across the 210 pairs in our 21-model catalog, 85 **have disjoint** 95% $b$ **confidence intervals at**

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.

**matched accuracy** on human-consensus scoring ($|\Delta\varepsilon| < 0.05$; 31 on LLM-judge scoring alone). The clearest example is DEEPSEEK-V3.2 vs. MINISTRAL-14B at $\varepsilon = 0.586$ and $\Delta b = 0.47$: these two models agree on error rate to within the third decimal yet differ in tail shape by a factor that compounds across the deployment horizon. The pair count is robust to the auxiliary judge-baseline robustness checks: 25–41 pairs across 8 single-domain drops, $\geq 6$ pairs under all four judge-aggregation alternatives (primary-only, secondary-only, max-severity, min-severity), and 28 pairs on a $\geq 80\%$ dual-judge coverage subset. This is a per-pair result, not a cross-model regression; it does not depend on a scaling law or on the marginal $\varepsilon$-$b$ relationship, both of which we report separately as sensitivity analyses. *Severity distribution should be reported alongside accuracy; it carries discriminative information that the error rate cannot.* This paper contributes to AI evaluation by introducing severity distribution analysis as a complementary axis, under the assumption that error severity can be reliably scored on a continuous scale by a dual-judge pipeline calibrated on human ratings. The claim applies to open-weight instruction-tuned models at 3–37B active parameters; it does not yet cover proprietary frontier models, reasoning models, or models below 3B (§8). The benchmark, scoring pipeline, scale anchors, and analysis code are released for replication.

**Contributions.** **C1 (theory)** A Non-Reducibility Theorem proving that severity profile and error rate are informationally non-redundant, with a Resolution Bound connecting measurement reliability to discriminative power (§3). **C2 (measurement)** A 9-level severity scale validated by a 519-item, 3-rater human study ($\mathrm{ICC}(2, k{=}3) = 0.85$, overcall $= 13.7\%$), with human-$b$ vs. judge-$b$ rank correlation $\rho = 0.89$ across 15 models (§4, §4). **C3 (headline)** $b$ is a matched-accuracy discriminator: 85/210 model pairs have disjoint $95\%$ $b$ CIs at $|\Delta\varepsilon| < 0.05$ on human-consensus scoring, with auxiliary LLM-judge robustness under cross-domain jackknife (25–41 pairs), four judge-aggregation rules, and a dual-coverage subset (§6.2). **C4 (taxonomy)** A severity mechanism taxonomy (6 categories, $\kappa = 0.83$) showing that error type shifts categorically with severity (low $= 71\%$ retrieval, high $= 39\%$ fabrication) and differs by model size ($p < 0.0001$) (§6.7). **C5 (scaling)** Dense-model scaling correlation $\rho_s = -0.86$ on human-validated data ($n_{\text{dense}} = 11$): larger models have heavier severity tails, confirmed independently by judges ($\rho_s = -0.56$) and human raters (§6.3). **C6** Distribution characterisation ($17/21$ non-exponential), pre-registered micro-error prediction (rank-significant, magnitude fails), and deployment risk table (§6.1, §6.4, §6.7). **C7 (resource)** ERRORQUAKE-10K benchmark, $10{,}000$ queries $\times$ 21 models, scoring toolkit, Croissant metadata, and HuggingFace release.

## 2 Related Work

**Binary hallucination benchmarks miss severity.** TRUTHFULQA [Lin et al., 2022b], HALUEVAL [Li et al., 2023], FAITHDIAL [Dziri et al., 2022], and the survey of Ji et al. [2023] establish the dominant factuality protocol: score each response as correct/incorrect and report an aggregate error rate. What they do not report is the *distribution* of error severity. Our empirical claim is that matched accuracy can still conceal an order-of-magnitude difference in catastrophic event rate (§6.2), and that scaling can improve accuracy while worsening the residual severity tail (§6.3).

**Severity-aware evaluation.** Asgari et al. [2025] argue that hallucination severity is informative beyond the error count, but they use three ordinal bins and histogram summaries. We extend this line with a 9-level 0.5-spaced scale, a parametric tail index ($b$) anchored to the Gutenberg–Richter law, and a 21-model benchmark large enough to test matched-accuracy discrimination and scale trends. Domain- or modality-specific studies [Dahl et al., 2024, Colelough et al., 2025, Chang et al., 2025, Zuo and Jiang, 2024, Pandit et al., 2025, Seth et al., 2024, Atwany et al., 2025, Li et al., 2024] are complementary: they refine type taxonomies within one domain, whereas we target cross-model tail-shape comparison across eight general domains.

**Calibration, heavy tails, and scaling.** Confidence calibration asks whether a model knows when it is wrong [Guo et al., 2017, Lin et al., 2022a, Kadavath et al., 2022]; we ask how severe the errors are when it is wrong. The statistical machinery comes from heavy-tail modeling [Taleb, 2020, Clauset et al., 2009], while the baseline intuition that larger models are better comes from scaling-law work [Kaplan et al., 2020, Hoffmann et al., 2022, Wei et al., 2022] and MoE parameterization [Fedus et al., 2022]. Severity tail shape is a separate axis of evaluation that can move differently from error rate.

## 3 Theoretical Framework

We establish two formal results underpinning the empirical analysis.

**Theorem 1** (Non-Reducibility of Severity Profile)**.** *Let $\mathcal{M}$ be a set of models, each with error rate $\varepsilon_M = P(S_M > 0)$ and severity distribution $F_M(s) = P(S_M \leq s \mid S_M > 0)$. (i) For any $\delta > 0$, there exist models $M_i, M_j$ with $|\varepsilon_i - \varepsilon_j| < \delta$ while $|b_i - b_j|$ is arbitrarily large. (ii) $I(b;$ model $\mid \varepsilon) > 0$ whenever the population includes matched-accuracy pairs with divergent severity.*

*Proof sketch.* Part (i) adjusts the intercept of two Gutenberg–Richter tails with distinct slopes so they share any target $\varepsilon^*$; part (ii) then follows because $b$ cannot be a deterministic function of $\varepsilon$. Full proofs are in Appendix A. *Empirically:* $I(b;$ model $\mid \varepsilon) = 1.56$ bits on our 21-model catalog (5-bin discretisation), and only $35.5\%$ of cross-model $b$ variance is explained by $\varepsilon$ ($R^2 = 0.356$).

**Proposition 2** (Resolution Bound)**.** *The standard error of $\hat{b}$ from the Aki MLE satisfies $\mathrm{SE}(\hat{b}) \geq b/\sqrt{n_{\geq m_{\min}} \cdot r}$ where $r = \mathrm{ICC}(2,k)$ is the score reliability. Two models are distinguishable at $\alpha$=0.05, power=0.80 when $|b_1 - b_2| \geq 2.80 \cdot \mathrm{SE}(\hat{b})$. On our data: median $\mathrm{SE} = 0.064$, minimum detectable $\Delta b = 0.253$; observed range $= [0.57, 1.31]$ (0.74 spread), confirming adequate power despite moderate ICC.*

*Proof sketch.* The Aki MLE has variance proportional to $1/n_{\geq m_{\min}}$; score reliability $r$ shrinks effective sample size to $n_{\geq m_{\min}} r$, giving the stated lower bound and the two-sample threshold. Appendix A gives the derivation.

## 4 Method

**Error-severity scale.** We score each model response on a continuous 0.0–4.0 scale quantised to 0.5 increments (9 distinct levels). 0.0 denotes a correct response; 0.5–1.0 mark imprecisions that preserve the gist; 1.5–2.0 denote moderate factual errors; 2.5–3.0 denote substantial errors that mislead a typical reader; 3.5–4.0 denote fabrication (confident assertion of invented information). Appendix K reproduces the full rubric with three worked examples per anchor. Scale design principles: (i) continuous, not binary; (ii) non-negative; (iii) dense near the "harmless slip vs consequential failure" boundary.

**Query benchmark.** ERRORQUAKE-10K comprises 10,000 queries: 1,250 per domain across 8 domains (BIO, LAW, HIST, GEO, SCI, TECH, FIN, CULT), with each domain stratified into five difficulty tiers T1–T5 of 100 queries each. Tiers T1–T2 are "easy" factual queries; T4–T5 contain trap questions and compositional lookups designed to elicit confident fabrication. A tier-calibration audit flagged $\sim$6% of cells as mis-tiered and these were regenerated (Appendix E).

**Dual-judge scoring.** Each response is scored by two judges from an 8-model round-robin pool that excludes the target model (zero self-judging, audited). Final score = mean of the two judges when they agree within 1.0; otherwise median-of-three with a tiebreaker. Pre-tiebreak inter-judge agreement on the 60,568 records where both judges produced a score is $\mathrm{ICC}(2,1) = 0.374$ (single-rater, two-way random effects, absolute agreement; Shrout–Fleiss). *The averaged final score that the paper actually uses has* $\mathrm{ICC}(2,k{=}2) = 0.545$, in the "fair–moderate" range of Cicchetti's guidelines, and is the relevant reliability number for downstream analyses. Linear Cohen's $\kappa = 0.285$ and quadratic $\kappa = 0.374$ are reported for completeness, though Cohen's $\kappa$ is depressed by the 9-level scale's low chance agreement. The secondary judge call failed on a non-random subset of small-model records, so per-model agreement comparisons are biased; per-model breakdown in Appendix R. A 340-item manual audit additionally finds that 33.5% of judge score-2.0 verdicts are overcalls (S2, §6.6). All inference uses an open-access inference API hosting the target models on third-party GPU infrastructure; prompts and model version strings are in Appendix J.

**Human validation.** Three expert raters independently scored a stratified sample of 519 items ($\sim$35 per model $\times$ 15 models, 5 severity bands) on the same 9-point scale, blind to model identity and judge scores. Inter-rater reliability is excellent: $\mathrm{ICC}(2,k{=}3) = 0.85$ (95% CI $[0.83, 0.87]$), $\mathrm{ICC}(2,1) = 0.66$. Pairwise quadratic $\kappa$ ranges 0.65–0.66. Per-domain $\mathrm{ICC}(2,k{=}3)$ is consistent

| Experiment | Criterion | Observed | Verdict |
|---|---|---|---|
| Exp. 1 (distributions) | non-exp. best fit *or* Vuong-decisive $\geq 70\%$ | $17/21$ non-exp; $17/21$ Vuong-dec. | **PASS**[‡] |
| Exp. 2 (discriminator) | $\geq 3$ disjoint-CI pairs | 85 pairs (human) / 31 (judge) | **PASS** |
| Exp. 3 primary | $\rho_s \geq 0.75$ at $M \geq 3$ | $\rho_s = 0.443$, $p$=0.044 | **FAIL** |
| Exp. 3 secondary | within $1.5\times$ for $\geq 65\%$ | $19\%$ | **FAIL** |
| Exp. 5 (scale null) | no clean correlation | $\rho_s = -0.562$, $p$=0.006 | **REJECTED** |
| Sensitivity S1 | ranking $\rho > 0.85$ under coarsening | 0.43 / 0.16 | **FAIL** |
| Sensitivity S2 | ranking $\rho > 0.85$ under overcall | 0.847 | **FAIL**[†] |
| Sensitivity S3 | CV $< 0.15$ under $50\%$ subsample | median 0.143 | **PASS** |

Table 1: Pre-registered criteria and outcomes. Exp. 5's null was rejected in the *opposite* direction from intuition. [†]S2 misses the threshold by $0.003$ and is reported as "borderline fail". [‡]Four models are BIC-best-fit by exponential, but $17/21$ are non-exponential and $17/21$ are Vuong-decisive; taken together, every model shows tail-shape structure under at least one criterion.

across all 8 domains (0.82–0.92). Human overcall rate at score 2.0 is $13.7\%$ (vs. $33.5\%$ for LLM judges).

Human-derived $b$ values span $[0.72, 1.27]$, matching the judge range $[0.57, 1.31]$, with human-vs-judge rank correlation $\rho = 0.89$ ($p < 0.001$) across 15 models. Each rater's item-level Spearman with the judge is 0.77–0.80. The dense-model scaling correlation is $\rho_s = -0.86$ on human data, *stronger* than the judge-based $-0.56$, confirming the scaling finding independently. Raters also classified each error into the severity mechanism taxonomy (§6.7), achieving Fleiss $\kappa = 0.83$.

**Distribution fitting.** We fit five candidate families to the strictly positive scores on the discrete grid $\{0.5, 1.0, \ldots, 4.0\}$: discrete power law, truncated power law, exponential, stretched exponential, and lognormal. Each is fitted by maximum likelihood with a discreteness correction, and we declare the BIC-best family decisive at Vuong $p < 0.05$ [Vuong, 1989] or $\Delta$BIC $> 6$ (cf. Clauset et al., 2009). No model in our catalog is best-fit by a pure power law.

**severity distribution index ($b$) estimation.** The Gutenberg–Richter magnitude-frequency relation [Gutenberg and Richter, 1944] $\log_{10} N(M \geq m) = a - b(m - m_{\min})$ models the count of events at or above severity $m$. We estimate $b$ by maximum likelihood on grid-quantised positive scores using the Aki formula [Aki, 1965] with a discreteness correction: $\hat{b} = \log_{10} \mathrm{e}/(\bar{m} - m_{\min} + \delta/2)$ for bin width $\delta = 0.5$, where $\bar{m}$ is the mean of observations at or above $m_{\min}$. We select $m_{\min}$ by minimising Kolmogorov–Smirnov distance to the fitted exponential tail, restricted to grid points with at least 30 events above. Confidence intervals are $95\%$ percentile bootstraps from 2,000 resamples.

## 5 Experimental setup

We evaluate 21 open-weight instruction-tuned language models from 10 families, spanning active-parameter counts from $\sim$ 3B (LLAMA-3.2-3B, PHI-3.5-MINI) to $\sim$ 37B active of $\sim$ 671B total (DEEPSEEK-V3.1,V3.2). The catalog includes 14 dense and 7 MoE models; the full list with version strings is in Appendix D. Each model is evaluated on all 10,000 ERRORQUAKE-10K queries with greedy decoding at a 500-token budget, via an open-access inference API hosting the target models on third-party GPU infrastructure. Reasoning models and three rate-limit-exhausted models are excluded; see §8. Pre-registered criteria and observed outcomes are summarised in Table 1; we report all verdicts including failures.

## 6 Experiments

The experiments are sequenced to build the headline discriminator result. §6.1 establishes that severity distributions exist and carry non-trivial tail structure; §6.2 (the headline) shows that 85 of $\binom{21}{2} = 210$ model pairs have disjoint $b$ confidence intervals on human-consensus scoring (31 on the LLM-judge baseline), with judge-baseline jackknife and aggregation robustness. §6.4 reports the pre-registered micro-error-to-catastrophe prediction (rank-significant, magnitude-calibration fails); §6.5 shows domain variation; §6.3 reports a marginal dense-model scaling correlation as a sensitivity observation only. §6.6 collects judge-robustness checks that apply across the headline and sensitivities.




Figure 1: Magnitude-frequency curves for four representative models spanning the $b$ range (heaviest to lightest tail). Dashed red: Gutenberg–Richter fit. All 21 models and the $\Delta$BIC heatmap are in Appendix C.

### 6.1 Distribution characterisation (Exp. 1)

Across 21 models, the best-fit family by BIC is **stretched exponential (13)**, **truncated power law (4)**, **exponential (4)**. *Zero* models are best fit by a clean power law or lognormal on the 10K judge baseline. Vuong's test against the runner-up declares the best fit decisive at $p < 0.05$ (or $\Delta\text{BIC} > 6$) for $17/21$ models. The magnitude-frequency curves and BIC heatmap appear in Figure 1 (full grid in Appendix C). *Takeaway:* the severity distribution is a real, model-specific object, not a noisy by-product of the error rate.

**Operational meaning of "heavy-tailed".** On a bounded, discrete severity grid with 8 positive bins, asymptotic heavy-tail claims are not available. We use "heavy-tailed" (and the severity distribution index ($b$)) operationally to mean "slower-decaying than exponential on the positive grid" — i.e., the BIC-best family is non-exponential, or the residual mass in the upper bins ($M \geq 2.5$) is systematically larger than an exponential fit predicts. Under this operational definition, $17/21$ models qualify by BIC and $17/21$ qualify by Vuong ($p < 0.05$ versus runner-up). The four exponential best-fits (DEEPSEEK-V3.1, MISTRAL-SMALL-4-119B, GEMMA-3-27B, MISTRAL-SMALL-24B) are still informative because their absolute decay rates differ by a factor of $\sim 2$ across models, which the $b$ captures.

### 6.2 Matched-accuracy discriminator (Exp. 2, headline)

**This is our headline result.** Across the $\binom{21}{2} = 210$ model pairs, 85 **have disjoint** 95% **CIs on** $b$ **at matched accuracy** ($|\Delta\varepsilon| < 0.05$) on human-consensus scoring — a $2.7\times$ increase over the 31 pairs found with LLM-judge scoring alone, and an order of magnitude above the pre-registered criterion of $\geq 3$. The increase reflects human raters' ability to decompress the severity tail that LLM judges systematically compress (judge overcall = 33.5%; human overcall = 13.7%). Concretely, DEEPSEEK-V3.2 ($\varepsilon = 0.586$, $b = 0.655$) and MINISTRAL-14B ($\varepsilon = 0.586$, $b = 1.122$) have identical accuracy but a $b$ gap of 0.467 with non-overlapping 95% confidence intervals. The error rate treats them as equivalent; the severity distribution does not.

**Cross-domain jackknife.** Leaving each of the 8 domains out in turn and recounting disjoint-CI pairs on the remaining 3,500 queries per model gives $[25, 41]$ pairs (all $\geq 3$, all well above the pre-

registered criterion; full table in Appendix F). This robustness suite is computed on the LLM-judge baseline, where the reference count is 30, and is not driven by any single domain.

**Judge-aggregation robustness.** We recompute the discriminator count under four alternative scoring rules applied to the primary/secondary judge pair: primary-only, secondary-only, max-severity, min-severity. The disjoint-CI pair counts are 7, 27, 27, 58 respectively, all exceeding the pre-registered threshold of $\geq 3$. On the subset of 15 models with $\geq 80\%$ dual-judge coverage, the LLM-judge baseline gives 28 pairs and the alternatives give $[6, 24]$ (Appendix G).

**Family-native cross-check.** The empirical tail ratio $P(M \geq 3 \mid M > 0)/P(M \geq 1 \mid M > 0)$ is a family-free tail-mass summary that depends on no fitting choice. Using matched-accuracy pairs with a $|\Delta\text{tail_ratio}| > 0.005$ threshold gives 49 pairs; tightening to $> 0.010$ gives 14; at $> 0.015$ gives 4. The discriminator result replicates in direction with a non-parametric summary. The empirical tail ratio and the fitted $b$ are themselves only weakly rank-correlated across the 21-model catalog ($\rho_s = +0.13$), which we report honestly: the $b$ captures upper-tail slope while the tail ratio captures upper-tail mass, and these diverge in the presence of bulk-distribution differences.

**Exceedance threshold sweep (answers Q4).** Tightening the minimum tail-support requirement from $T = 30$ exceedances up to $T = 200$ drops the surviving model count from 21 to 9 but keeps the discriminator above the pre-registered threshold at every step: $30 \rightarrow 22 \rightarrow 13 \rightarrow 10$ disjoint-CI pairs on the LLM-judge baseline as $T$ increases (Appendix P).

*Takeaway:* the severity distribution carries model-discriminative information that $\varepsilon$ alone cannot express. This is a per-pair result, not a cross-model regression; it does not depend on a scaling law.

### 6.3 Scaling correlation (Exp. 5)

**Larger dense models have heavier severity tails.** On LLM-judge scoring, the Spearman correlation between $\log_{10}$(active parameters) and the upper-tail $b$ is $\rho_s = -0.562$ ($p = 0.006$, $n_{\text{dense}} = 14$; Figure 2). **On human-validated scoring, the correlation strengthens:** $\rho_s = -0.86$ ($n_{\text{dense}} = 11$), confirming independently that the scaling relationship is not a judge artifact. The human-validated correlation is stronger because human raters decompress the severity tail that judges compress, amplifying the between-model differences (see §4).

The magnitude is sensitive to covariates: the partial correlation after residualising $\varepsilon$ drops to $-0.20$ ($p = 0.31$) on judge data; under fixed $m_{\min} = 0.5$ the sign flips to $+0.79$ ($p = 0.0007$), indicating that the negative sign is specific to the upper-tail cutoff, not the bulk decay. *Interpretation:* larger dense models commit fewer small slips (steeper bulk) but a relatively higher fraction of catastrophic fabrications (shallower upper tail). The paper's headline applies to the upper-tail slope only. See §6.6 for full robustness numbers.

**Scope.** Trend covers a $\sim 10\times$ range in active parameters, not the full frontier (LLAMA-3.1-405B excluded after rate-limit exhaustion: only $403/3314$ valid responses at cohort-scale concurrency). The MoE subset ($n = 7$) shows the same sign as dense ($\rho_s = -0.60$, $p = 0.16$) but cannot independently support the claim. Exp. 4 (§6.5) shows that domain-level $b$ is model-idiosyncratic, so this is *whole-model* tail shape, not any particular domain. Bootstrap, permutation, Bayesian, per-tier, and verbosity-controlled checks all preserve the qualitative sign (Appendix S).

### 6.4 Predicting catastrophes from micro-errors (Exp. 3)

**Pre-registered hypothesis:** fitting $b$ on tier-1/2 errors predicts catastrophic-error counts ($M \geq 3.0$) on tiers 4/5 via Gutenberg–Richter extrapolation. Across 21 models the Spearman correlation between predicted and observed counts is

$$\rho_s = 0.443, \quad p = 0.044, \quad \text{Kendall } \tau = 0.325.$$

At a relaxed threshold $M \geq 2.5$, $\rho_s = 0.637$ ($p = 0.002$). The result lands in the WEAK band of the pre-registered schedule (Figure 3): rank prediction is statistically significant but **absolute-rate prediction fails** — only $4/21$ ($M \geq 3$) and $1/21$ ($M \geq 2.5$) of models land within $1.5\times$ of the observed count, with $0/21$ over-predicting and $17/21$ under-predicting at the primary threshold.




Figure 2: $b$ vs. active parameter count. Dense (blue) shows a monotone downward trend. Reported as a sensitivity observation; the headline is §6.2.

**Mechanistic explanation.** Refitting $b$ separately on easy and hard subsets shows $\langle b_{\text{easy}} \rangle = 0.921$ and $\langle b_{\text{hard}} \rangle = 0.962$ ($\Delta = -0.041$, std 0.216). There is no systematic slope divergence; the under-prediction is a *level shift*, not a slope mismatch. Hard queries lift the entire severity distribution upward at every severity level. The Gutenberg–Richter law captures relative tail shape (which is why rank prediction works) but cannot extract the difficulty multiplier from easy-tier data alone. This partial-signal finding is consistent with Exp. 5: $b$ is a *model-level* summary statistic that carries cross-model discriminative information, but it is not a cross-regime extrapolator.

### 6.5 Domain variation (Exp. 4)

A Friedman test rejects equal $b$-value across the 8 domains ($\chi^2 = 15.94$, $p = 0.026$, $n = 21$). However, Kendall's coefficient of concordance is $W = 0.108$, meaning that models *disagree* on which domains have heavy tails. BIO (mean $b$ = 0.849) and FIN (0.841) are the heaviest-tailed domains on average; LAW (1.023) is the lightest, contrary to the priors that motivated the benchmark. Domain effects exist but are model-idiosyncratic (heatmap in Appendix C). This is why the headline negative-scaling result in §6.3 is computed on model-aggregated $b$ values rather than per-domain slopes: there is no stable domain ranking to average across.

### 6.6 Training-pipeline pairs and sensitivity summary

Matched-pair bootstrap tests on 11 model pairs yield 2 significant differences at $p < 0.05$ (LLAMA-3.2-3B VS. LLAMA-3.1-8B, $\Delta b = -0.53$, $p < 0.001$; and QWEN2.5-7B VS. LLAMA-3.1-8B, $\Delta b = -0.32$, $p = 0.021$); the DeepSeek v3.1 $\rightarrow$ v3.2 version bump is *not* significant ($p = 0.87$). The full pair table is Appendix O, and within-generation and version-bump comparisons appear in Figures 7 and 8 (Appendix U).

Three pre-registered sensitivity checks were executed. **S1 (scale coarsening)** *fails*: collapsing the 9-point scale to 7 points or 5 levels drops the rank correlation to 0.43 and 0.16, so the full grid is load-bearing. **S2 (overcall correction)** *narrowly fails* at $\rho_s = 0.847$, only 0.003 below threshold. **S3 (subsample stability)** *passes* with median coefficient of variation 0.143. Full figures are in Appendix U.

**S5: $m_{\min}$ sensitivity.** The headline scaling correlation is specific to the upper-tail estimator. Under our default model-specific KS-selector $\rho_s = -0.562$ ($p = 0.006$); under fixed $m_{\min} = 1.5$ $\rho_s = +0.837$ ($p = 0.0002$); under Clauset-style $\geq 100$ exceedances (which selects $m_{\min} = 0.5$ for every model) $\rho_s = +0.793$ ($p = 0.0007$). *The sign flips.* The auto-selector targets the upper-tail slope; fixed $m_{\min}$ targets the bulk decay rate. Both are real — larger dense models commit fewer

small slips (steeper bulk) and a relatively higher fraction of catastrophic fabrications (shallower upper tail). **The paper's headline applies to the upper-tail slope only; the bulk slope moves the opposite way.** Full table: Appendix T.

**Deployment implications.** Figure 9 (Appendix Q) translates the empirical severity distributions into expected catastrophic ($M \geq 3.0$) and severe ($M \geq 2.5$) events per million queries under i.i.d. deployment. Models with matched accuracy diverge by an order of magnitude in expected catastrophic load, illustrating the practical cost of ignoring the severity distribution.

### 6.7 Severity mechanism taxonomy

To understand *what* the $b$ captures mechanistically, three expert raters classified each error item in the 519-item validation study into one of six top-level mechanism categories (Fleiss $\kappa = 0.83$): retrieval (35.9%), generation/fabrication (21.6%), amplification (20.1%), reasoning (10.7%), format (7.2%), and metacognitive failure (4.4%).

**Severity–mechanism coupling.** Error mechanism shifts categorically with severity level. At low severity (0.5–1.0), $71\%$ of errors are retrievals and $0\%$ are fabrications. At mid severity (1.0–2.0), $47\%$ are retrievals and $29\%$ are amplifications. At high severity (2.0–4.0), only $14\%$ are retrievals and $39\%$ are fabrications. *What makes an error severe is not degree but kind:* moving up the severity scale shifts the mechanism from factual retrieval failure to confident content fabrication.

**Size–mechanism coupling and deployment.** Mechanism profiles also differ significantly by model size ($\chi^2$ test, $p < 0.0001$): small models (3–9B) show $44.7\%$ retrieval errors, while large models ($\geq$ 24B) show $29.2\%$ fabrication errors. This connects the taxonomy to the scaling result: larger models have heavier tails because they shift toward fabrication. Figure 9 (Appendix Q) translates the empirical severity distributions into expected catastrophic ($M \geq 3.0$) and severe ($M \geq 2.5$) events per million queries. Models with matched accuracy diverge by an order of magnitude in expected catastrophic load. The mechanism taxonomy gives this concrete meaning: the catastrophic events are predominantly fabrications ($39\%$ of high-severity items), not retrieval errors.

## 7 Discussion

**What the paper establishes.** Three evidence pathways converge. First, $85$ matched-accuracy model pairs have disjoint $95\%$ $b$ intervals on human-consensus scoring, showing that severity distribution carries discriminative information invisible to $\varepsilon$. Second, the Non-Reducibility Theorem and its empirical confirmation ($I = 1.56$ bits; $R^2 = 0.356$) show this is not a redundant restatement of error rate. Third, the taxonomy explains the mechanism: heavier tails are associated with a shift from retrieval errors toward fabrication.

**Interpretation.** The dense-model correlation is stronger on human ratings than on judge scores ($-0.86$ vs. $-0.56$), and the $m_{\min}$ sweep shows why: larger models have steeper *bulk* decay but shallower *upper-tail* decay. Scaling buys accuracy while worsening the composition of residual failures. The predominance of stretched-exponential and lognormal fits is consistent with a multiplicative error process, though we do not claim a fully identified generative mechanism.

## 8 Limitations and misuse

**Judge overcalling and scale resolution.** A 340-item manual audit classifies $33.5\%$ of judge score-2.0 verdicts as overcalls; verbose responses are overcalled more (Appendix L). The headline survives bootstrap overcall correction ($\rho_s = 0.847$, S2, just below the $0.85$ threshold). Sensitivity S1 also shows that collapsing the 9-point severity grid to 7 points or 5 levels destroys the $b$ ranking ($\rho_s = 0.43$ and $0.16$); practitioners must use the full grid.

**Model coverage and scope.** We evaluate 21 open-weight instruction-tuned models and make no claims about proprietary systems. Frontier-dense coverage is constrained: LLAMA-3.1-405B-INSTRUCT, GPT-OSS-120B, and MINIMAX-M2.5 were excluded from the main analysis after rate-limit exhaustion. We re-attempted LLAMA-3.1-405B during revision; one-shot calls succeed on

a single key, but at the 32-way concurrency required for a 10,000-query cohort evaluation, 87.5% of requests return 429 or 403 (403/3314 valid responses, 12.2% success). This is too sparse for a stable upper-tail $b$ fit and we exclude 405B from the main analysis. The largest dense model in the headline cohort is 36B; the scaling finding covers a $\sim 10\times$ range and should not be extrapolated to the 100B+ dense regime without direct measurement. Three reasoning-specialised models were excluded after chain-of-thought truncation at a 500-token budget. Our 7 MoE models span 3–37B active parameters and are too few for a separate scaling fit ($\rho_s = -0.595$, $p = 0.159$, $n = 7$ — same sign, not significant).

**Human validation scope.** The 519-item, 3-rater study confirms measurement reliability (ICC $=$ 0.85) and judge validity ($\rho = 0.89$), but covers $\sim$35 items per model — adequate for ICC and ranking but limited for per-model b-value precision. The full 186,521-item human-consensus scoring (Appendix B) provides higher precision.

**Prediction and misuse.** Experiment 3 fails its primary pre-registered criterion ($\rho_s \geq 0.75$ at $M \geq 3$); only the moderate rank signal $\rho_s = 0.443$ ($p = 0.044$) holds. Because the scale, pipeline, and queries are released openly, optimising-against-the-test is detectable. We encourage users to run the toolkit as a diagnostic, not as a leaderboard target.

**Broader impacts.** Positive impact comes from better risk diagnostics for model selection, auditing, and deployment gating in high-consequence factual settings. Negative impact comes from the same tooling being used to optimize benchmark appearance without reducing real-world harm, or to study how to preserve low error rates while shifting failures into rarer but more severe categories; this is why we release the benchmark as a diagnostic artifact rather than as a single-number leaderboard.

**LLM-generated queries.** All 10,000 queries were generated by a frontier LLM, not authored by humans. This may bias the difficulty distribution and phrasing in ways that affect severity distributions. A human-authored validation subset would strengthen ecological validity.

## 9 Conclusion

**At matched accuracy, open-weight LLMs differ in tail shape in ways the error rate cannot see.** In our 21-model catalog, 85 of 210 pairs have disjoint 95% $b$ confidence intervals on human-consensus scoring; the theorem and mutual information analysis show that this is genuinely new information, not a restatement of $\varepsilon$; and the taxonomy shows that the tail shift corresponds to a change from retrieval errors toward fabrication. Our operational recommendation is simple: *report $b$ alongside $\varepsilon$ whenever you report an error rate.*

## References


Keiiti Aki. Maximum likelihood estimate of $b$ in the formula $\log n = a - bm$ and its confidence limits. *Bulletin of the Earthquake Research Institute*, 43:237–239, 1965.

Pardis Asgari et al. Beyond accuracy: Measuring the severity of LLM hallucinations. *Findings of the 2025 Conference on Empirical Methods in Natural Language Processing (EMNLP Findings)*, 2025.

Hanin Atwany, Abdul Waheed, Rita Singh, Monojit Choudhury, and Bhiksha Raj. Lost in transcription, found in distribution shift: Demystifying hallucination in speech foundation models. In *Findings of the Association for Computational Linguistics: ACL 2025*, 2025. Introduces the Hallucination Error Rate (HER) metric.

Aofei Chang, Le Huang, Parminder Bhatia, Taha Kass-Hout, Fenglong Ma, and Cao Xiao. MedHEval: Benchmarking hallucinations and mitigation strategies in medical large vision-language models. *arXiv preprint arXiv:2503.02157*, 2025.

Aaron Clauset, Cosma Rohilla Shalizi, and M. E. J. Newman. Power-law distributions in empirical data. *SIAM Review*, 51(4):661–703, 2009.

Brandon Colelough, Davis Bartels, and Dina Demner-Fushman. Overview of the ClinIQLink 2025 shared task on medical question-answering. In *Proceedings of the 24th BioNLP Workshop (ACL 2025)*, 2025.

Matthew Dahl, Varun Magesh, Mirac Suzgun, and Daniel E. Ho. DAHL: Domain-specific hallucination decomposition for legal LLMs. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2024.

Nouha Dziri, Ehsan Kamalloo, Sivan Milton, Osmar Zaiane, Mo Yu, Edoardo Ponti, and Siva Reddy. FaithDial: A faithful benchmark for information-seeking dialogue. *Transactions of the Association for Computational Linguistics (TACL)*, 10:1473–1490, 2022.

William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23(120):1–39, 2022.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, pages 1321–1330, 2017.

B. Gutenberg and C. F. Richter. Frequency of earthquakes in California. *Bulletin of the Seismological Society of America*, 34(4):185–188, 1944.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, et al. Training compute-optimal large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Yejin Bang, Andrea Madotto, and Pascale Fung. Survey of hallucination in natural language generation. *ACM Computing Surveys*, 55(12):1–38, 2023.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

Junyi Li, Xiaoxue Cheng, Wayne Xin Zhao, Jian-Yun Nie, and Ji-Rong Wen. HaluEval: A large-scale hallucination evaluation benchmark for large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6449–6464, 2023.

Junyi Li et al. HaluEval 2.0: Updated hallucination evaluation benchmark for large language models. In *Findings of the Association for Computational Linguistics (ACL Findings)*, 2024.

Stephanie Lin, Jacob Hilton, and Owain Evans. Teaching models to express their uncertainty in words. *Transactions on Machine Learning Research*, 2022a.

Stephanie Lin, Jacob Hilton, and Owain Evans. TruthfulQA: Measuring how models mimic human falsehoods. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 3214–3252, 2022b.

Shrey Pandit, Jiawei Xu, Junyuan Hong, Zhangyang Wang, Tianlong Chen, Kaidi Xu, and Ying Ding. MedHallu: A comprehensive benchmark for detecting medical hallucinations in large language models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2025.

Ashish Seth, Dinesh Manocha, and Chirag Agarwal. Towards a systematic evaluation of hallucinations in large-vision language models (HALLUCINOGEN). *arXiv preprint arXiv:2412.20622*, 2024.

Nassim Nicholas Taleb. *Statistical Consequences of Fat Tails: Real World Preasymptotics, Epistemology, and Applications*. STEM Academic Press, 2020.

Quang H. Vuong. Likelihood ratio tests for model selection and non-nested hypotheses. *Econometrica*, 57(2):307–333, 1989.

Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, et al. Emergent abilities of large language models. *Transactions on Machine Learning Research*, 2022.

Kaiwen Zuo and Yirui Jiang. MedHallBench: A new benchmark for assessing hallucination in medical large language models. *arXiv preprint arXiv:2412.18947*, 2024.

# A Proof details

*Proof of Theorem 1.* For part (i), fix a positive severity grid $\mathcal{S} = \{m_{\min}, m_{\min} + \delta, \ldots, s_{\max}\}$ and define a normalized Gutenberg–Richter tail $q_b(s) \propto 10^{-b(s-m_{\min})}$ on $\mathcal{S}$. For any target error rate $\varepsilon^\star \in (0,1)$, set $P(S=0) = 1-\varepsilon^\star$ and $P(S=s \mid S>0) = q_b(s)$. Then $\varepsilon = \varepsilon^\star$ is fixed while the slope parameter $b$ remains free. Choosing $b_1 \neq b_2$ yields two models with identical error rate and distinct severity profiles; by taking the pair arbitrarily close in $\varepsilon$ we obtain the stated matched-accuracy divergence.

For part (ii), suppose instead that $I(b;\, \text{model} \mid \varepsilon) = 0$ for a population containing matched-accuracy pairs with different $b$ values. Then, conditional on $\varepsilon$, the model identity carries no information about $b$, which implies that $b$ is almost surely a deterministic function of $\varepsilon$ on that population. Part (i) provides a counterexample: two models can share the same $\varepsilon$ while differing in $b$. Hence the conditional mutual information must be strictly positive. □

*Proof of Proposition 2.* For the Aki estimator on exceedances above $m_{\min}$, $\hat{b} = \log_{10} \mathrm{e}/(\bar{m} - m_{\min} + \delta/2)$, standard delta-method calculations give asymptotic variance $\mathrm{Var}(\hat{b}) \approx b^2/n_{\geq m_{\min}}$ when the severity scores are measured without annotation noise. If the effective reliability of the averaged score is $r = \mathrm{ICC}(2,k)$, then the effective sample size is attenuated to $n_{\geq m_{\min}} r$, yielding the lower bound $\mathrm{SE}(\hat{b}) \geq b/\sqrt{n_{\geq m_{\min}} r}$.

For two independent model estimates with similar standard errors, the standard error of $\hat{b}_1 - \hat{b}_2$ is at most $\sqrt{2}\,\mathrm{SE}(\hat{b})$. A two-sided level-$\alpha$ test with power $1-\beta$ therefore requires $|b_1 - b_2| \geq (z_{\alpha/2} + z_\beta)\sqrt{2}\,\mathrm{SE}(\hat{b})$. Substituting $\alpha = 0.05$ and $1-\beta = 0.80$ gives the constant $2.80$ used in the proposition. □

# B 4K vs 10K scale-up comparison

This appendix accompanies the v6 scale-up from 4,000 to 10,000 queries (ERRORQUAKE-10K). All headline claims in the main text are recomputed on the 10K dataset; the comparison below shows both batches side-by-side.

| metric | 4K (v5/v6) | 10K (v7) |
|---|---|---|
| Total queries per model | 4000 | 10000 |
| Disjoint-CI matched-accuracy pairs (Exp. 2) | 30 | 31 |
| Qualifying pairs $\lvert\Delta\varepsilon\rvert < 0.05$, $\lvert\Delta b\rvert > 0.15$ | 42 | 44 |
| Models with valid $b$ fit | 21 | 21 |
| Vuong-decisive distribution best-fit | 18 | 17 |
| Non-exponential best-fit | 17 | 17 |
| Dense scaling $\rho_s$ | $-0.689$ | $-0.562$ |
| Partial $\rho_s(\log_{10} \mathrm{p}, b \mid \varepsilon)$ | $-0.292$ | $-0.204$ |
| $\rho_s(\varepsilon, b)$ dense | $-0.732$ | $-0.842$ |

Table 2: 4K-vs-10K comparison of the LLM-judge baseline metrics.

**B1: Hierarchical bootstrap (judge-noise-aware).** Resampling queries with replacement and simulating primary/secondary swap noise (200 iterations on 10K), the median number of disjoint-CI matched-accuracy pairs is 58 (95% CI [30, 84]).

**B2: Fixed-$m_{\min}$ discriminator counts.**

| $m_{\min}$ | $n_{\text{models}}$ | disjoint-CI pairs |
|---|---|---|
| 1.5 | 21 | 22 |
| 2.0 | 21 | 38 |
| 2.5 | 21 | 27 |
| 3.0 | 20 | 2 |

**B3: Model-agnostic tail-slope estimators.** Log-linear regression over the $\{2.5, 3.0, 3.5, 4.0\}$ upper-bin counts gives 68 matched-accuracy pairs with $|\Delta b_{\text{ll}}| > 0.15$. The empirical tail ratio $P(M \geq 3)/P(M \geq 1)$ gives 45 pairs with $|\Delta\text{tail_ratio}| > 0.01$.

**B4: Binomial catastrophic-rate test.** Fisher's exact test on per-model counts at $M \geq 3.0$ applied to each matched-accuracy pair, then BH-FDR corrected, yields 58 significant pairs at $q < 0.05$; at $M \geq 2.5$, 76 pairs are significant.

**B5: Judge leniency.** Kruskal–Wallis $H = 96286.7$ ($p = 0$) on per-judge score distributions across the 10K dataset shows significant differences in mean leniency, but the round-robin pool aggregation removes this as a per-model bias.

# C Supplementary figures (Exp. 1, 3, and 4)

Figure 3 is the prediction calibration plot for Experiment 3 (two panels: the pre-registered $M \geq 3.0$ threshold and the exploratory $M \geq 2.5$ threshold). Figure 4 gives the full 21-model magnitude-frequency grid (small multiples) that Figure 1 summarises with four representative models. Figure 5 is the BIC heatmap showing $\Delta$BIC between each candidate distribution family and the BIC-best for each model (stars mark the selected family). Figure 6 is the $21 \times 8$ model-by-domain $b$ heatmap.




Figure 3: Predicted vs. observed catastrophic counts per model for Experiment 3. **Left:** pre-registered $M \geq 3.0$ threshold, $\rho_s = 0.443$. **Right:** exploratory $M \geq 2.5$ threshold, $\rho_s = 0.637$. Solid line is identity, dashed lines mark $\pm 1.5\times$. Only $4/21$ models land within $1.5\times$ at $M \geq 3.0$; $0/21$ over-predict.

# D Full 21-model results table

Table 3 reports each model's $b$ with 95% bootstrap confidence interval, the selected $m_{\min}$, the number of events at or above $m_{\min}$, the total error count, the error rate, and the BIC-best distribution family. Rows are sorted by $b$ (heaviest tail first). Active-parameter counts and architecture labels (dense vs MoE) appear in Appendix N.




Figure 4: All 21 models sorted by $b$ (heaviest-tailed at top). Blue markers are the empirical cumulative counts; dashed red is the fitted tail. Compact form of Figure 1.

# E Query benchmark construction

ERRORQUAKE-10K was generated by a dense frontier model prompted to produce stratified queries in eight domains and five difficulty tiers, then verified by an independent dual-judge audit that flagged tier-miscalibrated cells. Approximately 6% of the generated queries failed the tier-calibration audit (most commonly T5 queries that were easier than the tier specification required, and T1 queries in LAW that were harder) and were regenerated using a more capable model with a stricter prompt. Query text, reference answers, tier labels and difficulty audit metadata are released with the benchmark.

# F Exp. 2 cross-domain jackknife (judge baseline)

Removing each of the 8 domains in turn and recounting matched-accuracy disjoint-CI pairs on the 3,500-query residual:

| dropped domain | $n$ pairs | relative to judge baseline (30) |
|---|---|---|
| BIO | 29 | 0.97 |
| CULT | 25 | 0.83 |
| FIN | 31 | 1.03 |
| GEO | 41 | 1.37 |
| HIST | 36 | 1.20 |
| LAW | 40 | 1.33 |
| SCI | 31 | 1.03 |
| TECH | 34 | 1.13 |
| min / max | 25 / 41 | |




Figure 5: ΔBIC between each distribution family and the best-fit family for each of the 21 models, capped at 60. Stars mark the selected family.

All 8 drops exceed the pre-registered criterion of $\geq 3$ disjoint-CI pairs. The judge-baseline discriminator is not driven by any single domain.

## G Exp. 2 judge-aggregation robustness (judge baseline)

Recomputing the disjoint-CI pair count under alternative per-record aggregation rules of the primary and secondary judge scores:

| aggregation rule | # pairs (all 21 models) | # pairs (dual-coverage 15) | $n$ with valid $b$ |
|---|---|---|---|
| `final_score` (judge baseline) | 30 | 28 | 21 / 15 |
| `primary_only` | 7 | 6 | 21 / 15 |
| `secondary_only` | 27 | 24 | 19 / 15 |
| `max`(primary, secondary) | 27 | 23 | 21 / 15 |
| `min`(primary, secondary) | 58 | 13 | 21 / 15 |

Every aggregation rule exceeds the pre-registered criterion of $\geq$ 3 disjoint-CI pairs. The `primary_only` count is the lowest because per-judge $b$ values cluster more tightly than the aggregated values, so fewer pairs meet $|\Delta b| > 0.15$ — but the pairs that do qualify still have disjoint CIs.

## H Judge LOO ablation (full)

We leave each of the 22 judges in our pool out in turn (removing all records where that judge participated, rebuilding the final score from the surviving judges) and recompute the dense scaling correlation. The *sign* is preserved in $22/22$ drops; the $p < 0.05$ significance threshold is preserved in $6/22$, with the magnitude weakening as the largest-contribution judges (DEEPSEEK-V3.2, QWEN3-NEXT-80B, EUROLLM-9B) are removed. Full per-judge rows are in




Figure 6: $b$ by model $\times$ domain. Red = heavier tail. Per-model rows are sorted by mean $b$. Kendall $W = 0.108$ across the 21 models indicates strong model-idiosyncrasy in the domain ranking.

`results/analysis/judge_loo_ablation.json`. The *sign stability* is consistent with the headline discriminator (§6.2), which passes under all judge drops; the *magnitude instability* is the reason we demote the scaling correlation to a sensitivity observation (§6.3).

# I Extended human validation (100-item pilot)

On the 100-item pilot subset where an expert rater scored responses on the same 9-level grid, the dual-judge pipeline has:

| $M^*$ threshold | sensitivity | specificity | PPV | NPV |
|---|---|---|---|---|
| $\geq 2.0$ | 1.000 | 0.826 | 0.333 | 1.000 |
| $\geq 2.5$ | 1.000 | 0.908 | 0.182 | 1.000 |
| $\geq 3.0$ | 1.000 | 0.929 | 0.222 | 1.000 |

**Sensitivity is** $100\%$ **at every severity threshold**: the judges catch every response a human rater flagged as severe. The low PPV ($0.18$ at $M \geq 2.5$) reflects the overcall problem documented in Appendix L: the judges flag $\sim 5\times$ as many items as severe as a human would, so absolute severity-

| model | $b$ | 95% CI | $m_{\min}$ | $n_{\geq m_{\min}}$ | $n_{\text{err}}$ | $\varepsilon$ | best fit |
|---|---|---|---|---|---|---|---|
| DEEPSEEK-V3.2 | 0.595 | [0.582, 0.609] | 0.5 | 5548 | 5548 | 0.580 | stretched exp |
| GEMMA-2-27B | 0.631 | [0.617, 0.644] | 0.5 | 6307 | 6307 | 0.655 | stretched exp |
| GPT-OSS-20B | 0.887 | [0.796, 1.000] | 2.5 | 171 | 5865 | 0.607 | trunc. power law |
| MISTRAL-SMALL-4-119B | 0.900 | [0.796, 1.019] | 2.5 | 142 | 5831 | 0.603 | exponential |
| SEED-OSS-36B | 0.904 | [0.811, 1.023] | 2.5 | 126 | 5808 | 0.602 | stretched exp |
| GEMMA-3-12B | 0.917 | [0.843, 1.005] | 2.5 | 266 | 6257 | 0.650 | stretched exp |
| SOLAR-10.7B | 0.923 | [0.857, 1.004] | 2.5 | 304 | 6256 | 0.650 | stretched exp |
| DEEPSEEK-V3.1 | 0.937 | [0.834, 1.058] | 2.5 | 131 | 5324 | 0.586 | exponential |
| QWEN3-NEXT-80B | 0.939 | [0.822, 1.083] | 2.5 | 106 | 5917 | 0.612 | trunc. power law |
| LLAMA-3.1-8B | 0.952 | [0.905, 1.003] | 2.0 | 965 | 5926 | 0.615 | stretched exp |
| MISTRAL-MEDIUM-3 | 0.965 | [0.859, 1.091] | 2.5 | 135 | 5632 | 0.585 | stretched exp |
| GEMMA-3-27B | 0.989 | [0.935, 1.049] | 2.0 | 606 | 4527 | 0.633 | exponential |
| MINISTRAL-14B | 0.991 | [0.906, 1.093] | 2.5 | 231 | 5700 | 0.593 | stretched exp |
| KIMI-K2 | 1.016 | [0.951, 1.084] | 2.0 | 547 | 5029 | 0.601 | trunc. power law |
| GEMMA-3-4B | 1.038 | [0.972, 1.113] | 3.0 | 371 | 5323 | 0.558 | stretched exp |
| EUROLLM-9B | 1.115 | [0.996, 1.252] | 3.0 | 129 | 4816 | 0.505 | stretched exp |
| PHI-3.5-MINI | 1.119 | [0.985, 1.279] | 3.0 | 123 | 4755 | 0.497 | stretched exp |
| LLAMA-3.2-3B | 1.149 | [1.061, 1.248] | 3.0 | 301 | 5459 | 0.575 | stretched exp |
| QWEN2.5-7B | 1.197 | [1.066, 1.363] | 3.0 | 124 | 4758 | 0.496 | stretched exp |
| LLAMA-4-MAVERICK | 1.199 | [1.062, 1.337] | 2.5 | 107 | 5327 | 0.554 | trunc. power law |
| MISTRAL-SMALL-24B | 1.250 | [1.063, 1.454] | 3.0 | 41 | 5435 | 0.564 | exponential |

Table 3: Full 21-model $b$ table. Bootstrap CIs from $n = 2000$ resamples.

count estimates are inflated. The *ranking-of-models* headline discriminator of §6.2 is unaffected because overcalling is not specific to particular models (Appendix L shows per-model overcall rates range from $15\%$ to $55\%$ around the $33.5\%$ pooled rate). Full ICC and per-threshold confusion matrices are in `results/analysis/extended_human_validation.json`. The pilot covers only 3 models, so human-only scaling verification at $n \geq 5$ dense models is not yet feasible; this is flagged as a limitation in §8.

## J Scoring and judge prompts

The scoring pipeline executes the following stages per query: (i) send the query to the target model with `temperature=0` and a 500-token budget; (ii) store the raw response; (iii) draw a primary and secondary judge from the pool by a round-robin rule that excludes self-judging; (iv) send the response together with the reference answer and the full 9-level rubric to each judge and parse a single-float score from each reply; (v) average the two scores if they agree within $1.0$, else invoke a tiebreaker judge and take the median. The exact judge prompt template, the scoring rubric (all 9 anchor levels with three worked examples each), the model-version strings, and the round-robin configuration are included in the code release.

## K Error-severity scale anchors

The 9-level continuous severity scale has anchors at $\{0.0, 0.5, 1.0, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0\}$ with the following semantic labels:

**0.0 — correct.** The response answers the query accurately and completely.

**0.5 — trivial imprecision.** A minor phrasing issue or a date off by one in an irrelevant direction; a careful reader would not be misled.

**1.0 — minor imprecision.** A detail is wrong but the overall answer is essentially correct (wrong middle name, wrong decade but right century for a less salient event).

**1.5 — moderate imprecision with possible misdirection.** A specific claim is wrong in a way that a reader acting on it might reach a modestly wrong conclusion.

**2.0 — moderate error.** A substantively wrong claim that a typical reader would rely on (wrong year for a major event, wrong country for a person's origin).

**2.5 — substantial error.** Multiple wrong claims, or one wrong claim that is central to the query's purpose; a reader acting on this answer would be clearly misled.

**3.0 — major error.** The response is built around a wrong central claim (wrong person attributed to an event, wrong law cited in a legal query).

**3.5 — minor fabrication.** The response invents information that is not true and presents it confidently, but the fabrication is localised.

**4.0 — major fabrication.** The response fabricates a substantial portion of the answer (an invented statute, a non-existent book, a hallucinated court case) and presents it with no uncertainty marker.

Each level has three worked examples released with the benchmark. The pilot human-rating study distinguished 6 of the 9 levels reliably; levels $0.5$, $1.5$, $2.5$, $3.5$ were used less often by the human rater and less often still by the LLM judges (Appendix L).

## L Overcall diagnostic (clearest examples)

We manually classified $340$ score-$2.0$ judgements across $17$ models, stratified $20$ items per model, using a single expert rater. Each item was placed into one of three categories: *genuine* (the judge's $2.0$ matches what a human would assign), *ambiguous* (the rater thought either $0.5$/$1.0$ or $2.0$ was defensible), or *overcall* (the judge marked $2.0$ for a response that a human would score $0.0$ or $0.5$).

**Overall:** $163/340$ genuine ($47.9\%$), $63/340$ ambiguous ($18.5\%$), $114/340$ overcall ($33.5\%$). Per-model overcall rates are reported in Figure 12. The four clearest overcall patterns observed in the manual audit were: (i) "verbose hedge" — a response that is factually correct but wraps the answer in qualifications or caveats the judge mistook for uncertainty; (ii) "partial synonym" — a correct answer phrased with a different noun than the reference (e.g., "emperor" vs "king" for a historical ruler who used both titles); (iii) "pedantic detail missing" — the correct answer but without a minor qualifying phrase the judge required; and (iv) "correct but rounded" — a correct answer rounded to a different precision than the reference.

## M Experiment 3 per-model breakdown

Figure 3 aggregates the prediction results; the per-model breakdown (predicted vs observed catastrophic counts at $M \geq 3.0$ and $M \geq 2.5$, the ratio, and whether each model lands within $1.5\times$ of the observed) is released as `results/analysis/exp3_prediction.json`. The mechanistic diagnostic — refitting the $b$ separately on easy and hard tiers — is in `exp3_diagnostic.json`; mean $\Delta b_{\text{easy}-\text{hard}} = -0.041$ (std $0.216$), $10/21$ models have easy steeper and $11/21$ have hard steeper.

## N Leave-one-out scaling robustness

Table 4 gives the per-drop values from the leave-one-out robustness check on the Exp. 5 headline correlation. Dropping each of the $14$ dense models in turn and recomputing the Spearman correlation between $\log_{10}(\text{active params})$ and $b$ on the remaining $13$ models, the correlation stays negative and significant in all $14$ drops. The worst-case $p$-value ($p = 0.0263$) is achieved when SEED-OSS-36B, the heaviest-tailed and largest dense model, is removed.

## O Training-pipeline pair comparisons

Table 5 lists the $11$ matched pairs tested. For each pair we estimate the $b$ on the two models separately, fit at a shared $m_{\min}$, and report the bootstrap-resampled difference distribution.

## P Exceedance threshold sweep (Q4)

This appendix answers Q4 (how many exceedances are required for a stable $b$ fit, and does the headline discriminator survive a stricter requirement). For each minimum-exceedance threshold

| model dropped | LOO Spearman $\rho$ | $p$-value |
|---|---|---|
| MINISTRAL-14B | $-0.777$ | 0.0018 |
| GEMMA-3-4B | $-0.736$ | 0.0042 |
| SOLAR-10.7B | $-0.725$ | 0.0051 |
| GEMMA-3-12B | $-0.711$ | 0.0065 |
| LLAMA-3.2-3B | $-0.705$ | 0.0071 |
| MISTRAL-SMALL-24B | $-0.704$ | 0.0072 |
| EUROLLM-9B | $-0.700$ | 0.0078 |
| GEMMA-3-27B | $-0.680$ | 0.0106 |
| LLAMA-3.1-8B | $-0.678$ | 0.0109 |
| QWEN2.5-7B | $-0.667$ | 0.0128 |
| MISTRAL-MEDIUM-3 | $-0.663$ | 0.0135 |
| PHI-3.5-MINI | $-0.634$ | 0.0201 |
| GEMMA-2-27B | $-0.622$ | 0.0233 |
| SEED-OSS-36B | $-0.612$ | 0.0263 |

Table 4: Leave-one-out Spearman correlations on the Exp. 5 headline. All 14 drops preserve sign and significance. Baseline $\rho_s = -0.562$, $p = 0.006$ ($n = 14$).

| pair | hypothesis | $\Delta b$ | 95% CI | $p$ | verdict |
|---|---|---|---|---|---|
| llama-3.2-3b vs 3.1-8b | within-Llama scale | $-0.532$ | $[-0.749, -0.287]$ | 0.000 | sig |
| qwen2.5-7b vs llama-3.1-8b | family at 8B | $-0.317$ | $[-0.556, -0.040]$ | 0.021 | sig |
| gemma-3-12b vs 27b | within-Gemma-3 scale | $-0.198$ | $[-0.389, +0.008]$ | 0.057 | marg. |
| gemma-3-12b vs ministral-14b | family at $\sim$ 13B | $-0.189$ | $[-0.408, +0.030]$ | 0.091 | n.s. |
| gemma-3-4b vs 12b | within-Gemma-3 scale | $-0.169$ | $[-0.453, +0.069]$ | 0.205 | n.s. |
| mistral-24b vs gemma-3-27b | family at $\sim$ 25B | $-0.132$ | $[-0.378, +0.127]$ | 0.301 | n.s. |
| mistral-24b vs medium-3 | Mistral tier | $+0.098$ | $[-0.143, +0.366]$ | 0.446 | n.s. |
| gemma-2-27b vs gemma-3-27b | generation upgrade | $+0.040$ | $[-0.076, +0.155]$ | 0.496 | n.s. |
| deepseek-v3.1 vs v3.2 | minor version bump | $-0.006$ | $[-0.071, +0.063]$ | 0.872 | n.s. |
| llama-4-maverick vs ministral-14b | MoE vs dense $\sim$ 14B | $+0.001$ | $[-0.272, +0.281]$ | 0.982 | n.s. |
| gemma-3-4b vs 27b | scale span | $+0.023$ | – | – | insuf. |

Table 5: Training-pipeline pair tests. $2/11$ pairs reach $p < 0.05$; notably, the DeepSeek version bump v3.1 $\rightarrow$ v3.2 does *not* significantly change the severity distribution.

$T \in \{30, 50, 75, 100, 150, 200\}$, we exclude models whose $m_{\min}$-selected tail contains fewer than $T$ events (insufficient statistical support), refit per-model $b$ on the survivors, and recount both the Exp. 2 disjoint-CI discriminator pairs and the Exp. 5 dense scaling correlation plus partial correlation.

| $T$ | $n_{\text{surv}}$ | $n_{\text{dense}}$ | discrim. pairs | $\rho_s^{\text{scale}}$ | $p$ | partial $\rho_s \mid \varepsilon$ | partial $p$ |
|---|---|---|---|---|---|---|---|
| 30 | 21 | 14 | 30 | $-0.562$ | 0.006 | $-0.270$ | 0.35 |
| 50 | 18 | 13 | 22 | $-0.704$ | 0.007 | $-0.207$ | 0.32 |
| 75 | 11 | 8 | 13 | $-0.850$ | 0.008 | $-0.548$ | 0.16 |
| 100 | 11 | 8 | 13 | $-0.850$ | 0.008 | $-0.548$ | 0.16 |
| 150 | 9 | 6 | 10 | $-0.928$ | 0.008 | $-0.600$ | 0.21 |
| 200 | 9 | 6 | 10 | $-0.928$ | 0.008 | $-0.600$ | 0.21 |

Table 6: Exceedance threshold sweep. At every tested threshold the Exp. 2 discriminator count exceeds the pre-registered criterion of $\geq 3$ disjoint-CI pairs (minimum 10 at $T = 200$). The dense scaling correlation strengthens as the threshold tightens (from $-0.562$ to $-0.928$) because the survivors are the best-supported tail fits; the partial correlation controlling for $\varepsilon$ weakens with the shrinking sample and does not reach $p < 0.05$ at any threshold, consistent with the underpowered regime.

## Q Deployment table (judge baseline, full)

This appendix answers Q10: expected events per million queries at multiple severity thresholds. Table 7 gives the per-model counts at $M \geq \{1.5, 2.0, 2.5, 3.0, 3.5, 4.0\}$ scaled to per-million-query rates, computed directly from the empirical LLM-judge baseline evaluation on the 4K subset (no




Figure 7: Gemma-2 vs. Gemma-3 at 27B (generation upgrade). Within-family generation comparison; the $\Delta b$ is small and not statistically significant (Table 5).




Figure 8: DeepSeek v3.1 vs. v3.2 (minor version bump). The two versions are statistically indistinguishable in tail shape ($p = 0.872$, Table 5).

extrapolation, no fit). The table answers the practitioner question: "how many events of severity $\geq m^*$ should I expect per million queries if I deploy model $X$?"

Figure 9 visualises the $M \geq 2.5$ and $M \geq 3.0$ columns. GEMMA-3-4B and LLAMA-3.2-3B have the highest catastrophic rate ($\sim$53,000–63,000 per million at $M \geq 3.0$), consistent with their small dense size and correspondingly flat tails. At the other end, QWEN3-NEXT-80B and LLAMA-4-MAVERICK have $\sim$3,000 catastrophic events per million — a $\sim 20\times$ spread. Fitted $b$ values provide a distribution-shape summary but are not a calibrated extrapolator (§6.4).

## R Inter-judge agreement (per-model)

We compute linear- and quadratic-weighted Cohen's $\kappa$ between the primary and secondary judge scores on the 9-level severity grid. The pooled values across 60,568 dual-scored records are $\kappa_{\text{lin}} = 0.285$ ("fair" on the Landis–Koch scale) and $\kappa_{\text{quad}} = 0.374$ ("fair–moderate"). The 60,568 count is the union of records where both judges produced a non-null score; for several models, especially

| model | $\varepsilon$ | $b$ | $M{\geq}1.5$ | $M{\geq}2.0$ | $M{\geq}2.5$ | $M{\geq}3.0$ | $M{\geq}3.5$ | $M{\geq}4.0$ |
|---|---|---|---|---|---|---|---|---|
| QWEN3-NEXT-80B | 0.592 | 1.052 | 122,061 | 56,278 | 10,755 | 3,252 | 250 | 0 |
| LLAMA-3.2-3B | 0.450 | 1.046 | 315,695 | 275,366 | 81,428 | 52,915 | 13,357 | 4,110 |
| GPT-OSS-20B | 0.586 | 0.938 | 160,991 | 78,368 | 17,026 | 5,759 | 1,252 | 250 |
| PHI-3.5-MINI | 0.285 | 1.309 | 202,076 | 197,012 | 17,220 | 13,928 | 2,279 | 0 |
| GEMMA-3-4B | 0.387 | 0.979 | 334,883 | 305,964 | 101,730 | 62,742 | 22,205 | 2,066 |
| QWEN2.5-7B | 0.316 | 1.257 | 214,828 | 211,285 | 21,761 | 17,206 | 3,289 | 0 |
| LLAMA-3.1-8B | 0.607 | 1.001 | 193,250 | 95,750 | 25,000 | 9,750 | 500 | 0 |
| EUROLLM-9B | 0.344 | 1.067 | 243,147 | 231,726 | 24,873 | 17,766 | 5,076 | 508 |
| SOLAR-10.7B | 0.644 | 0.905 | 203,759 | 106,516 | 27,820 | 9,524 | 2,757 | 501 |
| GEMMA-3-12B | 0.631 | 0.938 | 209,960 | 104,605 | 25,275 | 8,509 | 2,002 | 250 |
| MINISTRAL-14B | 0.586 | 1.122 | 208,218 | 99,975 | 18,291 | 4,260 | 752 | 0 |
| MISTRAL-SMALL-4-119B | 0.579 | 0.888 | 154,693 | 70,588 | 17,272 | 5,507 | 2,503 | 250 |
| LLAMA-4-MAVERICK | 0.553 | 1.118 | 121,988 | 53,464 | 11,797 | 3,012 | 251 | 0 |
| MISTRAL-MEDIUM-3 | 0.589 | 0.906 | 296,137 | 160,566 | 18,177 | 7,574 | 505 | 252 |
| MISTRAL-SMALL-24B | 0.566 | 0.999 | 146,037 | 63,266 | 11,503 | 3,501 | 750 | 0 |
| GEMMA-2-27B | 0.666 | 0.619 | 172,043 | 75,769 | 20,255 | 6,752 | 1,000 | 250 |
| GEMMA-3-27B | 0.630 | 0.956 | 174,779 | 79,697 | 25,725 | 5,801 | 1,009 | 0 |
| KIMI-K2 | 0.615 | 1.041 | 131,316 | 61,281 | 15,258 | 5,003 | 250 | 0 |
| SEED-OSS-36B | 0.568 | 0.574 | 185,725 | 92,988 | 13,571 | 6,032 | 754 | 251 |
| DEEPSEEK-V3.1 | 0.571 | 0.808 | 131,045 | 56,126 | 13,029 | 5,011 | 1,253 | 0 |
| DEEPSEEK-V3.2 | 0.587 | 0.655 | 150,125 | 69,424 | 11,028 | 4,261 | 501 | 0 |

Table 7: Expected event counts per $1{,}000{,}000$ queries at six severity thresholds, computed from the $10{,}000$-query empirical evaluation. Wilson $95\%$ binomial CIs and raw counts are in `results/analysis/deployment_table.json`. Rows sorted by $\log_{10}$(active params). No fit, no extrapolation.

the smaller ones, the secondary judge call failed on a non-random subset of records (e.g., PHI-3.5-MINI has only $95/4000$ dual-scored records because the secondary judge errored on the rest), so the per-model $\kappa$ values are not directly comparable across models. We nonetheless report them in `results/analysis/judge_agreement.json` for transparency.

The pooled $\kappa$ is lower than the typical $\kappa > 0.6$ target for high-stakes evaluation. Two structural factors contribute: (i) our 9-level scale produces lower chance agreement than the 3– or 5-level scales used in most LLM-as-judge studies, and (ii) the response-style confound documented in Appendix L introduces systematic disagreement on verbose, hedged outputs. The headline scaling correlation is computed on the *final* score (the mean of the two judges, with tiebreak when needed), so judge disagreement is averaged out per-record before the $b$ fit; the leave-one-out robustness check ($14/14$, §6.3) demonstrates that the final-score noise is small enough not to undermine the headline.

## S Per-tier scaling decomposition (judge baseline)

Table 8 reports the within-tier scaling correlation: $\rho_s(\log_{10}(\text{active params}), b_{\text{tier}})$ on the $14$ dense models, with $b$ refit on the $\sim 200$–$500$ within-tier errors per model. The aggregate (across all tiers) correlation is $\rho_s = -0.562$ ($p = 0.006$). Within tiers, the sign is preserved in $4/5$ tiers and only T2 reaches conventional significance individually. T4 is the one tier where the correlation flattens to $\rho_s \approx 0$. The aggregate effect benefits from the larger per-model error counts ($\sim 2000$ vs $\sim 400$), which reduce per-fit noise and let the underlying signal emerge. The per-tier sign-preservation is the relevant robustness statement; the aggregate $p$-value is the relevant magnitude statement.

| tier | $n$ | dense $\rho_s(\log_{10}$ params, $b_{\text{tier}})$ | $p$ |
|---|---|---|---|
| T1 (easy) | 14 | $-0.493$ | $0.073$ |
| T2 (easy) | 14 | $-0.562$ | $0.037^*$ |
| T3 (intermediate) | 14 | $-0.322$ | $0.262$ |
| T4 (hard) | 14 | $+0.046$ | $0.875$ |
| T5 (hard) | 14 | $-0.425$ | $0.130$ |
| aggregated (all 5) | 14 | $\mathbf{-0.562}$ | $\mathbf{0.006}$ |

Table 8: Per-tier scaling correlation on the $14$ dense models. Sign preserved in $4/5$ tiers; T2 individually significant. The addendum's prediction (T4–T5 should drive the headline) is *not* borne out — the strongest individual tier is T2.




Figure 9: Empirical event rate per million queries for 21 models, sorted by catastrophic count ($M \geq 3.0$, red bars) with severe ($M \geq 2.5$, orange bars) for comparison.

# T S5 — $m_{\min}$ sensitivity (judge baseline)

Table 9 reports each dense model's $b$ under three $m_{\min}$ strategies: (a) our default model-specific KS-selector, (b) fixed $m_{\min} = 1.5$, and (c) the Clauset-style criterion of $\geq 100$ exceedances (which selects $m_{\min} = 0.5$ for every model in the catalog). The dense Spearman correlation between $\log_{10}(\text{active params})$ and $b$ is $-0.562$ under (a), $+0.837$ under (b), and $+0.793$ under (c). The interpretation of this sign flip is in §6.6.

# U Sensitivity figures

# NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract and introduction summarize the matched-accuracy discriminator result, the theory contribution, the human-validation study, and the scope limits on model coverage. Limitations and scope restrictions are also stated explicitly in the introduction and the Limitations section.

2. **Limitations**

| model | $b_{\text{def}}$ | $b_{m=1.5}$ | $b_{m=0.5}$ | $n_{\geq 0.5}$ |
|---|---|---|---|---|
| LLAMA-3.2-3B | 1.046 | 0.469 | 0.290 | 1750 |
| PHI-3.5-MINI | 1.309 | 0.530 | 0.298 | 1126 |
| GEMMA-3-4B | 0.979 | 0.439 | 0.243 | 1497 |
| QWEN2.5-7B | 1.257 | 0.517 | 0.299 | 1247 |
| LLAMA-3.1-8B | 1.001 | 0.737 | 0.566 | 2429 |
| EUROLLM-9B | 1.067 | 0.526 | 0.297 | 1356 |
| SOLAR-10.7B | 0.905 | 0.711 | 0.562 | 2571 |
| GEMMA-3-12B | 0.938 | 0.742 | 0.555 | 2521 |
| MINISTRAL-14B | 1.122 | 0.795 | 0.534 | 2340 |
| MISTRAL-MEDIUM-3 | 0.906 | 0.767 | 0.434 | 2334 |
| MISTRAL-SMALL-24B | 0.999 | 0.834 | 0.639 | 2265 |
| GEMMA-2-27B | 0.619 | 0.786 | 0.619 | 2665 |
| GEMMA-3-27B | 0.956 | 0.760 | 0.610 | 2500 |
| SEED-OSS-36B | 0.574 | 0.781 | 0.574 | 2260 |
| dense Spearman vs. $\log_{10}$(params) | $-0.562$ | $+0.837$ | $+0.793$ | |
| $p$-value | 0.006 | 0.0002 | 0.0007 | |

Table 9: S5: dense $b$ under three $m_{\min}$ strategies. The default model-specific KS-selector targets the upper tail; fixed $m_{\min} = 1.5$ and the Clauset-style $\geq 100$-exceedances rule both target the bulk of the positive distribution. The sign of the scaling correlation flips between the two regimes: larger dense models have heavier upper tails but lighter bulk decay rates.

**Figure 13: b-value ranking is preserved under scale coarsening (S1)**




Figure 10: S1: $b$ under scale coarsening. The 9-point grid is load-bearing; both coarsenings fall well below the $\rho > 0.85$ stability threshold.

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [Yes]

Justification: Section 8 discusses judge overcalling, the load-bearing nature of the 9-point scale, model-coverage gaps, limited human-sample size, failed predictive calibration, benchmark misuse, and the fact that queries are LLM-generated.

3. **Theory assumptions and proofs**

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [Yes]




Figure 11: S2: ranking stability under overcall correction. Mean Spearman $\rho = 0.847$ across 50 bootstrap trials, narrowly below the pre-registered 0.85 threshold.




Figure 12: Per-model overcall breakdown on the 340-item human-rated subset (Appendix L).

Justification: Theorem 1 and Proposition 2 are stated in Section 3, and complete proofs are provided in Appendix A. The main text includes proof sketches for intuition and the appendix provides the formal derivations.

4. **Experimental result reproducibility**

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: Sections 4 and 5, together with the appendices and supplemental artifact, describe the benchmark construction, model catalog, scoring pipeline, fitting procedure, and statistical analyses used for the main claims. The supplemental artifact also includes scripts and a reproduction guide for rerunning the analyses from saved data.

5. **Open access to data and code**

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: The anonymized supplemental artifact includes the code, saved analysis outputs, released data files, Croissant metadata, and reproduction instructions. The paper states that the benchmark, scoring toolkit, human-validation data, and analysis code are released for replication.

6. **Experimental setting/details**

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [Yes]

Justification: The paper specifies the 10,000-query benchmark design, domain/tier stratification, model catalog, decoding setup, severity scale, dual-judge resolution pipeline, human-validation protocol, candidate distribution families, and bootstrap procedures. Additional tables and prompts are included in the appendix and supplemental files.

7. **Experiment statistical significance**

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: The paper reports bootstrap confidence intervals for $b$, p-values for correlation and goodness-of-fit tests, mutual-information decomposition, and additional robustness analyses. The bootstrap setup and significance thresholds are described in the paper and supplemental scripts.

8. **Experiments compute resources**

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [No]

Justification: The paper states that inference was run through an open-access third-party API hosting the target models, but it does not provide exact GPU types, memory, or wall-clock runtime for every experiment. We chose not to over-claim compute reproducibility where the provider abstraction hides the underlying hardware.

9. **Code of ethics**

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

Answer: [Yes]

Justification: The submission is anonymized, the paper discusses misuse risks and limitations, and the released artifact is intended for auditing and evaluation rather than unsafe deployment. We are not aware of any aspect of the work that conflicts with the NeurIPS Code of Ethics.

10. **Broader impacts**

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [Yes]

Justification: Section 8 includes a Broader impacts paragraph discussing positive impacts for risk auditing and deployment gating, as well as negative impacts from benchmark gaming or optimizing for better-looking but still dangerous failure profiles.

11. **Safeguards**

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: [N/A]

Justification: The paper releases an evaluation benchmark, scores, and analysis code, not a new generative model or scraped multimedia dataset with elevated release risk. We therefore view the high-risk-model safeguard question as not directly applicable to this artifact.

12. **Licenses for existing assets**

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [No]

Justification: The paper cites the upstream benchmarks and model families used in the evaluation, and the supplemental artifact includes licenses for the released ERRORQUAKE code/data. However, the submission does not enumerate every upstream model or provider license directly in the manuscript, so we answer conservatively.

13. **New assets**

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: The benchmark release includes a datasheet, Croissant metadata, reproduction instructions, and scripts for the reported analyses. The paper and supplemental material document the query structure, severity scale, scoring fields, and released outputs.

14. **Crowdsourcing and research with human subjects**

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [No]

Justification: The supplemental artifact includes the full rating instructions used in the human-validation study. However, the submission does not currently document participant compensation or an equivalent statement that compensation was not applicable.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [No]

Justification: The submission reports a human-rating study but does not include an IRB-approval statement or a fuller discussion of participant-risk disclosure. We therefore answer conservatively rather than implying review documentation that is not present in the anonymized materials.

16. **Declaration of LLM usage**

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: [Yes]

Justification: The paper explicitly states that the benchmark queries were generated by a frontier LLM and that response scoring uses an LLM-judge pipeline with human validation. These components are described in Sections 4, 5, and 8.