



A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise
learning
methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects

Cross-validation
Exact online
learning

Take home
messages

A two-step method to incorporate task features for large output spaces

Michiel Stock¹, Tapio Pahikkala², Antti Airola², Bernard
De Baets¹ & Willem Waegeman¹

¹KERMIT

Department of Mathematical Modelling, Statistics and Bioinformatics
Ghent University

²Department of Computer Science
University of Turku

NIPS: extreme classification workshop
December 12, 2015



What will we read next?

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example

Relational
learning
Other
applications






Pairwise
learning
methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects

Cross-validation
Exact online
learning

Take home
messages

	Alice	Bob	Cedric	Daphne
	5		4	
	1			4
		4		
	2		1	
	4		3	



What will we read next?

A two-step method for large output spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory example

Relational learning

Other applications

Pairwise learning methods

Kronecker kernel ridge regression

Two-step kernel ridge regression

Computational aspects

Cross-validation

Exact online learning

Take home messages

Social graph



Genre

Alice

Bob

Cedric

Daphne

1 1 0 1



5

4

0 0 1 0



1

4

1 1 0 0



4

0 0 1 0



2

1

0 1 0 1



4

3



What will we read next?

A two-step method for large output spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory example

Relational learning

Other applications

Pairwise learning methods

Kronecker kernel ridge regression
Two-step kernel ridge regression

Computational aspects

Cross-validation
Exact online learning

Take home messages

Social graph



Genre

Alice

Bob

Cedric

Daphne

1 1 0 1



5

2.3

4

3.1

0 0 1 0



1

4.5

1.3

4

1 1 0 0



3.9

4

3.8

0.8

0 0 1 0



2

5.2

1

4.5

0 1 0 1



4

2.5

3

3.6



What will we read next?

A two-step method for large output spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory example

Relational learning

Other applications

Pairwise learning methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational aspects

Cross-validation
Exact online learning

Take home messages

Social graph



Genre

Alice

Bob

Cedric

Daphne

1 1 0 1



5

2.3

4

3.1

0 0 1 0



1

4.5

1.3

4

1 1 0 0



3.9

4

3.8

0.8

0 0 1 0



2

5.2

1

4.5

0 1 0 1



4

2.5

3

3.6

1 1 0 1



4.8

1.1

3.7

2.3




What will we read next?

A two-step method for large output spaces

Michiel Stock
twitter:
@michielstock

Social graph



Genre

		Alice	Bob	Cedric	Daphne	Eric
1 1 0 1		5	2.3	4	3.1	2.3
0 0 1 0		1	4.5	1.3	4	4.0
1 1 0 0		3.9	4	3.8	0.8	1.7
0 0 1 0		2	5.2	1	4.5	4.8
0 1 0 1		4	2.5	3	3.6	2.9
1 1 0 1		4.8	1.1	3.7	2.3	

Motivation

Introductory example

Relational learning

Other applications

Pairwise learning methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational aspects

Cross-validation
Exact online learning

Take home messages



What will we read next?

A two-step method for large output spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory example

Relational learning

Other applications

Pairwise learning methods


Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational aspects

Cross-validation
Exact online learning

Take home messages

Social graph



Genre

Alice

Bob

Cedric

Daphne

Eric

1 1 0 1



5

2.3

4

3.1

2.3

0 0 1 0



1

4.5

1.3

4

4.0

1 1 0 0



3.9

4

3.8

0.8

1.7

0 0 1 0



2

5.2

1

4.5

4.8

0 1 0 1



4

2.5

3

3.6

2.9

1 1 0 1



4.8

1.1

3.7

2.3

2.4



Learning relations

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications


Pairwise learning methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational aspects

Cross-validation
Exact online
learning

Take home messages





Other cool applications: drug design

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example

Relational
learning

Other
applications

Pairwise
learning
methods


Kronecker kernel
ridge regression

Two-step kernel
ridge regression

Computational
aspects

Cross-validation
Exact online
learning

Take home
messages



Predicting interaction between **proteins** and **small compounds**



Other cool applications: social network analysis

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example

Relational
learning

Other
applications

Pairwise learning methods


Kronecker kernel
ridge regression

Two-step kernel
ridge regression

Computational aspects

Cross-validation
Exact online
learning

Take home messages



Predicting links between people



Other cool applications: food pairing

A two-step method for large output spaces

Michiel Stock
twitter:
@michielsstock

Motivation

Introductory example

Relational learning

Other applications

Pairwise learning methods

Kronecker kernel ridge regression


Two-step kernel ridge regression

Computational aspects

Cross-validation

Exact online learning

Take home messages



Finding ingredients that pair well



Learning with pairwise feature representations

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise
learning
methods


Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects


Cross-validation
Exact online
learning

Take home
messages

Features
books

 Φ

Features
readers

 Ψ

- d : instance (e.g. book)
- $\phi(d)$: instance features (e.g. genre)
- t : task (e.g. reader)
- $\psi(t)$: task features (e.g. social network)



Learning with pairwise feature representations

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise
learning
methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects

Cross-validation
Exact online
learning


Take home
messages

Features
books



Φ


Features
readers



Ψ



=



$\Phi \otimes \Psi$

- d : instance (e.g. book)
- $\phi(d)$: instance features (e.g. genre)

- t : task (e.g. reader)
- $\psi(t)$: task features (e.g. social network)



Learning with pairwise feature representations

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise
learning
methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects

Cross-validation
Exact online
learning


Take home
messages

Features
books



Φ


Features
readers



Ψ



=



$\Phi \otimes \Psi$

- d : instance (e.g. book)
- $\phi(d)$: instance features (e.g. genre)

- t : task (e.g. reader)
- $\psi(t)$: task features (e.g. social network)

Pairwise prediction function: $f(d, t) = \mathbf{w}^T(\phi(d) \otimes \psi(t))$



Learning relations in two steps

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications


Pairwise
learning
methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects

Cross-validation
Exact online
learning

Take home
messages



- 1 Build a ridge regression model to generalize to **new instances**
- 2 Build a ridge regression model to generalize to **new tasks**



The two-step ridge regression

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise
learning
methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects

Cross-validation
Exact online
learning

Take home
messages

Prediction function:

$$f(d, t) = \phi(d)^T \mathbf{W} \psi(t)$$

Parameters can be found by solving:

$$\Phi^T \mathbf{Y} \Psi = (\Phi^T \Phi + \lambda_d \mathbf{I}) \mathbf{W} (\Psi^T \Psi + \lambda_t \mathbf{I})$$



The two-step ridge regression

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise
learning
methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects

Cross-validation
Exact online
learning

Take home
messages

Prediction function:

$$f(d, t) = \phi(d)^T \mathbf{W} \psi(t)$$

Parameters can be found by solving:

$$\Phi^T \mathbf{Y} \Psi = (\Phi^T \Phi + \lambda_d \mathbf{I}) \mathbf{W} (\Psi^T \Psi + \lambda_t \mathbf{I})$$

Two hyperparameters: λ_d and λ_t !



Four ways of cross validation

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise
learning
methods


Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects


Cross-validation
Exact online
learning

Take home
messages


Setting A




Setting B



Setting C



Setting D



Train

Test

Discarded



Four ways of cross validation

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise
learning
methods


Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects


Cross-validation
Exact online
learning

Take home
messages


Setting A




Setting B



Setting C



Setting D



Train

Test

Discarded


- Analytic shortcuts can be derived to perform LOOCV for each setting!
- Tuning λ_d and λ_t essentially free!



Effect of regularization for the four settings

Data: protein-ligand interactions.

Evaluation by AUC (lighter = better performance)



Clear difference between four settings and λ_d and λ_t !



Learning with mini-batches

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications


Pairwise learning methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational aspects

Cross-validation
Exact online
learning

Take home messages





Learning with mini-batches

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise
learning
methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects

Cross-validation
Exact online
learning

Take home
messages



Exact updating of the
parameters when new
training instances and/or
tasks become available

- scalable for “Big Data” applications
- updating model in dynamic environment



Exact online learning for hierarchical text classification

A two-step method for large output spaces

Michiel Stock
twitter:
@michielstock

Motivation

- Introductory example
- Relational learning
- Other applications

Pairwise learning methods


- Kronecker kernel ridge regression
- Two-step kernel ridge regression

Computational aspects

- Cross-validation
- Exact online learning

Take home messages

Hierarchical text classification ($> 12,000$ labels): from 5,000 to 350,000 instances in steps of 1,000 instances.





Why two-step ridge regression?

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise learning methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational aspects

Cross-validation
Exact online
learning

Take home messages

- Zero-shot learning, transfer learning, multi-task learning...
in one line of code



Why two-step ridge regression?

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise learning methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational aspects

Cross-validation
Exact online
learning

Take home messages

- Zero-shot learning, transfer learning, multi-task learning... in one line of code
- Theoretically well founded



Why two-step ridge regression?

A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise learning methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational aspects

Cross-validation
Exact online
learning

Take home messages

- Zero-shot learning, transfer learning, multi-task learning... in one line of code
- Theoretically well founded
- Allows for nifty computational tricks
 - ‘free’ tuning for the hyperparameters
 - ‘free’ LOOCV for all four settings!
 - closed-form solution for updating with mini-batches



A two-step
method for
large output
spaces

Michiel Stock
twitter:
@michielstock

Motivation

Introductory
example
Relational
learning
Other
applications

Pairwise
learning
methods

Kronecker kernel
ridge regression
Two-step kernel
ridge regression

Computational
aspects

Cross-validation
Exact online
learning

Take home
messages

A two-step method to incorporate task features for large output spaces

Michiel Stock¹, Tapio Pahikkala², Antti Airola², Bernard
De Baets¹ & Willem Waegeman¹

¹KERMIT

Department of Mathematical Modelling, Statistics and Bioinformatics
Ghent University

²Department of Computer Science
University of Turku

NIPS: extreme classification workshop
December 12, 2015