Phase One Evidence for Bounded Visual Memory

Controlled prediction experiments and equal capacity deletion tests
Academic progress report | 16 October 2026

1 Research objective

Our proposal asks which historical observations a model should retain when its memory is limited. The intended learning signal is the prediction cost of deleting an observation: a memory should matter when forgetting it makes useful future prediction worse. The research goal is a better retention decision, rather than a predictor that solves every possible future.

Phase One tests the prerequisites: whether stored visual features contain the missing evidence, and whether a predictor can use it. The later deletion assay adds a bridge toward policy learning, while keeping the predictor and memory capacity fixed. No retention policy has been trained.




Figure 1. Why the past is needed. Paired episodes A and B share recent images and actions but have different earlier evidence and future outcomes. Gate requires a transient cue; Motion requires pre-occlusion positions. These drawings are conceptual illustrations, not sampled test images or model outputs.

Three questions guide the experiments

Question	Evidence needed
Representation	Can the relevant cue or motion evidence be recovered from frozen image features?
Prediction	Does supplying historical evidence improve forecasts over recent observations alone?
Deletion signal	At the same memory capacity, does losing critical evidence cause more harm than losing a nuisance frame?

Scope. The original proposal places controlled prediction before selector training. The deletion assay is an additional transition experiment; it does not establish an online retention algorithm or replace the earlier prediction acceptance tests.

2 Experimental design




Figure 2. Shared prediction pipeline. A frozen I-JEPA encoder [1] maps images into cached features. The predictor sees recent context, legal history, actions and timestamps. Simulator truth is used only to score outputs. All retained entries are read; there is no separate retrieval or learned retention selector.

Component	Specification
Controlled tasks	Gate cue and occluded Motion
Data per task	512 training pairs; 96 validation pairs; 128 test pairs in each of 3 conditions
Test conditions	Ordinary; longer gaps or occlusion; changed visual distractors
Prediction context	4 recent frames; historical budget B = 2; horizons h = 3 and h = 6
Complete candidate models	2 tasks x seeds 17, 29, 43 = 6 models; 120 epochs and 7680 steps each
Visual representation	Frozen I-JEPA; train-only normalization and 128-dimensional basis; full 5120-dimensional scored output
Model selection	Earliest minimum of validation MSE, equally weighting 4 conditions and both horizons
Data separation	Pairs stay in one split; no simulator state, sibling identity or future image is a predictor input

What was compared

Condition	Information provided
Recent only	Recent buffer and actions; no historical evidence
Full history	All available legal history; a diagnostic upper information reference
Privileged small budget	Two important historical frames, chosen using task construction
Content intervention	Replace the relevant historical content to test whether prediction depends on it

The last complete candidate used centered visual differences, attention pooling over observed history and explicit elapsed-time transport. These components were motivated by Set Transformer [2] and NLinear [3]; the candidate is an adaptation, not a reproduction or a novelty claim. Its empty-history output equals the frozen recent-only reference.

Statistics. Feature error is mean squared error (MSE); task error measures lane or position. Reported prediction intervals use paired bootstrap resampling over 128 base trajectory pairs. Seed-averaged intervals are conditional on the three tested training seeds. Forks, siblings and seeds are not treated as extra independent episodes.

3 History helps prediction but support is uneven




Figure 3. Prediction gain from the history-conditioned candidate versus the frozen recent-only reference. Points show relative feature-MSE reduction, with paired 95 percent intervals after averaging seeds within each pair. Positive is better. The dashed 10 percent line is the material-effect floor for these comparisons. Data: D1.

Task and condition	Recent only MSE	Full history MSE	Two memories MSE	Gain and 95 percent CI
Gate Ordinary	0.0997	0.0562	0.0776	22.2% [15.2, 28.5]
Gate Long gap	0.0995	0.0960	0.0737	26.0% [20.0, 31.9]
Gate Distractor shift	0.1385	0.1003	0.1196	13.7% [10.3, 17.1]
Motion Ordinary	0.1526	0.0995	0.1161	23.9% [21.7, 26.1]
Motion Long gap	0.1831	0.1879	0.1804	1.5% [-1.5, 4.6]
Motion Distractor shift	0.2908	0.2713	0.2726	6.3% [4.3, 8.3]

Six-step normalized feature errors, averaged over three seeds. The last column compares privileged two-memory prediction with recent only. Full history uses more memory and is an information reference, not a capacity-matched competitor. Data: D1.

Acceptance check	Gate	Motion
Evidence readable from features	3 / 3	3 / 3
Privileged history benefit under original task rules	23 / 24	8 / 24
Response to historical content intervention	24 / 24	24 / 24
Fixed recent-reference feature comparisons	24 / 24	8 / 24
Critical error improvement over prior predictor at the same budget	8 / 8	0 / 8

Table 1. Counts of prespecified checks, not independent sample counts or percentages of project completion. The original task checks total 51 per task; the additional fixed-reference checks total 32 per task. All required checks had to pass. Data: D1.

Interpretation. Gate passed 50/51 original and 32/32 additional checks, but the ordinary h6 task-benefit interval for seed 43 was inconclusive. Motion passed 35/51 and 8/32: its ordinary gains did not extend

reliably to long occlusion and shifted distractors. Both tasks therefore failed the complete development acceptance protocol; fresh confirmation was not opened.

4 Does deletion cost identify important memory

We reused the six complete models and their existing feature caches. From the same parent set of three real observations, we removed each entry in turn and compared the resulting forecasts. Every fork retained exactly two historical entries, so a gain cannot be explained by a larger memory budget.




Figure 4. Same-capacity intervention. Each branch is reset to its common parent and differs only in the deleted memory. Gate pools contain one cue and two post-cue frames; Motion pools contain start and end observations plus a shutter frame. Two fixed nuisance-time variants were tested. Pools are privileged diagnostics, not online policy states.

Deletion contrast = loss after deleting critical evidence minus loss after deleting a nuisance frame. Positive values favor keeping the critical observation. The prospective entry rule required a positive 95 percent paired interval and at least 10 percent mean relative benefit, for both feature error and task error in every seed, horizon and critical role.




Figure 5. Reliability of critical-versus-nuisance deletion contrasts. Gate has one critical role, giving 6 checks per condition; Motion has two roles, giving 12. Each check uses 128 base pairs. Different denominators reflect the design, not different dataset sizes. Data: D2.

Task	Ordinary	Long gap	Distractor shift	Cross horizon checks
Gate	4 / 6	0 / 6	2 / 6	18 / 18
Motion	12 / 12	12 / 12	12 / 12	18 / 18

Table 2. Cross-horizon tests choose a deletion using feature loss at h3 and score it at h6, and vice versa, against uniform deletion. This future-informed diagnostic is not a deployable past-only policy. Ranking alone is insufficient: Gate fails the critical-deletion requirement. Data: D2.

5 Effect sizes and uncertainty




Figure 6. Ordinary-condition deletion effects at h6, shown separately for every training seed and critical memory role. Filled points are feature error; open points are lane or position error. Bars are paired 95 percent intervals. The dashed line is the 10 percent mean-effect floor, not a requirement that the entire interval exceed 10 percent. Data: D2.

Selected contrast	Delete critical feature MSE	Delete nuisance feature MSE	Difference and 95 percent CI
Gate cue seed 43	0.0987	0.0923	0.0065 [-0.0026, 0.0152]
Motion start seed 17	0.5005	0.1163	0.3842 [0.3529, 0.4162]
Motion end seed 17	0.1636	0.1163	0.0473 [0.0430, 0.0519]

Table 3. Illustrative numeric contrasts at h6. Within each row, only the deletion differs. Losses across Gate and Motion are not calibrated to the same task difficulty. All seeds and both Motion roles are shown in Figure 6.

Motion. Keeping the start observation reduced feature error by 76.3 to 77.8 percent across seeds; keeping the end observation reduced it by 28.3 to 30.5 percent. Position-error contrasts agreed. Both observations therefore carry complementary useful evidence, and all tested Motion deletion contrasts passed.

Gate. Seed 43 failed both ordinary deletion checks. At h3 the lane-error interval crossed zero; at h6 feature benefit was only 6.5 percent and lane-error benefit 6.3 percent, with both intervals crossing zero. A seed-average result would hide this instability.

Why Motion can pass this test while failing prediction acceptance. Reliable deletion cost asks which forgetting choice is worse. Absolute prediction quality asks whether the forecast is sufficiently good. The first can be reliable while the second remains inadequate; neither result cancels the other.

6 A useful signal does not prove a better policy




Figure 7. Descriptive one-decision baseline costs in the ordinary Motion pools at h6. Bars average the same three seeds; dots show their separate means. The future-feature oracle chooses using unavailable future information and is only an optimistic reference. This is not a streaming-policy benchmark. Data: D2.

Deletion rule	Feature MSE	Position MSE
FIFO	0.503474	0.025186
Uniform	0.261175	0.014506
Reject newest	0.116061	0.007548
Future oracle	0.115305	0.007338

The oracle feature MSE is only 0.65 percent lower than rejecting the newest frame: 0.115305 versus 0.116061. This small headroom matters. These constructed pools show which evidence is useful, but a simple rule already finds most of that value; they do not yet demonstrate a need for a learned selector.

What the experiments have achieved

We have a working visual-feature prediction pipeline, paired causal input comparisons, auditable model checkpoints, and a fast same-capacity deletion evaluation. Motion supplies a reproducible signal about relative memory value. Gate supplies a concrete counterexample to assuming that feature-level utility is always stable across training seeds.

Limits that should shape the next experiment

Adaptive development data. The same development trajectories informed predictor repairs. No untouched-data confirmation has been run.

Privileged pools. Candidate times were constructed using known task evidence. This does not show that a policy can discover them from past inputs alone.

Single deletion. Every fork resets to its parent. Continuous irreversible forgetting, accumulated errors and long-term redundancy remain untested.

Uncertain learning headroom. A learned policy must beat strong past-only rules in more varied memory states, not merely beat random deletion in an easy diagnostic pool.

7 Evidence summary and research decision

Research claim	Gate	Motion
Relevant evidence exists in frozen features	Supported in tested splits	Supported in tested splits
History improves prediction robustly under all acceptance checks	Not fully supported	Not fully supported
Same-capacity deletion cost is reliable in ordinary conditions	Not supported for every seed	Supported in all tested seeds and roles
A learned retention policy beats strong baselines	Not tested	Not tested
Untouched-data independent confirmation	Not run	Not run

Evidence and reproducibility

D1 is the last complete six-model predictor experiment, with 720 epoch records and 69120 evaluation scalar records. A separate audit checked the raw axes, finite values and all 64 fixed-reference comparisons. D2 is the subsequent equal-capacity deletion assay: 55296 fork-horizon records and 180 independently recomputed scalar comparisons. The 128 trajectory pairs per task and condition, rather than these raw row totals, are the statistical units. Transferred compact evidence matched its native hashes.

D2 performed no new fitting, feature encoding or GPU allocation; CPU inference took 163.7 seconds. Total settled GPU use across the proposal validation and repair attempts was 12723 seconds, or 3 h 32 min 03 s, within the approved 8 h cap. Incomplete later repair trials are excluded from the performance results above. No retention policy was trained.

Sources

[1] Assran et al. Self-Supervised Learning from Images with a Joint-Embedding Predictive Architecture. CVPR, 2023. https://arxiv.org/abs/2301.08243

[2] Lee et al. Set Transformer A Framework for Attention-based Permutation-Invariant Neural Networks. ICML, 2019. https://proceedings.mlr.press/v97/lee19d.html

[3] Zeng et al. Are Transformers Effective for Time Series Forecasting. AAAI, 2023. https://arxiv.org/abs/2205.13504

D1 Frozen predictor experiment 7574, evaluation 7575 and independent audit 7576. Archived evaluation outcome, fixed-reference intervals and final native verification in phase1_predictor_repair_v2.

D2 Equal-capacity deletion assay 7590. Archived summary, baseline estimates, independent audit and pair-level scalar contrasts in phase1_deletion_assay. The assay protocol was fixed before its outcomes; the model and data were already development-selected.

Conclusion

Phase One has established useful evidence for the proposal, but it has not established a complete two-task pass. Both tasks retain relevant information in frozen visual features, and history improves prediction in important settings. Motion also provides reliable deletion-cost contrasts, supporting a narrowly scoped learnability pilot. Gate remains unstable, Motion prediction under long occlusion remains insufficient, and neither an online retention advantage nor fresh independent confirmation has been shown. The defensible achievement is a tested mechanism and a clear next experiment, not a completed memory-retention method.