Phase One Study of Bounded Visual Memory

Research goals Experimental design Individual tests Findings and next tasks

I-JEPA prototype | 16 October 2026

1 Research objective

Overall objective. When a model cannot remember everything it has seen, which observations should it keep? Our proposal tests whether the extra prediction error caused by deleting a memory can teach a small retention policy to make better choices.

Objective of this stage. Establish the prerequisites before learning a policy: useful evidence must survive visual encoding, the predictor must respond to that evidence, and equal-sized memory alternatives must produce informative differences in prediction cost. The original Phase One covers the first two questions; the deletion assay is a transition toward the later retention stage.




Figure 1. Read left to right: earlier evidence, recent view, future outcome. Paired scenes A and B have the same recent view but different futures. The earlier Gate cue or Motion positions distinguish them. These are explanatory drawings, not sampled test frames or model predictions.

Question	Why it matters
Can the features preserve the clue?	A policy cannot keep useful information if encoding has already removed it.
Can prediction use that clue?	Deletion cost is meaningful only when the predictor responds to what remains.
Does the cost distinguish forgetting choices?	This is the proposed supervision signal for a future retention scorer.

The intended contribution is a better bounded-memory decision. A perfect general dynamics model is not the research objective. Current results concern I-JEPA and these controlled tasks; no learned retention-policy advantage, V-JEPA transfer or fresh confirmation has been demonstrated.

2 Experimental design

2.1 Data and preprocessing

We use generated, controlled visual trajectories rather than a public video benchmark. Each matched pair contains two episodes with identical recent images and action sequences, but different earlier evidence and later outcomes. Gate tests a transient cue; Motion tests pre-occlusion movement. Historical split names contain the word test, but these data are now development evidence because predictor repairs were informed by them.

Split per task	Matched pairs	Episodes per task	Purpose
Training	512	1024	Fit predictors and train-only preprocessing
Validation	96	192	Select readout settings and predictor checkpoint
Ordinary test condition	128	256	Conditions similar to training
Long gap or occlusion	128	256	Stress longer missing-information intervals
Distractor shift	128	256	Stress changed visual distractions
Total per task	992	1984	Two tasks give 3968 episodes in total

Processing. Rendered 96 x 96 RGB frames pass through the pinned official I-JEPA image processor without a center crop. The frozen encoder is spatially pooled into four cells, producing a 5120-dimensional vector per frame. Mean and scale are fitted using training frames only; a train-only 128-dimensional basis reduces predictor input size. Prediction error is still scored in the complete normalized 5120-dimensional output.

2.2 Understanding the three test conditions

These are three versions of each task, not three different tasks. Both Gate and Motion are evaluated in all three. Each condition has its own 128 matched pairs. Within a pair, recent images and actions match, while earlier evidence distinguishes the two possible futures.

Ordinary means a familiar delay and familiar scenery

Motion example: the model sees two observations of the moving object, then a shutter hides it. It must use that earlier motion and known actions to predict a later position. Ordinary already includes occlusion; it does not mean that the object stays visible. The last evidence frame is followed by 5 to 10 intervening steps before the 4-frame recent window begins. These settings match the training distribution.


Gate example: a brief geometric cue appears and disappears. Later, the model must combine the old cue with the action to predict which lane the object takes. The question is whether history helps under familiar conditions.

Long gap means the same evidence must help after a longer delay

The intervening gap increases to 20 to 32 steps. Gate must use a cue that disappeared longer ago; Motion must predict after a longer period of hidden movement. The task rules, recent-window length and evaluated future horizons remain the same. This tests delayed use of evidence, rather than a different prediction target.

Distractor shift means changed irrelevant scenery

The ordinary gap and task rules are retained. Only the irrelevant decorative objects outside the arena change: 3 circles become 7 rectangles and the color palette changes. This does not change the movement rule or replace the correct cue. It tests whether unfamiliar visual distractions interfere with using the relevant evidence.



Timing guide. Read each row from left to right. The gap measures how long ago the clue occurred before the recent window. The prediction horizon measures how far ahead to forecast after that window. Distractor shift shares ordinary timing; its difference is the irrelevant scenery described above.

Why the same condition can be easy for one test and hard for another

T1 directly reads the stored features of the earlier evidence frames. Waiting longer afterward does not erase those cached features, so long gap need not reduce T1 accuracy. T2 and T4 instead require a future forecast using the evidence, actions and elapsed time. They can fail even when T1 is perfect. Condition names describe the generated episodes; they do not guarantee that every test becomes harder by the same amount.

2.3 Tests and the questions they answer

Test	Actual comparison	What it can establish
T1 Evidence readout	Historical feature versus recent-only feature readout	Did the frozen features retain the cue or movement direction?
T2 History benefit	Two key memories versus recent observations alone	Does supplying historical evidence improve future prediction?
T3 History replacement	Correct history versus the paired episode history	Does changing historical content change the predicted future?
T4 Fixed reference	Current candidate versus an earlier frozen predictor	Did repair improve prediction against a stable reference?
T5 Critical deletion	Delete a key frame versus delete nuisance content; both retain 2	Does deletion cost recognize useful evidence at equal capacity?
T6 Cross horizon	Choose a deletion at 3 steps and score at 6, then reverse	Does the usefulness of the deletion choice transfer across time?
T7 Policy advantage	A learned past-only scorer versus strong streaming baselines	Can a deployable policy exploit the signal? Not run.
T8 Fresh confirmation	Locked procedure evaluated with untouched data	Does the result repeat beyond inspected development data? Not run.

Legacy labels: Original prediction checks combine T1, T2 and T3. Additional fixed-reference checks are T4. The previously combined last row contains two different future studies, T7 and T8. They have no completed result.

2.4 Structure and recorded data




Figure 2. Images become stored features. A small predictor reads recent context, legal historical entries, timestamps and action continuations, then predicts future features. Simulator state is used by diagnostics and scoring, not supplied as predictor input. I-JEPA is frozen; no retention selector is present.

Block	What it does	What is recorded
Controlled data	Create paired Gate and Motion episodes	RGB, actions, timestamps, pair and split IDs, evidence times; state and labels reserved for diagnostics
Frozen encoder and cache	Encode each observed frame once	Feature arrays, shape, precision, checkpoint and processor identity, per-file hashes
Train-only preprocessing	Normalize features and fit the input basis	Training episode membership, mean, scale, basis and their hashes
Recent reference and candidate	Predict features with different history conditions	Epoch and step, training loss, validation error, best checkpoint, optimizer and RNG evidence
Prediction evaluation	Compare forecasts with targets and paired alternatives	Feature MSE, task error, pair margin, condition, seed, horizon, memory count and bytes
Deletion evaluation	Fork the same parent into alternative removals	Removed and retained entry IDs, equal-capacity checks, feature and task losses per fork
Statistical audit	Check pairing and recompute contrasts	128-pair aggregates, uncertainty intervals, x/y criterion counts and provenance ledger

Shared settings

The candidate starts with a frozen recent-only forecast and adds a learned correction from centered historical features. It reads every retained entry, weights their content, and uses elapsed time with observed feature differences to transport evidence forward. This is a prediction mechanism, not a trained memory-retention policy; no retrieval or selector chooses the stored entries.

Recent context is 4 frames; the bounded history contains 2 real entries; future horizons are 3 and 6 steps. Full history is an additional information reference, not an equal-capacity competitor. The complete candidate experiment trained seeds 17, 29 and 43 for each task: six models, 120 epochs and 7680 steps each. Checkpoints were selected by the earliest minimum of validation MSE across four balanced conditions and both horizons.

Reading the numbers

MSE means average squared error: lower is better. A positive error reduction means history helped. For prediction tests, 95 percent confidence intervals use 2000 paired bootstrap replicates of 128 base pairs; the deletion assay uses 10000 replicates. Siblings, deletion forks and seed means are not additional independent examples. An uncertainty interval crossing zero leaves the direction unresolved.

3 Results for each test

3.1 T1 Can the features preserve the evidence

Question. Before asking a predictor to use memory, did the visual representation preserve what the task needs?

Comparison. A simple linear readout was fitted on training features, selected on validation, and scored on each test condition. It reads the Gate cue or the two-frame Motion evidence. A recent-only readout is the control. These previously fitted probes are reused; no new fitting was performed for this report.




Figure 3. Taller bars mean the clue is easier to decode. Black bars use historical evidence and gray bars use recent frames only. History reaches 100 percent in all six task-condition combinations; recent-only stays at 50 percent, as expected for the matched pairs. These are classification results, not future-prediction accuracies.

Condition	Gate history / recent	Motion history / recent
Ordinary	100% / 50%	100% / 50%
Long gap	100% / 50%	100% / 50%
Distractor shift	100% / 50%	100% / 50%

Coverage. Gate 3/3 pass; Motion 3/3 pass. Each uses 128 base pairs per condition. The frozen criterion required at least 75 percent accuracy and a Wilson lower bound above 50 percent; the observed historical readout lower bound is 97.1 percent.

Why exactly 50 and 100 percent. The original values are 0.5 and 1.0, not rounded approximations. Paired recent inputs are identical but their labels are opposite: the recent-only classifier gives the same answer to both, getting exactly one right. Historical inputs are explicitly chosen evidence frames, and a supervised linear readout has learned to decode them. It correctly classified all evaluated examples in these controlled conditions. This is an observed ceiling on a deliberately simple diagnostic, not guaranteed perfection on new data.

Meaning. The relevant discrete evidence survives this encoding and pooling pipeline, so there is something useful for memory to preserve. The Motion readout distinguishes movement direction; it does not establish exact speed recovery, future position accuracy or success after long occlusion. The splits were held out from probe fitting but have since been inspected during development.

3.2 T2 Does historical evidence improve prediction

Question. Does the same predictor forecast better when given important past observations in addition to the identical recent context?

Comparison. Recent-only forecasts are compared with privileged two-memory forecasts. Full history provides an additional reference. A counted history-benefit check requires sufficient improvement and positive uncertainty bounds in both feature error and the task metric: Gate lane error or Motion position MSE. The original rules retain their absolute-gain fallback when the baseline is near zero.




Figure 4. Further right means a bigger reduction in prediction error from two key memories. Squares are 3-step forecasts; circles are 6-step forecasts. Horizontal lines show 95 percent uncertainty. A line crossing zero leaves the direction unresolved. The dashed 10 percent line is the material-effect benchmark. Means average the three seeds within each pair.

Task and condition	Recent only MSE	Full history MSE	Two-memory MSE	Two-memory gain at 6 steps
Gate Ordinary	0.0997	0.0562	0.0776	22.2% [15.2, 28.5]
Gate Long gap	0.0995	0.0960	0.0737	26.0% [20.0, 31.9]
Gate Distractor shift	0.1385	0.1003	0.1196	13.7% [10.3, 17.1]
Motion Ordinary	0.1526	0.0995	0.1161	23.9% [21.7, 26.1]
Motion Long gap	0.1831	0.1879	0.1804	1.5% [-1.5, 4.6]
Motion Distractor shift	0.2908	0.2713	0.2726	6.3% [4.3, 8.3]

Coverage. Gate 23/24 pass; Motion 8/24 pass. The 24 comparisons are 3 conditions x 2 horizons x 4 summaries: three seeds and their mean. These are not 24 independent datasets.

Meaning. Gate shows broad history benefit, with an inconclusive ordinary 6-step task benefit for seed 43. Motion improves substantially in ordinary conditions, but the longer-gap 6-step feature gain is only 1.5 percent with an interval from -1.5 to 4.6 percent. The harder conditions limit the generalization claim.

3.3 T3 Does changing history change the forecast

Question. Is the model using the content of the old observation, or merely responding to the presence of extra memory entries?

Comparison. Keep recent images and actions fixed, but replace relevant memory features with those from the paired episode. For Gate, swap the cue associated with the other outcome; for Motion, swap the evidence for the other movement. Measure how much the predicted feature moves toward the paired alternative future.




Figure 5. Points further right show a larger shift toward the other episode future after swapping history. Lines show paired 95 percent intervals. Positive shifts in both tasks show that historical content affects prediction. The score is a normalized feature-distance margin change, not a percentage accuracy. The plot shows 6-step, seed-averaged results.

Task and condition	Shift at 3 steps	Shift at 6 steps and 95 percent CI
Gate Ordinary	0.681	0.693 [0.546, 0.834]
Gate Long gap	0.703	0.728 [0.586, 0.868]
Gate Distractor shift	0.612	0.638 [0.510, 0.768]
Motion Ordinary	0.741	0.740 [0.688, 0.787]
Motion Long gap	0.505	0.466 [0.417, 0.512]
Motion Distractor shift	0.625	0.635 [0.594, 0.678]

Coverage. Gate 24/24 pass; Motion 24/24 pass. The original criterion requires a mean margin shift of at least 0.05 and a positive lower confidence bound. The 24 summaries have the same condition, horizon and seed structure as T2.

Meaning. The predictor responds to which history it receives. This supports historical-content use, even where overall future prediction is weak. It does not establish an intervention on the physical environment, a reliable deletion ranking or a learned retention policy. Those are different questions.

3.4 T4 Does repair improve a fixed predictor reference

Question. Did the current candidate improve against an unchanged earlier reference, rather than simply change its own comparison baseline?

Comparison. There are 24 candidate two-memory versus frozen recent-only comparisons, plus 8 comparisons where both earlier and current predictors receive two memories. The latter target Gate distractor shift and Motion long occlusion. They require a positive paired error reduction; the recent-only comparisons retain the original material-benefit rule.




Figure 6. Shorter bars mean lower prediction error. Gray is the earlier predictor; black is the current candidate, both with the same two key memories. Gate improves in the designated hard condition. Motion becomes worse than this reference under long occlusion. Bars average three seeds; the table gives paired intervals for the difference.

Task and horizon	Reference MSE	Candidate MSE	Reference minus candidate and CI
Gate 3 steps	0.1481	0.1180	0.0301 [0.0239, 0.0370]
Gate 6 steps	0.1576	0.1196	0.0380 [0.0321, 0.0443]
Motion 3 steps	0.1428	0.1659	-0.0231 [-0.0292, -0.0172]
Motion 6 steps	0.1621	0.1804	-0.0183 [-0.0237, -0.0129]

Fixed-reference comparison	Gate	Motion
Candidate with 2 memories versus frozen recent only	24/24 pass	8/24 pass
Both predictors with 2 memories on the hard condition	8/8 pass	0/8 pass
Combined descriptive coverage	32/32 pass	8/32 pass

Meaning. The repair has broad fixed-reference support for Gate. For Motion, ordinary gains coexist with a clear long-occlusion regression against the earlier two-memory predictor. This is a specific limitation of the candidate; it does not imply that Motion evidence is absent from the encoder or that every memory mechanism is ineffective.

3.5 T5 Does deletion cost identify useful memories

Question. At the same storage capacity, does losing critical evidence harm prediction more than losing a nuisance observation?

Comparison. Each parent has three real historical frames. Gate contains the cue and two post-cue nuisance frames; Motion contains start, end and a shutter frame. Remove each candidate in turn, always leaving two entries and the same recent context. Two fixed parent-time variants are averaged within each base pair. No predictor or policy is retrained.




Figure 7. Further right means keeping that memory is more useful at 6 steps in ordinary conditions. Black points measure feature error; white points measure lane or position error. Lines show 95 percent uncertainty. Motion start and end memories help in every seed. Gate seed 43 is near zero and uncertain. The dashed line marks the 10 percent mean-benefit requirement.

Task	Ordinary	Long gap	Distractor shift	Total
Gate	4/6 pass	0/6 pass	2/6 pass	6/18 pass
Motion	12/12 pass	12/12 pass	12/12 pass	36/36 pass

A counted contrast requires at least 10 percent relative benefit from retaining the critical observation, plus a positive paired interval, for both feature and task error. Gate has one critical role; Motion has two, explaining the different denominators. Each contrast uses 128 base pairs, averaging siblings and parent variants first.

Meaning. Motion supplies consistent relative deletion value in the examined conditions. At ordinary h6, preserving start reduces feature error by 76.3 to 77.8 percent and preserving end by 28.3 to 30.5 percent across seeds. Gate provides partial support, with both ordinary exceptions coming from seed 43. Useful deletion value and accurate absolute forecasting are distinct capabilities.

3.6 T6 Does a deletion choice transfer across future times

Question. Is a deletion choice useful beyond the single future time used to choose it?

Comparison. Select the removal with lowest feature error at 3 steps, then score it at 6 steps against uniform-random deletion. Reverse the times and repeat. Each counted comparison requires positive paired uncertainty bounds for both feature and task advantage. This uses future outcomes to select the removal; it is an oracle diagnostic, not a past-only policy.




Figure 8. All points and their uncertainty lines are right of zero in these ordinary-condition examples: the cross-time choice saves feature error compared with random deletion. A label such as 17 3 to 6 means seed 17, choose at step 3, score at step 6. The two tasks use different horizontal scales. Full condition coverage is below.

Condition	Gate coverage	Motion coverage	Mean choice agreement Gate / Motion
Ordinary	6/6 pass	6/6 pass	91.2% / 96.5%
Long gap	6/6 pass	6/6 pass	91.9% / 90.1%
Distractor shift	6/6 pass	6/6 pass	94.3% / 91.3%
Total	18/18 pass	18/18 pass	Agreement is descriptive, not a readiness criterion

The 18 comparisons per task are 3 conditions x 3 seeds x 2 selection directions. Choice agreement describes how often the best removal agrees across horizons, averaged over the tested seeds and directions; near ties are averaged, not resolved using evidence labels.

Meaning. The deletion signal is not confined to one scoring time. Gate has strong cross-horizon coverage despite weaker critical-versus-nuisance contrasts in T5: the two tests ask different questions. This transfer does not prove usefulness beyond the tested 3- and 6-step futures, or that a scorer can choose well without seeing the future.

3.7 T7 Can a learned policy beat strong baselines

Status. Not run: no retention scorer has been trained and no learned irreversible streaming policy has been evaluated.

The intended study would train a scorer on offline deletion costs, restrict its inputs to past and present information, and compare it with FIFO, reservoir sampling and other strong baselines under the same predictor and memory budget. Its result would establish deployable policy value rather than privileged evidence value.

Existing descriptive Motion comparison at ordinary h6	Feature MSE	Position MSE
FIFO	0.503474	0.025186
Uniform	0.261175	0.014506
Reject newest	0.116061	0.007548
Future oracle	0.115305	0.007338

The available one-deletion baseline data are preparation for T7, not a T7 result. Reject-newest reaches feature MSE 0.116061, close to the future-feature oracle at 0.115305, only 0.65 percent lower. A learned advantage is therefore not established; more varied memory states are needed to test whether learning offers useful headroom.

3.8 T8 Does the finding repeat on untouched data

Status. Not run: fresh independent confirmation data have not been opened or generated.

The registered confirmation plan requires fresh data, new train-only preprocessing, reference and candidate models for both tasks and all three seeds, and locked model selection before test outcomes are opened. Existing development weights evaluated on another test set would not satisfy that plan. The complete 12-model confirmation and its compute guard must be frozen before execution.




Figure 9. Planned studies, not completed experiments. The top row asks whether a past-only learned scorer beats streaming baselines. The bottom row asks whether locked findings repeat with fresh data and newly fitted models. These answer two distinct questions; neither is included in the reported pass counts.

4 Overall results analysis and next tasks

Evidence category	Gate	Motion
T1 Historical evidence readable	3/3 pass	3/3 pass
T2 History improves prediction	23/24 pass	8/24 pass
T3 Forecast responds to historical content	24/24 pass	24/24 pass
T4 Fixed-reference coverage	32/32 pass	8/32 pass
T5 Critical deletion value	6/18 pass; ordinary 4/6	36/36 pass; ordinary 12/12
T6 Cross-horizon deletion value	18/18 pass	18/18 pass
T7 Learned-policy advantage	Not run	Not run
T8 Fresh confirmation	Not run	Not run

4.1 What has been achieved

The pipeline preserves the relevant discrete evidence, and both predictors respond to its content. Gate has broad prediction coverage. Motion provides consistent deletion value and cross-horizon transfer, even though its long-occlusion forecast quality remains limited. This is meaningful mechanism evidence for a bounded-memory project, with task- and condition-specific limits.

Counts are not votes of equal weight or probabilities of success. The legacy original total is T1 + T2 + T3: Gate 50/51 and Motion 35/51. It excludes other guards. In particular, Gate full-history predictions at long-gap h6 triggered mean-level degradation warnings for seeds 17 and 29, with intervals spanning no change. The earlier strict all-checks acceptance record remains unmet; this descriptive summary does not change it.




Figure 10. A useful deletion signal does not automatically leave room for a learned policy. In these constructed Motion pools, rejecting the newest entry is already close to the future-informed oracle. Bars show mean feature error; dots show the three training seeds. This is a one-deletion diagnostic, not a streaming-policy evaluation.

4.2 Next tasks and unresolved questions

Priority	Bounded next task	What would be learned
1	Motion pilot with varied memory states and strong simple rules	Can a past-only scorer exploit deletion costs beyond an easy reject-newest heuristic?
2	Targeted Gate seed and full-history diagnostics	Which conditions make its useful-history signal unstable?
3	Freeze a separate confirmation and resource plan before fresh data	Do the selected claims repeat without further adaptation?
Scope	Treat any V-JEPA study as a separate backbone validation	Does the mechanism transfer beyond this I-JEPA implementation?

No further experiment is initiated by this report. Existing predictors and caches were reused for the deletion assay, adding zero GPU time. Settled proposal-validation and repair GPU use is 12723 seconds, or 3 h 32 min 03 s, within the approved 8 h cap. Learned retention, streaming policy success and new-data confirmation remain future evidence.

4.3 Sources and verification

[1] Assran et al. Self-Supervised Learning from Images with a Joint-Embedding Predictive Architecture. CVPR 2023. https://arxiv.org/abs/2301.08243

[2] Lee et al. Set Transformer. ICML 2019. https://proceedings.mlr.press/v97/lee19d.html

[3] Zeng et al. Are Transformers Effective for Time Series Forecasting. AAAI 2023. https://arxiv.org/abs/2205.13504

Evidence: complete predictor run 7574, evaluation 7575 and independent audit 7576; verified inherited feature probes; deletion assay 7590 and its independent 180-comparison audit. The predictor evaluation contains 69120 scalar rows and deletion 55296 rows, not that many independent episodes. Compact evidence hashes were verified.

Conclusion

Phase One has produced substantial but uneven evidence. Historical information survives encoding, the predictors use it, and Motion deletion costs consistently distinguish useful evidence in the tested pools. Gate deletion stability and Motion hard-condition prediction remain limitations. These findings support a scoped next-stage feasibility study, while leaving learned-policy advantage, V-JEPA transfer and independent confirmation unproven.