

```
In [1]: import torch
import torch.nn as nn
import torch.nn.functional as F
import torchvision
import numpy as np
import pandas as pd
from matplotlib import pyplot as plt
```

```
In [2]: # Detect if we have a GPU available
device = torch.device("cuda:0" if torch.cuda.is_available() else "cpu")
if torch.cuda.is_available():
    print("Using the GPU!")
else:
    print("WARNING: Could not find GPU! Using CPU only")
```

Using the GPU!

```
In [3]: x_train_images = np.load("data/x_train_images.npy")
x_test_images = np.load("data/x_test_images.npy")

x_train_images_100 = np.load("data/x_train_images_100.npy")
x_test_images_100 = np.load("data/x_test_images_100.npy")

x_train_images_50 = np.load("data/x_train_images_50.npy")
x_test_images_50 = np.load("data/x_test_images_50.npy")

y_train = np.load("data/y_train.npy")
y_test = np.load("data/y_test.npy")
print("The sample size of training set is: ", x_train_images.shape[0])
print("The sample size of testing set is: ", x_test_images.shape[0])

print(y_train.shape)
print(y_test.shape)
```

```
The sample size of training set is: 3556
The sample size of testing set is: 889
(3556, 1)
(889, 1)
```

```

In [4]: # bridge numpy to torch
x_train_images_torch = torch.as_tensor(x_train_images).float()
x_test_images_torch = torch.as_tensor(x_test_images).float()

x_train_images_torch_100 = torch.as_tensor(x_train_images_100).float()
x_test_images_torch_100 = torch.as_tensor(x_test_images_100).float()

x_train_images_torch_50 = torch.as_tensor(x_train_images_50).float()
x_test_images_torch_50 = torch.as_tensor(x_test_images_50).float()

y_train_torch = torch.as_tensor(y_train[:,0])
y_test_torch = torch.as_tensor(y_test[:,0])
n_train = x_train_images.shape[0]
n_test = x_test_images.shape[0]
# inputs: x_train_nhts, x_train_images, x_test_nhts, x_test_images, y_train
K = len(np.unique(y_train))
#
pd.value_counts(y_train[:,0])/y_train.shape[0]

```

```

Out[4]: 2    0.336333
        1    0.325928
        3    0.251969
        0    0.085771
dtype: float64

```

```

In [5]: ##### Type 2: CNN with images.
# To-Do: Use GPU...
class CNN(nn.Module):
    def __init__(self):
        super(CNN, self).__init__()
        # To-Do: need to have more channels for higher accuracy.
        self.conv1 = nn.Conv2d(in_channels=4, out_channels=5, kernel_size=
        self.conv2 = nn.Conv2d(in_channels=5, out_channels=10, kernel_size=
        # Question: Why is this 48*48 correct? bc 97//2 = 48
        self.fc1 = nn.Linear(in_features=10 * 48 * 48, out_features=80)

        self.fc2 = nn.Linear(in_features=10 * 23 * 23, out_features=80)

        self.fc3 = nn.Linear(in_features=10 * 11 * 11, out_features=80)
        self.fcFinal = nn.Linear(in_features=80*3, out_features=K)
        self.relu = F.relu
        self.pool = F.max_pool2d
        self.softmax = nn.Softmax(dim=1)
    def forward(self, x1, x2, x3):
        out = self.relu(self.conv1(x1))
        out = self.pool(out, 2)
        out = self.relu(self.conv2(out))
        out = self.pool(out, 2)
        #print(out.shape, "out1")

```

```

out = out.reshape(out.size(0), -1)
out = self.relu(self.fc1(out))

out2 = self.relu(self.conv1(x2))
out2 = self.pool(out2, 2)
out2 = self.relu(self.conv2(out2))
out2 = self.pool(out2, 2)
#print(out2.shape, "out2")
out2 = out2.reshape(out2.size(0), -1)
out2 = self.relu(self.fc2(out2))

out3 = self.relu(self.conv1(x3))
out3 = self.pool(out3, 2)
out3 = self.relu(self.conv2(out3))
out3 = self.pool(out3, 2)
#print(out3.shape, "out3")
out3 = out3.reshape(out3.size(0), -1)
out3 = self.relu(self.fc3(out3))

#print(torch.cat((torch.cat((out,out2),1),out3),1).shape)
final_out = self.fcFinal(torch.cat((torch.cat((out,out2),1),out3)
#print("hello")
final_out = self.softmax(final_out)
return final_out

```

```

In [6]: # normalize the data
x_train_images_norm_torch = x_train_images_torch/255.0
x_test_images_norm_torch = x_test_images_torch/255.0

x_train_images_norm_torch_100 = x_train_images_torch_100/255.0
x_test_images_norm_torch_100 = x_test_images_torch_100/255.0

x_train_images_norm_torch_50 = x_train_images_torch_50/255.0
x_test_images_norm_torch_50 = x_test_images_torch_50/255.0
#
cnn_net = CNN().float().to(device)
optim = torch.optim.Adam(cnn_net.parameters(), lr=0.001)
criterion = nn.CrossEntropyLoss()
#
n_epochs = 150 # To-Do: need more epochs.
batch_size = 200

```

```

In [8]: # training
train_losses = []
test_losses = []
train_accuracies = []
test_accuracies = []
for n_epoch in range(n_epochs):
    # create permutation for batch training

```

```

# To-Do: add permutation for SGD...But it is slow.
# permutation = torch.randperm(x_train_images_norm_torch.size()[0])
for i in range(0, x_train_images_norm_torch.size()[0], batch_size):
    print(n_epoch, i)
    # clear gradients first (for each iteration!)
    optim.zero_grad()
    # forward pass
    batch_x, batch_y = x_train_images_norm_torch[i:i+batch_size, :, :]

    batch_x_100 = x_train_images_norm_torch_100[i:i+batch_size, :, :]
    batch_x_50 = x_train_images_norm_torch_50[i:i+batch_size, :, :]

    batch_y_pred_train = cnn_net(batch_x, batch_x_100, batch_x_50)
    # loss
    loss = criterion(batch_y_pred_train.squeeze(), batch_y)
    # compute gradients
    loss.backward()
    # one step optim
    optim.step()

# eval training accuracy
with torch.no_grad():
    y_pred_train = cnn_net(x_train_images_norm_torch.to(device), x_train_images_norm_torch_100.to(device), x_train_images_norm_torch_50.to(device))
    loss_train = criterion(y_pred_train.squeeze(), y_train_torch.to(device))
    train_losses.append(loss_train)

    _, predict_train = torch.max(y_pred_train, axis = 1)
    accuracy_train = (predict_train == y_train_torch.to(device)).sum()
    train_accuracies.append(accuracy_train)
    # evaluate testing sets step-wise
    cnn_net.eval()
    y_pred_test = cnn_net(x_test_images_norm_torch.to(device), x_test_images_norm_torch_100.to(device), x_test_images_norm_torch_50.to(device))

    loss_test = criterion(y_pred_test.squeeze().to(device), y_test_torch.to(device))
    test_losses.append(loss_test)
    _, predict_test = torch.max(y_pred_test.to(device), axis = 1)
    accuracy_test = (predict_test == y_test_torch.to(device)).sum()
    test_accuracies.append(accuracy_test)
    # print info
    if n_epoch % 1 == 0:
        print('Epoch {}: train loss: {}; test loss: {}'.format(n_epoch, loss_train, loss_test))
        print('Epoch {}: train accuracy: {}; test accuracy: {}'.format(n_epoch, accuracy_train, accuracy_test))

# notes:
# CPU training: about 30 mins, with SIMPLEST CNN architecture, 20 epoches
# training accuracy: 60%; testing accuracy: 60%.

```

```

0 0
n 200

```

```

0 200
0 400
0 600
0 800
0 1000
0 1200
0 1400
0 1600
0 1800
0 2000
0 2200
0 2400
0 2600
0 2800
0 3000
0 3200
0 3400

```

```

Epoch 0: train loss: 1.236401081085205; test loss: 1.2213208675384521
Epoch 1: train loss: 1.1533440000000001; test loss: 1.1743250

```

```


In [9]: plt.plot(train_losses, label = "train loss")
plt.plot(test_losses, label = "test loss")
plt.legend()

```

```


Out[9]: <matplotlib.legend.Legend at 0x7f81280d9438>

```



```
In [10]: plt.plot(train_accuracies, label = "train accuracy")  
plt.plot(test_accuracies, label = "test accuracy")  
plt.legend()
```

Out[10]: <matplotlib.legend.Legend at 0x7f8128056320>



```
In [12]: torch.save(cnn_net.state_dict(), "data/cnn_gaussian_2conv")
```

```
In [ ]:
```