



Budgetary quote - Wheat Straw Line

NEMO Feed LLC

50726 State Highway 15
Baring, MO 63531
United States

Alvin Burkholder

alvin@nemofeed.com
660-341-0674

Reference: 20260428-101712645

Quote created: April 28, 2026

Quote expires: July 27, 2026

Quote created by: Jason Shipley

jason@usemce.com

+16202009109

Comments from Jason Shipley

We are pleased to provide the selected components and equipment based on the following application information:

Location: Baring, MO

Feedstock: Wheat Straw Bales

Infeed rate: 14 TPH

Two Tandem lines into shaker, loadout, and bins

Products & Services

Item & Description	Quantity	Unit Price	Total
60" x 72" Bale Shredder	2	\$69,950.00	\$139,900.00
60" x 72" Bale Shredder			
- per drawing 108100001			
- Bale opening 66" x 72" opening			
- with 4 large Lexan impact resistant viewing windows			
- with Structural Stand			
- 2 x 20,000 lumen LED lights with folding housing			
- with 5 high speed counter rotating star drive bale shredding shafts			
- with heavy weight counter impact curtain to prevent inert debris projectiles			
- with 2 HD Bearing Take Up assemblies			
- with chain drive infeed WR78 Chain 2.609 P. W/ Attach. on cotter side, R.H.			
- 5 HP motor and gear reduction for chain drag			
- 10 HP motor and gear reduction drive for shredder wall			
- Overall Dim: 95" W x 293" L x 154" H			
Est Ductwork for shredder	2	\$13,995.00	\$27,990.00
Estimated ductwork - final sizing TBD upon site plan layout			
21" dia			
14 ga			
Estimate consists of 50' of straight duct and four (4) 90° elbows			

Item & Description	Quantity	Unit Price	Total
XF-45 Fan	2	\$21,995.00	\$43,990.00
XF-45 fan			
- Arrangement #9F heavy-gauge steel base with continuous welds.			
- Heavy-duty pillow block bearings.			
- Turned, ground, and straightened shaft.			
- Dynamically and statically balanced rotor with tapered hub and bushing.			
- Open Vane, straight bladed, heavy-duty rotor.			
- Rotor to be fabricated of AR 235 Plate Steel.			
- Heavy duty housing with continuous welds.			
- Housing to be fabricated of carbon steel.			
- Motor slide base with integral drive tensioning mechanism.			
- 75 HP, 1800 RPM, class TEFC, 230-460V/3/60 NEMA Premium efficient motor.			
- NOTE: TEFC motor with no environmental marking/T Code.			
- V-belt drive with 1.5 to 2.0 service factor.			
- Totally enclosed sanitary belt and shaft guard.			
- Factory test run prior to shipment.			
- Inlet to 26" Dia.			
- Flanged rectangular outlet.			
- Louvered damper available of \$3,950			
- Vibration isolation sleeve with clamps for fan inlet. Available for \$399/ea			
- Bolt-on inspection door.			
- Housing to have a drain port in the bottom.			
- Product contact zones unpainted, all other surfaces painted Basalt Gray; guards painted safety orange. Please specify otherwise.			

Item & Description	Quantity	Unit Price	Total
HE-47 Cyclone New HE-47 Cyclone, 10 ga, mild steel rated up to 12,600 CFM High Efficiency Centrifugal Collector Model HE-47 • CW inlet rotation • 10 gauge mild steel construction • Exterior welds continuous where possible and cleaned free of weld slag and splatter • 47" Diameter flanged collector housing with riser tube • Flanged 77.25° cone, welded to expansion chamber • Product discharge is flanged 10" round • Flanged rectangular inlet, 33.0" x 13.75" • Draw-thru fitting mounted on riser tube flange, 21.25" x 21.25" exhaust size • Standard mount pads • 8" Dia. bolted inspection port, F/G white sponge gasket • Housing flange gasketing to be Food Grade silicone caulking • Airstream Temperature: 70°F • painted RAL #7012 Basalt Grey • If stand with 40" clearance is desired, please add \$3,500 • If insulated with 1" insulation and aluminum cladding please add \$5,995 • If 304 Stainless Construction, please add \$9,000 http://midwestcustomsolutions.com/suppequip/cyclone/he47.html	2	\$15,950.00	\$31,900.00

Item & Description	Quantity	Unit Price	Total
Airlock EMVDL-RVEX-HT45 Series EMVDL-RVEX-HT45 Series. Certified Rotary Valve - Differential pressures up to 40* W.G. Certified: ATEX EN 15089 CE 0588 EX II ID/ C T4 EX D Certificate #: FSA 15 ATEX 1661/1662 X. NFPA 69 Compliant: Flex tip design certified to prevent flame passage NFPA 69 12.2.4.3.6 Product Code: 58000 Explosion & Flame Proof up to 1.7 bar / 24.65 psi (polyurethane flex tips) Body & Covers: Cast iron with safety red finish or nickel plated Shaft Seals: Feit ring and simmering Bearings: Oil bronze slide Drive Unit: Direct with coupling and gear motor. Choice of IP 65 and Haz-Loc IP65 Gearmotors IP 65 Gearmotor rated for outdoor installations Haz-Loc Gearmotor rated for hazardous locations (Class 1, Div. 2, Group A, 8, C & D, Class 2, Div. 2, Group F & G) and rated IP 65 for outdoor installations. Rotor / Rotor blade Combination (8 Vanes): Mild steel rotor with polyurethane (flex tip) EMVDL-RVEX-HT450 - 30 RPM HP: 2.00 Capacity: 1.23 FT* (35 Liters) per rotation	2	\$22,998.00	\$45,996.00
Place holder for separation system Place holder for separation system	2	\$100,000.00	\$200,000.00

Item & Description	Quantity	Unit Price	Total
Belt Conveyor from Separation System to Hammer Mill Mild Steel Construction - 40' Centerline of Pulleys, 8" x 11.5# Structural Channel Frame - Inclined Operation (10 Degrees) - 30" Wide, Smooth Rubber Belt with Recessed Mechanical Splice - 20" Diameter Head Pulley with 1/2" Vulcanized Herringbone Lagging - 18" Diameter Spiral Winged Tail Pulley - Martin Engineering QC #1 Primary Belt Scraper with Urethane Blade and Twist Tensioner - Dodge Regreasable Pillow Block Bearings - Protected Screw Take-Up - CEMA C 5", Sealed 35 Degree Troughing Idlers on 4' Centers and CEMA C 5" Flat, Sealed Return Idlers on 10' Centers - 10' of Skirtboards with Adjustable Rubber Skirting and 1/4" A/R Liners - Infeed Area with with (4) Impact Idlers on 12" Centers - Smooth Galvanized Top Covers - 1/4" A/R 400 Lined Discharge - Painted Industrial Gray Polyurethane (619-0-0079/619-0-0040) - 7.5 HP TEFC 230/460V/60HZ 3 Phase Motor - Dodge TA3203, Class II Shaft Mount Reducer with V-Belt Drive, Motor Mount, and Guard for 300 FPM Belt Speed - Zero Speed Switch (NEMA 4) - Conveyor Components Co. RS-1 Emergency Switch with - Less: Wiring, Controls and Supports	2	\$48,995.00	\$97,990.00
XM-48" MC Magnet Adapter · Manual Clean 60 degree magnet chute · Stainless steel front, stainless steel hinged magnet plate, and two manual clamps for magnet door · SF 300 48" plate Magnet · One micro safety switch to indicate when door is open	2	\$10,600.00	\$21,200.00

Item & Description	Quantity	Unit Price	Total
Fully Refurbished - Bliss Hammer Mill Fully Refurbished - Bliss hammer mill Model 3848-TF HP range: 250 - 400 HP Grinding Chamber: 38" diameter x 48" wide approx 4800 sq in screen area. Hammermill Ser No. 6657. Unit inspection/ refurbish will include the following: - hammers, rods, spacers fully inspected - replaced as needed - bearings and seals - fully inspected - replaced as needed - fully sandblasted, primed, and painted Bliss tan - electrical components inspected but not guaranteed - motor quoted below	2	\$55,000.00	\$110,000.00
Teco Westinghouse 300 HP motor Teco Westinghouse 300 HP motor Motor Type MAX-E1 NEMA Premium Efficiency Severe Duty TEFC/Inverter Duty Frame 449T Output Power 300 HP RPM 1800 RPM Voltage 575V 3-Phase 60Hz Enclosure Totally Enclosed Fan Cooled (TEFC) IP54 for 280 Frames and below IP55 for 280TS Frames and above Full Load Efficiency 96.2 % Full Load Power Factor 88.0 % Full Load Amps 266 Amps @ 575V Shipping Weight 2855 lbs	2	\$16,649.00	\$33,298.00
Drop Down Air Pan Drop Down Air Pan - with structure - with air pickup fitting	2	\$9,204.00	\$18,408.00

Item & Description	Quantity	Unit Price	Total
XF-29 Fan	2	\$14,995.00	\$29,990.00
XF-29			
- Arrangement #9F heavy-gauge steel base with continuous welds.			
- Heavy-duty pillow block bearings.			
- Turned, ground, and straightened shaft.			
- Dynamically and statically balanced rotor with tapered hub and bushing.			
- Narrow width high static, heavy-duty rotor.			
- Rotor to be fabricated of AR 235 Plate Steel.			
- Heavy duty housing with continuous welds.			
- Housing to be fabricated of carbon steel.			
- Motor slide base with integral drive tensioning mechanism.			
- 40 HP, 1800 RPM, class TEFC, 230-460V/3/60 NEMA Premium efficient motor.			
- NOTE: TEFC motor with no environmental marking/T Code.			
- V-belt drive with 1.5 to 2.0 service factor.			
- Totally enclosed sanitary belt and shaft guard.			
- Factory test run prior to shipment.			
- Inlet to 17" OD.			
- Flanged rectangular outlet.			
- Louvered damper available			
- Vibration isolation sleeve with clamps for fan inlet.			
- Bolt-on inspection door.			
- Housing to have a drain port in the bottom.			
- Product contact zones unpainted, all other surfaces painted Basalt Gray; guards painted safety orange. Please specify otherwise.			

Item & Description	Quantity	Unit Price	Total
HE-39 Cyclone New HE 39 Cyclone, 10 ga, mild steel rated up to 8,800 CFM High Efficiency Centrifugal Collector Model HE-39 • CW inlet rotation • 10 gauge mild steel construction • Exterior welds continuous where possible and cleaned free of weld slag and splatter • 39" Diameter flanged collector housing with riser tube • Flanged 77.25° cone, welded to expansion chamber • Product discharge is flanged 10" round • Flanged rectangular inlet, 27.0" x 11.75" • Draw-thru fitting mounted on riser tube flange, 17.75" x 17.75" exhaust size • Standard mount pads • 8" Dia. bolted inspection port, F/G white sponge gasket • Housing flange gasketing to be Food Grade silicone caulking • Airstream Temperature: 70°F • painted RAL #7012 Basalt Grey • If stand with 40" clearance is desired, please add \$2,500 • If insulated with 1" insulation and aluminum cladding please add \$4,995	2	\$11,950.00	\$23,900.00
Est Ductwork Estimated ductwork - final sizing TBD upon site plan layout 17" dia 14 ga Estimate consists of 100' of straight duct and four (4) 90° elbows	2	\$19,995.00	\$39,990.00

Item & Description	Quantity	Unit Price	Total
Filter for Hammer Mill 60 SERIES 49AST 10 STYLE II DUST CONTROL FILTER WITH 804 SQ. FT. OF CLOTH INCLUDING THE FOLLOWING FEATURES: FILTER TO HANDLE 6,240 CFM OF GROUND CORN DUST AT 70°F FILTER STRESSED TO 17" W.G. FLANGED CONSTRUCTION TOP BAG REMOVAL LIFT OFF STYLE TOP SERVICE DOORS 16 OZ. D/P SNAP BAND TOP REMOVAL BAGS NO TOOL GALVANIZED CAGES NEMA 4 ENCLOSURE MAGNEHELIC GAUGE KIT LADDER, CAGE,TOP GUARDRAIL, AND SAFETY GATE EXTERIOR PRIMED & PAINTED AIRLANCO WHITE SAFETY EQUIPMENT PAINTED SAFETY YELLOW NOTE: A 110 VOLT SINGLE PHASE ELECTRICAL SOURCE IS REQUIRED FOR THE TIMER BOX. A COMPRESSED AIR SOURCE OF 10.85 SCFM AT 90-100 PSI IS REQUIRED FOR MEDIA CLEANING.	2	\$46,172.00	\$92,344.00

Item & Description	Quantity	Unit Price	Total
Airlock EMVDL-RVEX-HT45 Series EMVDL-RVEX-HT45 Series. Certified Rotary Valve - Differential pressures up to 40* W.G. Certified: ATEX EN 15089 CE 0588 EX II ID/ C T4 EX D Certificate #: FSA 15 ATEX 1661/1662 X. NFPA 69 Compliant: Flex tip design certified to prevent flame passage NFPA 69 12.2.4.3.6 Product Code: 58000 Explosion & Flame Proof up to 1.7 bar / 24.65 psi (polyurethane flex tips) Body & Covers: Cast iron with safety red finish or nickel plated Shaft Seals: Feit ring and simmering Bearings: Oil bronze slide Drive Unit: Direct with coupling and gear motor. Choice of IP 65 and Haz-Loc IP65 Gearmotors IP 65 Gearmotor rated for outdoor installations Haz-Loc Gearmotor rated for hazardous locations (Class 1, Div. 2, Group A, 8, C & D, Class 2, Div. 2, Group F & G) and rated IP 65 for outdoor installations. Rotor / Rotor blade Combination (8 Vanes): Mild steel rotor with polyurethane (flex tip) EMVDL-RVEX-HT450 - 30 RPM HP: 2.00 Capacity: 1.23 FT* (35 Liters) per rotation	2	\$22,998.00	\$45,996.00
2006 Andritz 26LM Pellet Mill 2006 Andritz 26LM Pellet Mill, incl: 400 hp, 1,200 rpm motor. Model 26 Centri-Feeder; and Model 18 X 56 in-line feeder conditioner	1	\$243,750.00	\$243,750.00
2005 Andritz 26LM Pellet Mill 2005 Andritz 26LM Pellet Mill - incl: 400 hp, 1,200 rpm motors. - Model 26 Centri-Feeders - Model 18 X 56 in-line feeder conditioner	1	\$243,750.00	\$243,750.00
Hot Pellets Belt Conveyor Hot Pellets Belt Conveyor Fully Enclosed, Powder coated 12" Wide x 30' long 10 ga bolted construction 4-1/2" x 12" pulley 12" Wide belt - 2 ply 581 RPM	2	\$21,995.00	\$43,990.00

Item & Description	Quantity	Unit Price	Total
BR-304 SS Rotary Feeder 14x12 BR-304 SS Rotary Feeder RF14x12 with 1 HP, 3 PH, 460 Volt, TEFC Gearmotor with coupling & safety shield	2	\$11,470.00	\$22,940.00
CC-8-130-6 · Round Bin Counter Flow Cooler · 304 Stainless Steel Bin Walls and Top · 304 Stainless Steel Rotary Feeder With 2HP 3ph/60HZ/480V/Class 2 Div. 2 Motor · Three level Indicators for Low Level, Normal Level and High Level · Electric Air Control Damper · Mild Steel Fixed Grid Air Operated Louvre Discharge Floor · Mild Steel Hopper Under the Floor · Door Safety Switch · Sight Glass · Explosion Proof Light	2	\$53,934.00	\$107,868.00
XF-29 Fan XF-29 - Arrangement #9F heavy-gauge steel base with continuous welds. - Heavy-duty pillow block bearings. - Turned, ground, and straightened shaft. - Dynamically and statically balanced rotor with tapered hub and bushing. - Narrow width high static, heavy-duty rotor. - Rotor to be fabricated of AR 235 Plate Steel. - Heavy duty housing with continuous welds. - Housing to be fabricated of carbon steel. - Motor slide base with integral drive tensioning mechanism. - 40 HP, 1800 RPM, class TEFC, 230-460V/3/60 NEMA Premium efficient motor. - NOTE: TEFC motor with no environmental marking/T Code. - V-belt drive with 1.5 to 2.0 service factor. - Totally enclosed sanitary belt and shaft guard. - Factory test run prior to shipment. - Inlet to 17" OD. - Flanged rectangular outlet. - Louvered damper available - Vibration isolation sleeve with clamps for fan inlet. - Bolt-on inspection door. - Housing to have a drain port in the bottom. - Product contact zones unpainted, all other surfaces painted Basalt Gray; guards painted safety orange. Please specify otherwise. http://midwestcustomsolutions.com/suppequip/fan/xf-29.html	2	\$11,995.00	\$23,990.00

Item & Description	Quantity	Unit Price	Total
HE-30 Cyclone	2	\$7,950.00	\$15,900.00
New HE 30 Cyclone, 10 ga, mild steel			
rated up to 4,900 CFM			
High Efficiency Centrifugal Collector Model HE-30			
• CW inlet rotation			
• 10 gauge mild steel construction			
• Exterior welds continuous where possible and cleaned			
free of weld slag and splatter			
• 30" Diameter flanged collector housing with riser tube			
• Flanged 77.25° cone, welded to expansion chamber			
• Product discharge is flanged 10" round			
• Flanged rectangular inlet, 22.0" x 8"			
• Draw-thru fitting mounted on riser tube flange, 13.25" x 13.25" exhaust			
size			
• Standard mount pads			
• 10" Dia. bolted inspection port, F/G white sponge gasket			
• Housing flange gasketing to be Food Grade silicone			
caulking			
• Airstream Temperature: 130°F			
• painted RAL #7012 Basalt Grey			
• If stand with 40" clearance is desired, please add \$2,500			
• If insulated with 1" insulation and aluminum cladding please add			
\$2,995			

Item & Description	Quantity	Unit Price	Total
Airlock EMVDL-RVEX-HT37 EMVDL-RVEX-HT37 Series. Certified Rotary Valve - Differential pressures up to 40* W.G. Certified: ATEX EN 15089 CE 0588 EX II ID/ C T4 EX D Certificate #: FSA 15 ATEX 1661/1662 X. NFPA 69 Compliant: Flex tip design certified to prevent flame passage NFPA 69 12.2.4.3.6 Product Code: 58000 Explosion & Flame Proof up to 1.7 bar / 24.65 psi (polyurethane flex tips) Body & Covers: Cast iron with safety red finish or nickel plated Shaft Seals: Felt ring and simmering Bearings: Oil bronze slide Drive Unit: Direct with coupling and gear motor. Choice of IP 65 and Haz-Loc IP65 Gearmotors IP 65 Gearmotor rated for outdoor installations Haz-Loc Gearmotor rated for hazardous locations (Class 1, Div. 2, Group A, 8, C & D, Class 2, Div. 2, Group F & G) and rated IP 65 for outdoor installations. Rotor / Rotor blade Combination (8 Vanes): Mild steel rotor with polyurethane (flex tip) EMVDL-RVEX-HT450 - 30 RPM HP: 1 HP Capacity: 0.70 FT ³ (20 Liters) per rotation	2	\$10,272.50	\$20,545.00
Est Ductwork Estimated ductwork - final sizing TBD upon site plan layout 17" dia 14 ga Estimate consists of 50' of straight duct and four (4) 90° elbows	2	\$9,995.00	\$19,990.00
Automation and Controls Est Automation and Controls - includes PLC programming of all infeed, outfeed, and product conveyance into through, and out of system includes modulation programming for burner management system (BMS) - 21.5" HMI display with modeled equipment interface includes data logging for temperatures and hours of components - includes on site programming for 1 man weeks, additional costs billed at \$1,350/day plus expenses - includes visualization programming - includes reports via emailed pdf's in customer chosen frequency - Mobile data access	1	\$289,950.00	\$289,950.00

Item & Description	Quantity	Unit Price	Total
Storage Bin for Wheat Seed Heavy-duty, storage bin designed for use in feed, grain, biomass, and ingredient processing environments. The unit includes a fully welded upper wall assembly, converging lower hopper section, access door with viewing window, and reinforced leg structure for stable floor mounting. Approximate Overall Dimensions: Height: ~245 in (20.4 ft) Width: ~136 in (11.3 ft) Depth: ~136 in (11.3 ft) (Refer to Dwg 109200100 for dimensions) Internal Capacity (Approx.): 800-900 cu ft (typical working range) Standard Features: - 1/4" A36 mild steel hopper - 14 ga A36 mild steel upper side wall - Reinforced structural frame and legs - Access door for inspection - Top cover - Suitable for dry bulk materials	1	\$38,000.00	\$38,000.00

Item & Description	Quantity	Unit Price	Total
Compact Industrial Blower Package Roots 406 RAM / 30 HP / 4" Pressure Blower Package System Parameters: 13 FTASL, 90°F. Ambient, 350 ICFM @ 10 PSIG Discharge Pressure, 14 PSIG relief valve setting - ROOTS blower – 406 RAM - Motor - 30 HP, 1770 RPM 460 Volt 60 Hz, 3 phase, premium efficient, TEFC, inverter duty - TECO - Adjustable motor mount - Spring loaded for constant tension - Premium belt drive - (low overhung load) - OSHA belt guard - Elevated forklift-compatible steel base - Air intake filter/silencer - 4" - filter efficiency is 99% @ 1-micron particle size - Intake silencer - 4" premium chambered absorption - Removeable and replaceable - Discharge silencer - 4" premium chambered absorption - Removeable and replaceable - Expansion joint between silencer and blower - Discharge spool pipe for relief valve, check valve, pressure gauge, and ports for instrumentation - Weighted relief valve - 2" set at 14 PSIG - Check valve - 4" - Pressure gauge - Painted and assembled - Start-up oil & grease	1	\$20,804.00	\$20,804.00
Est Ductwork for Wheat 4" dia tubing Est 100' tubing Est 4 90 deg elbows	1	\$10,000.00	\$10,000.00

Item & Description	Quantity	Unit Price	Total
Filter Receiver AVS FILTER, MODEL 72AVSI6 STYLE II COMPLETE WITH: • Filter stressed for 30" WC (2.20" HG) vacuum/pressure • 145.6 Sq.ft. of media with an air to media ratio of 5.2:1 @ 750 CFM • Carbon steel construction, all product contact parts • Carbon steel clean air plenum • WU exterior welds (continuous where possible and cleaned free of weld slag and spatter) • W1 product contact welds (continuous welds, ground to 60-70 RA) • Food grade epoxy coated product contact areas - W1 interior product contact welds (continuous welds, ground to 60-70 RA) • 18" x 38" Hinged T-handle style housing access door • 3/4" SMC Immersion Diaphragm Valves with 4" diameter compressed gas header • NCC Timer and Goyen solenoid valves mounted and prewired in a Nema 4X polycarbonate enclosure • Timer and accessory voltage, 120VAC/1/60HZ • Timer enclosure airlines to diaphragm valves, Polyflo tubing • Mineral reinforced nylon bag cup and venturi • 5" O.D. exhaust stub • Side mount fan mounting brackets, SB12 fan provided by Coperion • Man supportable 4x4 mesh(grate) • Differential pressure Magnehelic Gauge kit, 20 F to 140 F • Filter housing flange gasketing to be Food Grade silicone caulking • Filter requires 5.0 SCFM of 90-100 PSIG clean, dry air, to be supplied by customer • (16) 6" dia. X 72" long galvanized carbon steel bag cages • (16) 6" dia. X 72" long 16 oz. Polyester bottom cuff bags • Stainless steel bag clamps • Filter Location: Outdoors • Serial Number Assembly • Paint: Polane D8700 Urethane (or Powdura GL Superdurable TGIC Free Polyester High Gloss), RAL9003 Signal White • Laser etched anodized aluminum serial number plate	1	\$12,867.00	\$12,867.00

Item & Description	Quantity	Unit Price	Total
Fan for Filter Receiver CENTRIFUGAL FAN, MODEL CINCINNATI FAN MODEL PB-10A , ARRANGEMENT 4 • 750 ACFM 6" SP @ 3,450 RPM requiring 1.71 BHP • CFM is corrected for 70° F. temperature and 20 foot elevation above sea level • 2 HP, TEFC, 56C frame, 230/460 volt, 3-phase,60 Hz motor • Wheel width 100% • Cold start design temperature 30° F. • Teflon Shaft seal • Straight blade wheel • Direct drive • Flanged inlet • NPT drain • Outlet damper + Cast Aluminum Pressure Blower	1	\$3,119.00	\$3,119.00
Cooled Pellets Belt Conveyor Cooled Pellets Belt Conveyor Fully Enclosed, Powder coated 12" Wide x 20' long 10 ga bolted construction 4-1/2" x 12" pulley 12" Wide belt - 2 ply 581 RPM	1	\$16,995.00	\$16,995.00
HD 5'x8' Screener 5' x 8' single deck screener - with screen of choice (please specify perf) - 3 HP TEFC motor and eccentric drive system - requires 3 HP VFD to control and adjust conveyance rate - mounted on Carbon Fiber Control Arms - HD Channel iron fram	1	\$58,950.00	\$58,950.00

Item & Description	Quantity	Unit Price	Total
Fines return 4" Tubular Screw Conveyor 4" Tubular Screw Conveyor	1	\$6,995.00	\$6,995.00
Screw conveyor configured to convey 19 cu ft/hr with a 30% trough loading at 45 RPM, with the following properties:			
Motor: 1/3 HP 230/460V TEFC motor (P/N: MTR2-P33-3BD18)			
Drive: Right angle direct drive (P/N: WG-175-040-H)			
Housing to be 4" SCH 40 pipe			
Material: Carbon steel, non-food grade			
Assumed product _____ with a density of 25-35#/cu.ft.			
Inlet to match customer's hopper. Discharge is Ø4" SCH40 pipe with a 150# pipe flange.			
1-1/4" NPT coupling for Bindicator: P/N TBD			
6" cleanout/inspection port not included (quoted upon request).			
Overall tube length: 120".			
Finish Notes:			
8. Exterior fully welded. Interior skip welded where applicable. All welds cleaned free of slag and splatter.			
Screw conveyor painted RAL 7012 (Basalt Gray).			
Guarding to be painted safety orange.			

Item & Description	Quantity	Unit Price	Total
Finished Pellet Leg Junior 1000 BPH 60' Junior Unlined 1.75-1.44 Head Assembly 8" Unlined Transition Motor Mount; Out the Back Platform Mount Drive; TA 1107-25; 3 HP; Class 1 Drive Guard 13 - 8 Ft. Trunking; 9"X13"; Angle Iron Flanges (Std.); 14 ga. (Std.); Painted Angle Iron (Std.) Trunking Brace Inspection Section; 9"X13"; Painted BELT; PF250; 10" WIDE; 8" SPACING;.25" BOLTS (3X 3.625" SP); 9"X 6" CUPS Belt Splice 9X6 High-Density Polyethylene #4 Vented Cups 1/4" x 1 1/4" Norway Bolt 1/4" Whiz Nut 5/16" X 1 1/4" Whiz Bolt 5/16" Whiz Nut Standard Boot Clean Out Drawer Unlined Standard Boot Hopper Head Platform Distributor Platform (Bolt-Together) 1 - RH OSHA Platform 1 - LH OSHA Platform 6 - 8' Ladder & Bracket Assembly 1 - 4' Ladder & Bracket Assembly 1- Safety Cage 3 - Entry Cage 1 - 8" Square to Round	1	\$26,995.00	\$26,995.00
2 way loadout valve 2 way loadout valve with electric actuator	1	\$2,695.00	\$2,695.00

Item & Description	Quantity	Unit Price	Total
Lot of 2 Silos with Skirts	1	\$110,000.00	\$110,000.00
Lot of 2 Silos with Skirts			
4070 CF			
12' X 48'7'			
Carbon Steel,			
Columbia Tec Tank			
YR.2004			
S/N's 03-3012, 03-3013			
W/Top Mounted Horizon Baghouse			
Handrails w/ Toe Plate			
Est Engineering Time	1	\$55,000.00	\$55,000.00
Estimated Time for Engineering			
Time to create layouts, process flow diagrams, piping and instrumen-			
tation diagrams, electrical, plumbing.			
Infrastructure not included - quoted upon request			

Item & Description	Quantity	Unit Price	Total
Additional Terms	1	\$0.00	\$0.00
Freight Charges: (FOB Origin)			
This project will be (FOB Origin) prepaid and add and all current freight charges that apply to this project will be forwarded to customer.			
NOTE: The above prices does not include the following items and will be the responsibility of the owner or others:			
A. Any freight charges of any sort.			
B. Any applicable sales taxes and/or permits.			
C. Any electrical such as work, wiring, starters outside our scope.			
D. Any water requirements or piping.			
E. Concrete slab cutting & removal, supply and install footings, piers, j-bolts, grouting			
F. Roofing work; seals, flashings (new or existing).			
G. Compressed air of any sort or piping.			
H. Removal of obsolete equipment from premises.			
I. Refurbishment of existing equipment			
J. Liquidated damages			
K. Performance or payment bonds			
L. Special coatings or insulation			
M. Special voltage motors (all motors are TEFC 230/460 volt)			
N. Relocation of underground utilities, conduits or water lines			
O. Road blockage or barricades or escorts			
P. Blankets for coverage of electrical lines			
Q. Scrap bin, pick-up or delivery if required			
R. Roof penetrations, curbing or flashing to roof			
S. Union labor or non-union labor to install / demo services			
T. PE stamped drawings			
U. Filter sprinklers (optional) / heat sensors / broken bag detectors			
V. Concrete grade, floor, cutting, concrete wall penetrations.			
W. System sequence start-up / shut-down control panel.			
X. Speed sensors			
One-time subtotal			\$2,397,985.00
Total			\$2,397,985.00

Purchase terms

50% down, Balance before shipment.

Signature

Signature

Date

Printed name

Questions? Contact me



Jason Shipley
jason@usemce.com
+16202009109

Midwest Custom Engineering, Inc.
6526 S Kanner Hwy #215
Stuart, FL 34997
United States