

Case 2 Reserve (example)

1.50 TPH wet Wood shavings
9.26 C.Y./hr @ 324 lb/C.Y. and 50% moisture
5x32 Single-pass rotary drum · XD-60 (5'x25')
Elevation 1,200 feet (above sea level)

Fuel to Burner
Natural Gas
22,800 Btu/lb
102 lb/hr
2.33 MMBtu/hr

Combustion Air
466 ACFM
60 deg F
25% X-S air

Make-Up Air
1,828 SCFM
60 deg F

Mixed Inlet Gases
2,315 SCFM
900 deg F

Wet Feed
50.0% moisture
1,500 lb/hr solids
1,500 lb/hr water
3,000 lb/hr total

Dry Fuel (product burned)
0 lb/hr total

Net Dry Product
1,667 lb/hr total

Exhaust Gases
3,889 ACFM
15 hp fan

Dryer Outlet Gases
3,889 ACFM
180 deg F

Dry Material
10.0% moisture
1,500 lb/hr solids
167 lb/hr water
1,667 lb/hr total
200 deg F

DEHYDRATION SYSTEM MASS-ENERGY BALANCE

1,594 Btu's/lb evaporation (rigorous)

EVAPORATION RATE
1,333 LB/HR H2O

XD-60 (5'x25') · 32 ft long · 2.8 MMBtu/hr burner

