

Cover letter

Application Information:Bagging Line for textured feedProduct: Textured feed, heavy molasees (up to 10% inclusion)Rate: 4-6 bags/,min plusSize: 50 lb bags, plain sewnAutomatic bag placer: yesBag Type: Paper, multi layerDiscounts shown per line item.



Quote

Quote ref.	20240611-022830098
Issue date	Jun 11, 2024
Expires	Aug 30, 2024
Currency	USD

Seller

Midwest Custom Engineering, Inc.
6526 S Kanner Hwy #215
Stuart, FL 34997
United States

Contact
Jason Shipley (jason@usemce.com)
+16202009109

Buyer

Top Bead Welding Svc
190 5th Street
Broadway, VA 22815
United States

Contacts
Lanny Beach (lanny@topbeadwelding.com)

Effective date	Total discount	Total contract value
On agreement	\$30,833.16	\$459,431.32

Line items

Name	Quantity	Unit price	Unit discount	Net price
HOPP & SUPT 87 CU' CM MS HOPP & SUPT 87 CU' CM MS For Simplex scale only, mild steel construction Gray Powder Coated	1	\$13,400.00	\$1,340.00	\$12,060.00
BIN LEVEL SENSOR - Solido 115V Install level sensor (Hi/Lo), includes mounting couplings and protective baffles installed in the hopper. Customer to wire the level sensor to product feeding equipment to control the high and low level of product. Rotating Paddle Switch 115 VAC 50/60Hz	2	\$455.00	\$45.50	\$819.00
LID 87 CU' SURGE HOPPER M.S. LID 87 CU' SURGE HOPPER M.S. Mild Steel Construction bolted on - Inlet hole for product delivery, level sensor & dust relief can be added, need to advise size and location.	1	\$1,437.50	\$143.75	\$1,293.75
BAGGING SCALE CM-780D-II - Main scale assembly, - air operated double door 3.5 CU' standard weigh hopper (2.0 & 4.0 available), - 100KG load cells, - 1280 Express Digital Programmable Controller with digital readout, - RS232 output, - operator station. - Protect individual or all parameters via pass code protection (inquire about checklist), - Ethernet connection (inquire about communication abilities)	1	\$25,000.00	\$2,500.00	\$22,500.00
BELT FEEDER Belt Feeder (1 HP Motor) 1-speed belt pneumatically operated stream depth regulator for 2 rates of feed, - for handling semi-free flowing products such as texturized feeds, - with an 18" x 10" inlet chute. 230V/480V - 3 Ph standard.	1	\$9,762.50	\$976.25	\$8,786.25

Name	Quantity	Unit price	Unit discount	Net price
VFD 1 HP 480V NEMA 4/12 1 HP AC Variable speed drive for 2 rate of feed filling controlled via programmable controller keypad, - memory retained speeds via product ID, - includes drive, - analog input card, - voltage noise choke and programming	1	\$2,687.50	\$268.75	\$2,418.75
PULLEYS (2 SELF CLEANING) PULLEYS (2 SELF CLEANING) OPTION: Adder - Tail and Head Self-Cleaning pulleys vs. standard drum pulley	1	\$1,406.25	\$140.62	\$1,265.62
TRANS JOHNSON BH ADAPTER MS TRANS JOHNSON BH ADAPTER MS	1	\$1,043.75	\$52.19	\$991.56
AUTOMATIC BAG PLACER JBH9400 Series II Automatic Bag placer - Designed for automatically hanging both paper and laminated poly woven bags. - Vacuum pump. Motorized to supply a large volume of vacuum. - Double bag magazine. When one magazine runs empty it will shift over to the filled magazine. - Self-centering magazines. - Quick and easy adjustments for different bag sizes. - Bag in place sensors & protection. - Double protection to detect when a bag has not been placed, preventing the scale from discharging. - Gripper Arms are equipped with sensors to detect if they have missed or lost a bag. - Both bag clamps are equipped with sensors if either clamp does not securely have the bag the scale will not discharge. - Inputs & outputs. All controlled by Johnson's "WALDO" and designed to isolate all electronics from the outside world. - Internal timers. Accessible through the "WALDO" keypad. - Movements and positioning. All mechanical movements monitored by sensors so that through inputs we know all the positions of each cylinder. - Able to fill while hanger is in operation. - Complete. This hanger is sold complete, ready for plants supply of electricity and compressed air. - Signals between the scale and the hanger. "Dry set of contacts" will be closed from the bag hanger when a bag has been placed onto the bag spout, this will give the bagging scale a "Bag Ready" signal. - The bag hanger will need to receive a signal from a "Dry set of contacts" from the bagging scale telling the hanger that the bag has been filled. "Dump Complete". - Control Switch Functions: - Mushroom Switch- When pushed in this will immediately stop the bag placer and will prevent it from recycling. This also resets an ERROR in the event that the hanger should miss a bag. - THREE-POSITION SWITCH - Place by Hand/Stop- When set to this position bags can be placed onto the fill spout by hand and the foot pedal used to actuate the bagging scale. The rest of the hanger does not function. - If the hanger is running in auto and this switch is moved to "place by hand/stop" it will freeze the hanger in its current position.	1	\$87,375.00	\$4,368.75	\$83,006.25
BAG CLOSING CONVEYOR Bag Closing Conveyor 12' overall length, 1/2 HP motor, 12" wide 3-ply neoprene smooth-top belt, 110V variable speed motor mounted internally, adjustable conveyor height 13.5" to 18.5", and adjustable back plate. Electrical controls include on/off switch	1	\$7,231.25	\$723.12	\$6,508.12

Name	Quantity	Unit price	Unit discount	Net price
AMERICAN NEW LONG PLAIN SEW American Newlong Plain Sew A1-PB-EL 480 - PEDESTAL W/MOTORIZED ELEC.LIFT DS-9C BAG CLOSER - PL(CM)STD.FT W/102134A,102161 CM4900-1 - PLAIN SEWING INFEED CM4900-1 BOX FOR PLAIN SEWING INFEED A1-PB EL 480V + DS-9C + CM4900-1 Plain Sew Infeed 1 Adjustable Height Pedestal with safety type gear assembly for control in setting sewing head positioning over conveyor. 2 Electric Lift Actuator 3. Vibration free sewing head with the following features: a. Capable of running up to 2700 RPM b. Able to sew both plain and tape bound closures with no modifications made to the system or head. c. Oil bath lubrication system. d. Automatic cutting system. 4. Casters for easy mobility of the unit. 5. Omron PLC. 6. Vector drive for sewing machine drive motor. 7. Photoelectric start/stop and knife actuation. 9. American-Newlong CM4900-1 Plain Sew Infeed 10. DS-9C Sewing Head	1	\$28,687.50	\$2,868.75	\$25,818.75
BAG KICKER Bag Kicker - to allow 90 degree turn in product layout flow 4' or 5' long, 12" wide smooth-top belting conveyor, with photo eye, kicker plate and complete pneumatic system - Optional adder: \$1,295 STABILIZER: Vibration Stabilizer Assembly Option - Required when a bag kicker is interfaced with a lift assembly or a bag printer, minimal millwork is required by customer.	1	\$12,625.00	\$1,262.50	\$11,362.50
STABILIZER FOR KICKER STABILIZER FOR KICKER	1	\$1,295.00	\$129.50	\$1,165.50
BAG FLATTENER 10' OAL BAG FLATTENER 10' OAL Dwg: MSCVE0003 Industrial Bag Flattener/Incline Conveyor. - 1.5 HP and 1 HP motors, fixed speed 90 FPM. 10' long, 15 degree incline conveyor with an opposed 5- 1/2' long conveyor with parallel linkage and adjustable spacing (factory setting 3-1/2" to 9-1/2") for various bag thicknesses. - Spacing adjustment is not rigid as a result of pneumatic and hydraulic shocks that allow for optimum flexibility in bag shaping. - 24" wide black rough-top belting, standard 12" inlet/42" discharge height. - Powder coated Industrial Gray (RAL 7046) - Electrical Requirements: 230V/460V-3Ph 10.2/5.1 amps (1.0 & 1.5 HP Motors) - Air Requirements: 90 PSI at 4CFM Note: Flattener required for future automation of palletizing	1	\$21,168.75	\$2,116.88	\$19,051.87
GRAVITY ROLLER ACCUMULATION TABLE GRAVITY ROLLER ACCUMULATION TABLE Gravity conveyor 3'-6" long with 1.9 x 16 gauge rollers set high on 2" centers 30"EFF. 30" BF feeding to 18" radius adjustable top. "H" type support legs 36" to 42" height. Half moon table to stop bag from rolling.	1	\$1,787.50	\$178.75	\$1,608.75
CRATING CHARGE CRATING CHARGE four crates at \$250.00 each, Net	1	\$1,000.00	—	\$1,000.00

Name	Quantity	Unit price	Unit discount	Net price
PALLETIZER ROBOT - Dual Zone PALLETIZER ROBOT - Dual Zone KUKA 180R3200 PA. Robot Floor Mounting plate. Piab Bag gripper. Light curtain in front of the pallet locator. Pallet locators and sensors. Stack lights and reset interface. Sensors for bag detection and distance sensors for stack high confirmation. End feed Conveyor. Installation/programing of two sizes of bags and two pallet patterns. Stack lights and reset interface, 2 year warranty on parts and labor for robot. * Safety Systems: o Light curtains with integration (with required safety relay and remote entry) o Safety cage up to and including 16' X 16' *Will need to define required penetrations (job specific per below Preliminary Drawing) - Integration/Materials /Fabrication - Required electrical and pneumatic connections (electrical and pneumatic service to be supplied by customer) - Required mechanical (cage and robot anchoring to be supplied by customer) - Required Licensing software Included in Robot Cost - Robot platform (Customer to confirm height) All components shipped to BG's facility for Preliminary Integration - Integrator to arrange and ship all components to final customer (within Continental U.S.) at cost PrePay and add to final customer invoice unless otherwise requested by End User approx. (\$5,850) * Start up & Training (Robot Programmer) and Installation assistance (Service Tech) required - Includes 2 days travel x 4 Days on site - Not to exceed \$10,500.00. (applies to initial installation) 1-2year Service Visit at cost, i.e.- Preventative Maintenance. Customer responsible for conveyor placement, power supplies, air supply and all equipment anchoring. * Pricing Valid for 14 days and Subject to Robot Availability -Normal Lead times are 12-14 weeks, plus 4-6 weeks for integration. Total 20 weeks turn around. * 50% with PO, 50% due when goods ready to ship ***All Bag sizes and specifications will need to be confirmed	1	\$247,000.00	\$12,350.00	\$234,650.00

STRETCH WRAPPER Automatic Stretch Wrap System The Lantech Q-300 delivers top performance. Its unique design gets the critical components of a stretch wrapper right. TURNTABLE SYSTEM - a unique turntable system that supports heavy loads and continuously stands up to the shock of loading year after year. FILM DELIVERY SYSTEM - A film delivery system that delivers consistent wrap force and maintains prestretch over the long haul. CONTROLS SYSTEM - Anybody can run the Q-300. It's intuitive, easy, and safe. Everything is easily visible and the control panel is located on the same machine side as the film delivery system. OPTION - Auto Film Cut-Off \$1,100.00 When the load finishes wrapping the Automatic Film Cut-Off will cut the film. Estimate savings of approximately 30 seconds per load. NOTE: Not recommended for loads under 200 lbs.	1	\$26,447.00	\$1,322.35	\$25,124.65
---	---	-------------	------------	-------------

Subtotal	\$459,431.32
Discount included in the subtotal	\$30,833.16
Total contract value	\$459,431.32

Terms

50% down, Balance before shipment.

Acceptance

This section is designated for the authorized representatives from both parties involved in this agreement. By signing below, the signatories confirm their acceptance of the terms and conditions outlined in this document.

Signature

Date

Printed name

Questions? Contact me

Jason Shipley
jason@usemce.com
+16202009109

Midwest Custom Engineering, Inc.
6526 S Kanner Hwy #215
Stuart, FL 34997
United States