

《语义计算与知识检索》研究生课程

词汇语义计算（三）

万小军

北京大学语言计算与互联网挖掘组

2018年3月21日

<http://www.icst.pku.edu.cn/lcwm/course/sckr2018>

内容

- 词义消歧(WSD)
- 词汇语义应用

词义消歧(WSD)

词义消歧(WSD)概述

定义

- **词义消歧(Word Sense Disambiguation)** : 为一个词语从预先设定的词义项集中选择一个词义
 - 词义项集来自与词典或知识库
 - 基于知识的方法 & 监督学习的方法
- **词义区分(Word Sense Discrimination)**: 在没有预定义的词义项集的情况下, 将一个词语的使用划分为不同意义项
 - 无监督方法

WSD问题定义

- 许多词语具有多个词义 (homonymy / polysemy)

–Ex: “**chair**” – furniture or person

–Ex: “**child**” – young person or human offspring

- 确定在特定句子中一个词语采用哪个词义

- 说明:

- 通常一个词语的不同词义紧密相关

Ex: **Bank**: -financial institute

-building of the financial institute

- 有时候几个词义能够在同一个上下文中同时被激发(co-activation)

Ex: “*This could bring competition to the trade*”

competition: - the act of competing

- the people who are competing

词义表示

- 词在给定上下文中的意义

- 词义表示

- 根据词典

- chair* = a seat for one person, with a support for the back; "he put his coat over the back of the chair and sat down"

- chair* = the position of professor; "he was awarded an endowed chair in economics"

- 根据在另一语言中的翻译

- chair* = chaise (法语)

- chair* = directeur (法语)

- 根据词出现的上下文(discrimination)

- "Sit on a *chair*" "Take a seat on this *chair*"

- "The *chair* of the Math Department" "The *chair* of the meeting"

- 向量表示 (词义嵌入)

- 每个词对应多个向量表示, 而非传统的一个向量表示

计算机 vs. 人

- 一词多义-很多词具有多个意义
- 计算机程序没有消歧的基础，即使对于人来说很容易
- 歧义在人们的日常交流中并不是问题，除非在极端情况下
 - “阿隆索因车祸不幸去世”

对于计算机的歧义

- The fisherman jumped off the **bank** and into the water. (河岸)
- The **bank** down the street was robbed! (银行)
- Back in the day, we had an entire **bank** of computers devoted to this problem. (排)
- The **bank** in that road is entirely too steep and is really dangerous. (斜坡)
- The plane took a **bank** to the left, and then headed off towards the mountains. (倾斜飞行, 倾斜转弯)

WSD历史

- 认为是影响机器翻译的一个问题 (Weaver, 1949)
 - 一个词只有知道其特定意义才能被翻译
- 1970s - 1980s
 - 基于规则的系统
 - 依赖于人工构造的知识资源
- 1990s
 - 基于语料的方法
 - 依赖于标注好词义的文本
- 2000s
 - 混合方法
 - 利用Web数据和资源

实际应用

- 机器翻译(Machine Translation)
 - Translate “**bank**” from English to Chinese
 - Is it a “银行” or a “河堤” ?
- 信息检索(Information Retrieval)
 - Find all Web Pages about “**cricket**” (蟋蟀/板球)
 - The sport or the insect?
- 智能问答(Question Answering)
 - What is **George Miller**’ s position on gun control?
 - The psychologist or US congressman?
- 知识获取(Knowledge Acquisition)
 - Add to KB: Herb Bergson is the mayor of **Duluth**.
 - Minnesota or Georgia?

WSD任重而道远

Translate

From: English ▾



To: Chinese (Simplified) ▾

Translate

The plane took a bank to the left, and then headed off towards the mountains.

飞机起飞一间银行，向左侧，然后攻向山。

Translate

From: English ▾



To: Chinese (Simplified) ▾

Translate

The bank in that road is entirely too steep and is really dangerous.

银行在这条道路是完全太陡，实在是危险的。

词义消岐两类任务

- **All Words Word Sense Disambiguation**
 - 对文本中的所有词进行词义消岐
 - “He put his suit over the back of the chair”
- **Targeted Word Sense Disambiguation**
 - 对一个目标词进行词义消岐
 - “Take a seat on this **chair**”
 - “The **chair** of the Math Department”

词义消岐方法

- **基于知识的消岐**
 - 使用外部词典、知识库资源
 - 使用篇章属性
- **有监督的消岐**
 - 基于标注的训练数据
- **无监督的消岐**
 - 基于未标注数据
 - 不使用词典、知识库资源
 - 不使用标注数据

WSD评价

- **评价准则**
 - Precision
 - Recall
- **基于标准数据集**
 - SEMCOR corpus, SENSEVAL corpus, ...
- **评估的困难性**
 - 词义的性质对结果有影响
 - 粗粒度 vs. 细粒度词义区分

词义消歧(WSD)之基于知识的方法

方法概述

- **Knowledge-based WSD** = 依赖于从词典知识库或原文本中得到的知识
- **资源**
 - **使用**
 - 机器可读词典
 - 原文本
 - **不使用**
 - 人工标注的语料
- **可处理所有开放词语**

机器可读词典(MRD)

- 近些年许多词典机器可读(MRD)
 - Oxford English Dictionary
 - Collins
 - Longman Dictionary of Ordinary Contemporary English (LDOCE)
- 辞典 (Thesauruses) – 添加了同义词信息
 - Roget Thesaurus
- 语义网络(Semantic Network) – 添加了更多的语义关系
 - WordNet
 - BabelNet

MRD

- 对于每一个词语，MRD提供如下信息：
 - 词义列表
 - 词义的定义
 - 典型使用样例

WordNet definitions/examples for the noun *plant*

1. buildings for carrying on industrial labor; "they built a large plant to manufacture automobiles"
2. a living organism lacking the power of locomotion
3. something planted secretly for discovery by another; "the police used a plant to trick the thieves"; "he claimed that the evidence against him was a plant"
4. an actor situated in the audience whose acting is rehearsed but seems spontaneous to the audience

MRD

- 词义之间的同义关系

WordNet synsets for the noun
“plant”

1. plant, works, industrial plant
2. plant, flora, plant life

- Hypernymy/hyponymy (IS-A),
meronymy/holonymy (PART-OF),
antonymy, entailment, etc.

WordNet related concepts for the meaning “plant life”
{plant, flora, plant life}

hypernym: {organism, being}

hypomym: {house plant}, {fungus}, ...

meronym: {plant tissue}, {plant part}

holonym: {Plantae, kingdom Plantae, plant kingdom}

Lesk算法

- 通过定义重叠(definition overlap)识别上下文中的词义(Michael Lesk 1986)
 - 从MRD中获取待消歧词语的所有词义定义
 - 确定所有词义组合的词义定义的重叠程度
 - 选择具有最高重叠度的词义组合

Example: disambiguate **PINE CONE**

• PINE

1. kinds of evergreen tree with needle-shaped leaves /松树
2. waste away through sorrow or illness /憔悴

• CONE

1. solid body which narrows to a point /圆锥体
2. something of this shape whether solid or hollow /圆锥形物
3. fruit of certain evergreen trees /松果

Pine#1 \cap Cone#1 = 0
Pine#2 \cap Cone#1 = 0
Pine#1 \cap Cone#2 = 1
Pine#2 \cap Cone#2 = 0
Pine#1 \cap Cone#3 = 2
Pine#2 \cap Cone#3 = 0

利用Lesk算法对多个词(>2)进行词义消岐?

- *I saw a man who is 98 years old and can still walk and tell jokes*
 - nine open class words: *see*(26), *man*(11), *year*(4), *old*(8), *can*(5), *still*(4), *walk*(10), *tell*(8), *joke*(3)
- **43,929,600种词义组合! 如何快速找到最优的词义组合?**
- **模拟退火(Simulated annealing) [Cowie et al. 1992]**
 - 定义一个函数 $E = 1/(1+R)$, R: 词义组合的冗余度(基于词出现的次数).
 - 找到最优的词义组合, 最小化E
 1. 初始, 每个词选择其最频繁(常用)词义, 计算E
 2. 每次迭代中, 随机选择一个词将其词义替换为另一个词义, 计算E'
如果 $\Delta E = (E' - E) < 0$, 那么保留新词义, 然后进行新的随机替换
如果 $\Delta E = (E' - E) \geq 0$, 那么以一定的概率($P = \exp(-\Delta E/T)$, T为常数, 初始为1, 每1000次后变为0.9T)保留新词义
 3. 当词义组合不再变化, 停止迭代

简化的Lesk算法

- 原始Lesk算法: 评估上下文中所有词语词义的重叠程度
 - 同时识别上下文中所有词语的准确词义
- 简化Lesk算法: 评估一个词的词义与**当前上下文**的重叠程度
 - 每次识别一个词的准确词义
- 搜索空间显著减小

简化的Lesk算法

- 算法步骤:

1. 从MRD中获取待消歧词语的所有词义定义
2. 确定每个词义与当前上下文之间的重叠度
3. 选择具有最高重叠度的词义

Example: disambiguate PINE in

“*Pine* cones hanging in a tree”

- PINE

1. kinds of evergreen tree with needle-shaped leaves
2. waste away through sorrow or illness


Pine#1 \cap Sentence = 1
Pine#2 \cap Sentence = 0

基于图排序的方法

- [Mihalcea 2005]
- 同时对所有词同时进行消歧，考虑词义之间的关联关系
- 步骤
 - 词义图的构建
 - 词的每个词义作为一个节点，词义之间的关联关系作为边(权重)
 - 基于图的排序
 - 基于Pagerank算法，一个节点的权值由跟它相连的其他节点所决定
 - 词义标记选择
 - 对每个词选择权值最大的词义

$$P(V_a) = (1 - d) + d * \sum_{V_b \in In(V_a)} \frac{P(V_b)}{|Out(V_b)|}$$

基于图排序的方法



基于每个篇章段落一种意义

- 在一个篇章段落中，一个词的所有出现都倾向于表达同一个意义

E.g. The ambiguous word **PLANT** occurs 10 times in a discourse
all instances of “plant” carry the same meaning

基于每个词语搭配一种意义

- 词语搭配(collocation): 经常共同出现, 强相关的词对
- 一个词在同样的搭配使用中倾向于表达同样的意义
 - 相邻搭配中更加明显
 - 词语距离增大则减弱

The ambiguous word **PLANT** preserves its meaning in all its occurrences within the collocation “**industrial plant**”, regardless of the context where this collocation occurs

词义消歧(WSD)之基于有监督学习的方法

方法概述

- 有监督的WSD: 从人工标注词义的文本上学习到分类器
- 将WSD问题看作一个分类问题
 - 基于目标词的上下文为目标词从给定词义选项中选择最准确的词义

标注词义的文本

Bonnie and Clyde are two really famous criminals, I think they were **bank/1** robbers

My **bank/1** charges too much for an overdraft.

I went to the **bank/1** to deposit my check and get a new ATM card.

The University of Minnesota has an East and a West **Bank/2** campus right on the Mississippi River.

My grandfather planted his pole in the **bank/2** and got a great big catfish!

The **bank/2** is pretty muddy, I can't walk there.

词义的词袋模型表示 (基于在上下文窗口中词的共现)

FINANCIAL_BANK_BAG:

a an and are ATM Bonnie card charges check Clyde
criminals deposit famous for get I much My new overdraft
really robbers the they think to too two went were

RIVER_BANK_BAG:

a an and big campus cant catfish East got grandfather great
has his I in is Minnesota Mississippi muddy My of on planted
pole pretty right River The the there University walk West

简单的有监督WSD方法

给定包含 “bank” 的句子S;

对于S中每个词 W_i :

如果 W_i 属于FINANCIAL_BANK_BAG, 那么

$Sense_1 = Sense_1 + 1;$

如果 W_i 属于RIVER_BANK_BAG 那么

$Sense_2 = Sense_2 + 1;$

如果 $Sense_1 > Sense_2$, 那么选择词义 “Financial”

否则如果 $Sense_2 > Sense_1$, 那么选择词义 “River”

否则, 打印 “Can’ t Decide” ;

有监督方法框架

- **训练数据获取**: 构建训练数据, 每个目标词人工从预定义词义集中标注词义
- **特征选择**: 选择特征集合, 表示上下文
- **训练集特征向量构建**: 将标注词义的训练样例转换为特征向量
- **分类器学习**: 使用一种机器学习算法学习一个分类器
- **测试集特征向量构建**: 将单独的测试样例转换成特征向量
 - 正确的词义标签已知, 但不使用
- **分类器测试**: 使用分类器为测试样例赋予词义标签

从文本到特征向量

- My/pronoun grandfather/noun used/verb to/prep fish/verb along/adv the/det **banks/SHORE** of/prep the/det Mississippi/noun River/noun. (S1)
- The/det **bank/FINANCE** issued/verb a/det check/noun for/prep the/det amount/noun of/prep interest/noun. (S2)

	<u>P-2</u>	<u>P-1</u>	<u>P+1</u>	<u>P+2</u>	<u>fish</u>	<u>check</u>	<u>river</u>	<u>interest</u>	<u>SENSE TAG</u>
S1	adv	det	prep	det	Y	N	Y	N	SHORE
S2		det	verb	det	N	Y	N	Y	FINANCE

有监督学习算法

- 机器学习领域提供了很多这样的算法，许多算法都在WSD上取得好结果
 - Support Vector Machines
 - Nearest Neighbor Classifiers
 - Decision Trees
 - Decision Lists
 - Naïve Bayesian Classifiers
 - Perceptrons
 - Neural Networks
 - Graphical Models
 - Log Linear Models

使用单分类器的有监督WSD


- 大多数有监督机器学习能够有效进行WSD
- 不同的方法一般在所采用的特征上有所区别
- 有效的特征包括:
 - Co-occurrences or keywords
 - Collocations
 - Part of speech
 - Predicate-argument relations
 - Verb-object, subject-verb
 - ...

分类器集成(Ensemble)

- 将不同性质的分类器集成起来通常能够提高总体效果
 - 不同的学习算法
 - 不同角度/视角的特征表示
 - 对训练集的不同采样(sampling)
- Bagging, Stacking, Boosting, ...
- 怎样融合分类器结果?
 - Simple Majority Voting
 - Averaging of probabilities across multiple classifier output
- 许多WSD系统都采用了集成方法

是否可以用深度学习技术？

- 当然
 - 深度信念网络(DBN)




Wiriathamabhum P, Kijsirikul B, Takamura H, et al.
Applying Deep Belief Networks to Word Sense
Disambiguation[J]. arXiv preprint arXiv:1207.0396, 2012.


是否可以用深度学习技术？

- 当然

Bidirectional LSTM sequence labeling



Encoder-decoder architecture for sequence-to-sequence WSD



Raganato, A., Bovi, C. D., & Navigli, R. (2017). Neural sequence learning models for word sense disambiguation. In *Proceedings of EMNLP 2017* (pp. 1156-1167).

词义消歧(WSD)之基于半监督学习的方法

方法概述


- **有监督(Supervised)WSD** = 从足量标注数据中学习词义分类器
- **半监督(Semi-supervised)WSD** = 从少量标注数据与大量未标注数据中学习词义分类器

自举方法(Bootstrapping)

- 基于少量训练数据构建词义分类器
 - 扩展分类器的适用性
- 自举方法
 - Co-training
 - Self-training

自举方法的部件

- **输入**
 - 少量标注数据
 - 大量未标注数据
 - 基本的分类器
- **输出**
 - 比基本分类器具有更好效果的分器



通用自举过程

- 已标注的训练集L
- 未标注集合U
- 基本分类器C

- 1. 创建一个样例池U'
 - 从U中随机选择P个样例
- 2. 循环I次：
 - 基于L训练C，并用C标注U'
 - 从U' 中选择G个最可信的样例添加到L
 - 保持L中的分布
 - 从U中选择样例重填U'
 - 保持U'的大小为P

通用自举过程

- 已标注的训练集L
- 未标注集合U
- 基本分类器C

• 1. 创建一个样例池U'

- 从U中随机选择P个样例

Pool Size

• 2. 循环I次:

Iteration Number

- 基于L训练C, 并用C标注U'
- 从U' 中选择G个最可信的样例添加到L
 - 保持L中的分布
- 从U中选择样例重填U'
 - 保持U'的大小为P

Growth Size

Self-training

- 单个分类器
- 基于自己的输出重新训练
- Self-training for NLP
 - Part of speech tagging
 - Co-reference resolution
 - Sentiment analysis

协同学习(Co-training)

- **两个分类器**
 - 两种相互独立的视角
 - [独立性要求可放宽]
- **Co-training in NLP**
 - Statistical parsing
 - Co-reference resolution
 - Part of speech tagging
 - Sentiment analysis
 - ...

协同学习(Co-training)

- 已标注的训练集 L , 每个样例两种视角表示
- 未标注集合 U , 每个样例两种视角表示
- 基本分类器 C

- 1. 创建一个样例池 U'
 - 从 U 中随机选择 P 个样例
- 2. 循环 I 次:
 - 基于 L 和视角一训练 C_1 , 并用 C_1 标注 U' , 从 U' 中选择 G 个最可信的样例;
 - 基于 L 和视角二训练 C_2 , 并用 C_2 标注 U' , 从 U' 中选择 G 个最可信的样例;
 - 将选择的样例添加到 L 中;
 - 从 U 中选择样例重填 U'
 - 保持 U' 的大小为 P

词义消歧(WSD)之基于无监督学习的方法

方法概述

- **无监督的词义区分(Word Sense Discrimination):**
基于上下文相似性将词进行聚类
- **假设**
 - **具有相似意义的词倾向于出现在相似的上下文中**
- **仅使用原文本中的信息，不使用外部知识库或人工标注**
- **没有词义列表/目录的知识，因此聚类没有词义标签**

方法概述

- 资源:
 - 大量的原始语料
- **Word Sense Discrimination**看作是发现那些出现在相似上下文中的目标词，并将它们聚集成一个类簇的问题
 - 需要计算上下文的相似程度
 - 对于词义类簇并不赋词义标签

聚类方法

- **特征选择**

E.g. (Pedersen and Bruce, 1997) explore discrimination with a small number (approx 30) of features near target word.

- Morphological form of target word (1)
- Part of Speech two words to left and right of target word (4)
- Co-occurrences (3) most frequent content words in context
- Unrestricted collocations (19) most frequent words located one position to left or right of target, OR
- Content collocations (19) most frequent content words located one position to left or right of target

- **相似度计算**

- **聚类算法**

- 层次式聚类, EM算法、基于图切割的聚类等

分析

- 无监督方法不能发现与通过有监督学习得到的相同的词义类簇
- 基于已有词义类别/标签对无监督学习结果进行评价过于苛刻.
 - 可考虑人工评价

利用隐含语义分析

- Adapted by (Schütze, 1998) to word sense discrimination
- 数据表示为词语共现矩阵(co-occurrence matrix)
- 对共现矩阵进行SVD(Singular Value Decomposition)分解降维
 - 重要的维度跟语义概念关联
- 目标词汇的特征表示为其上下文中所有词汇特征向量的平均值（二阶表示）
- 通过余弦测度计算特征向量的相似度，然后进行聚类

分析

- 基于直接/一阶(first order)特征的聚类方法需要大量数据来获取有效特征
- 二阶表示(Second order representations)可以很好地利用少量数据获得丰富的非稀疏的上下文表示
- <http://senseclusters.sourceforge.net> 包括了SVD的完整无监督词义区分的系统

词义标注数据

- Senseval/Semeval评测数据
 - <http://www.senseval.org>
- Data for lexical sample
 - English (with respect to Hector, WordNet, Wordsmyth)
 - Basque, Catalan, Chinese, Czech, Romanian, Spanish, etc.
 - Data produced within Open Mind Word Expert project
<http://teach-computers.org>
- Data for all words
 - English, Italian, Czech (Senseval-2 and Senseval-3)
 - SemCor (200,000 running words)
<http://www.cs.unt.edu/~rada/downloads.html>
- Pointers to additional data available from
 - <http://www.senseval.org/data.html>

WSD Software – Lexical Sample

- **Duluth Senseval-2 systems**
 - Lexical decision tree systems that participated in Senseval-2 and 3
 - <http://www.d.umn.edu/~tpederse/senseval2.html>
- **SyntaLex**
 - Enhance Duluth Senseval-2 with syntactic features, participated in Senseval-3
 - <http://www.d.umn.edu/~tpederse/syntalex.html>
- **WSDShell**
 - Shell for running Weka experiments with wide range of options
 - <http://www.d.umn.edu/~tpederse/wsdshell.html>
- **SenseTools**
 - For easy implementation of supervised WSD, used by the above 3 systems
 - Transforms Senseval-formatted data into the files required by Weka
 - <http://www.d.umn.edu/~tpederse/sensetools.html>
- **SenseRelate::TargetWord**
 - Identifies the sense of a word based on the semantic relation with its neighbors
 - <http://search.cpan.org/dist/WordNet-SenseRelate-TargetWord>
 - Uses WordNet::Similarity – measures of similarity based on WordNet
 - <http://search.cpan.org/dist/WordNet-Similarity>

WSD Software – All Words

- **SenseLearner**
 - A minimally supervised approach for all open class words
 - Extension of a system participating in Senseval-3
 - <http://lit.csci.unt.edu/~senselearner>
- **SenseRelate::AllWords**
 - Identifies the sense of a word based on the semantic relation with its neighbors
 - <http://search.cpan.org/dist/WordNet-SenseRelate-AllWords>

WSD Software – Unsupervised

- **Clustering by Committee**
 - <http://www.cs.ualberta.ca/~lindek/demos/wordcluster.htm>
- **InfoMap**
 - Represent the meanings of words in vector space
 - <http://infomap-nlp.sourceforge.net>
- **SenseClusters**
 - Finds clusters of words that occur in similar context
 - <http://senseclusters.sourceforge.net>

互联网与WSD

- 互联网已成为NLP的一个重要数据来源，包括WSD
- 通过搜索能找到目标词汇的大量实例
- 搜索引擎能够选择与验证词语搭配(collocations)及其他的关联(association).
 - “strong tea” : 13,000 hits
 - “powerful tea” : 428 hits
 - “sparkling tea” : 376 hits

互联网与WSD

- 维基百科提供了大量的词义列表/目录，包含新词。

Jordan (disambiguation)

From Wikipedia, the free encyclopedia

Jordan is a country in the Middle East.

Jordan or **Jordán** may also refer to:

Geographical

Middle East

- The Jordan River
- Jordan, Tehran, Iran, an avenue and a surrounding district

United States

See also: Jordan Township (disambiguation)

- Jordan, Indiana (disambiguation), several places
- Jordan, Iowa
- Jordan, Minnesota, a city in Scott County
- Jordan, Minneapolis, a neighborhood of Minneapolis, Minnesota
- Jordan, Montana
- Jordan, New York
- Jordan, North Carolina
- Jordan, Oregon
- Jordan, Wisconsin, a town
- Jordan, Portage County, Wisconsin, an unincorporated community

Elsewhere

- Germán Jordán Province, Bolivia
- Jordan, Guimaras, Philippines
- Jordan, Hong Kong
- Jordan (Neumark), Poland
- Jordán Pond, pond in Tábor, Czech Republic
- Jordan River, New Zealand
- Jordan, Ontario, Canada
- Jordanhill, Glasgow, UK

Music

- "Jordan", a hymn tune by composer William Billings
- "Jordan" a 1998 song from Megahertz's *Kopfschuss*
- "Jordan" (song), a Buckethead song
- "Jordan", a 2006 song from Bellowhead's *Burlesque*
- "Jordan, Minnesota", a 1986 song from Big Black's *Atomizer*

Mathematics

- Gauss–Jordan elimination, version of Gaussian elimination
- Jordan algebra, a non-associative algebra over a field
- Jordan curve theorem in topology
- Jordan decomposition (disambiguation), several measures
- Jordan measure or Jordan content, an early form of measure
- Jordan normal form or Jordan canonical form of a matrix
- Jordan's lemma in complex analysis
- Jordan's theorem (multiply transitive groups)
- Jordan–Schönflies theorem in geometric topology
- Jordan–Hölder theorem in group theory
- Jordan's theorem in economics

People

- Jordan (name), list of people with this surname or given name

People adopting name Jordan

- Jordan (Katie Price), English former glamour model
- Jordan (Pamela Rooke), model and actress related to the punk movement

Other

- Jordan almonds, a type of candy
- Jordan Grand Prix, which competed in Formula 1 from 1991-2005
- Jordan Motor Company, an automobile manufacturer of the 1920s
- Jordan College (disambiguation), several colleges both real and fictional
- Jordan, archaic slang for a chamber pot


互联网与WSD

但是，互联网存在如下不足：

- **互联网上存在大量的垃圾内容，需要过滤**
- **搜索引擎返回的结果页面数只是估计值，并且不断变化**
- **搜索引擎可能关闭API，阻止访问**
- **访问互联网获取数据通常比较慢**

词汇语义在信息检索中的应用

信息检索



Vocabulary Gap

Semantic Gap

信息检索

- **查询与文档的相似/相关性**
 - **查询表示**
 - **文档表示**
 - 词袋模型(Bag of words)
 - **相关性计算**
 - Vector space model: Cosine
 - Probabilistic model: Okapi BM25
 - Language model: KL divergence

查询重构与扩展

- 查询词通常很短，带有歧义
 - Cat: animal/Unix command
 - 在查询中加入更多的词进行消歧、改进
- 相关反馈(Relevance feedback)
 - 利用初始查询检索
 - 展示检索结果
 - 让用户标注相关性/非相关性
 - 扩展查询使之接近相关文档，远离非相关文档

$$q_{i+1} = q_i + \frac{\beta}{R} \sum_{j=1}^R r_j - \frac{\gamma}{NR} \sum_{k=1}^S s_k$$

- 伪相关反馈(Pseudo-Relevance feedback)

词义与信息检索

- 动机


- **Homonymy** = Bank (financial, river)
- **Polysemy** = Bat ((the club used in playing cricket), (a small racket with a long handle used for playing squash))
- **Synonymy** = doctor, doc, physician, MD, medico (a licensed medical practitioner)

- 上述语言现象如何影响信息检索性能?

- **Homonymy and Polysemy: 降低检索准确率**
- **Synonymy: 降低检索召回率**

基于词义进行索引与检索

- 对查询词进行词义消歧;
- 对文档中词语进行词义消歧;
- 基于词义进行相关度匹配;
- “Word sense disambiguation in information retrieval revisited” in SIGIR03
- “Information Retrieval Using Word Senses: Root Sense Tagging Approach” In SIGIR04.



基于词义关系的查询扩展

- 基于WordNet进行查询扩展 (通常在WSD之后)
 - Synonyms, definition words, hyponyms, etc.
 - “car” => “car automobile auto motorcar vehicle”
- 从结果文档中进行伪相关反馈
 - 基于词义从Top ranked documents中选择扩展词
 - “An effective approach to document retrieval via utilizing WordNet and recognizing phrases” in SIGIR04

基于词语相似度的相关度计算

- 查询与文档中词语相似度值能够对相关文档和不相关文档进行区分, e.g. the sum of SR scores, the average SR score, etc.
 - “A study on the semantic relatedness of query and document terms in information retrieval”, in EMNLP09.
- 基于词语相似度值进行查询扩展
- 将词语相似度值集成到查询-文档相关度计算中
- “Semantic similarity methods in WordNet and their application to information retrieval on the Web” in WIDM05

$$Sim(q, d) = \frac{\sum_i \sum_j q_i d_j sim(i, j)}{\sum_i \sum_j q_i d_j},$$

问题

- **词汇语义能否有效改善现实中的信息检索？**
 - **实验室环境下结果有好有坏**
 - 如果扩展到真实Web检索...
 - **WSD自身的效果影响？**
 - **对不同用户查询采用同一种查询扩展方法的合理性？**
 - **性能问题？**

其他应用

- 文本分类
- 文本聚类
 - WordNet, WSD, Word Similarity...
 - Wikipedia

阅读材料

- “Automatic sense disambiguation using machine readable dictionaries: How to tell a pine cone from an ice cream cone.” by Lesk, M. SIGDOC1986.
- “Lexical disambiguation using simulated annealing” by Cowie, L. and Guthrie, J. A. and Guthrie, L, COLING1992.
- “co-training and self-training for word sense disambiguation” by Rada Mihalcea, CONLL2004.
- “Distinguishing Word Sense in Untagged Text.” by Pedersen and Bruce. EMNLP1997.
- “Automatic Word Sense Discrimination” by Schutze. Computational Linguistics, 1998.
- “Word Sense Disambiguation: a survey” by R. Navigli. ACM Computing Surveys, 2009.
- “An Experimental Study of Graph Connectivity for Unsupervised Word Sense Disambiguation.” by R. Navigli, M. Lapata, IEEE Trans. Pattern Anal. Mach. Intell. 2010
- “Word sense disambiguation in information retrieval revisited” by C. Stokoe, M. P. Oakes, J. Tait. SIGIR03.
- “Information retrieval using word senses: root sense tagging approach” by S.-B. Kim et al. SIGIR04.
- “An effective approach to document retrieval via utilizing WordNet and recognizing phrases” by S. Liu et al. SIGIR04.
- “A study on the semantic relatedness of query and document terms in information retrieval” by C. Müller and I. Gurevych. EMNLP09.
- “Inducing word senses to improve web search result clustering” by R. Navigli and G. Crisafulli. EMNLP2010.
- “Unsupervised large-vocabulary word sense disambiguation with graph-based algorithms for sequence data labeling” by Rada Mihalcea, EMNLP05.
- “SensEmbed: learning sense embeddings for word and relational similarity.” by Iacobacci, Ignacio, Mohammad Taher Pilehvar, and Roberto Navigli. Proceedings of ACL. 2015.

- **Some slides were borrowed or adapted from related slides written by Ted Pedersen, Rada Mihalcea, etc. Thank them for sharing their slides.**

