API Documentation (OpenAPI/Swagger)

January 31, 2026

1 Overview

Local:

```
Base URL: http://localhost:8080
```

Introduction

This API documentation describes the Byte Me backend REST API, generated via **OpenAPI/Swagger**. It explains how to call each endpoint using `curl`, along with request and response examples.

Including these seven controllers:

2. **auth-controller**
3. **bundle-controller**
4. **category-controller**
5. **order-controller**
6. **issue-controller**
7. **gamification-controller**
8. **AnalyticsController**

2 AuthController (`/api/auth`)

2.1 Register

POST `/api/auth/register`

Example Request

```
curl -X POST http://localhost:8080/api/auth/register \
  -H "Content-Type: application/json" \
  -d '{
    "email": "seller@example.com",
    "password": "password123",
    "role": "SELLER",
    "businessName": "ABC",
    "location": "Exeter"
  }'
```

Example Response

```
{}
```

2.2 Login

POST `/api/auth/login`

Example Request

```
curl -X POST http://localhost:8080/api/auth/login \
  -H "Content-Type: application/json" \
  -d '{
    "email": "seller@example.com",
    "password": "password123"
  }'
```

Example Response

```
{}
```

2.3 Current user

GET `/api/auth/me`

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/auth/me' \
  -H 'accept: */*'
```

Example Response

```
{}
```

3 BundleController (`/api/bundles`)

3.1 List available bundles

GET `/api/bundles/`

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/bundles?page=0&size=1&sort=string' \
  -H 'accept: */*'
```

Example Response


```json
{
  "totalPages": 0,
  "totalElements": 0,
  "first": true,
  "last": true,
  "numberOfElements": 0,
  "pageable": {
    "pageNumber": 0,
    "pageSize": 0,
    "paged": true,
    "unpaged": true,
    "offset": 0,
    "sort": [
      {
        "direction": "string",
        "nullHandling": "string",
        "ascending": true,
        "property": "string",
        "ignoreCase": true
      }
    ]
  },
  "size": 0,
  "content": [
    {
      "postingId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "seller": {
        "sellerId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
        "name": "string",
        "locationText": "string",
        "openingHoursText": "string",
        "contactStub": "string",
        "createdAt": "2026-01-30T23:29:45.182Z"
      },
      "category": {
        "categoryId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
        "name": "string"
      },
      "title": "string",
      "description": "string",
      "pickupStartAt": "2026-01-30T23:29:45.182Z",
      "pickupEndAt": "2026-01-30T23:29:45.182Z",
      "quantityTotal": 0,
      "quantityReserved": 0,
      "priceCents": 0,
      "discountPct": 0,
      "allergensText": "string",
      "status": "DRAFT",
      "createdAt": "2026-01-30T23:29:45.182Z",
      "available": 0
    }
  ],
  "number": 0,
  "sort": [
    {
      "direction": "string",
```

```
      "nullHandling": "string",
      "ascending": true,
      "property": "string",
      "ignoreCase": true
    }
  ],
  "empty": true
}
```


3.2 Get a bundle by id

GET `/api/bundles/{id}`

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/bundles/23f45e89-8b5a-5c55-9df7-240
     d78a3ce15' \
  -H 'accept: */*'
```

Example Response


```
{
  "postingId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "seller": {
    "sellerId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "name": "string",
    "locationText": "string",
    "openingHoursText": "string",
    "contactStub": "string",
    "createdAt": "2026-01-30T23:30:37.984Z"
  },
  "category": {
    "categoryId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "name": "string"
  },
  "title": "string",
  "description": "string",
  "pickupStartAt": "2026-01-30T23:30:37.984Z",
  "pickupEndAt": "2026-01-30T23:30:37.984Z",
  "quantityTotal": 0,
  "quantityReserved": 0,
  "priceCents": 0,
  "discountPct": 0,
  "allergensText": "string",
  "status": "DRAFT",
  "createdAt": "2026-01-30T23:30:37.984Z",
  "available": 0
}
```


3.3 Create a bundle

POST `/api/bundles`

Example Request

```
curl -X POST http://localhost:8080/api/bundles \
  -H "Authorization: Bearer <JWT>" \
  -H "Content-Type: application/json" \
  -d '{
    "categoryId": "22222222-2222-2222-2222-222222222222",
    "title": "Surprise Bag",
    "description": "Random items",
    "pickupStartAt": "2026-01-30T16:00:00Z",
    "pickupEndAt": "2026-01-30T18:00:00Z",
    "quantityTotal": 10,
    "priceCents": 599,
    "discountPct": 50,
    "allergensText": "gluten",
    "activate": true
  }'
```

Example Response

```
{}
```

3.4 Update a bundle

PUT `/api/bundles/{id}`

Example Request

```
curl -X PUT http://localhost:8080/api/bundles/3fa85f64-5717-4562-b3fc-2c963f66afa6 \
  -H "accept: */*" \
  -H "Content-Type: application/json" \
  -d '{
    "title": "Updated title",
    "description": "Updated description",
    "quantityTotal": 12,
    "priceCents": 499,
    "discountPct": 60,
    "allergensText": "gluten"
  }'
```

Example Response

```
{}
```

3.5 Activate a bundle

POST `/api/bundles/{id}/activate`

Example Request

```
curl -X POST http://localhost:8080/api/bundles/3fa85f64-5717-4562-b3fc-2c963f66afa6/activate \
  -H "accept: */*"
```

Example Response (200 OK)

```
{}
```

3.6 Close a bundle

POST `/api/bundles/{id}/close`

Example Request

```
curl -X 'POST' \
  'http://localhost:8080/api/bundles/23f45e89-8b5a-5c55-9df7-240
     d78a3ce15/close' \
  -H 'accept: */*' \
  -d ''
```

Example Response

```
{}
```

3.7 List bundles by seller

GET `/api/bundles/seller/{sellerId}`

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/bundles/seller/23f45e89-8b5a-5c55-9df7-240
     d78a3ce14' \
  -H 'accept: */*'
```

Example Response

```
[
  {
    "postingId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "seller": {
      "sellerId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "name": "ABC",
      "locationText": "Exeter",
      "openingHoursText": "string",
      "contactStub": "string",
      "createdAt": "2026-01-30T17:54:04.890Z"
    },
    "category": {
      "categoryId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "name": "food"
    },
    "title": "string",
    "description": "string",
    "pickupStartAt": "2026-01-30T17:54:04.890Z",
    "pickupEndAt": "2026-01-30T17:54:04.890Z",
    "quantityTotal": 0,
    "quantityReserved": 0,
```

```
    "priceCents": 0,
    "discountPct": 0,
    "allergensText": "gluten",
    "status": "DRAFT",
    "createdAt": "2026-01-30T17:54:04.890Z",
    "available": 0
  }
]
```

4 CategoryController (/api/categories)

4.1 List categories

GET /api/categories

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/categories' \
  -H 'accept: */*'
```

Example Response

```
[
  { "categoryId": "22222222-2222-2222-2222-222222222222",
    "name": "Bakery"
  }
]
```

5 OrderController (/api/orders)

5.1 Create order

POST /api/orders

Example Request

```
curl -X POST http://localhost:8080/api/orders \
  -H 'accept: */*' \
  -H 'Content-Type: application/json' \
  -d '{
    "postingId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "orgId": "44444444-4444-4444-4444-444444444444",
    "quantity": 2
  }'
```

Example Response

```
{}
```

5.2 Cancel order

POST /api/orders/{id}/cancel

Example Request

```
curl -X 'POST' \
  'http://localhost:8080/api/orders/23f45e89-8b5a-5c55-9df7-240
     d78a3ce15/cancel' \
  -H 'accept: */*' \
  -d ''
```

Example Response

```
{}
```

5.3 Collect order

POST `/api/orders/{id}/collect`

Example Request

```
curl -X 'POST' \
  'http://localhost:8080/api/orders/23f45e89-8b5a-5c55-9df7-240
     d78a3ce15/collect' \
  -H 'accept: */*' \
  -d ''
```

Example Response

```
{}
```

5.4 Get orders by seller

GET `/api/orders/seller/{sellerId}`

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/orders/seller/23f45e89-8b5a-5c55-9df7-240
     d78a3ce15' \
  -H 'accept: */*'
```

Example Response

```
[
  {
    "orderId": "55555555-5555-5555-5555-555555555555",
    "quantity": 2,
    "totalPriceCents": 1198,
    "status": "RESERVED",
    "reservedAt": "2026-01-30T02:00:00Z",
    "collectedAt": null,
    "cancelledAt": null
  }
]
```

5.5 Get orders by organisation

GET `/api/orders/org/{orgId}`

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/orders/org/23f45e89-8b5a-5c55-9df7-240
     d78a3ce15' \
  -H 'accept: */*'
```

Example Response

```
[
  {
    "orderId": "55555555-5555-5555-5555-555555555555",
    "quantity": 2,
    "totalPriceCents": 1198,
    "status": "RESERVED",
    "reservedAt": "2026-01-30T02:00:00Z"
  }
]
```

6 IssueController (/api/issues)

6.1 Create issue

POST `/api/issues`

Example Request

```
curl -X 'POST' \
  'http://localhost:8080/api/issues' \
  -H 'accept: */*' \
  -H 'Content-Type: application/json' \
  -d '{
  "orderId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "orgId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "type": "UNAVAILABLE",
  "description": "string"
}'
```

Example Response

```
{}
```

6.2 Respond to issue

POST `/api/issues/{id}/respond`

Example Request

```
curl -X 'POST' \
  'http://localhost:8080/api/issues/23f45e89-8b5a-5c55-9df7-240
     d78a3ce15/respond' \
  -H 'accept: */*' \
  -H 'Content-Type: application/json' \
  -d '{
  "response": "string",
  "resolve": true
}'
```

Example Response

```
{}
```

6.3 Resolve issue

POST `/api/issues/{id}/resolve`

Example Request

```
curl -X 'POST' \
  'http://localhost:8080/api/issues/23f45e89-8b5a-5c55-9df7-240
     d78a3ce15/resolve' \
  -H 'accept: */*' \
  -d ''
```

Example Response

```
{}
```

6.4 Get issues by seller

GET `/api/issues/seller/{sellerId}`

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/issues/seller/23f45e89-8b5a-5c55-9df7-240
     d78a3ce15' \
  -H 'accept: */*'
```

Example Response

```
[
  {
    "issueId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "order": {
      "orderId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "quantity": 0,
      "totalPriceCents": 0,
      "status": "RESERVED",
```

```
      "reservedAt": "2026-01-30T18:06:33.422Z",
      "collectedAt": "2026-01-30T18:06:33.422Z",
      "cancelledAt": "2026-01-30T18:06:33.422Z"
    },
    "organisation": {
      "orgId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "name": "string",
      "locationText": "string",
      "billingEmail": "string",
      "currentStreakWeeks": 0,
      "bestStreakWeeks": 0,
      "lastOrderWeekStart": "2026-01-30",
      "totalOrders": 0,
      "createdAt": "2026-01-30T18:06:33.422Z"
    },
    "type": "UNAVAILABLE",
    "description": "string",
    "status": "OPEN",
    "sellerResponse": "string",
    "createdAt": "2026-01-30T18:06:33.422Z",
    "resolvedAt": "2026-01-30T18:06:33.422Z"
  }
]
```


6.5 Get open issues by seller

GET /api/issues/seller/{sellerId}/open

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/issues/seller/23f45e89-8b5a-5c55-9df7-240
     d78a3ce15/open' \
  -H 'accept: */*'
```

Example Respons


```
[
  {
    "issueId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "order": {
      "orderId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "quantity": 0,
      "totalPriceCents": 0,
      "status": "RESERVED",
      "reservedAt": "2026-01-30T18:08:18.317Z",
      "collectedAt": "2026-01-30T18:08:18.317Z",
      "cancelledAt": "2026-01-30T18:08:18.317Z"
    },
    "organisation": {
      "orgId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "name": "string",
      "locationText": "string",
      "billingEmail": "string",
      "currentStreakWeeks": 0,
      "bestStreakWeeks": 0,
```

```
      "lastOrderWeekStart": "2026-01-30",
      "totalOrders": 0,
      "createdAt": "2026-01-30T18:08:18.317Z"
    },
    "type": "UNAVAILABLE",
    "description": "string",
    "status": "OPEN",
    "sellerResponse": "string",
    "createdAt": "2026-01-30T18:08:18.317Z",
    "resolvedAt": "2026-01-30T18:08:18.317Z"
  }
]
```


6.6 Get issues by organisation

GET /api/issues/org/{orgId}

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/issues/org/23f45e89-8b5a-5c55-9df7-240
     d78a3ce17' \
  -H 'accept: */*'
```

Example Response


```
[
  {
    "issueId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "order": {
      "orderId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "quantity": 0,
      "totalPriceCents": 0,
      "status": "RESERVED",
      "reservedAt": "2026-01-30T18:09:36.676Z",
      "collectedAt": "2026-01-30T18:09:36.676Z",
      "cancelledAt": "2026-01-30T18:09:36.676Z"
    },
    "organisation": {
      "orgId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "name": "string",
      "locationText": "string",
      "billingEmail": "string",
      "currentStreakWeeks": 0,
      "bestStreakWeeks": 0,
      "lastOrderWeekStart": "2026-01-30",
      "totalOrders": 0,
      "createdAt": "2026-01-30T18:09:36.676Z"
    },
    "type": "UNAVAILABLE",
    "description": "string",
    "status": "OPEN",
    "sellerResponse": "string",
    "createdAt": "2026-01-30T18:09:36.676Z",
    "resolvedAt": "2026-01-30T18:09:36.676Z"
  }
]
```

7 GamificationController (/api/gamification)

7.1 List all badges

GET /api/gamification/badges

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/gamification/badges' \
  -H 'accept: */*'
```

Example Response

```
[
  {
    "badgeId": "77777777-7777-7777-7777-777777777777",
    "code": "FIRST_ORDER",
    "name": "First Order",
    "description": "Placed first rescue order"
  }
]
```

7.2 Get org badges

GET /api/gamification/badges/{orgId}

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/gamification/badges/23f45e89-8b5a-5c55-9
     df7-240d78a3ce15' \
  -H 'accept: */*'
```

Example Response

```
[
  {
    "orgId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "badgeId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "organisation": {
      "orgId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "name": "string",
      "locationText": "string",
      "billingEmail": "string",
      "currentStreakWeeks": 0,
      "bestStreakWeeks": 0,
      "lastOrderWeekStart": "2026-01-30",
      "totalOrders": 0,
      "createdAt": "2026-01-30T18:12:46.077Z"
    },
    "badge": {
      "badgeId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "code": "string",
      "name": "string",
```

```
      "description": "string"
    },
    "awardedAt": "2026-01-30T18:12:46.077Z"
  }
]
```

7.3 Get streak

GET `/api/gamification/streak/{orgId}`

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/gamification/streak/23f45e89-8b5a-5c55-9df7-240d78a3ce15' \
  -H 'accept: */*'
```

Example Response

```
{}
```

7.4 Get stats

GET `/api/gamification/stats/{orgId}`

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/gamification/stats/23f45e89-8b5a-5c55-9df7-240d78a3ce12' \
  -H 'accept: */*'
```

Example Response

```
{}
```

8 AnalyticsController (`/api/analytics`)

8.1 Seller dashboard metrics

GET `/api/analytics/dashboard/{sellerId}`

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/analytics/dashboard/23f45e89-8b5a-5c55-9df7-240d78a3ce15' \
  -H 'accept: */*'
```

Example Response

```
{}
```

8.2 Sell-through breakdown

GET `/api/analytics/sell-through/{sellerId}`

Example Request

```
curl -X 'GET' \
  'http://localhost:8080/api/analytics/sell-through/23f45e89-8b5a-5c55
     -9df7-240d78a3ce15' \
  -H 'accept: */*'
```

Example Response

```
{}
```

9 Notes on Example Responses

- The example response is shown as `{}` because the schema does not define the exact fields.