

Problem Set 4: Neural Networks

This assignment requires a working IPython Notebook installation, which you should already have. If not, please refer to the instructions in Problem Set 2.

The programming part is adapted from [Stanford CS231n](http://cs231n.stanford.edu/) (<http://cs231n.stanford.edu/>).

Total: 100 points.


[30pts] Problem 1: Backprop in a simple MLP

This problem asks you to derive all the steps of the backpropagation algorithm for a simple classification network. Consider a fully-connected neural network, also known as a multi-layer perceptron (MLP), with a single hidden layer and a one-node output layer. The hidden and output nodes use an elementwise sigmoid activation function and the loss layer uses cross-entropy loss:

$$f(z) = \frac{1}{1+exp(-z)}$$

$$L(\hat{y}, y) = -y \ln(\hat{y}) - (1 - y) \ln(1 - \hat{y})$$

The computation graph for an example network is shown below. Note that it has an equal number of nodes in the input and hidden layer (3 each), but, in general, they need not be equal. Also, to make the application of backprop easier, we show the *computation graph* which shows the dot product and activation functions as their own nodes, rather than the usual graph showing a single node for both.



The forward and backward computation are given below. NOTE: We assume no regularization, so you can omit the terms involving Ω .

The forward step is:

Require: Network depth, l
Require: $\mathbf{W}^{(i)}, i \in \{1, \dots, l\}$, the weight matrices of the model
Require: $\mathbf{b}^{(i)}, i \in \{1, \dots, l\}$, the bias parameters of the model
Require: \mathbf{x} , the input to process
Require: \mathbf{y} , the target output

$$\mathbf{h}^{(0)} = \mathbf{x}$$

for $k = 1, \dots, l$ **do**

$$\quad \mathbf{a}^{(k)} = \mathbf{b}^{(k)} + \mathbf{W}^{(k)} \mathbf{h}^{(k-1)}$$

$$\quad \mathbf{h}^{(k)} = f(\mathbf{a}^{(k)})$$

end for

$$\hat{\mathbf{y}} = \mathbf{h}^{(l)}$$

$$J = L(\hat{\mathbf{y}}, \mathbf{y}) + \lambda \Omega(\theta)$$

and the backward step is:

After the forward computation, compute the gradient on the output layer:

$$\mathbf{g} \leftarrow \nabla_{\hat{y}} J = \nabla_{\hat{y}} L(\hat{y}, \mathbf{y})$$

for $k = l, l-1, \dots, 1$ **do**

Convert the gradient on the layer's output into a gradient into the pre-nonlinearity activation (element-wise multiplication if f is element-wise):

$$\mathbf{g} \leftarrow \nabla_{\mathbf{a}^{(k)}} J = \mathbf{g} \odot f'(\mathbf{a}^{(k)})$$

Compute gradients on weights and biases (including the regularization term, where needed):

$$\nabla_{\mathbf{b}^{(k)}} J = \mathbf{g} + \lambda \nabla_{\mathbf{b}^{(k)}} \Omega(\theta)$$

$$\nabla_{\mathbf{W}^{(k)}} J = \mathbf{g} \mathbf{h}^{(k-1)\top} + \lambda \nabla_{\mathbf{W}^{(k)}} \Omega(\theta)$$

Propagate the gradients w.r.t. the next lower-level hidden layer's activations:

$$\mathbf{g} \leftarrow \nabla_{\mathbf{h}^{(k-1)}} J = \mathbf{W}^{(k)\top} \mathbf{g}$$

end for

Write down each step of the backward pass explicitly for all layers, i.e. for the loss and $k = 2, 1$, compute all gradients above, expressing them as a function of variables x, y, h, W, b . We start by giving an example.

Note that we have replaced the superscript notation $u^{(i)}$ with u^i , and \odot stands for element-wise multiplication.

$$\nabla_{\hat{y}} L(\hat{y}, y) = \nabla_{\hat{y}} [-y \ln(\hat{y}) - (1-y) \ln(1-\hat{y})] = \frac{\hat{y}-y}{(1-\hat{y})\hat{y}} = \frac{h^2-y}{(1-h^2)h^2}$$

Next, please derive the following.

Hint: you should substitute the updated values for the gradient g in each step and simplify as much as possible.

[5pts] Q1.1: $\nabla_{a^2} J$

The previous g is:

$$g^0 = \nabla_{\hat{y}} L(\hat{y}, y) = \nabla_{\hat{y}} [-y \ln(\hat{y}) - (1-y) \ln(1-\hat{y})] = \frac{\hat{y}-y}{(1-\hat{y})\hat{y}} = \frac{h^2-y}{(1-h^2)h^2}$$

Then the gradient for this question is:

$$\begin{aligned} \nabla_{a^2} J &= g^0 * \nabla_{a^2}[f(a^2)] = g^0 * \nabla_{a^2}\left[\frac{1}{1 + \exp(-a^2)}\right] \\ &= g^0 * \left[\frac{\exp(-a^2)}{(1 + \exp(-a^2))^2}\right] = g^0 * f(a^2)(1 - f(a^2)) \end{aligned}$$

Update g:

$$g^1 = g^0 * \left[\frac{\exp(-a^2)}{(1 + \exp(-a^2))^2}\right]$$

[5pts] Q1.2: $\nabla_{b^2} J$

Use the previous g we got

$$g^1 = g^0 * \left[\frac{\exp(-a^2)}{(1+\exp(-a^2))^2} \right]$$

$$\nabla_{b^2} J = g^1 * \nabla_{b^2} [W^2 h^1 + b^2] = g^1 * 1 = g^1$$

[5pts] Q1.3: $\nabla_{W^2} J$

Hint: this should be a vector, since W^2 is a vector.

Use the previous g we got

$$g^1 = g^0 * \left[\frac{\exp(-a^2)}{(1+\exp(-a^2))^2} \right]$$

$$\nabla_{W^2} J = g^1 * \nabla_{W^2} [W^2 h^1 + b^2] = g^1 h^{1T}$$

[5pts] Q1.4: $\nabla_{h^1} J$

$$\nabla_{h^1} J = g^1 * \nabla_{h^1} [W^2 h^1 + b^2] = W^{2T} g^1$$

Update g:

$$g^2 = W^{2T} g^1$$

[5pts] Q1.5: $\nabla_{b^1} J, \nabla_{W^1} J$

[double click here to add a solution]

$$\nabla_{b^1} J = \nabla_{a^1} J * \nabla_{b^1} [W^1 h^0 + b^1]$$

In this case, we need to compute the gradient of a1 first:

$$\nabla_{a^1} J = g^2 * \nabla_{a^1} f(a^1) = g^2 * \left[\frac{\exp(-a^1)}{(1+\exp(-a^1))^2} \right] = g^3$$

Then, we can compute gradients of b1 and W1

$$\begin{aligned} \nabla_{b^1} J &= \nabla_{a^1} J * \nabla_{b^1} [W^1 h^0 + b^1] = g^3 * \nabla_{b^1} [W^1 h^0 + b^1] = g^3 \\ \nabla_{W^1} J &= \nabla_{a^1} J * \nabla_{W^1} [W^1 h^0 + b^1] = g^3 * \nabla_{W^1} [W^1 h^0 + b^1] = g^3 h^{0T} \end{aligned}$$

[5pts] Q1.6 Briefly, explain how the computational speed of backpropagation would be affected if it did not include a forward pass

If there is no forward pass in advance, the computation of the backpropagation will not be able to be done from the tail to the front. That is because we will not have the loss from forward functions. In this case, for every computation, we need to get the values for all of the forward functions that it requires to compute the gradient.

[50pts] Problem 2 (Programming): Implementing a simple MLP

In this problem we will develop a neural network with fully-connected layers, or Multi-Layer Perceptron (MLP). We will use it in classification tasks.

In the current directory, you can find a file `mlp.py`, which contains the definition for class `TwoLayerMLP`. As the name suggests, it implements a 2-layer MLP, or MLP with 1 *hidden* layer. You will implement your code in the same file, and call the member functions in this notebook. Below is some initialization. The `autoreload` command makes sure that `mlp.py` is periodically reloaded.

In [1]:

```
# setup
import numpy as np
import matplotlib.pyplot as plt
from mlp import TwoLayerMLP

%matplotlib inline
plt.rcParams['figure.figsize'] = (10.0, 8.0) # set default size of plots
plt.rcParams['image.interpolation'] = 'nearest'
plt.rcParams['image.cmap'] = 'gray'

# for auto-reloading external modules
# see http://stackoverflow.com/questions/1907993/autoreload-of-modules-in-ipython
%load_ext autoreload
%autoreload 2

def rel_error(x, y):
    """ returns relative error """
    return np.max(np.abs(x - y) / (np.maximum(1e-8, np.abs(x) + np.abs(y))))
```

Next we initialize a toy model and some toy data, the task is to classify five 4-d vectors.

In [2]:

```
# Create a small net and some toy data to check your implementations.
# Note that we set the random seed for repeatable experiments.
input_size = 4
hidden_size = 10
num_classes = 3
num_inputs = 5

def init_toy_model(actv, std=1e-1):
    np.random.seed(0)
    return TwoLayerMLP(input_size, hidden_size, num_classes, std=std, activation=actv)

def init_toy_data():
    np.random.seed(1)
    X = 10 * np.random.randn(num_inputs, input_size)
    y = np.array([0, 1, 2, 2, 1])
    return X, y

X, y = init_toy_data()
print('X = ', X)
print()
print('y = ', y)

X = [[ 16.24345364 -6.11756414 -5.28171752 -10.72968622]
     [ 8.65407629 -23.01538697  17.44811764 -7.61206901]
     [ 3.19039096 -2.49370375  14.62107937 -20.60140709]
     [ -3.22417204 -3.84054355  11.33769442 -10.99891267]
     [ -1.72428208 -8.77858418   0.42213747   5.82815214]]

y = [0 1 2 2 1]
```

[5pts] Q2.1 Forward pass: Sigmoid

Our 2-layer MLP uses a softmax output layer (**note**: this means that you don't need to apply a sigmoid on the output) and the multiclass cross-entropy loss to perform classification. Both are defined in Problem Set 2.

Please take a look at method `TwoLayerMLP.loss` in the file `m1p.py`. This function takes in the data and weight parameters, and computes the class scores (aka logits), the loss L , and the gradients on the parameters.

- Complete the implementation of forward pass (up to the computation of scores) for the sigmoid activation: $\sigma(x) = \frac{1}{1+exp(-x)}$.

Note 1: Softmax cross entropy loss involves the log-sum-exp operation (<https://en.wikipedia.org/wiki/LogSumExp>). This can result in numerical underflow/overflow. Read about the solution in the link, and try to understand the calculation of loss in the code.

Note 2: You're strongly encouraged to implement in a vectorized way and avoid using slower for loops. Note that most numpy functions support vector inputs.

Check the correctness of your forward pass below. The difference should be very small (<1e-6).

In [3]:

```
net = init_toy_model('sigmoid')
loss, _ = net.loss(X, y, reg=0.1)
correct_loss = 1.182248
print(loss)
print('Difference between your loss and correct loss:')
print(np.sum(np.abs(loss - correct_loss)))
```

```
1.1822479803941373
Difference between your loss and correct loss:
1.9605862711102873e-08
```

[10pts] Q2.2 Backward pass: Sigmoid

- For sigmoid activation, complete the computation of grads, which stores the gradient of the loss with respect to the variables W1, b1, W2, and b2.

Now debug your backward pass using a numeric gradient check. Again, the differences should be very small.

In [4]:

```
# Use numeric gradient checking to check your implementation of the backward pass.
# If your implementation is correct, the difference between the numeric and
# analytic gradients should be less than 1e-8 for each of W1, W2, b1, and b2.
from utils import eval_numerical_gradient

loss, grads = net.loss(X, y, reg=0.1)

# these should all be very small
for param_name in grads:
    f = lambda W: net.loss(X, y, reg=0.1)[0]
    param_grad_num = eval_numerical_gradient(f, net.params[param_name], verbose=False)
    print('%s max relative error: %e'%(param_name, rel_error(param_grad_num, grads[param_name])))

W2 max relative error: 8.048892e-10
b2 max relative error: 5.553999e-11
W1 max relative error: 1.126755e-08
b1 max relative error: 2.035406e-06
```

[5pts] Q2.3 Train the Sigmoid network

To train the network we will use stochastic gradient descent (SGD), implemented in TwoLayerNet.train. Then we train a two-layer network on toy data.

- Implement the prediction function TwoLayerNet.predict, which is called during training to keep track of training and validation accuracy.

You should get the final training loss around 0.1, which is good, but not too great for such a toy problem. One problem is that the gradient magnitude for W1 (the first layer weights) stays small all the time, and the neural net doesn't get much "learning signals". This has to do with the saturation problem of the sigmoid activation function.

In [5]:


```

net = init_toy_model('sigmoid', std=1e-1)
stats = net.train(X, y, X, y,
                  learning_rate=0.5, reg=1e-5,
                  num_epochs=100, verbose=False)
print('Final training loss: ', stats['loss_history'][-1])

# plot the loss history and gradient magnitudes
plt.subplot(2, 2, 1)
plt.plot(stats['loss_history'])
plt.xlabel('epoch')
plt.ylabel('training loss')
plt.title('Training Loss history')
plt.subplot(2, 2, 2)
plt.plot(stats['grad_magnitude_history'])
plt.xlabel('iteration')
plt.ylabel('||W1||')
plt.ylim(0,1)
plt.title('Gradient magnitude history (W1)')
plt.subplot(2, 2, 3)
plt.plot(stats['train_acc_history'])
plt.xlabel('iteration')
plt.ylabel('accuracy')
plt.title('training accuracy')
plt.subplot(2, 2, 4)
plt.plot(stats['val_acc_history'])
plt.xlabel('iteration')
plt.ylabel('accuracy')
plt.title('validation accuracy')
plt.show()

```

Final training loss: 0.10926794610680679



[5pts] Q2.4 Using ReLU activation

The Rectified Linear Unit (ReLU) activation is also widely used: $\text{ReLU}(x) = \max(0, x)$.

- Complete the implementation for the ReLU activation (forward and backward) in `mlp.py`.
- Train the network with ReLU, and report your final training loss.

Make sure you first pass the numerical gradient check on toy data.

In [6]:

```
net = init_toy_model('relu', std=1e-1)

loss, grads = net.loss(X, y, reg=0.1)
print('loss = ', loss) # correct_loss = 1.320973

# The differences should all be very small
print('checking gradients')
for param_name in grads:
    f = lambda W: net.loss(X, y, reg=0.1)[0]
    param_grad_num = eval_numerical_gradient(f, net.params[param_name], verbose=False)
    print('%s max relative error: %e'%(param_name, rel_error(param_grad_num, grads[param_name])))

loss =  1.3037878913298206
checking gradients
W2 max relative error: 3.440708e-09
b2 max relative error: 3.865091e-11
W1 max relative error: 3.561318e-09
b1 max relative error: 8.994864e-10
```

Now that it's working, let's train the network. Does the net get stronger learning signals (i.e. gradients) this time? Report your final training loss.

In [7]:

```


net = init_toy_model('relu', std=1e-1)
stats = net.train(X, y, X, y,
                   learning_rate=0.1, reg=1e-5,
                   num_epochs=50, verbose=False)

print('Final training loss: ', stats['loss_history'][-1])

# plot the loss history
plt.subplot(2, 1, 1)
plt.plot(stats['loss_history'])
plt.xlabel('epoch')
plt.ylabel('training loss')
plt.title('Training Loss history')
plt.subplot(2, 1, 2)
plt.plot(stats['grad_magnitude_history'])
plt.xlabel('iteration')
plt.ylabel('||W1||')
plt.title('Gradient magnitude history (W1)')
plt.show()

```

Final training loss: 0.0178562204869839



Load MNIST data

Now that you have implemented a two-layer network that works on toy data, let's try some real data. The MNIST dataset is a standard machine learning benchmark. It consists of 70,000 grayscale handwritten digit images, which we split into 50,000 training, 10,000 validation and 10,000 testing. The images are of size 28x28, which are flattened into 784-d vectors.

Note 1: the function `get_MNIST_data` requires the `scikit-learn` package. If you previously did anaconda installation to set up your Python environment, you should already have it. Otherwise, you can install it following the instructions here: <http://scikit-learn.org/stable/install.html> (<http://scikit-learn.org/stable/install.html>)

Note 2: If you encounter a HTTP 500 error, that is likely temporary, just try again.

Note 3: Ensure that the downloaded MNIST file is 55.4MB (smaller file-sizes could indicate an incomplete download - which is possible)

In [8]:

```
# Load MNIST
from utils import get_MNIST_data
X_train, y_train, X_val, y_val, X_test, y_test = get_MNIST_data()
print('Train data shape: ', X_train.shape)
print('Train labels shape: ', y_train.shape)
print('Validation data shape: ', X_val.shape)
print('Validation labels shape: ', y_val.shape)
print('Test data shape: ', X_test.shape)
print('Test labels shape: ', y_test.shape)

Train data shape: (50000, 784)
Train labels shape: (50000,)
Validation data shape: (10000, 784)
Validation labels shape: (10000,)
Test data shape: (10000, 784)
Test labels shape: (10000,)
```

Q2.5 Train a network on MNIST

We will now train a network on MNIST with 64 hidden units in the hidden layer. We train it using SGD, and decrease the learning rate with an exponential rate over time; this is achieved by multiplying the learning rate with a constant factor `learning_rate_decay` (which is less than 1) after each epoch. In effect, we are using a high learning rate initially, which is good for exploring the solution space, and using lower learning rates later to encourage convergence to a local minimum (or saddle point (<http://www.offconvex.org/2016/03/22/saddlepoints/>), which may happen more often)).

- Train your MNIST network with 2 different activation functions: sigmoid and ReLU.

We first define some variables and utility functions. The `plot_stats` function plots the histories of gradient magnitude, training loss, and accuracies on the training and validation sets. The `visualize_weights` function visualizes the weights learned in the first layer of the network. In most neural networks trained on visual data, the first layer weights typically show some visible structure when visualized. Both functions help you to diagnose the training process.

In [9]:

```
input_size = 28 * 28
hidden_size = 64
num_classes = 10

# Plot the Loss function and train / validation accuracies
def plot_stats(stats):
    plt.subplot(3, 1, 1)
    plt.plot(stats['grad_magnitude_history'])
    plt.title('Gradient magnitude history (W1)')
    plt.xlabel('Iteration')
    plt.ylabel('||W1||')
    plt.ylim(0, np.minimum(100,np.max(stats['grad_magnitude_history'])))
    plt.subplot(3, 1, 2)
    plt.plot(stats['loss_history'])
    plt.title('Loss history')
    plt.xlabel('Iteration')
    plt.ylabel('Loss')
    plt.ylim(0, 100)
    plt.subplot(3, 1, 3)
    plt.plot(stats['train_acc_history'], label='train')
    plt.plot(stats['val_acc_history'], label='val')
    plt.title('Classification accuracy history')
    plt.xlabel('Epoch')
    plt.ylabel('Classification accuracy')
    plt.show()

# Visualize the weights of the network
from utils import visualize_grid
def show_net_weights(net):
    W1 = net.params['W1']
    W1 = W1.T.reshape(-1, 28, 28)
    plt.imshow(visualize_grid(W1, padding=3).astype('uint8'))
    plt.gca().axis('off')
    plt.show()
```

[10pts] Q2.5.1 Sigmoid network

In [10]:

```

sigmoid_net = TwoLayerMLP(input_size, hidden_size, num_classes, activation='sigmoid', s

# Train the network
sigmoid_stats = sigmoid_net.train(X_train, y_train, X_val, y_val,
                                   num_epochs=20, batch_size=100,
                                   learning_rate=1e-3, learning_rate_decay=0.95,
                                   reg=0.5, verbose=True)

# Predict on the training set
train_acc = (sigmoid_net.predict(X_train) == y_train).mean()
print('Sigmoid final training accuracy: ', train_acc)

# Predict on the validation set
val_acc = (sigmoid_net.predict(X_val) == y_val).mean()
print('Sigmoid final validation accuracy: ', val_acc)



# Predict on the test set
test_acc = (sigmoid_net.predict(X_test) == y_test).mean()
print('Sigmoid test accuracy: ', test_acc)

# show stats and visualizations
plot_stats(sigmoid_stats)
show_net_weights(sigmoid_net)

```

C:\Users\ljsPC\Desktop\CS542\HW4\pset4\mlp.py:90: RuntimeWarning: overflow encountered in exp
a1 = 1 / (1 + np.exp(-z1))

Epoch 1: loss 78.980750, train_acc 0.280000, val_acc 0.258300
Epoch 2: loss 49.838630, train_acc 0.430000, val_acc 0.459300
Epoch 3: loss 32.431795, train_acc 0.540000, val_acc 0.563200
Epoch 4: loss 21.732892, train_acc 0.710000, val_acc 0.640700
Epoch 5: loss 15.111877, train_acc 0.730000, val_acc 0.688400
Epoch 6: loss 10.906376, train_acc 0.680000, val_acc 0.718700
Epoch 7: loss 8.077669, train_acc 0.740000, val_acc 0.746200
Epoch 8: loss 6.229287, train_acc 0.760000, val_acc 0.766000
Epoch 9: loss 4.979639, train_acc 0.760000, val_acc 0.777300
Epoch 10: loss 4.108814, train_acc 0.780000, val_acc 0.791700
Epoch 11: loss 3.480617, train_acc 0.850000, val_acc 0.802500
Epoch 12: loss 3.065671, train_acc 0.800000, val_acc 0.816400
Epoch 13: loss 2.673266, train_acc 0.870000, val_acc 0.828100
Epoch 14: loss 2.496009, train_acc 0.880000, val_acc 0.837300
Epoch 15: loss 2.355747, train_acc 0.790000, val_acc 0.845900
Epoch 16: loss 2.138493, train_acc 0.840000, val_acc 0.852900
Epoch 17: loss 2.090350, train_acc 0.860000, val_acc 0.856900
Epoch 18: loss 1.974509, train_acc 0.900000, val_acc 0.861900
Epoch 19: loss 1.952709, train_acc 0.870000, val_acc 0.865300
Epoch 20: loss 1.859285, train_acc 0.900000, val_acc 0.868600
Sigmoid final training accuracy: 0.87384
Sigmoid final validation accuracy: 0.8686
Sigmoid test accuracy: 0.8676

**[10pts] Q2.5.2 ReLU network**

In [11]:

```
relu_net = TwoLayerMLP(input_size, hidden_size, num_classes, activation='relu', std=1e-3)

# Train the network
relu_stats = relu_net.train(X_train, y_train, X_val, y_val,
                             num_epochs=20, batch_size=100,
                             learning_rate=1e-3, learning_rate_decay=0.95,
                             reg=0.5, verbose=True)



# Predict on the training set
train_acc = (relu_net.predict(X_train) == y_train).mean()
print('ReLU final training accuracy: ', train_acc)

# Predict on the validation set
val_acc = (relu_net.predict(X_val) == y_val).mean()
print('ReLU final validation accuracy: ', val_acc)

# Predict on the test set
test_acc = (relu_net.predict(X_test) == y_test).mean()
print('ReLU test accuracy: ', test_acc)

# show stats and visualizations
plot_stats(relu_stats)
show_net_weights(relu_net)
```

```
Epoch 1: loss 76.094922, train_acc 0.930000, val_acc 0.860900
Epoch 2: loss 46.876140, train_acc 0.950000, val_acc 0.887700
Epoch 3: loss 29.967661, train_acc 0.920000, val_acc 0.889600
Epoch 4: loss 19.382890, train_acc 0.970000, val_acc 0.915700
Epoch 5: loss 13.073030, train_acc 0.940000, val_acc 0.927100
Epoch 6: loss 8.889162, train_acc 0.970000, val_acc 0.935900
Epoch 7: loss 6.325204, train_acc 0.940000, val_acc 0.939900
Epoch 8: loss 4.410905, train_acc 0.980000, val_acc 0.947600
Epoch 9: loss 3.229653, train_acc 0.990000, val_acc 0.951800
Epoch 10: loss 2.440271, train_acc 0.950000, val_acc 0.954600
Epoch 11: loss 1.817740, train_acc 0.980000, val_acc 0.958100
Epoch 12: loss 1.411437, train_acc 0.990000, val_acc 0.959400
Epoch 13: loss 1.120475, train_acc 1.000000, val_acc 0.959900
Epoch 14: loss 0.994299, train_acc 0.970000, val_acc 0.962700
Epoch 15: loss 0.822049, train_acc 0.950000, val_acc 0.963700
Epoch 16: loss 0.714592, train_acc 0.970000, val_acc 0.964000
Epoch 17: loss 0.586014, train_acc 0.960000, val_acc 0.963400
Epoch 18: loss 0.475392, train_acc 0.990000, val_acc 0.965200
Epoch 19: loss 0.476712, train_acc 0.980000, val_acc 0.965700
Epoch 20: loss 0.379706, train_acc 1.000000, val_acc 0.966100
ReLU final training accuracy:  0.9734
ReLU final validation accuracy:  0.9661
ReLU test accuracy:  0.9637
```



[5pts] Q2.5.3

Which activation function would you choose in practice? Why?

ReLU, because it has faster decreasing rate on gradient magnitude on W1 and loss. Moreover, it has higher accuracy on training, validation and test sets.

[20pts] Problem 3: Simple Regularization Methods

You may have noticed the `reg` parameter in `TwoLayerMLP.loss`, controlling "regularization strength". In learning neural networks, aside from minimizing a loss function $\mathcal{L}(\theta)$ with respect to the network parameters θ , we usually explicitly or implicitly add some regularization term to reduce overfitting. A simple and popular regularization strategy is to penalize some *norm* of θ .

[10pts] Q3.1: L2 regularization

We can penalize the L2 norm of θ : we modify our objective function to be $\mathcal{L}(\theta) + \lambda \|\theta\|^2$ where λ is the weight of regularization. We will minimize this objective using gradient descent with step size η . Derive the update rule: at time $t + 1$, express the new parameters θ_{t+1} in terms of the old parameters θ_t , the gradient $g_t = \frac{\partial \mathcal{L}}{\partial \theta_t}$, η , and λ .

$$\begin{aligned}\theta_{t+1} &= \theta_t - \eta \frac{\partial \mathcal{L}(\theta)}{\partial \theta_t} + \lambda \frac{\partial \|\theta_t\|^2}{\partial \theta_t} \\ &= \theta_t - \eta g_t + \lambda \frac{\partial \sum \theta_t^2}{\partial \theta_t} \\ &= \theta_t - \eta g_t + 2\lambda \sum \theta_t\end{aligned}$$

[10pts] Q3.2: L1 regularization

Now let's consider L1 regularization: our objective in this case is $\mathcal{L}(\theta) + \lambda \|\theta\|_1$. Derive the update rule.

(Technically this becomes *Sub-Gradient* Descent since the L1 norm is not differentiable at 0. But practically it is usually not an issue.)

$$\begin{aligned}\theta_{t+1} &= \theta_t - \eta \frac{\partial \mathcal{L}(\theta)}{\partial \theta_t} + \lambda \frac{\partial \|\theta_t\|_1}{\partial \theta_t} \\ &= \theta_t - \eta g_t + \lambda \frac{\partial \sum |\theta_t|}{\partial \theta_t} \\ &= \theta_t - \eta g_t + \lambda \sum \frac{|\theta_t|}{\theta_t}\end{aligned}$$

In []: