

Atenxion Agent Trigger API

Call the agent trigger endpoint with an `event_id` and your API token. For file jobs, include `file_urls`.

Base URLs

Environment	Base URL
Production	https://backend.atenxion.ai
QA	https://api-qa.atenxion.ai

POST /api/trigger/agent-trigger

Authentication

Header	Value
Authorization	Atenxion API token (raw value, no Bearer)
Content-Type	application/json

Request body (JSON)

Required

Field	Type	Description
event_id	string	Unique id for this trigger (e.g. event_fd963328a70f).

Files

Field	Type	Description
file_urls	array of strings	Public HTTPS URLs Atenxion can download.

```
"file_urls": ["https://files.example.com/report.pdf"]
```

```
"file_urls": [  
  "https://files.example.com/a.pdf",  
  "https://files.example.com/b.pdf"  
]
```

Examples

QA

```
curl -X POST "https://api-qa.atenxion.ai/api/trigger/agent-trigger" \  
-H "Authorization: YOUR_ATENXION_TOKEN" \  
-H "Content-Type: application/json" \  
-d '{  
  "event_id": "event_fd963328a70f",  
  "file_urls": ["https://files.example.com/report.pdf"]  
}'
```

Production

```
curl -X POST "https://backend.atenxion.ai/api/trigger/agent-trigger" \  
-H "Authorization: YOUR_ATENXION_TOKEN" \  
-H "Content-Type: application/json" \  
-d '{  
  "event_id": "event_fd963328a70f",  
  "file_urls": ["https://files.example.com/report.pdf"]  
}'
```

Response (HTTP 200)

Field	Description
success	Whether the trigger was accepted
message	Status message
workflow_id	Temporal workflow id
run_id	Temporal run id

```
{  
  "success": true,  
  "message": "Trigger success",  
  "workflow_id": "agent-workflow-abc123",  
  "run_id": "0192a1b2-c3d4-7e8f-9abc-def012345678"  
}
```

HTTP status	Meaning
400	Invalid request
401	Invalid or missing token
500	Server error

OpenAPI

openapi.yaml

Atenxion — Agent Trigger API specification.