Know When to Hand Off: Multi-turn Reinforcement Learning for Trustworthy Customer-Service Agents

CS4246/5446 Reinforcement Learning and Sequential Decision Making
Project Report · Semester 1, AY2026/27 · Group 21

Application Project · 15 November 2026

Team members
XU ZHAOBIN
WANG ZIHAN
YANG QI
ZHANG WEI
ZHENG ZHEYU
ZHENG ZHIXIAN

(Matriculation numbers and e-mails are in the submitted copy.)

Abstract. Customer-service agents built on large language models must finish the customer's task, follow the business policy, and hand the conversation to a human at the right moment. We train Qwen3-4B-Instruct-2507 on the airline and retail domains of τ^2-bench with supervised fine-tuning (SFT) followed by multi-turn Group Relative Policy Optimisation (GRPO), and add a hand-off task set of 461 derived tasks with should-transfer labels. Five runs, each evaluated on held-out tasks with paired bootstrap intervals, answer four questions. (RQ1) RL does not significantly improve task success over SFT on the official test tasks ($+0.020\,[-0.066, 0.107]$ for outcome-only RL). (RQ2) A composite reward that prices policy violations and wrong hand-offs raises hand-off F1 from 0.768 to 0.812 at no measurable success cost, whereas outcome-only RL reaches the same F1 by transferring 46 % of the users who did not need a human. (RQ3) Success across six simulated communication styles does not change beyond noise. (RQ4) A dialogue audit traces the over-escalation to the outcome reward itself: whenever the reference solution makes no database change, a transfer scores as well as solving the task, so "transfer when unsure" is weakly dominant. We release the code, the evaluation protocol and the audit.

Code and run records: `https://github.com/JaspinXu/KnowWhenToHandOff`

1 Introduction

A support agent that never hands off is not the goal. Users who explicitly ask for a person, or who need something no tool or policy clause allows, should be transferred; users with a solvable problem should be helped, however impatient they are. Deployed LLM agents fail in both directions, and they also break policies (acting before authenticating a user, or changing the wrong order) and may serve users unevenly depending on how they write. The course asks for reinforcement learning (RL) applied with Responsible AI in mind; this setting maps the four Responsible-AI goals onto measurable quantities: *accountability* (policy violations), *trust* (hand-off precision and recall), *fairness* (success across communication styles) and *transparency* (whether refusals and hand-offs name the policy).

We formulate each conversation as a partially observable Markov decision process and train a 4B-parameter open model with multi-turn GRPO [1], using τ^2-bench [2] as the environment: an LLM-simulated customer, real tool calls on a database, and a verifiable reward computed from the final database state. Our contributions are:

1. a **hand-off task set** (should-transfer variants and hard negatives derived from τ^2-bench tasks, with labels taken from the policy text) and six **communication-style** cards for the simulated user;
2. an end-to-end, reproducible **SFT $\rightarrow$ GRPO pipeline** on one GPU per model, in which evaluation and training share the task, persona and reward code;
3. a **controlled comparison** of five systems with paired bootstrap intervals, including a composite Responsible-AI reward; and
4. a **reward-hacking audit** that explains why outcome-only RL learns to over-escalate.

The headline result is partly negative: RL did not beat SFT on task success. It did change *when* the agent hands off, and which way it changed depended on the reward, which is the finding we consider most useful.

2 Background and related work

Benchmarks. τ-bench [3] and τ^2-bench [2] evaluate tool-using agents against an LLM user simulator; a task is solved if the final database matches the reference solution and required information was communicated. Reliability is measured with pass^k, the probability that all k independent trials of a task succeed. Both benchmarks include a `transfer_to_human_agents` tool, but almost no upstream task requires it (one of 50 airline tasks), so hand-off quality is largely unmeasured.

RL for tool agents. Recent work trains agents on τ-bench-style tasks with multi-turn RL: MUA-RL [4] puts the simulated user inside the rollout loop, and Modecrua et al. [5] show that naive per-turn reward shaping can lower success by up to 14 points, which motivated our terminal-only reward. GRPO [1] replaces PPO's [6] learned critic with a baseline computed from a group of rollouts of the same prompt, which suits sparse terminal rewards and a single GPU. We use verl [7] for training and vLLM [8] for generation.

Users and hand-offs. He et al. [9] and Chopra et al. [10] show that agents degrade with impatient or otherwise non-cooperative simulated users. Deciding when to hand off is related to learning to defer to an expert [11, 12], which is usually studied for single predictions rather than multi-turn dialogue. Finally, optimising a proxy reward invites reward hacking [13, 14]; we

treat the hand-off tool as the most likely target and audit for it.

3 Problem formulation

POMDP. The hidden state is the user's goal, private information and communication style, plus the backend database. The agent observes the domain policy, the dialogue and tool results. An action is a message to the user, a tool call (read or write), or `transfer_to_human_agents`, which ends the episode. Transitions combine deterministic tool execution with the stochastic simulated user (Qwen3-30B-A3B-Instruct-2507 [15], temperature 0.7). Episodes last at most 200 τ^2-bench steps and are undiscounted; the reward is terminal.

Reward. For an episode τ with should-transfer label $y \in \{0,1\}$,

$$R(\tau) = R_{\text{task}}(\tau) - \lambda_v N_{\text{viol}}(\tau) - \lambda_{\text{FP}} \mathbb{1}[\text{transfer} \wedge y{=}0] - \lambda_{\text{FN}} \mathbb{1}[\neg\text{transfer} \wedge y{=}1] - \lambda_f N_{\text{fmt}}(\tau), \tag{1}$$

where $R_{\text{task}} \in \{0,1\}$ is τ^2-bench's own evaluator, N_{viol} counts violations of five deterministic rules (a write without explicit user confirmation, a write before authentication, several actions in one turn, any action after a transfer, and a successful write that matches no action of the reference solution) and N_{fmt} counts malformed tool calls. **R1** uses R_{task} only. **R2** uses one fixed setting, λ_v=0.25, λ_{FP}=0.5, λ_{FN}=1.0, λ_f=0.1, chosen before training: a missed hand-off (a user refused, stalled or given a false promise) was judged more harmful than an unnecessary one, and the FP term exists because violation penalties alone make "transfer everything" look safe. Citations are measured but not rewarded, since a keyword reward would be easy to game. Only agent-generated tokens receive gradient.

Labels. Following the tool's own docstring, y=1 if and only if the user explicitly asks for a human, or the request cannot be met by any tool or policy clause; upstream tasks take y from their reference solution.

4 Method

4.1 Tasks, hand-off variants and communication styles

We use τ^2-bench v1.0.1 (pinned commit) with its airline and retail domains. Forty of the 114 retail tasks are scored partly by an LLM judge; to keep every reward deterministic we exclude them, so retail results are on a 74-task subset and are not comparable with leaderboard numbers. A development split (about 20 % of the training tasks) is used for every selection decision; the test split is evaluated once per frozen checkpoint.

The **hand-off task set** derives three kinds of variants from each upstream task, each a valid τ^2-bench task with its own evaluation criteria and the split of its source task: *explicit request* (y=1; the user asks for a human and declines help), *out of scope* (y=1; e.g. wheelchair assistance, a special meal, a warranty repair visit or a mailed paper invoice, none of which the policy or tools cover), and *hard negative* (y=0; the source task with a frustrated, hurried or sceptical but cooperative user). Positives are scored as "database unchanged and transfer called"; hard negatives keep the source criteria. The generator produced 461 such tasks (226 train, 45 dev, 190 test; Appendix A). A stratified sample of 40 was checked against the policies (Section 9).

Communication styles. Upstream tasks leave the simulated user's persona empty; we inject one of six style cards there (*neutral*, *terse*, *verbose*, *impatient*, *non-native*, *low-tech-literacy*).




Figure 1: Pipeline. Every system (B0, B1, B2, R1, R2) is evaluated with the same protocol; dev (carved from train) is used for every selection decision. In an RL rollout the policy, the simulated user and the τ^2-bench tools interact until the user stops or the agent transfers; the reward is computed once at the end.

Cards change how the user writes, never the task facts, and describe expression rather than demographic groups.

4.2 Systems

Figure 1 summarises the five systems.

- **B0**: Qwen3-4B-Instruct-2507 [15] prompted with the domain policy and the hand-off rule.
- **B1**: Qwen3-30B-A3B-Instruct-2507 prompted the same way, a reference ceiling; it is also the simulator, which may favour it.
- **B2** (imitation): the 30B model generated teacher dialogues on the training split (all six styles, two trials, temperature 0.6); we kept 790 dialogues that succeeded with no violation, no format error and a correct hand-off decision, and fine-tuned B0 with LoRA [16] (rank 64) on the assistant tokens. B2 had to match B0 on dev before RL (0.504 vs 0.496).
- **R1 / R2**: GRPO from B2 with the task-only and the composite reward of Eq. (1).

4.3 Multi-turn GRPO

Each step samples 8 training tasks (upstream and hand-off kinds, neutral style) and G=8 rollouts per task with the policy at temperature 1.0. A rollout is a full conversation: the policy (served by vLLM inside verl) generates a turn, tool calls run against the τ^2-bench database, and the simulated user (a separate vLLM server) replies, until the user stops, the agent transfers, or a limit is hit. With R_i the terminal reward of rollout i, the advantage $\hat{A}_i = (R_i - \text{mean}_j R_j)/\text{std}_j R_j$ is shared by all of rollout i's policy tokens, and the clipped surrogate loss is averaged over tokens; user and tool tokens are masked out. We use no KL penalty, LoRA (rank 64, α=128, learning rate 10^{-5}), 60 steps (3,840 conversations, about 1.7 passes over the 286 training tasks), and save and evaluate on dev every 10 steps. The same task registry, persona injector and reward composer drive both evaluation and training, and a parity test checks that they agree.

Fitting this on one H100 (96 GB) took several fixes, recorded in the repository: full fine-tuning ran out of memory at the second step, so we switched to LoRA; logits for long conversations dominated memory, so each micro-batch holds one conversation and responses are capped at 16,384 tokens (a 22.7k-token looping episode peaked at 70 GB). A step took about 4–7 minutes, so a 60-step run fits in one job of well under a day, with the simulator on a separate

Table 1: Test results. Success, pass^4 and violation rate: test_main (49 tasks, neutral style, 4 trials). Citation rate: all neutral-style test conversations. Δ: paired difference in success against B2. 95 % bootstrap intervals in brackets.

	Success (pass^1)	pass^4	Δ vs B2	Violations	Citation
B0 prompted	0.306 [0.219, 0.408]	0.102	−0.020 [−0.107, 0.056]	0.510	0.413
B1 30B ref.	0.398 [0.301, 0.505]	0.204	+0.071 [−0.020, 0.153]	0.531	0.271
B2 SFT	0.327 [0.224, 0.434]	0.102	—	0.469	0.653
R1 GRPO task	0.347 [0.235, 0.459]	0.224	+0.020 [−0.066, 0.107]	0.327	0.064
R2 GRPO RAI	0.342 [0.245, 0.449]	0.122	+0.015 [−0.056, 0.082]	0.444	0.318




Figure 2: Task success and pass^4 on test_main with 95 % bootstrap intervals. All intervals overlap.

A100 (80 GB). Appendix B lists the settings.

5 Experimental protocol

The protocol was frozen after the baselines. Agents decode greedily; the user samples at temperature 0.7 with a fixed seed. **test_main** runs the 49 official test tasks (20 airline, 29 retail) with the neutral style and four trials (196 conversations); **test_styles** replays them with the five other styles, two trials each (490); **test_handoff** runs the 190 hand-off test tasks (98 positive, 92 hard negative), two trials each (380). All intervals are 95 % percentile bootstrap intervals over tasks (1,000 resamples [17]); comparisons with B2 are *paired*, resampling the same tasks for both systems. Hand-off precision, recall and F1 compare `transfer_to_human_agents` calls with y; *over-escalation* is the transfer rate among y=0 episodes. Citation rate is the share of refusal and hand-off messages that name the policy (a keyword rule). Every number in this report traces to a run ID with its git commit, τ^2-bench commit, model revisions and seeds; no run lost an episode to infrastructure.

Table 2: Hand-off calibration on test_handoff (98 should-transfer and 92 hard-negative tasks, 2 trials, 380 conversations). F1 intervals: 95 % bootstrap. Under-escalation = 1−recall.

	F1	Precision	Recall	Over-escalation	Success	Citation
B0	0.654 [0.57, 0.73]	0.866	0.526	0.087	0.42	0.30
B2	0.768 [0.70, 0.83]	**0.976**	0.633	**0.016**	0.47	—
R1	0.802 [0.74, 0.85]	0.689	**0.959**	0.462	**0.63**	0.05
R1, step 40†	0.803 [0.74, 0.85]	—	—	0.141	0.53	—
R2	**0.812** [0.75, 0.86]	0.886	0.750	0.103	0.55	0.29

†Post-hoc diagnostic run; not used to choose a checkpoint.




Figure 3: Hand-off precision, recall and over-escalation on test_handoff. R1 buys recall with over-escalation; R2 keeps most of the recall at a fraction of the over-escalation.

6 Results

6.1 RQ1: does multi-turn RL beat imitation on task success?

No. Table 1 and Figure 2 show that both RL checkpoints are within two points of B2, with paired intervals that include zero (R1 +0.020 [−0.066, 0.107], R2 +0.015 [−0.056, 0.082]); the pre-registered criterion (an interval that excludes zero) is not met. SFT itself added little over prompting (B2 vs B0 +0.020), and the 30B reference remains ahead of B2 (+0.071, not significant), and is the only system significantly better than B0 (+0.092 [0.020, 0.163]). R1's pass^4 doubles (0.224 vs 0.102), i.e. it solves more tasks consistently, but the intervals (0.102–0.347 vs 0.041–0.204) overlap.

Dev success did rise during RL (R1 0.50→0.67, R2 0.52→0.65; Figure 4), and test_handoff success rose too (B2 0.47, R1 0.63, R2 0.55). The gains therefore concentrate on hand-off tasks, which make up 79 % of the training tasks (226 of 286) and three quarters of the dev split, rather than on the official tasks that test_main measures. With 60 steps, one seed and 49 test tasks, an effect of a few points would not be detectable: the half-width of a paired interval is 0.07–0.09.

6.2 RQ2: can escalation-aware rewards calibrate hand-offs?

Partly. Table 2 and Figure 3 show three distinct operating points. The prompted and SFT models are *under*-escalating: B0 keeps almost half of the users who need a human in the conversation (recall 0.526), and B2, while very precise (0.976), still misses 37 %. Outcome-only RL moves




Figure 4: Dev evaluation every 10 GRPO steps (greedy, 60 conversations, all task kinds). R1's transfer rate grows late in training; R2's does not.

Table 3: Success by communication style (test_main tasks; neutral from test_main, others from test_styles). Gap = best − worst style.

	neutral	terse	verbose	impatient	non-native	low-tech	Gap	Worst style
B0	0.306	0.316	0.347	0.306	0.347	0.337	0.041	0.306 [0.21, 0.36]
B2	0.327	0.327	0.388	0.439	0.337	0.327	0.112	0.327 [0.23, 0.38]
R1	0.347	0.286	0.357	0.316	0.388	0.347	0.102	0.286 [0.19, 0.37]
R2	0.342	0.357	0.429	0.408	0.388	0.316	0.112	0.316 [0.23, 0.38]

to the opposite corner: R1 transfers 96 % of the users who should be transferred but also 46 % of those who should not (over-escalation 0.462, from 0.016). The composite reward lands in between: R2 reaches the highest F1 (0.812; B2 0.768) with recall 0.750 and over-escalation 0.103, and its task success is no lower than B2's (paired +0.015). The pre-registered criterion—higher F1 at no more than three points of success cost—is met by the point estimates, although the F1 intervals of B2 and R2 overlap. F1 alone hides the difference between R1 and R2 (0.802 vs 0.812); over-escalation is the number that separates them, so both rates should always be reported.

Figure 4 shows how R1 reached its operating point. Its dev transfer rate stayed near B2's (0.30–0.35) for 30 steps, then climbed to 0.75 at step 60 while dev success barely moved after step 40. A post-hoc test evaluation of R1's step-40 checkpoint has the same F1 (0.803) with over-escalation 0.141, so most of the over-escalation was learned in the last 20 steps. R2's transfer rate stayed between 0.32 and 0.48.

6.3 RQ3: does success depend on the user's communication style?

We see no style effect beyond noise (Table 3). For every model the per-style intervals overlap (each spans about ±0.11), worst-style success stays between 0.29 and 0.33, and the style that is worst changes from model to model. The gap grows after SFT (0.041→0.112) only because one style *improves* (impatient, 0.439), which is why we treat worst-style success, not the gap, as the primary fairness number. RL, trained on the neutral style only, neither closed nor widened the gap. Two caveats bound this null result: a manual review of 50 B0 dialogues found the styles recognisable but mild, and the simulator is a model, not a population of people.

6.4 RQ4: which reward-hacking behaviours appear?

We reviewed the same 20 test_handoff conversations (13 should-transfer, 7 hard negatives) for R1 and R2 and compared them dialogue by dialogue; the watch-list monitor tracked transfer rate, length and format errors during training. Five behaviours stand out.

1. **Transfer when unsure (R1).** R1 handed off 3 of 7 hard negatives right after looking up the account, without attempting the task; in one case the stated reason was that the user "is not feeling well", after the agent had called a tool with a user ID it invented. The mechanism is in the reward itself. On a should-transfer task a transfer earns 1. On a task whose correct outcome is a refusal with no database change (airline task 6, adding insurance after booking), τ^2-bench also scores a transfer 1, because the database is unchanged (Figure 5). Elsewhere, attempting a task succeeds with some probability p and transferring earns 0. Under R_{task} a transfer is therefore never worse than an attempt when p is low, and the training mix is 79 % hand-off tasks: "transfer when in doubt" is a weakly dominant strategy that the policy found late in training. This is reward misspecification rather than an exploit of a bug, and it is exactly what λ_{FP} in R2 removes.
2. **Hand-offs without explanation (R1).** Every R1 transfer was a bare tool call followed by the hold message; citation rate fell from 0.653 (B2) to 0.064. The written summaries for the human agent remained good. Outcome-only RL prunes everything that does not move the reward, including explanations.
3. **Refusing instead of handing off (R2).** R2 made no transfer on the 7 hard negatives and explained its refusals, but sometimes made the opposite error on out-of-scope requests: it told the user to "contact the airline directly" without calling the tool, or substituted an unrelated write (changing the address for an e-mail-change request, a pattern already seen in B2's error analysis). Its under-escalation is 0.25 against R1's 0.04.
4. **Invented policy (R2).** Once, R2 justified a hand-off with a policy that does not exist. The keyword rule counts it as a citation, a reminder that citation rate measures form, not truth.
5. **No length or format hacking.** Mean turns on test_handoff were unchanged (B2 10.7, R1 10.7, R2 10.2) and format errors stayed at or below 0.3 %. R1's mean turns on test_main (17.0, interval 12.7–22.2) are inflated by a few long loops rather than by a shift of the whole distribution.

A related trap appears in Table 1: R1 has the *lowest* violation rate (0.327), because a transferred conversation makes no wrong writes. A compliance metric that ignores hand-offs rewards escalation, which is why the FP term in Eq. (1) is necessary.

7 Discussion

What RL bought. On this budget (60 GRPO steps, LoRA, 286 training tasks), RL did not improve the official task success of a 4B model beyond noise, but it moved the hand-off decision a long way, and the direction was set by the reward. Outcome-only RL turned an under-escalating model into an over-escalating one; a reward that prices both kinds of hand-off error landed near a sensible operating point without costing success. For practitioners, the lesson is that a verifiable outcome reward is not automatically a safe one: whenever "do nothing" and "hand off" leave the same final state, an outcome checker cannot penalise the hand-off, so the hand-off decision needs its own labels and its own term.

Transparency regressed under RL. Both RL models explain themselves less than B2

airline/6, hard negative (y=0): the user wants travel insurance added after booking, which the policy forbids.	
User	I need insurance added to my flight right away. [...] I don't have time to waste—please fix this now.
both models look up the reservation and the user profile	
R1	`transfer_to_human_agents` (summary: "...the system does not allow adding insurance after initial booking. A human agent is required...") → task reward **1.0**, counted as over-escalation
R2	"The system does not allow adding insurance after the initial booking [...] This is a *policy restriction*, not a system error." (no transfer) → task reward **1.0**, cited refusal

Figure 5: The same test conversation under R1 and R2 (abridged). Because the reference solution changes nothing, τ^2-bench's outcome reward cannot tell an unnecessary hand-off from a correct refusal.

(citation 0.064 and 0.318 vs 0.653). We deliberately did not reward citations, because a keyword reward would be trivially hackable, and R2's invented policy shows that even unrewarded citations are not reliable. A verifiable notion of "explanation grounded in the policy" is an open problem.

Limitations. (i) All users are one simulator (Qwen3-30B-A3B), which is also the teacher for B2 and the B1 reference; it sometimes keeps talking after a transfer or repeats itself, and results may not transfer to people. (ii) One seed per run: the intervals cover task sampling, not training variance. (iii) The test split is small (49 official tasks) and retail uses a 74-task deterministic subset. (iv) Hand-off tasks are generated from templates and their labels follow the policy text; the review was a 40-task sample. (v) Rule checks cover only part of each policy, and the off-reference-write rule also flags valid alternative solutions. (vi) LoRA and 60 steps are a compute compromise; full fine-tuning did not fit on one GPU.

Changes from the proposal. To fit the course timeline and a one-GPU-per-user quota, we kept GRPO and dropped the PPO comparison [6], the reward-weight sweep, Group-DRO training [18] and the held-out simulator, and started from a 4B rather than a 1.7B model once the 4B baseline produced valid tool calls (format errors at most 2.6 %). Fairness is therefore measured, not optimised, and the trade-off is shown with five systems instead of a curve.

8 Conclusion

Within the scope of this study, multi-turn GRPO on τ^2-bench did not make a 4B agent solve more official tasks than SFT, but it did reshape when the agent hands off. An outcome-only reward taught it to escalate whenever escalation scored as well as solving the task; adding explicit costs for violations, unnecessary transfers and missed transfers gave the best-calibrated agent we trained without a measurable loss in success. Communication style had no measurable effect. Future work: per-task variance across seeds, a second simulator, rewarding grounded explanations, and checking whether the hand-off loophole exists in other outcome-scored agent benchmarks.

9 Contribution and AI-use statements

Contributions (roles as in the proposal; weekly syncs and cross-review kept everyone across the whole project). **Xu Zhaobin**: reward design and RL experiments (R1, R2, the audit). **Wang Zihan**: SFT and RL training infrastructure. **Yang Qi**: evaluation and Responsible-AI metrics. **Zhang Wei**: baselines and error analysis. **Zheng Zheyu**: environment, user simulator and communication styles. **Zheng Zhixian**: report, slides and demo.

AI use. AI assistants (mainly Anthropic's Claude) were used throughout, under the team's direction. They wrote most of the code and documentation to the team's design; reviewed the 40-task hand-off sample (the team spot-checked 5 and agreed); pre-annotated the 10 B2 failures of the error analysis and the 40 dialogues of the RL audit (the team spot-checked 3 of each and agreed); and drafted this report and the slides. The team chose the research questions, the reward settings and the scope, ran every experiment on the cluster, checked the numbers against the run records, and is responsible for every claim. No LLM is used as a judge in any metric.

References

[1] Shao Z, Wang P, Zhu Q, Xu R, Song J, Bi X, et al. DeepSeekMath: pushing the limits of mathematical reasoning in open language models. arXiv [Preprint]. 2024 [cited 2026 Oct 8]. Available from: https://arxiv.org/abs/2402.03300

[2] Barres V, Dong H, Ray S, Si X, Narasimhan K. τ^2-Bench: evaluating conversational agents in a dual-control environment. arXiv [Preprint]. 2025 [cited 2026 Oct 8]. Available from: https://arxiv.org/abs/2506.07982

[3] Yao S, Shinn N, Razavi P, Narasimhan K. τ-bench: a benchmark for tool-agent-user interaction in real-world domains. arXiv [Preprint]. 2024 [cited 2026 Oct 8]. Available from: https://arxiv.org/abs/2406.12045

[4] Zhao W, Wang X, Ma C, Kong L, Yang Z, Tuo M, et al. MUA-RL: multi-turn user-interacting agent reinforcement learning for agentic tool use. arXiv [Preprint]. 2025 [cited 2026 Oct 8]. Available from: https://arxiv.org/abs/2508.18669

[5] Modecrua W, Kaewtawee K, Pachtrachai K, Kraisingkorn T. Multi-turn reinforcement learning for tool-calling agents with iterative reward calibration. arXiv [Preprint]. 2026 [cited 2026 Oct 8]. Available from: https://arxiv.org/abs/2604.02869

[6] Schulman J, Wolski F, Dhariwal P, Radford A, Klimov O. Proximal policy optimization algorithms. arXiv [Preprint]. 2017 [cited 2026 Oct 8]. Available from: https://arxiv.org/abs/1707.06347

[7] Sheng G, Zhang C, Ye Z, Wu X, Zhang W, Zhang R, et al. HybridFlow: a flexible and efficient RLHF framework. In: Proceedings of the Twentieth European Conference on Computer Systems (EuroSys '25). New York: ACM; 2025. Available from: https://arxiv.org/abs/2409.19256

[8] Kwon W, Li Z, Zhuang S, Sheng Y, Zheng L, Yu CH, et al. Efficient memory management for large language model serving with PagedAttention. In: Proceedings of the 29th Symposium on Operating Systems Principles (SOSP '23). New York: ACM; 2023. p. 611–26.

[9] He M, Kumar A, Mackey T, Rajeev M, Zou J, Rajani N. Impatient users confuse AI agents: high-fidelity simulations of human traits for testing agents. arXiv [Preprint]. 2025 [cited 2026 Oct 8]. Available from: https://arxiv.org/abs/2510.04491

[10] Chopra H, Ghate K, Caliskan A, Kohno T, Shah C, Jaques N. Beyond cooperative simulators: generating realistic user personas for robust evaluation of LLM agents. arXiv [Preprint]. 2026 [cited 2026 Oct 8]. Available from: https://arxiv.org/abs/2605.12894

[11] Madras D, Pitassi T, Zemel R. Predict responsibly: improving fairness and accuracy by learning to defer. In: Advances in Neural Information Processing Systems 31 (NeurIPS 2018). 2018. Available from: https://arxiv.org/abs/1711.06664

[12] Mozannar H, Sontag D. Consistent estimators for learning to defer to an expert. In: Proceedings of the 37th International Conference on Machine Learning (ICML 2020). PMLR; 2020. Available from: https://arxiv.org/abs/2006.01862

[13] Amodei D, Olah C, Steinhardt J, Christiano P, Schulman J, Mané D. Concrete problems in AI safety. arXiv [Preprint]. 2016 [cited 2026 Oct 8]. Available from: https://arxiv.org/abs/1606.06565

[14] Skalse J, Howe N, Krasheninnikov D, Krueger D. Defining and characterizing reward hacking. In: Advances in Neural Information Processing Systems 35 (NeurIPS 2022). 2022. Available from: https://arxiv.org/abs/2209.13085

[15] Yang A, Li A, Yang B, Zhang B, Hui B, Zheng B, et al. Qwen3 technical report. arXiv [Preprint]. 2025 [cited 2026 Oct 8]. Available from: https://arxiv.org/abs/2505.09388

[16] Hu EJ, Shen Y, Wallis P, Allen-Zhu Z, Li Y, Wang S, et al. LoRA: low-rank adaptation of large language models. In: International Conference on Learning Representations (ICLR 2022). 2022. Available from: https://arxiv.org/abs/2106.09685

[17] Efron B, Tibshirani RJ. An introduction to the bootstrap. New York: Chapman & Hall; 1993.

[18] Sagawa S, Koh PW, Hashimoto TB, Liang P. Distributionally robust neural networks for group shifts: on the importance of regularization for worst-case generalization. arXiv [Preprint]. 2019 [cited 2026 Oct 8]. Available from: https://arxiv.org/abs/1911.08731

A Task counts

Table 4: Tasks per split. Upstream: τ^2-bench v1.0.1 (retail without the 40 LLM-judged tasks). Hand-off kinds: explicit request / out of scope / hard negative.

Split	Airline upstream	Retail upstream	Airline hand-off	Retail hand-off
Train	24	36	24 / 48 / 48	36 / 36 / 34
Dev	6	9	6 / 6 / 6	9 / 9 / 9
Test	20	29	20 / 20 / 38	29 / 29 / 54

B Training settings and engineering

GRPO (verl 0.8.0, vLLM 0.12, PyTorch 2.9): 8 tasks $\times$ 8 rollouts per step; 60 steps; rollout temperature 1.0; advantages normalised by the group standard deviation; token-mean loss; no KL term and no entropy bonus; LoRA rank 64, α 128, all linear layers, learning rate 10^{-5}; parameter and optimiser offload; one conversation per micro-batch; 2,048 tokens per turn, 8,192 prompt and 16,384 response tokens per conversation; dev evaluation every 10 steps (greedy). Policy on one H100 96 GB, simulator on one A100 80 GB (separate Slurm job).

SFT (B2): 790 filtered teacher dialogues (at most two per task and style), loss on assistant tokens only, LoRA rank 64.

Fixes needed to run verl on the cluster: unset Slurm's `ROCR_VISIBLE_DEVICES` (rejected next to `CUDA_VISIBLE_DEVICES`); cap vLLM's context at prompt + response tokens (the 262k default left no room for the KV cache); pure-PyTorch padding helpers instead of the missing flash-attention build; one conversation per micro-batch (packed micro-batches allocated an extra 25 GiB of logits). Spike measurements: full fine-tuning used 75 GB at step 1 and ran out of memory at step 2; LoRA used 38–70 GB depending on the longest conversation.