

JavaScript Syntax and Variables

JavaScript Syntax

JavaScript syntax refers to the **rules and structure** used to write JavaScript programs correctly.

Basic Syntax Rules

// Declaring variables

```
let x = 5;
```

```
let y = 6;
```

// Computing values

```
let z = x + y;
```

// This is a comment

JavaScript Values

JavaScript has two main types of values:

1. **Literals** – Fixed values
 2. **Variables** – Values stored in containers
-

JavaScript Literals

Literals are fixed values written directly in the code.

Number Literals

10.50

1001

String Literals

Strings are written inside quotes:

"John Doe"

'John Doe'

JavaScript Keywords

Keywords are reserved words that have special meanings in JavaScript.

Example:

```
let x = 5;
```

```
const fname = "John";
```

⚠ Keywords are **case-sensitive**

let is valid, but LET or Let is not.

JavaScript Variables

Variables are **containers used to store data values**.

Example:

```
let x;
```

```
x = 6;
```

JavaScript Identifiers

Identifiers are names given to variables.

Rules:

- Must start with a letter, _, or \$
- Can contain digits after the first character
- Cannot be JavaScript keywords
- Case-sensitive

Valid examples:

```
let firstName;
```

```
let _age;
```

```
let $price;
```

JavaScript Operators

Operators are used to perform operations.

Assignment Operator

```
let x = 5;
```

Arithmetic Operators

```
let sum = x + y;
```

```
let product = 5 * 10;
```

JavaScript Expressions

An expression is a combination of values, variables, and operators that produces a result.

Examples:

```
(5 + 6) * 10
```

```
x * 10
```

```
"John" + " " + "Doe"
```

JavaScript Case Sensitivity

JavaScript is case-sensitive.

```
let lastName = "Doe";
```

```
let lastname = "Peterson";
```

These are **different variables**.

JavaScript Naming Conventions (Camel Case)

- Hyphen case (not allowed): first-name
 - Underscore: first_name
 - Pascal Case: FirstName
 - Camel Case (recommended): firstName
-

JavaScript Statements

Statements are instructions executed by JavaScript.

Example:

```
let x = 5;
```

```
let y = 6;
```

```
let z = x + y;
```

JavaScript Programs

A JavaScript program is a **sequence of statements** executed by the browser in order.

Semicolons

Semicolons separate statements.

```
let a = 5;
```

```
let b = 6;
```

```
let c = a + b;
```

Semicolons are optional but **highly recommended**.

JavaScript White Space

JavaScript ignores extra spaces.

```
let person = "Hege";
```

```
let person="Hege";
```

Best practice:

```
let x = y + z;
```

Line Length & Line Breaks

Avoid long lines. Break lines after operators.

```
document.getElementById("demo").innerHTML =  
"Hello Dolly!";
```

JavaScript Code Blocks

Code blocks group statements using { }.

```
function myFunction() {  
    document.getElementById("demo1").innerHTML = "Hello";  
    document.getElementById("demo2").innerHTML = "How are you?";  
}
```

JavaScript Comments

Single-Line Comment

```
// This is a comment
```

```
let x = 5; // Assign value
```

Multi-Line Comment

```
/*
```

This is a multi-line comment

used to explain code

```
*/
```

JavaScript Variables (Detailed)

Ways to Declare Variables

Modern JavaScript:

- let
- const

Old (Not Recommended):

- var
 - Automatic declaration
-

Using let

```
let x = 5;
```

```
let y = 6;
```

```
let z = x + y;
```

- Block scoped
 - Cannot be redeclared
 - Can be reassigned
-

Using const

```
const price1 = 5;
```

```
const price2 = 6;
```

```
let total = price1 + price2;
```

- Block scoped
 - Cannot be redeclared
 - Cannot be reassigned
 - Must be initialized
-

Using var (Not Recommended)

```
var x = 5;
```

```
var y = 6;
```

```
var z = x + y;
```

Problems with var:

- No block scope
 - Can be redeclared
 - Hoisted
-

JavaScript Data Types

Basic data types:

```
const pi = 3.14;
```

```
let name = "John";
```

```
let answer = 'Yes';
```

One Statement, Multiple Variables

```
let person = "John", car = "Volvo", price = 200;
```

Assignment Operator

= assigns values, it is not a comparison operator.

```
x = x + 5;
```

Constant Arrays

```
cars = ["Audi"];
```

Constant Objects

```
car = {type:"Volvo"};
```
