Weld Inspection

Document Information:

Operator Name:	Project No:	
Drawing No:	Rev No:	**Quantity**:
First-Off Fitter Inspector Initials:	**Date:**	
First-Off Welded Inspector Initials:	**Date:**	
Final Inspection Sign-Off	**Date:**	

Welding Parameters:

Welding Process: **GMAW (Gas Metal Arc Welding)**	
Welding Rod Type: **0.045 - AWS A5.18 ER70S-6**	Shielding Gas Used: **. Stargold C15** **. Ar 85 / CO2 15**
Batch No:	Welding Machine No:
Material Temperature (surface):	Device No:

Table 5.3 (Concluded)

Thickness of thickest part at point of welding, mm (in)	Welding process: SMAW with other than low-hydrogen electrodes; FCAW and MCAW without diffusible hydrogen designators	SMAW low-hydrogen electrodes; FCAW and MCAW with diffusible hydrogen designators; GMAW and SAW		SMAW low-hydrogen electrodes; FCAW and MCAW with diffusible hydrogen designators; GMAW and SAW mild or alloy steel electrodes
1	2	3	4	5
	ASTM A 529 A 570 all grades A 572 Gr. 42, 50 A 607* Gr. 45, 50	ASTM A 529 A 570 all grades A 572 Gr. 42, 50 A 588 A 606 A 607 all grades A 618 A 633 Gr. A, C, D A 710 Gr. A Class 2 >50 mm A 913 Gr. 50 A 992/A 992M	ASTM A 572 Gr. 60, 65 A 633 Gr. E A 710 Gr. A Class 2 ≤50 mm A 710 Gr. A Class 3 >50 mm A 913 Gr. 60, 65	ASTM
mm (in) Up to 20 incl. Up to 3/4 incl. Over 20 to 40 Over 3/4 to 1-1/2 Over 40 to 60 Over 1-1/2 to 2-1/2 Over 60 Over 2-1/2	None‡ 65°C (150°F) 107°C (225°F) 150°C (300°F)	None‡ 10°C (50°F) 65°C (150°F) 107°C (225°F)	10°C (50°F) 60°C (150°F) 110°C (225°F) 150°C (300°F)	10°C (50°F) 50°C (125°F) 80°C (175°F) 110°C (225°F)

Visual Weld Defects:

Surface Cracks,	Porosity,	Misalignment
Spatters,	Incomplete weld	Cold Lap
Over-weld	Under- Weld	Undercut

Visual Weld Defects Corrected:

Comments:

Dimension Inspections:

Drawing Dimension #	Drawing Dimension	Actual Measurement	Inspection Device Used
Straightness:			
Flatness:			
Angle:			
Other Dimensions:			

Operator Sign:	**Date:**