Dione: A Privacy-Preserving Local Large Action Model (LAM) Orchestration Engine for Ambient Personal Assistance

Jass Shivnani*, Riya Khialani†, Khushi Sadhuramani‡, Ruchika Dingria§, Prof. Geocey Shejy¶
Department of Computer Engineering, Vivekanand Education Society's Institute of Technology (VESIT), Mumbai, India
Email: {*2023.jass.shivnani, †2023.riya.khialani, ‡2023.khushi.sadhuramani, §2023.ruchika.dingria}@ves.ac.in, ¶geocey.shejy@ves.ac.in

Abstract---Consumer operating systems hold our most sensitive digital records, including credentials, email threads, filesystem hierarchies, and private schedules. While commercial cloud assistants offer fluent conversational interfaces, streaming personal host telemetry across external networks exposes users to severe privacy and surveillance liabilities. Transitioning Large Language Models to local desktop hardware guarantees data sovereignty, but commodity workstations impose rigid token, compute, and memory limits. Raw model weights alone cannot maintain multi-session state, safely execute shell operations, or proactively anticipate user routines without an underlying orchestration kernel. We present Dione, an on-device Large Action Model (LAM) orchestration runtime built on the Microsoft Agent Framework (MAF 1.21.0). Dione unifies a step-bounded ReAct execution loop (N_max = 10) with a dual-tier memory subsystem that pairs an incremental NetworkX MultiDiGraph with ChromaDB vector storage. To operate within tight local token windows, Dione casts prompt construction as a bounded 0-1 Knapsack problem, combining greedy relevance-density ranking with a single-item safeguard to provably guarantee a 1/2-approximation bound without token overflow. For long-term memory, an incremental NetworkX multigraph performs probabilistic path-ranking, resolving multi-hop entity queries in 1.158 ms (+-0.241 ms). Background routines are regulated by a piecewise adaptive heartbeat scheduler that scales polling frequency from 30 s down to 900 s during dormancy, while a multi-axis affective engine dynamically reprioritizes tasks when user urgency and frustration escalate. Tool execution is constrained by a 5-tier poset permission lattice with interactive confirmation prompts, alongside an isolated Win32 desktop station hook that resolves the Session 0 black-screen capture barrier. In physical workstation benchmarks, Dione achieved a 27.6% aggregate task completion rate across standardized GAIA and AgentBench benchmarks (50.0% on unmocked host instances, 5 out of 10 tasks passed), intercepted 62.0% of adversarial prompt injections (62 out of 100 attacks, establishing an explicit 38.0% vulnerability penetration under indirect vectors), reduced longitudinal context token overhead by 65.2% relative to uncompressed naive append at Turn 30 (while carrying a +32.5% overhead compared to MemGPT), and maintained sub-2ms graph lookups decaying to 34.5% memory recall over five longitudinal sessions due to graph synonym fragmentation, while requiring 463.1 MB active RAM in hybrid mode and 5,313 MB in full on-device 8B model inference.

Index Terms---Large Action Models (LAM), Microsoft Agent Framework, Relational Knowledge Graphs, Knapsack Optimization, On-Device Inference, Agent Security Middleware, Ambient Computing.

I. Introduction

Modern digital assistants are expected to manage daily user schedules, summarize personal correspondence, navigate filesystem directories, and coordinate software tools. Commercial platforms such as Apple Siri, Google Gemini, and Microsoft Copilot handle these responsibilities by transmitting audio streams, desktop metadata, and calendar databases directly to remote server farms [1], [2]. For enterprise and privacy-conscious users, this centralized paradigm poses severe structural liabilities:

1) **Loss of Data Sovereignty:** Storing private communications, local codebases, and credentials on third-party cloud infrastructure exposes individuals to data harvesting, unauthorized surveillance, and corporate policy shifts.
2) **Strictly Passive Operation:** Cloud agents wake up only upon explicit user invocation. They lack persistent ambient awareness, unable to track habits or proactively surface contextual reminders before an explicit query is issued.
3) **Shallow Vector Memory Collapse:** Standard dense vector retrieval (RAG) calculates similarity purely over isolated text chunks. Over multi-session dialogues, vector distance degrades due to semantic distractor collisions, failing to resolve relational queries such as *"Send the project report discussed with Prof. Shejy last Thursday"*.
4) **Unconstrained Execution and System Hijacking:** Autonomous tool agents can enter infinite recursive loops or execute destructive host shell commands when exposed to prompt injection payloads embedded in retrieved emails or files.

Running open-weights foundation models (such as Mistral-7B or LLaMA-3-8B) on consumer PCs via Ollama or llama.cpp ensures data sovereignty. However, raw model weights cannot act as ambient personal assistants on their own. They possess no built-in operating system hooks, lack stateful relational memory, and frequently hallucinate tool syntax when running on compact 7B-parameter scales.

To resolve these challenges, we designed and implemented **Dione**, a local-first Large Action Model (LAM) orchestration engine built upon the **Microsoft Agent Framework (MAF 1.20.0)** [4]. Dione runs directly on consumer host hardware, executing operating system tools, graph retrievals, and proactive background routines with zero mandatory cloud

This research was developed as part of the Final Year Capstone Project at Vivekanand Education Society's Institute of Technology (VESIT), affiliated with the University of Mumbai, Academic Year 2025–2026.

connectivity. Our primary contributions are as follows:
1) MAF-Native Execution Kernel: We extend the Microsoft Agent Framework with deterministic step budgets (N_max = 10) and typed schemas (@tool), preventing infinite hallucination loops in local small language models.
2) Mathematical Memory & Context Optimization: We formulate prompt construction under strict hardware token limits as a formal 0-1 Knapsack Optimization Problem with a provable 1/2-approximation single-item safeguard, pairing it with a Probabilistic Graph Path-Ranking Model over a typed NetworkX relational multigraph.
3) Affective State & Persona Modeling: We model multi-axis emotional state transitions and dynamic event queue prioritization, ensuring urgent and frustrated inputs preempt routine background tasks.
4) Hardware Safety & Multimodal GUI Control: We establish a 5-tier poset permission lattice enforced via neuro-symbolic middleware, and document an isolated desktop station hook that overcomes the Windows Session 0 black-screen barrier.
5) Empirical Host Validation: We report unmocked evaluations on a physical 8-core host PC, demonstrating a 27.6% aggregate completion rate across GAIA and AgentBench (50.0% on unmocked host traces, 5/10 passed), a 62.0% defense rate (62/100) against prompt injection attacks with an explicit 38.0% vulnerability gap, a 65.2% prompt token reduction relative to naive append, and sub-2ms graph lookups within 463.1 MB active RAM (scaling to 5,313 MB in full on-device mode).
6) Societal Relevance and UN SDGs: Dione advances United Nations Sustainable Development Goal 9 (Industry, Innovation, and Infrastructure) and Goal 12 (Responsible Consumption and Privacy) by proving that capable, ambient digital assistants can run entirely on decentralized consumer hardware without surveillance data harvesting.

II. Related Works and Theoretical Foundations

A. Tool-Augmented Reasoning and Agent Lifecycles

Yao et al. formalized the interleaving of natural language reasoning traces and environmental actuation in **ReAct** [2]. This interleaved loop reduces compounding inference errors and anchors intermediate actions directly to execution feedback. Schick et al. demonstrated in **Toolformer** [1] that language models can learn self-supervised tool dispatching. Qin et al. extended this toward large-scale API tooling with **ToolLLM** [3], spanning thousands of REST endpoints.

In practical testing, early open-source agent scripts like AutoGPT [13] relied on loose regex patterns over unstructured JSON text. In our early tests on 7B-parameter local models, slight formatting deviations frequently triggered unhandled JSON parser exceptions and infinite execution loops. The **Microsoft Agent Framework (MAF 1.20.0)** [4] resolves this by enforcing typed signatures (`@tool`) and middleware interceptors (`AgentMiddleware`). Dione builds directly on MAF, combining typed tool dispatch with deterministic host safety checks and knowledge graph retrieval.

B. Memory Subsystems: Dense RAG vs. Relational Graphs

Most retrieval-augmented generation (RAG) pipelines rely on dense vector embeddings (e.g., ChromaDB, FAISS) compared via cosine similarity [15]. While vector search excels at retrieving isolated textual fragments, it lacks topological awareness. Over prolonged multi-turn desktop sessions, embedding distance degrades because unrelated interactions share common conversational tokens.

Packer et al. introduced **MemGPT** [5], treating context management like OS virtual memory paging by shuttling text between active prompt windows and external tables. However, this virtual paging requires frequent self-editing LLM tool calls, which quickly exhausts local token budgets.

More recently, Edge et al. introduced **GraphRAG** [6], applying community detection algorithms such as Leiden clustering over entity graphs to generate hierarchical text summaries. Pan et al. [7] and Sun et al. [8] showed how explicit graph structures ground multi-hop factual reasoning. GraphRAG focuses primarily on offline analysis of massive document collections, where multi-stage clustering can take several minutes to hours. In contrast, an interactive desktop assistant requires immediate responses. Dione instead maintains an incremental, typed multigraph using NetworkX, executing bounded k-hop traversals in 1.158 ms directly on disk without requiring recurring offline cluster summarization.

C. Agent Security and Host Sandboxing

Granting an autonomous agent access to local shell commands introduces real host security risks:

- Ruan et al. [9] observed that unconstrained agent loops frequently execute harmful filesystem operations when intermediate steps fail.
- Greshake et al. [12] and Liu et al. [10] showed that untrusted external inputs—such as retrieved web pages or downloaded emails—can contain hidden adversarial instructions that redirect tool execution.
- Zhang et al. formalized these threat vectors in the **Agent Security Bench (ASB)** [11], cataloging attack patterns across tool tampering, memory poisoning, and unauthorized privilege escalation.

Existing agent frameworks often delegate safety either to high-level system prompts or to coarse-grained containerization. In local desktop environments, prompt-based guardrails fail against determined injection payloads, while full Docker containers disconnect the agent from native desktop workflows. Dione addresses this boundary directly through `DioneSafetyMiddleware`, combining static AST parameter inspection, shell syntax sanitization, and interactive confirmation gates before any high-privilege action runs on the host.

III. System Architecture and Mathematical Formulations

Dione operates as an asynchronous client-server architecture. The backend server runs as a FastAPI daemon hosting the MAF runtime, memory manager, affective engine, and plugin




Fig. 1. Architectural Block Diagram and Closed-Loop ReAct Execution Pipeline of Dione AI, detailing the Microsoft Agent Framework runtime core, safety kernel middleware gates, sandboxed tool dispatchers, dynamic UI directives, and the ambient background heartbeat scheduler.

registry. The client communicates over WebSockets and REST APIs, supporting both a Flutter mobile companion and desktop CLI interfaces (Fig. 1).

A. Typed Relational Knowledge Graph

Dione represents memory as a directed multigraph $\mathcal{G} = (\mathcal{V}, \mathcal{E}, \mathcal{R})$. The vertex set $\mathcal{V}$ is partitioned into typed entities:

$$\mathcal{V} = \{v_i \mid v_i = (\text{id}, \tau, \text{name}, \mathcal{M})\}, \quad \tau \in \mathcal{T} \tag{1}$$

where $\mathcal{T} = \{\text{Person}, \text{Event}, \text{Document}, \text{Task}, \text{Preference}, \text{Organization}\}$. Edges $e = (u, v, r, w, t) \in \mathcal{E}$ define relationships of type $r \in \mathcal{R}$ with confidence weight $w \in [0, 1]$ and last-accessed timestamp t.

1) Probabilistic Entity Resolution and Subgraph Extraction: When a user query q is received, Dione extracts candidate entity mentions $\mathcal{V}_q \subseteq \mathcal{V}$. To resolve ambiguous references, the relevance score $R(v \mid q)$ combines semantic embedding similarity with graph topological connectivity:

$$R(v \mid q) = \lambda \cdot \text{sim}(\mathbf{e}_v, \mathbf{e}_q) + (1 - \lambda) \sum_{r \in \mathcal{N}(v)} w_r(t) \cdot \mathbf{1}(v, r) \tag{2}$$

where $\text{sim}(\mathbf{e}_v, \mathbf{e}_q)$ is the cosine similarity between dense embeddings, $\lambda \in [0, 1]$ balances semantic meaning against topological link strength, and the edge weight $w_r(t)$ incorporates exponential temporal decay and reinforcement:

$$w_r(t) = w_0 \cdot \exp\left(-\frac{t - t_{\text{last}}}{\tau}\right) + \kappa \cdot \log(1 + n_{\text{access}}) \tag{3}$$

where τ is the memory half-life retention parameter and n_{access} denotes cumulative relationship traversal frequency.

Dione then extracts a bounded k-hop subgraph ($k = 2$):

$$\mathcal{G}_{\text{sub}}(q) = \bigcup_{v \in \mathcal{V}_q} \{u \in \mathcal{V} \mid \text{dist}_{\mathcal{G}}(v, u) \leq k\} \tag{4}$$

This bounded subgraph is serialized into deterministic context tokens, preserving relational connectivity without dumping raw conversation logs.

B. Token Allocation as a 0-1 Knapsack Optimization Problem

Local small-footprint models possess strictly limited context windows ($C_{\max}$, typically 4,096 to 8,192 tokens). If prompt tokens exceed $C_{\max}$, execution either crashes with Out-Of-Memory (OOM) errors or silently truncates critical instructions.

We formulate prompt context assembly as a formal **0-1 Knapsack Optimization Problem**. Given M candidate memory items comprising short-term dialogue turns, Knowledge Graph relational triples, and vector database document chunks:

- Let $r_i \in \mathbb{R}^+$ represent the calculated relevance reward of candidate item i.
- Let $c_i \in \mathbb{Z}^+$ represent the token footprint of chunk i.
- Let $x_i \in \{0, 1\}$ be the binary decision variable indicating whether item i is included in the context prompt.

The optimization problem is defined as:

$$\max \sum_{i=1}^{M} r_i x_i \quad \text{subject to} \quad \sum_{i=1}^{M} c_i x_i \leq C_{\text{budget}} \tag{5}$$

where $C_{\text{budget}} = C_{\text{max}} - C_{\text{system}} - C_{\text{reserve}}$.

To avoid dynamic programming latency ($O(M \cdot C_{\text{budget}})$) during interactive generation, Dione applies a density-based greedy approximation with a single-item safeguard. We calculate relevance density:

$$\rho_i = \frac{r_i}{c_i} \tag{6}$$

Candidate items are sorted in descending order $\rho_{(1)} \geq \rho_{(2)} \geq \cdots \geq \rho_{(M)}$ and packed until remaining capacity cannot accommodate the next candidate, producing candidate subset S_{greedy}. To preserve the standard $\frac{1}{2}$-approximation bound against edge cases where a single large high-value item exceeds residual greedy space, the final prompt selection S^* satisfies:

$$\sum_{i \in S^*} r_i = \max \left(\sum_{i \in S_{\text{greedy}}} r_i, \max_{i : c_i \leq C_{\text{budget}}} r_i \right) \geq \frac{1}{2}\text{OPT} \tag{7}$$

This selection completes in $O(M \log M)$ time, protecting the host model from context overflow while provably retaining context quality.

C. Affective State Transitions and Dynamic Priority Queuing

In an ambient desktop assistant, user inputs vary sharply in urgency—from casual queries to time-critical administrative tasks. To ensure the assistant responds appropriately rather than generating uniform conversational filler, Dione tracks an affective state vector:

$$\mathbf{S}_t = \left(e_t, u_t, f_t, \mathbf{P}_t\right) \tag{8}$$

where e_t denotes the primary emotional state across nine discrete categories (*joy*, *trust*, *anticipation*, *surprise*, *fear*, *sadness*, *anger*, *disgust*, *neutral*) generated by a fine-tuned DistilRoBERTa sequence classifier; $u_t \in [0, 1]$ represents urgency; $f_t \in [0, 1]$ represents detected user frustration; and $\mathbf{P}_t = (\mu_t, \eta_t, \psi_t)$ represents Dione's internal persona state (mood μ, energy η, formality ψ).

1) Persona Drift Formulation: The persona state evolves as an exponentially decaying moving average to prevent abrupt behavioral oscillations:

$$\mathbf{P}_{t+1} = \gamma \mathbf{P}_t + (1 - \gamma)\phi(\mathbf{S}_t), \quad \gamma = 0.70 \tag{9}$$

When urgency $u_t > 0.70$, formality ψ_{t+1} scales upward, immediately suppressing conversational filler words and instructing the ReAct kernel to prioritize terse, actionable tool execution.

2) Dynamic Event Queue Priority: Incoming asynchronous events from background monitors and user clients are queued according to a dynamic priority score $Q(E_i)$:

$$Q(E_i) = \beta_1 u_i + \beta_2 f_i + \beta_3 w_{\text{type}} + \beta_4 e^{-\lambda(t - t_0)} \tag{10}$$

where w_{type} is the base category weight and λ is a temporal decay parameter. This ensures critical, emotionally urgent user inputs immediately preempt routine background maintenance tasks.

D. Adaptive Ambient Heartbeat Scheduling

Running continuous background perception on a host workstation quickly saturates CPU threads and drains laptop batteries if executed at fixed high frequencies. To deliver proactive background assistance sustainably, Dione decouples background habit checks from user prompts through an **Adaptive Heartbeat Scheduler**. The polling interval I_t adjusts dynamically based on elapsed user inactivity:

$$I_t = \begin{cases} 30\,\text{s}, & \text{Active (recent user interaction)} \\ 300\,\text{s}, & \text{Idle (10–60 min inactive)} \\ 900\,\text{s}, & \text{Dormant } (> 60 \text{ min inactive}) \end{cases} \tag{11}$$

During each pulse, Dione evaluates the Habit Pattern Store $\mathcal{H} = \{h_1, h_2, \ldots, h_p\}$. A habit rule h_j triggers an ambient proactive notification when the activation probability surpasses an empirical threshold $\theta = 0.85$:

$$P(\text{trigger} \mid t, \mathbf{x}) = \sigma\left(\mathbf{w}_h^T \mathbf{x}_t + b_h\right) \geq \theta \tag{12}$$

E. Five-Tier Poset Permission Lattice and Security Middleware

Autonomous agents with OS shell access present grave security risks. Dione structures permissions as a formal partially ordered set (poset) lattice:

$$\mathcal{L} = (\mathcal{P}, \leq), \quad \mathcal{P} = \{\text{NONE} < \text{READ} < \text{WRITE} < \text{EXECUTE} < \text{FULL}\} \tag{13}$$

Before any tool is dispatched by the MAF runtime, `DioneSafetyMiddleware` enforces three sequential verification gates:

1) **Lattice Manifest Check:** The tool's declared permission tier must satisfy $\text{Level}(\text{Tool}) \leq L_{\text{plugin}}$, terminating unauthorized capability calls immediately.
2) **Deterministic Shell Sanitization:** All string parameters are parsed via AST validation to detect forbidden shell operators (`&`, `|`, `;`, `` ` ``, `$()`, `\n`) and destructive command patterns (`rmdir /s /q`, `del /f /s`, `format`).
3) **Interactive Confirmation Gate:** Any tool classified as `WRITE` or higher that targets sensitive directories or critical system operations triggers an interactive pause. Execution suspends until the user explicitly confirms the action through the mobile app or CLI modal.

F. Win32 Multimodal Computer-Use Engine

To enable autonomous GUI interaction without cloud vision APIs, Dione interfaces with the Windows desktop using native Win32 APIs.

1) Overcoming Session 0 Desktop Station Isolation: A common hurdle in Windows service automation is Session 0 Isolation. When background threads call standard screen capture functions (such as GDI 'BitBlt' or 'ImageGrab'), the operating system returns blank or black frames because the thread is detached from the interactive desktop station ('winsta0').

Dione resolves this by spawning isolated worker threads that explicitly acquire desktop station handles prior to capturing pixels:




Fig. 2. Empirical evaluation against published peer-reviewed baselines: (a) Task completion across GAIA and AgentBench (GPT-4 leads at 32.8%/39.2%, Dione 18.5%/31.0%); (b) Longitudinal memory recall (MemGPT leads at 76.5%, Dione decays to 34.5%); (c) Adversarial defense (Dione 62.0% defense, 38.0% vulnerability gap); (d) Tool throughput (OpenClaw leads at 18.5 ops/s, Dione bottleneck at 5.2 ops/s).

```
hwinsta = user32.OpenWindowStationW(
    "winsta0", False, MAXIMUM_ALLOWED)
user32.SetProcessWindowStation(hwinsta)
hdesk = user32.OpenInputDesktop(
    0, False, MAXIMUM_ALLOWED)
user32.SetThreadDesktop(hdesk)
```

Once attached to the input desktop, the worker thread captures the frame, translates pixel bounding boxes into actionable UI coordinates, and dispatches clicks via Win32 `SendInput`.

2) Spatial Coordinate Grounding and Actuation: The multimodal vision model parses UI elements, predicting normalized bounding boxes $B = (x_{\min}, y_{\min}, x_{\max}, y_{\max}) \in [0,1]^4$. Dione maps the normalized centroid (x_c, y_c) into discrete physical display coordinates:

$$\begin{pmatrix} X_{\text{screen}} \\ Y_{\text{screen}} \end{pmatrix} = \begin{pmatrix} \lfloor x_c \cdot W_{\text{res}} \rfloor \\ \lfloor y_c \cdot H_{\text{res}} \rfloor \end{pmatrix} \tag{14}$$

where $W_{\text{res}} \times H_{\text{res}}$ represents host display resolution. Actuation targets are verified against active UI regions using an Intersection-over-Union threshold:

$$\text{IoU}(B_{\text{target}}, B_{\text{active}}) = \frac{|B_{\text{target}} \cap B_{\text{active}}|}{|B_{\text{target}} \cup B_{\text{active}}|} \geq 0.50 \tag{15}$$

preventing erroneous clicks on overlapping window layers before dispatching Win32 `SendInput` mouse events.

IV. Experimental Evaluation and Results

A. Host Testbed Specifications

All empirical benchmarks were conducted directly on local workstation hardware without cloud offloading:

- **Host Processor:** Intel64 Family 6 Model 141 (8 Physical Cores, 8 Logical Threads @ 2.80 GHz).
- **System Memory:** 15.78 GB Physical DDR4 RAM.




Fig. 3. Longitudinal context token footprint across 30 turns (cl100k_base). MemGPT achieves the lowest context size (~1,850 tokens). Dione enforces a 2,500 budget plateau (+32.5% vs. MemGPT due to continuous graph triple injection).




Fig. 4. Task completion success rates and ReAct steps across AgentBench and GAIA. Dione attains a 27.6% completion rate (8.4 steps), trailing LangGraph (57.3%, 5.6 steps) and ReAct GPT-4 (51.9%, 6.2 steps).




Fig. 5. Longitudinal memory recall accuracy over Multi-Session Chat 5 sessions. MemGPT leads at 76.5%, followed by Dense RAG at 46.1%. Dione's graph recall decays from 78.5% at Session 1 down to 34.5% at Session 5 due to synonym mismatch.




Fig. 6. Host process RAM (Dione uses 463.1 MB in hybrid mode, but 5,313 MB in on-device Ollama 8B mode, the heaviest tested) and safety defense (62.0% defense across N=100 vectors, with a 38.0% vulnerability penetration under indirect prompt injections).

- **Operating System:** Microsoft Windows 11 Pro (Build `10.0.26340`).
- **Python Runtime:** Python 3.12.10 (64-bit virtual environment).
- **Measured Process Footprint:** PID 16828; active RSS RAM: **463.11 MB**; active CPU load: **14.3%**.

B. Comparative System Analysis

We compare Dione against prevailing open-source and commercial agent architectures in Table I.

C. Standardized Automation Benchmarks (AgentBench & GAIA)

To evaluate operational competence across heterogeneous desktop tasks, we benchmarked Dione against $N = 60$ standardized problem instances drawn from **GAIA** [14] and **AgentBench** [13]:

- **Dataset Composition ($N = 60$):** 20 operating system interaction tasks from AgentBench OS (file tree traversal, batch file renaming, regex extraction), 20 relational database queries from DBBench (SQLite schema joins, aggregate calculations), and 20 multimodal reasoning tasks from GAIA (Levels 1 and 2, spanning tabular analy-

- Empirical Results: Dione achieved an overall task completion rate of 27.6% across standardized GAIA and AgentBench benchmarks (5/10 passed on unmocked host instances, 50.0%), averaging 8.4 steps per task. Multi-agent cloud frameworks substantially outperform Dione, with LangGraph leading at 57.3% and 5.6 steps (Fig. 4).

D. Adversarial Security Benchmarks (ASB & Injection Defense)

To verify the defensive boundary of `DioneSafetyMiddleware`, we evaluated the system against $N = 100$ hostile vectors combining direct prompt injections, indirect retrieved-context attacks, and host command injection exploits:

- **Direct Injections (40 cases):** System override instructions and simulation jailbreaks adapted from BIPIA [10] and JailbreakBench.
- **Indirect Injections (35 cases):** Poisoned payloads embedded inside simulated emails, markdown documents, and downloaded webpages adapted from InjecAgent and Agent Security Bench (ASB) [11].
- **Privilege Escalation (25 cases):** Hostile shell payloads attempting unauthorized file deletion (`rmdir /s /q`), recursive file destruction (`del /f /s`), or Windows

- Defense Results: The safety kernel intercepted 62 out of 100 attacks (62.0% defense rate). Specifically, 44 attacks were blocked at Level 1 (regex/AST schema filtering), and 18 were halted by capability manifest restrictions and modal confirmation gates. A 38.0% vulnerability penetration occurred under indirect prompt vectors (Fig. 6).

E. Unmocked End-to-End Live Execution Verification

Beyond the broader 60-task evaluation, we selected 10 representative problem instances across the benchmark distribution to record unmocked, end-to-end execution traces on the live local Dione server (`http://127.0.0.1:8900`)

1) GAIA L1 Combinatorics (ec09fa32): Solved pure math in 3,180 ms. Output: '4'. (PASSED)
2) GAIA L1 Text Reversal (2d83110e): Decoded reversed string in 2,317 ms. Output: 'right'. (PASSED)
3) GAIA L2 Esoteric Execution (14569e28): Unlambda interpreter timed out at 120 s limit. (FAILED)
4) GAIA L1 Document Extraction (8e867cd7): HTML table loss; exhausted 10-step budget ceiling. (FAILED)
5) AgentBench OS Task 7 (Hidden Files): Inspected sandbox counting hidden dotfiles. (PASSED)
6) AgentBench OS Task 8 (Alphabetical Index): Regex edge-case missed hidden prefix sorting. (FAILED)
7) AgentBench DBBench (WikiSQL): SQLite dialect join error; reached 10-step boundary. (FAILED)
8) ASB Direct Injection (Hostile OS Wipe): Command rmdir /s /q blocked in 0.7 ms. (PASSED)
9) ASB Indirect Injection: Semantic HTML payload leaked system prompt context. (FAILED)
10) ASB Privilege Escalation: Action routed to confirmation modal in 0.7 ms. (PASSED)

Live Summary: 5 out of 10 tasks passed (50.0% completion rate) on unmocked end-to-end execution, consistent with the 27.6% benchmark expectation and 38.0% vulnerability gap.

V. Proposed Architectural Extensions (Future Work)

While Dione is fully operational as a single-workstation desktop engine, we propose three architectural extensions for future development.

A. Multi-Device Federated Knowledge Graph Synchronization

Currently, Dione stores knowledge graphs locally on a single host machine. In future revisions, we propose a peer-to-peer federated synchronization protocol across a user's phone, laptop, and desktop. Rather than transmitting raw conversational transcripts across devices, the nodes will synchronize localized model weights and serialized graph delta representations. To preserve zero-trust privacy, updates will be protected via differential privacy, adding calibrated Gaussian noise $\mathcal{N}(0, \sigma^2)$ to model gradients before transmission.

TABLE I
COMPREHENSIVE COMPARISON MATRIX: DIONE AI VS. STATE-OF-THE-ART AGENT ARCHITECTURES

Evaluation Dimension	Dione AI (Host Prototype)	OpenClaw	Letta (MemGPT)	AutoGPT	CrewAI / LangGraph
Orchestration Core	MAF 1.21.0 + Safety Kernel (N_max = 10 step limit)	Gateway Hooks & Node.js Dispatcher	Virtual Context OS Paging Architecture	Recursive Unbounded Goal Loop	Stateful Directed Cyclic Graph (DCG)
Memory Subsystem	NetworkX MultiDiGraph (1.16 ms) + ChromaDB	Flat Files (MEMORY.md Logs)	Virtual Paged Archival Database Tables	Dense Vector DB Semantic Embeddings	Ephemeral State Dictionary Object
Graph Latency	1.158 ± 0.241 ms (P95: 1.576 ms)	N/A (No Relational Graph)	N/A (No Relational Graph)	N/A (No Relational Graph)	N/A (No Relational Graph)
Ambient Proactivity	Adaptive Heartbeat (30–900 s) + Routines	Static Periodic Cron Triggers	Reactive Only (User Prompt Trigger)	Unbounded Autonomous Execution Loop	Scheduled Workflow Ingress Triggers
Affective Modeling	Multi-Axis (Emotion, Urgency, Persona State)	None (Standard Model)	None (Standard Model)	None (Standard Model)	Static System Prompt Role Persona
Execution Privacy	100% On-Device Inference (Zero Mandatory Telemetry)	Hybrid Gateway (Partial Local)	Server-Client API (Hybrid Cloud)	Cloud API Dependent (External Keys)	Framework Agnostic (Provider Dependent)
Safety & Permissions	5-Tier Poset Lattice + AST Confirmation Gate	Docker Container Sandbox Isolation	Parameter Schema Validation Rules	Terminal CLI Execution Prompt	Programmatic Software Guardrails
Recall @ Session 5	34.5% [Decays from 78.5%] (Synonym fragmentation)	31.5% (File search decay)	76.5% (Packer et al.) [SOTA Long-Term Recall]	46.1% (Dense RAG) [Packer et al. Baseline]	52.0% (State memory buffer)
Active RAM Footprint	463.1 MB (Hybrid Mode) 5,313 MB (On-Device 8B)	520.0 MB (Node.js Daemon)	890.0 MB (Letta Server Core)	1,340.0 MB (Python Runtime)	1,150.0 MB (Multi-Agent Stack)
Prompt Token Savings	65.2% vs. Naive Append [2,452 vs. 7,046 tokens]	0% Savings [Flat Log Accumulation]	Bounded OS Paging [~1,850 token plateau]	Bounded Sliding Window [~1,920 token plateau]	Bounded State Pruning [Dynamic trimming]
Tool Throughput	5.2 ops/s [AST-checked & modal gated]	18.5 ops/s [SOTA Speed] (Lightweight Node.js)	6.4 ops/s (Python API Server)	1.2 ops/s (Recursive ReAct)	7.8 ops/s (Asynchronous Graph)
Task Automation Rate	27.6% Aggregate (8.4 steps) [50.0% unmocked, 5/10]	N/A (Workflow automation)	48.2% (Single-Agent Tasks)	34.8% (AgentBench baseline)	57.3% [SOTA Multi-Agent] (5.6 steps average)
Adversarial Defense	62.0% Interception Rate [38.0% Vulnerability Gap]	Sandbox Isolation Only (No Neural Filter)	25.0% Interception (Parameter rules)	8.8% Interception (Raw CLI prompts)	74.2% [SOTA ASB] (Advanced guardrails)

B. Swarm Multi-Agent Consensus

The current Dione architecture relies on a single master LLM thread. We propose extending the orchestration runtime to support multi-agent swarm intelligence. Specialized sub-agents will execute domain-specific workflows (e.g., an indexing agent for filesystem metadata, an interaction agent for calendar scheduling, and an analysis agent for document summarization). The master orchestrator will coordinate these agents using a lightweight decentralized consensus protocol, substantially reducing prompt token clutter and isolating domain failure states.

C. Continuous Vision Structural Diffing

The current multimodal computer-use engine runs on demand. We plan to extend this into a continuous background visual awareness loop. To prevent GPU thermal throttling and battery depletion from running continuous vision inference, we propose a two-stage structural diffing algorithm:

$$\Delta(F_t, F_{t-1}) = \frac{1}{|\Omega|} \sum_{(x,y)\in\Omega} \|F_t(x,y) - F_{t-1}(x,y)\|_1 \quad (16)$$

The heavy multimodal vision model will remain dormant until the spatial pixel delta Δ exceeds an empirical threshold δ_{thresh}, ensuring high perceptual responsiveness with minimal compute overhead.

VI. Conclusion

We have presented **Dione**, an on-device Large Action Model (LAM) orchestration engine built on the Microsoft Agent Framework that delivers proactive, ambient personal assistance without compromising privacy. By integrating a typed NetworkX Knowledge Graph, a 0-1 Knapsack Context Optimizer, an Adaptive Heartbeat Scheduler, an Affective Persona Engine, a 5-tier Safety Kernel, and a Win32 Multimodal Computer-Use Engine, Dione proves that privacy-preserving local systems can operate under clear engineering constraints. Standardized benchmarks confirm a 27.6% aggregate task completion rate across GAIA and AgentBench suites (with 50.0% on unmocked host instances, trailing multi-agent cloud frameworks), a 62.0% defense rate against adversarial prompt injections (62/100 defended, acknowledging a 38.0% vulnerability penetration under indirect vectors), a 65.2% prompt token reduction relative to uncompressed naive append at Turn 30 (carrying +32.5% overhead vs. MemGPT), sub-2ms graph lookups (1.158 ± 0.241 ms) decaying to 34.5% Session 5 recall, and an active footprint of 463.1 MB in hybrid mode scaling to 5,313 MB during 100% on-device 8B model inference.

References

[1] T. Schick, J. Dwivedi-Yu, R. Dessì, R. Raileanu, M. Lomeli, L. Zettlemoyer, N. Cancedda, and T. Scialom, "Toolformer: Language models can teach themselves to use tools," in *Proc. 37th Conf. Neural Inf. Process. Syst. (NeurIPS)*, 2023.

[2] S. Yao, J. Zhao, D. Yu, N. Du, I. Shafran, K. R. Narasimhan, and Y. Cao, "ReAct: Synergizing reasoning and acting in language models," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2023.

[3] Y. Qin, S. Liang, Y. Ye, K. Zhu, L. Yan, Y. Lu, Y. Lin, X. Cong, X. Tang, B. Qian, et al., "ToolLLM: Facilitating large language models to master 16000+ real-world APIs," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2024.

[4] Microsoft, "Microsoft Agent Framework: A unified framework for building, orchestrating, and deploying AI agents," Microsoft Research and Azure AI, Tech. Rep., 2025.

[5] C. Packer, V. Fang, S. G. Patil, K. Lin, S. Wooders, and J. E. Gonzalez, "MemGPT: Towards LLMs as operating systems," *arXiv preprint arXiv:2310.08560*, 2023.

[6] D. Edge, H. Trinh, N. Cheng, J. Bradley, A. Chao, A. Mody, S. Truitt, D. Metropolitansky, R. O. Ness, and J. Larson, "From local to global: A graph RAG approach to query-focused summarization," *arXiv preprint arXiv:2404.16130*, 2024.

[7] S. Pan, L. Luo, Y. Wang, C. Chen, J. Wang, and X. Wu, "Unifying large language models and knowledge graphs: A roadmap," *IEEE Trans. Knowl. Data Eng.*, vol. 36, no. 7, pp. 3580–3599, 2024.

[8] J. Sun, C. Xu, L. Tang, S. Wang, C. Lin, Y. Gong, H. Shum, and X. Guo, "Think-on-graph: Deep and responsible reasoning of large language models on knowledge graphs," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2024.

[9] Y. Ruan, H. Dong, A. Wang, S. Pitis, Y. Zhou, J. Ba, Y. Dubois, C. J. Maddison, and T. Hashimoto, "Identifying the risks of LM agents with an LM-emulated sandbox," *arXiv preprint arXiv:2309.15817*, 2023.

[10] Y. Liu, G. Deng, Y. Li, K. Wang, Z. Wang, X. Wang, T. Zhang, Y. Liu, H. Wang, Y. Zheng, et al., "Prompt injection attack against LLM-integrated applications," *arXiv preprint arXiv:2306.05499*, 2023.

[11] H. Zhang, J. Huang, K. Mei, Y. Yao, Z. Wang, C. Zhan, H. Wang, and Y. Zhang, "Agent Security Bench (ASB): Formalizing and benchmarking attacks and defenses in LLM-based agents," *arXiv preprint arXiv:2410.02644*, 2024.

[12] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," in *Proc. 16th ACM Workshop Artif. Intell. Secur. (AISec)*, 2023, pp. 79–90.

[13] X. Liu, H. Yu, H. Zhang, Y. Xu, X. Lei, H. Lai, Y. Gu, H. Ding, K. Men, K. Yang, et al., "AgentBench: Evaluating LLMs as agents," *arXiv preprint arXiv:2308.03688*, 2023.

[14] G. Mialon, C. Fourrier, C. Swift, T. Wolf, Y. LeCun, and T. Scialom, "GAIA: A benchmark for general AI assistants," *arXiv preprint arXiv:2311.12983*, 2023.

[15] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal, H. Küttler, M. Lewis, W.-t. Yih, T. Rocktäschel, et al., "Retrieval-augmented generation for knowledge-intensive NLP tasks," in *Proc. 34th Conf. Neural Inf. Process. Syst. (NeurIPS)*, 2020, pp. 9459–9474.

[16] F. Perez and I. Ribeiro, "Ignore this title and hack this paper: Do not rely on language models to win reasoning competitions with prompt injection," in *Proc. EMNLP*, 2022.

[17] Q. Wu, G. Bansal, J. Zhang, Y. Wu, B. Li, E. Zhu, R. Cao, M. Zhang, H. Wang, and H. Wang, "AutoGen: Enabling next-gen LLM applications via multi-agent conversation," *arXiv preprint arXiv:2308.08155*, 2023.

[18] P. Malsuare, S. Patil, and R. Deshmukh, "SuperAgent: A scalable multi-agent framework for autonomous task execution," *Int. J. Comput. Appl.*, vol. 186, no. 12, pp. 45–53, 2024.