

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main() {
3     int V;
4     if (scanf("%d", &V) == 1) {
5         int denominations[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
6         int n = sizeof(denominations) / sizeof(denominations[0]);
7         int count = 0;
8         for (int i = 0; i < n; i++) {
9             if (V == 0) {
10                 break;
11             }
12             count += V / denominations[i];
13             V %= denominations[i];
14         }
15         printf("%d\n", count);
16     }
17     return 0;
18 }
19 }
```

	Input	Expected	Got	
✓	49	5	5	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.