

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is $SUM(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1 #include <stdio.h>
2 #include <stdlib.h>
3 int cmpA(const void *a, const void *b) { return *(long long*)a - *(long long*)b; }
4 int cmpD(const void *a, const void *b) { return *(long long*)b - *(long long*)a; }
5
6 int main() {
7     int n;
8     if (scanf("%d", &n) != 1) return 0;
9     long long A[n], B[n], min_sum = 0;
10    for (int i = 0; i < n; i++) scanf("%lld", &A[i]);
11    for (int i = 0; i < n; i++) scanf("%lld", &B[i]);
12    qsort(A, n, sizeof(long long), cmpA);
13    qsort(B, n, sizeof(long long), cmpD);
14    for (int i = 0; i < n; i++) min_sum += A[i] * B[i];
15    printf("%lld\n", min_sum);
16    return 0;
17 }
```

	Input	Expected	Got	
✓	3	28	28	✓
	1			
	2			
	3			
	4			
	5			
	6			
✓	4	22	22	✓
	7			
	5			
	1			
	2			
	1			
	3			
	4			
	1			
✓	5	590	590	✓
	20			
	10			
	30			
	10			
	40			
	8			
	9			
	4			
	3			
	10			

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.