

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than $\lfloor n / 2 \rfloor$ times. You may assume that the majority element always exists in the array.

Example 1:

Input: `nums = [3,2,3]`

Output: `3`

Example 2:

Input: `nums = [2,2,1,1,1,2,2]`

Output: `2`

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 104`
- `-231 <= nums[i] <= 231 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int findMajorityElement(int nums[], int n) {
3     int candidate = 0, count = 0;
4     for (int i = 0; i < n; i++) {
5         if (count == 0) {
6             candidate = nums[i];
7         }
8         count += (nums[i] == candidate) ? 1 : -1;
9     }
10    return candidate;
11 }
12 int main() {
13     int n;
14     if (scanf("%d", &n) != 1) return 0;
15     int nums[n];
16     for (int i = 0; i < n; i++) {
17         scanf("%d", &nums[i]);
18     }
19     printf("%d\n", findMajorityElement(nums, n));
20     return 0;
21 }
```

	Input	Expected	Got	
✓	3 3 2 3	3	3	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.