

Ex No: 2b

IMPLEMENTATION OF UNIFICATION AND RESOLUTION

ALGORITHM

Aim:

To implement unification and resolution algorithm using python.

Procedure:

Program:

Unification and Resolution in Python

```
def unify(var1, var2, subst):  
    """Unify two variables or terms with substitution."""  
    if subst is None:  
        return None  
    elif var1 == var2:  
        return subst  
    elif isinstance(var1, str) and var1.islower():  
        return unify_var(var1, var2, subst)  
    elif isinstance(var2, str) and var2.islower():  
        return unify_var(var2, var1, subst)  
    elif isinstance(var1, list) and isinstance(var2, list) and len(var1) == len(var2):  
        return unify(var1[1:], var2[1:], unify(var1[0], var2[0], subst))  
    else:  
        return None
```

```

def unify_var(var, x, subst):
    """Handle unification for variables."""
    if var in subst:
        return unify(subst[var], x, subst)
    elif x in subst:
        return unify(var, subst[x], subst)
    elif occurs_check(var, x, subst):
        return None
    else:
        subst[var] = x
        return subst

def occurs_check(var, x, subst):
    """Check for cyclic dependencies in substitution."""
    if var == x:
        return True
    elif isinstance(x, list):
        return any(occurs_check(var, xi, subst) for xi in x)
    elif x in subst:
        return occurs_check(var, subst[x], subst)
    return False

def resolution(kb, query):
    """Apply resolution algorithm to check satisfiability."""
    clauses = kb + [negate(query)]
    while True:
        new_clauses = []
        for i, ci in enumerate(clauses):
            for j, cj in enumerate(clauses):
                if i >= j:

```

```

        continue
    resolvents = resolve(ci, cj)
    if [] in resolvents:
        return True # Query is satisfiable
    for res in resolvents:
        if res not in new_clauses:
            new_clauses.append(res)
    if all(new in clauses for new in new_clauses):
        return False # Query is not satisfiable
    clauses.extend(new_clauses)

def negate(literal):
    """Negate a literal or a list of literals."""
    if isinstance(literal, list):
        return [negate(lit) for lit in literal]
    if literal.startswith("~"):
        return literal[1:]
    else:
        return f"~{literal}"

def resolve(clause1, clause2):
    """Resolve two clauses to find resolvents."""
    resolvents = []
    for lit1 in clause1:
        for lit2 in clause2:
            if lit1 == negate(lit2):
                new_clause = list(set(clause1 + clause2))
                new_clause.remove(lit1)
                new_clause.remove(lit2)
                if new_clause not in resolvents:
                    resolvents.append(new_clause)

```

```

    return resolvents
if __name__ == "__main__":
    # Example knowledge base and query
    knowledge_base = [
        ["~P", "Q"],
        ["P"],
        ["~Q", "R"],
        ["~R"]
    ]
    query = ["R"] # Representing the query as a list
    print("Knowledge Base:", knowledge_base)
    print("Query:", query)
    result = resolution(knowledge_base, query)
    if result:
        print("The query is satisfiable.")
    else:
        print("The query is not satisfiable.")

```

Output:

Knowledge Base:

```

[
    ["~P", "Q"],
    ["P"],
    ["~Q", "R"],
    ["~R"]
]

```

Query:

```
["R"]
```

Knowledge Base: [['~P', 'Q'], ['P'], ['~Q', 'R'], ['~R']]

Query: ['R']

The query is not satisfiable.

Procedure

1. Define the unification function to find substitutions between terms.
2. Define `unify_var()` to handle variable substitutions.
3. Use `occurs_check()` to avoid cyclic substitutions.
4. Define the `resolution()` function to apply the resolution algorithm.
5. Negate the query and add it to the knowledge base.
6. Resolve pairs of clauses until a result is obtained.
7. Define the knowledge base and query R.
8. Execute the program and display the result.

Result:

The query is not satisfiable.

Output

```
*** Knowledge Base:
[
  ["~P", "Q"],
  ["P"],
  ["~Q", "R"],
  ["~R"]
]
Query:
["R"]
Knowledge Base: [['~P', 'Q'], ['P'], ['~Q', 'R'], ['~R']]
Query: ['R']
The query is not satisfiable.
```