

Tenant Onboarding Module – Database Schema

1. Overview

The tenant onboarding module manages registration, configuration, bot setup, and knowledge ingestion. All data is linked by `tenant_id` with Row-Level Security (RLS) to isolate tenant data.

tenants

Column	Type	Description
id	UUID (PK)	Unique tenant identifier
name	VARCHAR(255)	Tenant name
domain	VARCHAR(255)	Tenant domain (optional)
plan	VARCHAR(50)	Subscription plan (free, pro, enterprise)
status	ENUM('active','pending','suspended')	Tenant status
created_at	TIMESTAMP	Creation timestamp
updated_at	TIMESTAMP	Last update timestamp
settings	JSONB	Miscellaneous configuration (limits, billing IDs)

tenant_admins

Column	Type	Description
id	UUID (PK)	Unique ID
tenant_id	UUID (FK → tenants.id)	Tenant reference
email	VARCHAR(255)	Admin email
password_hash	TEXT	Hashed password
role	ENUM('owner','admin')	Admin role
verified	BOOLEAN	Email verified flag
last_login	TIMESTAMP	Last login time

agents

Column	Type	Description
id	UUID (PK)	Unique agent ID
tenant_id	UUID (FK → tenants.id)	Tenant reference
name	VARCHAR(255)	Agent name
description	TEXT	Bot persona summary
llm_config	JSONB	Model, temperature, top_p, etc.
retrieval_config	JSONB	Vector DB details, filters, RAG params
guardrails	JSONB	NeMo/PII/moderation rules
branding	JSONB	Logo URL, theme color, font, etc.
created_at	TIMESTAMP	Creation date
updated_at	TIMESTAMP	Last modified

knowledge_sources

Column	Type	Description
id	UUID (PK)	Source ID
tenant_id	UUID (FK → tenants.id)	Tenant reference
agent_id	UUID (FK → agents.id)	Optional (specific bot)
type	ENUM('file','url','integration')	Source type
name	VARCHAR(255)	Display name
source_url	TEXT	Original link or storage path
status	ENUM('pending','processing','indexed','error')	Current state

metadata	JSONB	Size, file type, crawl date, etc.
created_at	TIMESTAMP	Creation time
updated_at	TIMESTAMP	Last updated time

ingestion_jobs

Column	Type	Description
id	UUID (PK)	Job ID
tenant_id	UUID (FK → tenants.id)	Tenant reference
source_id	UUID (FK → knowledge_sources.id)	Related source
status	ENUM('queued','running','completed','failed')	Job status
progress	INTEGER	Percentage completed
logs	TEXT	Error or status logs
created_at	TIMESTAMP	Enqueued timestamp
completed_at	TIMESTAMP	Finished timestamp

installation_snippets

Column	Type	Description
id	UUID (PK)	Snippet ID
tenant_id	UUID (FK → tenants.id)	Tenant reference
script_url	TEXT	CDN-hosted script
embed_code	TEXT	Full JS snippet for installation
created_at	TIMESTAMP	Generated at
expires_at	TIMESTAMP	Expiry (optional)

subscriptions

Column	Type	Description
--------	------	-------------

id	UUID (PK)	Subscription ID
tenant_id	UUID (FK → tenants.id)	Tenant reference
plan	VARCHAR(50)	Plan name
status	ENUM('trial','active','expired')	Subscription status
start_date	DATE	Start date
end_date	DATE	End date
usage_metrics	JSONB	Monthly tokens, storage, API calls
billing_id	VARCHAR(100)	External payment system ref

3. Relationships & Security

- tenants → tenant_admins : 1-to-many
- tenants → agents : 1-to-many
- tenants → knowledge_sources : 1-to-many
- knowledge_sources → ingestion_jobs : 1-to-many
- tenants → installation_snippets : 1-to-many
- tenants → subscriptions : 1-to-1 (optional)

Row-Level Security (RLS) should be applied on all tenant-linked tables to enforce tenant data isolation.

4. Indexes:

- CREATE INDEX idx_tenant_id ON agents(tenant_id);
- CREATE INDEX idx_source_status ON knowledge_sources(status);
- CREATE INDEX idx_ingestion_jobs_tenant ON ingestion_jobs(tenant_id);
- All sensitive fields (passwords, API keys) must be encrypted or hashed (bcrypt + Vault/KMS).